

Package ‘oceanmap’

April 11, 2017

Type Package

Title A Plotting Toolbox for 2D Oceanographic Data

Version 0.0.5

Date 2017-04-11

Author Robert K. Bauer

Maintainer Robert K. Bauer <robert.bauer@ird.fr>

Depends R (>= 2.10), maps, mapdata, raster, extrafont

Imports abind, fields, marmap, plotrix, methods, utils, grDevices, maptools, sp, ncdf4, stats

Description Plotting toolbox for 2D oceanographic data (satellite data, sst, chla, ocean fronts & bathymetry). Recognized classes and formats include ncdf4, Raster, '.nc' and '.gz' files.

License GPL (>= 3)

NeedsCompilation no

Repository CRAN

Date/Publication 2017-04-11 11:53:02

SystemRequirements ImageMagick

R topics documented:

.get.worldmap	2
add.region	3
area_extrac	6
bindate2Title	7
check_gzfiles	8
check_ts	9
clim_plot	10
close_fig	11
cmap	12
delete.region	13
empty.plot	14
figure	15

get.bathy	16
internal.datasets	18
matrix2raster	18
name_join	19
name_split	20
nc2raster	22
nc2time	23
oceanmap	24
parameter_definitions	25
param_convert	26
plotmap	27
raster2matrix	30
readbin	31
regions	32
region_definitions	33
set.colorbar	35
v	37
v-class	45
writebin	45
Index	47

.get.worldmap	<i>World Map</i>
---------------	------------------

Description

Creates a world map database that allows longitude ranges between -180 and 360 degrees, and thus from the Pacific to the Atlantic and vise versa. It is based on the [worldHires](#) database (which itself is based on CIA World Data Bank II data and contains approximately 2 million points representing the world coastlines and national boundaries), from which polygon irritations of the Antarctic were also corrected.

Usage

```
.get.worldmap(resolution)
```

Arguments

resolution	number that specifies the resolution with which to draw the map. Resolution 0 is the full resolution of the database [default]. Otherwise, just before polylines are plotted they are thinned: roughly speaking, successive points on the polyline that are within resolution device pixels of one another are collapsed to a single point (see the Reference for further details). Thinning is not performed if plot = FALSE or when polygons are drawn (fill = TRUE or database is a list of polygons).
------------	---

Value

A list of class "map" with longitude (x) and latitude (y) positions of coastlines and state boundaries (different coastline or booundary elements are seperated by NA), single polygon names are provided by a names vector.

Author(s)

Robert K. Bauer

See Also

[worldHires](#)

<http://www.evl.uic.edu/pape/data/WDB/>

Examples

```
worldmap <- oceanmap:::.get.worldmap(worldmap)
str(worldmap)

## wordlmap usage in plotmap, with different center-options
par(mfrow=c(3,1))
plotmap(lon=c(80, -120), lat=c(-50, 10), main= "map from East to West")
plotmap(lon=c(-120, 80), lat=c(-50, 10), main= "map from West to East")
plotmap('tp')
```

add.region

adding a region to the [region_definitions](#) file

Description

adding a region to the [region_definitions](#)-file, taking or restoring a backup of region definitions. The basic idea is to provide a region-keyword that is used to access the region-information in later related function-calls (see: [v](#) and [plotmap, regions](#)). Information consists of a region-keyword, -longname, its spatial extent (longitudes and latitudes), grid resolution, as well as default colorbar position and figure size.

The required information can be provided by an interactive **session** (widget) that leads step by step through the region definition (is set default), in parts by an **extent**-object with the missing information then completed by the **session** or by a one-row data frame that holds the entire information (see: [region_definitions](#)).

ATTENTION! When reinstalling or updating the oceanmap package, previous region definitions are getting lost! It is therefore highly recommended to take and restore own backups (see: backup and restore).

Usage

```
add.region(add, add.px, cbx, cby, figdim, lib.folder,
           widget=T, backup=F, backup.folder='.', backup.name, restore=F, backup.regions)
```

Arguments

add	<p>extent-,raster-object or dataset containing all required region definition entries (label, name, latn, lats, lonw, lone, ncol, nrow, px, cbx1, cbx2, cby1, cby2, figxdim, figydim and grid.res). Ignored when add.px is supplied.</p> <p>The values latn, lats, lonw, lone define the regions extent, cbx1, cbx2, cby1 and cby2 define the position of the colorbar, gradient the orientation of the colorbar (x for horizontal, y for vertical), oticks the margin where to put the colorbar ticks relative to the colorbar rectangle ('l' left, 'r' right and 'b' for bottom; figxdim and figydim set the default window size of '.gz'-file figures and grid.res the default grid resolution.</p>
add.px	dataframe or list containing region data needed to read gz-compressed '.gz'-files. Required entries include 'label' to identify the region, 'ncol' and 'nrow', to define the number of columns and rows of the 'gz'-file, respectively. These values are automatically set if missing when writing gz-compressed '.gz'-files (see: writebin).
cbx	the horizontal limits (x1, x2) of the colorbar. If missing, the user will be asked for manual colorbar placement.
cby	the vertical limits (y1, y2) of the colorbar. If missing, the user will be asked for manual colorbar placement.
figdim	numeric vector indicating the width and height of the plot device in inches. If missing and force.figdim.widget is set FALSE, figdim is assigned a default width and height of 7in, otherwise the user will be asked to resize the plot device to set plot dimensions.
lib.folder	Character string indicating R-library path in which the oceanmap-package is installed.
widget	whether an interactive session (widget) shall assist the data entry procedure (default is TRUE).
backup	whether the current region_definitions-file should be backuped in the folder 'backup.folder' in the file backup.name (default is FALSE). ATTENTION! When reinstalling or updating the oceanmap package, previous region_definitions are getting lost!
backup.folder	Character string indicating the folder where to store the region_definitions-file backup (default is the current working directory).
backup.name	Character string indicating the filename of the region_definitions-file backup (If restore the default is the original oceanmap-region_definitions file; if backup the default is set to 'region_definitions.bkp.%Y%m%d.rda').
restore	whether to restore a backup of the region_definitions-file (default is FALSE).
backup.regions	Vector of region indicators defining which regions should be saved in backup file.

Author(s)

Robert K. Bauer

See Also

[delete.region](#), [region_definitions](#), [regions](#), [plotmap](#), [v](#)

Examples

```
## Example 1: Add region by supplying a one-row data.frame
##           that holds the entire required information
# data(region_definitions) # load region_definitions
# lion <- region_definitions[region_definitions$label == 'lion',] # selecting Gulf of Lions region
# lion
# junk <- lion
# junk$label <- 'junk' # rename region label
# add.region(junk) # add junk region
# data(region_definitions) # reload region_definitions
# region_definitions[,1:9]

## Example 2: Delete region
#delete.region("junk") # delete junk region
#data(region_definitions) # reload region_definitions
#region_definitions[,1:9]

## Example 3: Add region by supplying an extent- or raster-object and running the widget
library(raster)

ext <- extent(0,10,50,60)
plotmap(ext)
#add.region(ext) # extent-object

r <- raster(ext)
#add.region(r) # raster-object

## Example 4: Add region by supplying raster-object, colorbar positions and running the widget
#add.region(r,cbx=c(5,9.5),cby=c(51.7,52.4))

## Example 5: Add region by running the widget
#add.region()

## Example 6: Add region by running the widget
#add.region(add.px=list(label="lion",nrow=10,ncol=10))
#data(region_definitions)
#region_definitions[region_definitions$label == "lion",]

## Example 7: Creating a backup
#add.region(backup=T)
#add.region(backup=T, backup.folder=".",backup.regions=c("lion","medw4"))

## Example 8: Restoring the backup of the original region_definitions file
#add.region(restore=T)
```

area_extrac	<i>Extracts a pre-defined region from '.gz'-file and saves subset as a new '.gz'-file</i>
-------------	---

Description

Extracts a pre-defined region from '.gz'-file and saves subset as a new '.gz'-file (gzip compressed format). Basically it represents a combined call of [regions](#), [crop](#), [raster2matrix](#) and [writebin](#).

Usage

```
area_extrac(obj, area)
```

Arguments

obj	Character string indicating search criteria for '.gz'-files.
area	Character string identifying the region that should be extracted. area must be a subregion of the original region defined by the '.gz'-file. See region_definitions for area definitions and use add.region to add new regions.

Author(s)

Robert K. Bauer

See Also

[readbin](#), [writebin](#), [crop](#), [raster2matrix](#), [param_unconvert](#)

Examples

```
## Example 1: extract, write '.gz'-files, following default plot-procedure
library(raster)

# load sample-'.gz'-file
setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('*.gz')
print(gz.files)
# area_extrac(gz.files[1], area='lion')

# gz <- Sys.glob('lion*.gz') # load new-'.gz'-file
# v(gz) # visualize new-'.gz'-file
# system(paste('rm', gz))
# v(gz.files[1], v_area='lion')
```

bindate2Title	<i>returns formatted date string for v-plot titles</i>
---------------	--

Description

returns formatted date string for v-plot titles by provided date information (e.g. filename of '.gz'-files, name of raster-layers. bindate2Title is returned by default by [v](#)-calls. bindate2main and bindate2ylab are plotted when [v](#) is called with sidelabels=T.

Usage

```
bindate2Title(timestep, date1, date2=date1)
```

```
bindate2main(timestep, date1, date2=date1)
```

```
bindate2ylab(timestep, date1, date2=date1)
```

Arguments

timestep	character string, indicating the range of the time unit in numbers and the time unit (e.g. "1d" for daily data; "7d" or "1w" for weekly data; "1m" for monthly data)
date1, date2	character string, indicating the first and last date of the timeframe covered (recognized format is %Y%m%d%H or %Y%m%d). E.g. 20030301 and 20030331 for monthly data (timestep = 1m) of March 2003.

Author(s)

Robert K. Bauer

See Also

[name_split](#), [v](#)

Examples

```
## Example 1: output of different bindate2???-functions
setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('*.gz') # load sample-'.gz'-files
u <- name_split(gz.files)

print(gz.files[1]) # print filename
print(u[1,]) # print splitted filename
bindate2main(u$timestep[1],u$date1[1],u$date2[1]) # main
bindate2Title(u$timestep[1],u$date1[1],u$date2[1]) # Title
bindate2ylab(u$timestep[1],u$date1[1],u$date2[1]) # ylab
```

```
## Example 2: Visualize output for multiple '.gz'-files
u$option <- '... .'

dev.new(width=9.7,height=7.8,xpos=-1)
empty.plot()
box()
for (i in 1:nrow(u)){
  mtext(name_join(u[i,]),side=1,line=i-10)
  main <- bindate2main(u$timestep[i],u$date1[i],u$date2[i]) # main
  Title <- bindate2Title(u$timestep[i],u$date1[i],u$date2[i]) # Title
  ylab <- bindate2ylab(u$timestep[i],u$date1[i],u$date2[i]) # ylab
  mtext(c(Title,ylab,main),side=1:3,line=c(i,nrow(u)+1-i,nrow(u)+1-i))
  mtext(paste("file",i),side=c(1,1:3),line=c(i-10,i,nrow(u)+1-i,nrow(u)+1-i),adj=0)
}
mtext(c("filename",
        "bindate2Title (default)",
        "bindate2ylab (sidelabels=T)",
        "bindate2main (sidelabels=T)"),
      side=c(1,1:3),line=c(-11,rep(i+2,3)),font=2)
```

check_gzfiles

Returns summary on '.gz'-file types

Description

Returns summary table on '.gz'-file types available in a specified folder. Provided information include region (region covered, as described by the [region_definitions](#)), sat (satellite source), param (parameter), res (spatial resolution), ts (temporal resolution), filetype (file filetype)

Usage

```
check_gzfiles(sstring="*",folder=".",filetype=".gz")
```

Arguments

sstring	Character string indicating the search criteria for sat files (default is *, including all '.gz'-files).
folder	Character string indicating the folder in which searched files are located (default is current working directory)
filetype	Character string indicating the file type of sat files (default is .gz)

Value

An aggregated data frame, returning '.gz'-file type-information (see description) on available files in a specified folder.

Author(s)

Robert K. Bauer

See Also[name_split](#), [check_ts](#)**Examples**

```
## Example 1: plot '.gz'-files, following default plot-procedure
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table per filetype

## check for missing dates
check_ts('medw4*')
check_ts('medw4*', output=TRUE)
```

check_ts	<i>checks if daily '.gz'-file time series is complete</i>
----------	---

Description

checks if daily '.gz'-file time series in the present working directory is complete.

Usage

```
check_ts(sstring="*.gz", output=F)
```

Arguments

sstring	Character string indicating search criteria for gz-files (default is '*.gz').
output	weather the missing dates should be returned as vector (default is F).

Value

optional vector of missing dates (see output argument).

Author(s)

Robert K. Bauer

See Also[name_split](#), [check_gzfiles](#)

Examples

```
## Example 1: plot '.gz'-files, following default plot-procedure
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table per filetype

gz.files <- Sys.glob('*.gz') # load sample-'.gz'-files
name_split(gz.files) # return summary-table per file
```

clim_plot

plots '.gz'-file climatologies

Description

Creates climatology plots of '.gz'-files. **ATTENTION!** This function requires an ImageMagick installation, but runs also under Windows operating systems.

Usage

```
clim_plot(obj, plotfolder=".", plotname, question=T, sst.frontcolor='red',
          chla.frontcolor='blue', sidelabels = F, Ylab = F, axeslabels = T, v_area, ...)
```

Arguments

obj	Character string indicating search criteria for climatology '.gz'-files.
plotfolder	directory where image should be saved.
plotname	the name of the output file. If not provided, value will be derived from '.gz'-filenames.
question	whether the user shall be informed about the number of figures to plot before running the procedure (default is TRUE).
chla.frontcolor	color map to be plotted for chlorophyll fronts (default is blue; obtained from cmap-dataset)
sst.frontcolor	color map to be plotted for sea surface temperature fronts (default is red; obtained from cmap-dataset)
sidelabels	whether an additional y-axis label and title should be added to the plot device (default is FALSE). If TRUE, y-axis label is defined by Ylab, the additional title is derived from the date-information and gives the month information.
Ylab	an additional title for the y axis (default is date information), only used when sidelabels is set TRUE. Default value is year-information.
axeslabels	whether axeslabels should be shown (default is TRUE, set as 'longitude' and 'latitude')
v_area	character string identifying the region that should be plotted, or in case of obj == 'bathy', also a Raster* or Extent object. If missing, region is derived from the '.gz'-filename. See region_definitions for area definitions and use add.region to add new regions.

... Additional arguments to be passed to [v](#) and [plotmap](#) (e.g. main, sidelabels, Ylab, scale_arrow, minv, maxv, adaptive.vals, cb.xlab, suffix, v_area, v_image, v_contour, v_arrows, fill, col, border, grid, grid.res, bwd, axeslabels, ticklabels, cex.lab, cex.ticks)

Author(s)

Robert K. Bauer

See Also

[v](#), [readbin](#), [name_split](#), [regions](#), [plotmap](#)

Examples

```
## Example 1: plot seasonal '.gz'-files, following default plot-procedure
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table
gz.files <- Sys.glob('*1s_*.gz') # load seasonal '.gz'-files
v(gz.files) # as single plots

# as combined climatology plot, saved in plotfolder
clim_plot(gz.files, plotfolder=owd, plotname='chla.summary.png')
```

close_fig	<i>function to close current graphic device</i>
-----------	---

Description

function to close current graphic device, complement to [figure](#)-function that generates graphic devices in flexible fileformats.

Usage

```
close_fig(do.close=F, do.save=do.close)
```

Arguments

do.close, do.save

whether file should be saved or not (default is TRUE). if FALSE, new graphic device will be opened inside R.

Author(s)

Robert K. Bauer

See Also[figure](#)**Examples**

```
do.save <- TRUE
figure("Gulf_of_Lions", do.save=do.save, width=5, height=5, type="pdf")
plotmap("lion")
close_fig(do.save)

plotmap("lion")
close_fig(do.save)

do.save <- FALSE
figure("Gulf_of_Lions", do.save=do.save, width=5, height=5, type="pdf")
plotmap("lion")
close_fig(do.save)
```

cmap

color maps

Description

list holding different color maps that can be used in image plots (see: [v](#), [get.bathy](#), [image](#), [image.plots](#), [clim_plot](#))

available color maps are: ano, bathy, blue, chla, haxby, jet (obtained from matlab), rainbow, red, orange, green, sst and haxbyrev.

Usage

```
data(cmap)
data(cmap_topo)
```

Format

list

Author(s)

Robert K. Bauer

Examples

```
data('cmap') # load color maps data
names(cmap) # list available color maps

setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('*.gz')
figure(width=15,height=15)
par(mfrow=c(4,5))
for(n in names(cmap)) v(gz.files[2], v_area='lion', subplot=TRUE,
                        pal=n, adaptive.vals=TRUE, main=n)

## simple example of the \link{image}-function
x <- 10*(1:nrow(volcano))
y <- 10*(1:ncol(volcano))
image(x, y, volcano, col = terrain.colors(100))
image(x, y, volcano, col = cmap$jet) # jet color map
image(x, y, volcano, col = cmap$haxby) # haxby color map
image(x, y, volcano, col = cmap$chla) # chlorophyll color map
image(x, y, volcano, col = cmap$sst) # sst color map

data(cmap_topo)
image(x, y, volcano, col = cmap_topo$col) # topography color map

## another example: plot bathymetry and topography of the western Mediterranean Sea
#get.bathy("medw4",visualize=T,terrain=T,res=3)
#get.bathy("medw4",visualize=T,terrain=F,res=3,levels=c(200,2000)) # show contours
```

delete.region	<i>deletes a region from the region_definitions-definition file</i>
---------------	---

Description

deletes a specified region from the [region_definitions](#)-definition file

Usage

```
delete.region(region,lib.folder,restore=F)
```

Arguments

region	Character string identifying the region that should be deleted. See region_definitions for area definitions and use add.region to add new regions.
lib.folder	Character string indicating R-library path in which the oceanmap-package is installed.
restore	whether the original region_definitions -file should be restored.

Author(s)

Robert K. Bauer

See Also[add.region](#), [region_definitions](#), [regions](#), [writebin](#)**Examples**

```
## Example 1: Add region by supplying a one-row data.frame
##           that holds the entire required information
data(region_definitions)
lion <- region_definitions[region_definitions$label == 'lion',] # selecting Gulf of Lions region
lion
junk <- lion
junk$label <- 'junk' # rename region label
#add.region(junk) # add junk region
data(region_definitions) # reload region_definitions
region_definitions[,1:9]

## Example 2: Delete region
#delete.region("junk") # delete junk region
data(region_definitions) # reload region_definitions
region_definitions[,1:9]
```

empty.plot*Creates an empty scatter plot*

Description

Creates an empty scatter plot that is equal to the function call:

```
plot(1,lwd=0,axes=F,xlab="",ylab="",...)
```

Usage

```
empty.plot(..., xlab = "", ylab = "", new=T, add=!new, n=1, axes = F)
```

Arguments

...	other arguments of the generic x-y plotting function plot .
xlab, ylab	label for the x- and y-axis of the plot (default is empty).
new, add	whether to show add plot to a current plot device or to start a new figure (default is: new=TRUE and add=FALSE).
n	number of figures to be plotted (default is 1)
axes	whether to show plot axes (default is FALSE).

Author(s)

Robert K. Bauer

Examples

```
empty.plot()
title("empty plot")
box()
axis(1)
axis(2)
```

figure	<i>generate (and save) graphic devices with flexible fileformat selection</i>
--------	---

Description

figure generates graphic devices with flexible fileformat selection. **Function call with (figure(do.save=T) needs to be finished by close_fig(do.save=T), to close open file connection.**

Usage

```
figure(filename, folder, type, save=F, do.save=save,
        width=10, height=10, xpos=-1, do.overwrite=T, delete.old=do.overwrite, ...)
```

Arguments

filename	name of the figure to be generated (without file extension)
folder	plot folder (by default current working directory)
type	character string indicating the graphics format of the figure file. can be: <ul style="list-style-type: none"> • "jpg" • "jpeg" • "png" • "eps" • "pdf"
width, height	width and height of figure to be generated. default units are inches.
save, do.save	whether file should be saved or not (default is TRUE). if FALSE, new graphic device will be opened inside R.
xpos	horizontal screen position of graphic device (ignored if do.save == TRUE)
do.overwrite, delete.old	overwrite existing figure with same filename and extension (default is FALSE)
...	additional arguments to be passed to the graphic device

Author(s)

Robert K. Bauer

See Also[close_fig](#)**Examples**

```
## Example 1: plotmap() and figure()
do.save <- FALSE
figure("Gulf_of_Lions_extended", do.save=do.save, width=5, height=5, type="pdf")
plotmap("lion")
close_fig(do.save)

## now resize figure manually and get new figure dimensions:
width <- dev.size()[1]
height <- dev.size()[2]

do.save <- TRUE
figure("Gulf_of_Lions_extended", do.save=do.save, width=width, height=height, type="pdf")
plotmap("lion")
close_fig(do.save)
```

`get.bathy`*Returns bathymetric data from the NOAA ETOPO1 database as RasterLayer, given coordinate bounds and resolution.*

Description

Returns and optionally stores bathymetric data from the ETOPO1 database hosted on the NOAA server as a RasterLayer, based on the defined resolution and provided coordinate bounds or region definition. Stored bathymetry files can be reloaded through the same function call.

Usage

```
get.bathy(v_area, lon, lat, resolution=4, keep=F ,
          savename.bathy, folder.bathy, visualize=T, terrain=F,...)
```

Arguments

<code>v_area</code>	character string identifying the region that should be plotted, or in case of <code>x == 'bathy'</code> , also a Raster* or Extent object. If missing, region is derived from the <code>'.gz'</code> -filename. See region_definitions for area definitions and use add.region to add new regions.
<code>lon, lat</code>	longitude and latitude describing the extend of the region of interest.
<code>resolution</code>	resolution of the bathymetric grid, in minutes (default is 4).

keep	whether to write the data downloaded from NOAA into a file (default is FALSE).
savename.bathy	savename for the bathymetric data file, if not specified set to type 'bathy_lon-lat_res.resolution.dat' or 'bathy_v_area_res.resolution.dat'.
folder.bathy	directory where bathymetric data should be saved (default is current working directory).
visualize	whether the bathymetric data should be plotted instantly.
terrain	whether the to keep terrain data (default is FALSE). If set FALSE and visualize is TRUE, grid command in plotmap is disabled!
...	additional arguments to be passed to v , used if visualize is set TRUE.

Author(s)

Robert K. Bauer

See Also[v](#), [add.region](#), [region_definitions](#), [regions](#), [writebin](#), [get.bathy](#)**Examples**

```
## Example 1: load & plot bathymetry of the Baltic Sea, defined by longitudes and latitudes
lon <- c(9, 31)
lat <- c(53.5, 66)
# get.bathy(lon=lon, lat=lat, main="Baltic Sea", cbpos='r')

## Example 2: plot bathymetry using a v_area-keyword
#get.bathy("lion",res=4, keep=T) # can take some time, requires server connection!
#get.bathy("lion",res=1, keep=T,visualize=FALSE)

## Example 3: plot landmask of the Baltic Sea defined by an extent- or raster-object
library('raster')
ext <- extent(lon,lat)
#get.bathy(ext,visualize=T,main="Baltic Sea",res=4,levels=200) # extent-object

## Example 4: plot bathymetry and topography of the western Mediterranean Sea
### a) download, assign and save bathymetry
# bathy <- get.bathy("medw4",visualize=F,terrain=T,res=3,keep=T)
# # load('bathy_medw4_res.3.dat',verbose = T); bathy <- h
# par(mfrow=c(2,1))
# v(bathy,param="bathy",subplot = T)
# get.bathy("medw4",visualize=T,terrain=F,res=3,levels=c(200,2000),
# subplot = T,grid=F) # show contours

### b) only contour lines:
# par(mfrow=c(1,2))
# h <- get.bathy("lion",visualize=T,terrain=F,res=3,levels=c(200,2000),
# v_image=F, subplot=T,grid=F)

### use v-function for same plot but on subregion:
```

```
# v(h,v_area = "survey", param="bathy",subplot = T, v_contour = T,
#   v_image = F, levels=c(200,2000))
```

internal.datasets	<i>internal datasets</i>
-------------------	--------------------------

Description

internal (lazyload) datasets medm9_proj and regions.dim.bathy, accessed by `v.plot` and [read-bin](#) respectively.

Author(s)

Robert K. Bauer

matrix2raster	<i>Converts a matrix to a RasterLayer or arrays to a RasterStack-object</i>
---------------	---

Description

`matrix2raster` Converts a matrix to a RasterLayer or arrays to a RasterStack-object.

Usage

```
matrix2raster(z,x,y,layer,proj="+proj=longlat")
```

Arguments

<code>z</code>	matrix or array to be converted.
<code>x</code>	optional x-coordinates giving the horizontal range of the raster layer, its size does not need to coincide with <code>ncol(z)</code> !
<code>y</code>	optional y-coordinates giving the vertical range of the raster layer, its size does not need to coincide with <code>nrow(z)</code> !
<code>layer</code>	layer to be selected (only valid if <code>z</code> is an array).
<code>proj</code>	optional argument, setting the coordinate reference system (CRS) of a Raster* object (default is <code>+proj=longlat</code>).

Author(s)

Robert K. Bauer

Examples

```
## Example 1: convert a matrix
m <- matrix(3,2,2)
matrix2raster(m)

## Example 2: convert an array
a <- array(3,dim=c(2,2,2))
matrix2raster(a)
matrix2raster(a,layer=1)

## Example 3: convert '.nc'-file to raster-object manually
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
ncfile <- Sys.glob('herring*.nc') # load sample-'.nc'-files

library('ncdf4')
library('raster')
nc <- nc_open(ncfile) # open netcdf file
z <- ncvar_get(nc, 'Conc')[,,1]
lon <- as.vector(ncvar_get(nc, 'lon')) # fillvalues are automatically replaced by NA
lat <- as.vector(ncvar_get(nc, 'lat')) # fillvalues are automatically replaced by NA
matrix2raster(z,x=lon,y=lat)

## Example 4: convert '.nc'-file to raster-object using nc2raster
nc2raster(ncfile,varname='Conc',layer=1:4)
```

name_join	<i>create '' .gz'-filenames from a list or dataframe</i>
-----------	--

Description

creates filenames based on a list or dataframe with the (header)-names:
 area source parameter resolution timestep date1 date2 option
 by aligning the defined filetype:
 e.g. area_source_parameter_resolution_timestep_date1_date2.option.filetype

Usage

```
name_join(parts, filetype='gz')
```

Arguments

parts	a list or dataframe with the parts: <ul style="list-style-type: none"> • area , the region keyword • source , the data source • param , the parameter saved in the ' .gz '-file. Can only be one value!
-------	--

- resolution , the spatial resolution
- timestep , the temporal resolution
- date1 & date2 , the temporal resolution (the time interval covered).
- option a character string holding supplementary information of '.gz'-file treatment

filetype character string indicating the filtype to be checked. ('.gz' by default)

Author(s)

Herve Demarq, translated from IDL by Robert K. Bauer

See Also

See [check_gzfiles](#) to return summary of available '.gz'-files and [name_split](#) to split '.gz'-filenames

Examples

```
## Example: read and plot '.gz'-file
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table
gz.files <- Sys.glob('*.*.gz') # load sample-'.gz'-files

# return summary of availble '.gz'-files
# suffix-column corresponds to option column of the name_join-call
# addition n-column returns the number of available files per filetype
check_gzfiles(gz.files)

## Example: split and rejoin '.gz'-filenames
name_split(gz.files) # return summary-table per file
name_join(name_split(gz.files))
```

name_split	<i>Returns a summary data frame of '.gz' encoded oceanography files by splitting their name</i>
------------	---

Description

Returns a summary [data.frame](#) of '.gz' encoded oceanography files by splitting their name

Usage

```
name_split(gz.files)
get_gz.info(gz.files)
```

Arguments

gz.files Optional character vector or search criteria for .gz-encoded oceanography files.

Value

Returns a summary [data.frame](#) of '.gz' encoded oceanography files by splitting their name

area source parameter resolution timestep date1 date2 option

area	region keyword
source	data source
param	the parameter saved in the '.gz'-file. Can only be one value!
resolution	the spatial resolution
timestep	the temporal resolution
date1 & date2	the time interval covered in date format
option	a character string holding supplementary information of '.gz'-file treatment

Author(s)

Robert K. Bauer

See Also

See [check_gzfiles](#) to return summary of available '.gz'-files and [name_join](#) to create '.gz'-filenames from splitted names ([name_split](#))-calls

Examples

```
## Example: read and plot '.gz'-file
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table per filetype
gz.files <- Sys.glob('med4*.gz') # load sample-'.gz'-files

# return summary of available '.gz'-files
# suffix-column corresponds to option column of the name_split-call
# addition n-column returns the number of available files per filetype
check_gzfiles(gz.files)

## Example: split and rejoin '.gz'-filenames
gz.files
name_split(gz.files) # return summary-table per file
name_split() # return summary-table of all gz-file in current folder
name_join(name_split(gz.files))
```

nc2raster	<i>Convert Raster layer to a matrix or array</i>
-----------	--

Description

nc2raster converts a netcdf-file ('.nc'-file) or ncdf4-object to a Raster* object, setting the time variable as layer name.

Usage

```
nc2raster(nc, varname, t=layer, lonname="lon", latname="lat",
          layer, date=T)
```

Arguments

nc	character string indicating the filepath to a netcdf-file ('.nc'-file), or a ncdf4-object.
varname	character string indicating the name of the netcdf-variable to be selected.
lonname	character string indicating the name of the longitude-variable of ncdf4-objects and '.nc'-files to plot (default is 'lon')
latname	character string indicating the name of the latitude-variable of ncdf4-objects and '.nc'-files to plot (default is 'lat')
layer, t	layer/time stemp to select in multi-layer files.
date	whether the layer names should be set to the date of the ncdf-file layer (default is TRUE, format is 'X%Y%m%d').

Value

RasterLayer or RasterStack

Author(s)

Robert K. Bauer

Examples

```
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
nfiles <- Sys.glob('*.*.nc') # load sample-'.nc'-files

nc2raster(nfiles[1], "Conc", layer=1) # RasterLayer
nc2raster(nfiles[1], "Conc", layer=1:4) # RasterStack

library('ncdf4')
nc <- nc_open(nfiles[1])
nc2raster(nc, "Conc", layer=1:4) # RasterStack
```

```
##### load & plot sample netcdf-file ('.nc'-file)
setwd(system.file("test_files", package="oceanmap"))
nfiles <- Sys.glob('*.*.nc') # load list of sample-'.nc'-files
head(nfiles)

### option a) load netcdf-file with ncdf4-package and plot it
library('ncdf4')
ncdf <- nc_open(nfiles[1])
print(ncdf)
v(obj = ncdf, cbpos="r")

### option b) load and plot netcdf-file as RasterStack object
nc <- nc2raster(nfiles[1])
v(nc,cbpos="r") # plot RasterStack object
v(nfiles[1], cbpos="r",replace.na=TRUE) # plot directly netcdf-file

### option c) plot netcdf-file directly
v(nfiles[1], cbpos="r") # plot RasterStack object

##### plot multiple layers:
par(mfrow=c(2,2))
v(nfiles[1], t=1:4, cbpos="r", replace.na=TRUE, subplot = TRUE)

setwd(owd)
```

nc2time	<i>reads and converts the time variable of a netcdf-file ('.nc'-file) or ncdf4-object as as.Date-object</i>
---------	---

Description

reads and converts the time variable of a netcdf-file ('.nc'-file) or ncdf4-object as as.Date-object.

Usage

```
nc2time(nc,varname)
```

Arguments

nc	character string indicating the filepath to a netcdf-file ('.nc'-file), or a ncdf4-object.
varname	character string indicating the name of the time variable of the netcdf-file.

Author(s)

Robert K. Bauer

Examples

```

owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
nfile <- Sys.glob('herring*.nc') # load sample-'.nc'-files
head(nc2time(nfile))

library('ncdf4')
nc <- nc_open(nfile)
head(nc2time(nc))

setwd(owd)

```

oceanmap

oceanmap - plot tools for 2D oceanographic data

Description

oceanmap is a plotting toolbox for oceanographic data. Visualizing data is a crucial step in analyzing and exploring data. During the last two decades the statistical programming language R has become a major tool for data analyses and visualization across different fields of science. However, creating figures ready for scientific publication can be a tricky and time consuming task.

The oceanmap package provides some helpful functions to facilitate and optimize the visualization of geographic and oceanographic data, such as satellite and bathymetric data sets. Its plotting functions are written in a way that they do not require a large amount of their numerous arguments to be specified but still return nice plots. Its major functions are:

Major functions:

- [plotmap](#): plots landmask as basis or overlay
- [v](#): plots oceanographic data (fronts, SST, chl_a, bathymetry, etc.) from [raster](#)-objects, ncdf4- or gz-files
- [set.colorbar](#): adds a colorbar to current figure, allowing several placement methods
- [get.bathy](#): download bathymetric data at user defined resolution from the NOAA ETOPO1 database
- [add.region](#): generate region definitions to facilitate land mask and colorbar plotting using [plotmap](#) and [v](#)
- [figure](#) & [close_fig](#): generate and save graphic devices in flexible file formats (jpeg, png, eps, pdf and eps)

Getting Started

Check out some examples of the principle functions, listed above.

Author(s)

Robert K. Bauer

parameter_definitions	<i>parameter definitions dataframe</i>
-----------------------	--

Description

a dataframe containing definitions of parameters to plot or to save by [v](#), [readbin](#) and [writebin](#).

Usage

data(parameter_definitions)

Format

data.frame

Value

a dataframe with the following header, containing definitions of parameters to plot or to save by [v](#), [readbin](#) and [writebin](#):

param a b c log name1 unit pal1 minv maxv min max invalid_data_dc coast_dc land_dc no_data_dc

param	character string indicating the keyword of a parameter.
a,b,c	value for parameter parameter data conversion from/to byte data. (See param_convert and param_unconvert)
log	whether a logarithmic formula should be applied for data conversion (0 for FALSE and 1 for TRUE; See param_convert and param_unconvert).
name	character string indicating the long name of a parameter.
unit	character string or bgroup statement indicating the parameter unit.
pal1	default color map used by v calls on parameter related data.
minv, maxv	default minimum and maximum z-value used by v calls on parameter related data.
min, max	minimum and maximum byte-values to be considered when calculating absolute values.
invalid_data_dc, coast_dc, land_dc & no_data_dc	byte values used to mask invalid data, coast lines, land masses and missing data.

Author(s)

Robert K. Bauer

See Also

[v](#)

Examples

```
## Example
data(parameter_definitions)
head(parameter_definitions)

# selecting sea surface temperature parameter definition
parameter_definitions[parameter_definitions$param == "sst2",]
```

param_convert	<i>converts byte data to absolute values or vice versa (param_unconvert)</i>
---------------	--

Description

converts byte data as stored in '.gz'-files to absolute values (param_convert) or vice versa (param_unconvert) using the parameter_definitions-dataset. param_convert is used by [readbin](#), param_unconvert is used by [writebin](#).

Usage

```
param_convert(x,param)

param_unconvert(x,param)
```

Arguments

x	vector, matrix or raster-object holding byte-data that that should be converted to absolute values (param_convert) or vice versa (param_unconvert).
param	Character string indicating parameter of the dataset to be treated. See parameter_definitions for available parameters.

Author(s)

Robert K. Bauer

See Also

[param_unconvert](#), [readbin](#)

Examples

```
library('fields')
setwd(system.file("test_files", package="oceanmap"))
gz.file <- Sys.glob('*.gz')[1] # load sample-'.gz'-files
param <- name_split(gz.file)$parameter
print(param)

## converted data, according to param information
m <- readbin(gz.file, Raster=FALSE)
```

```

image.plot(m)

## byte data ("unconverted") according to param information, as stored in ".gz"files
bin <- param_unconvert(m,param)
image.plot(bin)

## reconvert byte data, according to param information
conv <- param_convert(bin,param)
image.plot(conv)

```

plotmap

plots landmask of a defined region

Description

plots the landmask of a region defined by a region-key word, geographical coordinates (longitude and latitude), a raster- or [extent](#)-object. See [add.region](#) to add and save new region definitions. Attention! Unlike [add.region](#), plotmap does not include colorbar placement (see: [set.colorbar](#))

Usage

```

plotmap(region=v_area, lon, lat, add=F, asp,
        grid=T, grid.res, resolution=0,
        main, axeslabels=T, ticklabels=T, cex.lab=0.8, cex.ticks=0.8,
        fill.land=T, col.land="grey", col.bg=NA, border='black', bwd=2, las=1,
        v_area, xlim, ylim
        )

```

Arguments

region, v_area	Character string identifying regions predefined by the region_definitions -dataset, Raster* or Extent object (corresponds to v_area of the v -function). If missing, region is derived from geographical coordinates, denoted by lat and lon. See add.region to define new region definitions and delete.region to delete unproper region definitions.
lon, xlim	Vector returning longitude coordinates of the area to be plotted.
lat, ylim	Vector returning latitude coordinates of the area to be plotted.
add	whether the a the landmask should be added to an existent figure (default is FALSE)
asp	numeric, giving the aspect y/x-ratio of the y- and x-axes. See plot.window for more details.
main	title to be plotted
axeslabels	whether axis-labels (longitude and latitude) should be added to the axes (default is TRUE). Can be a single value or a vector of size two.

ticklabels	whether tick-labels should be added to the axes (default is TRUE). Can be a single value or a vector.
cex.lab	font size of axis labels
cex.ticks	font size of tick labels
grid	whether a grid should be plotted (default is TRUE)
grid.res	resolution of the grid, in degrees (default is derived from the region extent)
resolution	number that specifies the resolution with which to draw the map. Resolution 0 is the full resolution of the database [default]. Otherwise, just before polylines are plotted they are thinned: roughly speaking, successive points on the polyline that are within resolution device pixels of one another are collapsed to a single point (see the Reference for further details). Thinning is not performed if plot = FALSE or when polygons are drawn (fill = TRUE or database is a list of polygons).
bwd	width is of the axes bars (default is 1)
fill.land	whether the a the landmask should be filled by a color (default is TRUE)
col.land	fill color of the landmask to be plotted (default is grey)
col.bg	background color (ocean) to be plotted (default is NA)
border	country border color of the landmask to be plotted (default is black)
las	numeric in 0,1,2,3; the style of axis labels. 0: always parallel to the axis, 1: always horizontal [default], 2: always perpendicular to the axis, 3: always vertical

Details

plotmap uses the maps and maptools functions to plot the landmask.

Author(s)

Robert K. Bauer

See Also

[v](#), [regions](#)

Examples

```
#### Example 1: plot landmask of the Mediterranean Sea
## a) by using longitude and latitude coordinates:
lon <- c(-6, 37)
lat <- c(30, 46)
figure(width=9.75,height=5.28)
plotmap(lon=lon, lat=lat, main="Mediterranean Sea")
plotmap(xlim=lon, ylim=lat, main="Mediterranean Sea")
```

```

## b) plot landmask of the Mediterranean Sea by using an extent-object:
library('raster')
ext <- extent(lon, lat)
plotmap(ext, main="Mediterranean Sea") # extent-object

## c) plot landmask of the Mediterranean Sea by using a raster-object:
r <- raster(ext)
plotmap(r, main="Mediterranean Sea") # raster-object

## d) plot landmask of the Mediterranean Sea by using a region label:
plotmap('med4', main="Mediterranean Sea") # region-label
# regions() ## check preinstalled region label

## e) add landmask to an existing plot:
plot(3.7008, 43.4079, xlim=lon, ylim=lat)
plotmap(add=T)
points(3.7008, 43.4079, pch=19)

#### Example 2: subplots and some additional arguments of plotmap()
par(mfrow=c(2, 1))
plotmap('medw4', main="Western Mediterranean Sea", col.bg="darkblue")
plotmap('medw4', main="Western Mediterranean Sea", bwd=3, border='grey', grid=FALSE)

#### Example 3: plotmap() and figure()
do.save <- FALSE ## open a plotting window
figure("Gulf_of_Lions_extended", do.save=do.save, width=5, height=5, type="pdf")
plotmap("lion", col.bg='darkblue', grid=FALSE)
close_fig(do.save)

## now resize figure manually and get new figure dimensions:
width <- dev.size()[1]
height <- dev.size()[2]

do.save <- TRUE ## do NOT open a plotting window, but save figure internally
figure("Gulf_of_Lions_extended", do.save=do.save, width=width, height=height, type="pdf")
plotmap("lion", col.bg='darkblue', grid=FALSE)
close_fig(do.save)

#### Example 4: between hemispheres
par(mfrow=c(2,1))
plotmap(lon=c(-180, 180), lat=c(-80, 80), main="map from West to East")
plotmap(lon=c(0, 360), lat=c(-80, 80), main="map from West to East")
# plotmap(lon=c(-360, 00), lat=c(-80, 80), main="map from West to East") # same as before

#### Example 5: plot bathymetry and topography of the western Mediterranean Sea
#get.bathy("medw4", visualize=T, terrain=T, res=3)
#get.bathy("medw4", visualize=T, terrain=F, res=3, levels=c(200,2000)) # show contours
#get.bathy("lion", visualize=T, terrain=F, res=3, levels=c(200,2000), v_image=F) # show only contours

```

raster2matrix	<i>Convert Raster layer to a matrix or array</i>
---------------	--

Description

raster2matrix converts a raster layer to a matrix or array. Used by [readbin](#) and [writebin](#).

Usage

```
raster2matrix(RasterLayer)
```

```
raster2array(RasterLayer)
```

Arguments

RasterLayer raster layer to be converted.

Author(s)

Robert K. Bauer

Examples

```
library('raster')
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table
gz.files <- Sys.glob('*.gz') # load sample-'.gz'-files

raster.file <- readbin(gz.files[1]) # loading gz-file as raster-layer
image(raster.file)

## Example 1: converting single raster layer to matrix
image(as.matrix(raster.file)) # unflipped conversion
m <- raster2matrix(raster.file) # converting raster-layer to matrix
image(m)

## Example 2: converting double raster layer to an array
stack.file <- stack(raster.file,raster.file)
image(as.array(stack.file)[,,1]) # unflipped conversion
a <- raster2array(stack.file) # converting raster-layer to array (works also with raster2matrix)
image(a[, ,1])
```

readbin	Returns '.gz'-file as matrix or raster-object
---------	---

Description

Returns '.gz'-file as [matrix](#) or [raster-object](#).

Usage

```
readbin(filename, area, Image = F, byte = F, Raster = T)
```

Arguments

filename	Character string indicating search criteria for the '.gz'-file of interest. Only '.gz'-files with valid filenames can be read, consisting of: area, source, parameter, resolution, timestep, date1, date2 and option-criteria, separated by an underscore with only option being aligned by a point and ending with '.gz', e.g.: area_source_parameter_resolution_timestep_date1_date2.option.gz. See region_definitions for valid area- and parameter_definitions for valid parameter-values, respectively.
Image	whether the a the '.gz'-file should be plotted immediately using image.plot -function of the fields -package (default is FALSE)
byte	whether the a the data of the '.gz'-file should be returned unconverted as a byte-values (default is FALSE)
Raster	whether the a the data of the '.gz'-file should be returned in a raster-object (default is TRUE)
area	Character string identifying the region that should be extracted. If missing, region is derived from the '.gz'-filename. See region_definitions for area definitions and use add.region to add new regions.

Author(s)

Robert K. Bauer

See Also

[writebin](#), [regions](#), [crop](#), [raster2matrix](#), [param_convert](#)

Examples

```
### Example: read and plot '.gz'-file
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table
gz.files <- Sys.glob('*.gz') # load sample-'.gz'-files
```

```

### all manual:
obj <- readbin(gz.files[2],area='lion')
obj
ticks <- seq(20,30,5)
data('cmap')
image(obj,zlim=range(ticks),col=cmap$jet)
plotmap('lion',add=TRUE) # add landmask
#set.colorbar(ticks=ticks,cb.title='cb.title',cb.xlab='cb.xlab')

### using v:

## ticks set by adaptive.vals
v(obj,varname="sst2",cb.title='cb.title',cb.xlab='cb.xlab')

## ticks set by parameter definition
v(obj,varname="sst2",cb.title='cb.title',cb.xlab='cb.xlab',adaptive.vals=FALSE)

### extracting subregion:
obj <- readbin(gz.files[2])
area.extent <- extent(c(5,10,35,40))
subarea <- crop(obj,area.extent)
# v(subarea)

## getting average value:
mean(subarea[,],na.rm=TRUE)

```

regions

Returns two-row summary table of a specified region.

Description

Reorganizes summary information of a specified region from the [region_definitions](#) set into a two-row dataframe. Region definitions can be added, backed up or restored by [add.region](#) or deleted by calling [delete.region](#).

ATTENTION! When reinstalling or updating the oceanmap package, previous region definitions are getting lost! It is therefore highly recommended to take and restore own backups (see: backup and restore).

Usage

```
regions(label)
```

Arguments

label	Character string indicating the name of the region of interest. If missing, list of available regions in the region_definitions -dataset will be returned by a error message.
-------	---

Value

a two-row dataframe with the following header, containing the summary information of the region specified:

```
xlim ylim dim name cbx cby align gradient figdim grid.res
```

xlim & ylim	the spatial extent of the region
dim	the number of grid points for both x & y-dimension
name	the long name of the region
cbx & cby	x & y-coordinates for colorbar
align	a vector defining the color-gradient of the colorbar (x for horizontal, and y for vertical), as well as the margin where the colorbar ticks should be plotted, relative to the colorbar rectangle ('l' left, 'r' right and 'b' for bottom)
figdim	the region-specific default plot device size
grid.res	the default grid resolution in degrees

Author(s)

Robert K. Bauer

See Also

[v](#), [plotmap](#)

Examples

```
## Example: return summary table for the Gulf of Lions
data('region_definitions')
region_definitions[region_definitions$label=='lion',] # select raw region data summary
regions('lion') # return formatted summary table
```

region_definitions	<i>region definitions dataframe</i>
--------------------	-------------------------------------

Description

dataset providing spatial extent and color bar placement information by a region-keyword in later related function-calls (see: [v](#), [plotmap](#) and [regions](#)). Information consists of a region-keyword, -longname, its spatial extent (longitudes and latitudes), grid resolution, as well as default colorbar position and figure size. Region definitions can be added, backed up or restored by [add.region](#) or deleted by calling [delete.region](#).

ATTENTION! When reinstalling or updating the oceanmap package, previous region definitions are getting lost! It is therefore highly recommended to take and restore own backups (see: backup and restore).

Usage

```
data(region_definitions)
```

Format

```
data.frame
```

Value

dataframe with the following header, containing the summary information of the region specified:

```
label name latn lats lonw lone ncol nrow px cbx1 cbx2 cby1 cby2 gradient oticks figxdim figydim grid.
```

label	region-keywords
name	the long name of the region
latn & lats	northern and southern most latitude of the region
lonw & lone	western and eastern most longitude of the region
ncol, nrow & px	default matrix size per region described by the number of columns, rows and pixels. ATTENTION!! Regions of the same spatial extent but different default (matrix-) resolution may cause errors when reading or writing '.gz'-files and must therefore be distinguished by different keywords.
cbx1 & cbx2	x-coordinates for colorbar
cby1 & cby2	y-coordinates for colorbar
gradient	the color-gradient of the colorbar (x for horizontal, and y for vertical)
oticks	the margin where the colorbar ticks should be plotted, relative to the colorbar rectangle ('l' left, 'r' right and 'b' for bottom)
figxdim & figydim	the region-specific default plot device size (width and height in inches)
grid.res	the default grid resolution in degrees

Author(s)

Robert K. Bauer

See Also

See [add.region](#) to add new, backup or restore region definitions, and [plotmap](#) for basic landmark plots

Examples

```
data(region_definitions)
head(region_definitions)
region_definitions$label
# ?region_definitions
```

```

figure(width=15,height=15)
par(mfrow=c(5,6))
for(n in region_definitions$label) plotmap(region = n,main=n)

# Mediterranean Sea with a spatial resolution of 4km (e.g. MODIS-Aqua)
region_definitions[region_definitions$label == 'med4',]

# Mediterranean Sea with a spatial resolution of 9km (e.g. dekkar)
region_definitions[region_definitions$label == 'med9',]

# plotting same landmasks by different region-keywords
plotmap('med4')
plotmap('med9')

## Example for selecting wrong area definition when saving files
setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('med4*.gz') # load sample-med4'.gz'-files
v(gz.files[1])

fname <- name_split(gz.files[1])
param <- fname$parameter
gz <- readbin(gz.files[1])
dim(gz)
v(gz.files[1])

# reset region name
fname$area <- 'med9'
fname <- name_join(fname)
writebin(gz,fname,param=param)
v(fname)
system(paste('rm', fname))

```

set.colorbar

Adds colorbar to an existing plot device

Description

Adds colorbar to an existing plot device. If position vectors are not provided, the user will be asked to define the colorbar placement by the mouse cursor.

Usage

```

set.colorbar(cbx, cby, cbpos, pal='jet', zlim, ticks=1:10, labels=ticks, gradient,
             oticks, cb.title="", cb.xlab="", font=1, cex=1,
             cex.cb.title=0.9, cex.cb.xlab=0.8, cex.cb.ticks=0.7, cb.ticks.srt=90,
             cb.ticks.length, cb.ticks.ypos, cb.ticks.lwd=1,
             integer=F, cb.xlab.line=0, ...)

set.colorbarp(cbyp, total.reg, ...)

```

Arguments

cbx, cby	(set.colorbarp-arguments) the horizontal and vertical limits of the colorbar. If missing, the user will be asked for manual colorbar placement.
cbxp, cbyp	(set.colorbarp-arguments) the horizontal and vertical limits of the colorbar in percent. If missing, the user will be asked for manual colorbar placement.
cbpos	letter ("b", "l", "t", "r") indicating the position of the colorbar (bottom, left, top, right). Overwrites cbx and cby values.
total.reg	(set.colorbarp-argument) if colorbar placement is relative to current subplot or entire figure region.
pal	color map to be plotted (default is 'jet' for direct calls). See cmap for available color maps and parameter_definitions for predefined colormaps of different parameters (for internal function calls, e.g. v)
zlim	(optional) value limits of the color bar. Overwrites ticks if ticks are provided.
ticks	the points at which tick-marks are to be drawn (default is 1:10). Non-finite (infinite, NaN or NA) values are omitted. Gets overwritten by zlim if provided.
labels	character or expression vector of labels to be placed at the tickpoints. (default equals ticks-values.)
gradient	whether to have a horizontal (x) or vertical (y) color gradient.
oticks	the margin where to put the colorbar ticks relative to the colorbar rectangle ('l' left, 'r' right and 'b' for bottom;
cb.title	character string indicating the title of the colorbar (default is set to date information/empty string if date information is missing.)
cb.xlab	character string indicating the x-axis label of the colorbar.
font	Integer specifying font to use for text. 1=plain [default], 2=bold, 3=italic, 4=bold italic, 5=symbol
cb.xlab.line	line of x-axis colorbar label
cex, cex.cb.title, cex.cb.xlab, cex.cb.ticks	<i>cex</i> : general font size, used as reference for colorbar labels and title <i>cex.cb.xlab</i> : font size of the x-axis label of the colorbar <i>cex.cb.title</i> : font size of the title of the colorbar
cb.ticks.srt, cb.ticks.length, cb.ticks.ypos, cb.ticks.lwd	rotation, length, relative y-position and line width of colorbar ticks
integer	(default is FALSE).
...	additional arguments to be passed to text or <code>set.colorbar</code>

Details

`set.colorbar` adds a colorbar to the current plot device. If colorbar positions are missing (cbx, cby), the user will be asked for manual placement. ticks and tick-labels should correspond to zlim-values of the plot. pal defines the colormap and should equal col of the selected plot.

Value

a list of colorbar definition vectors: oticks, gradient, cbx and cby. See function arguments for more details.

Author(s)

Robert K. Bauer

Examples

```
## Example 1: plot colorbars manually
par(mar=c(8,8,8,8))
plot(0.5,0.5,xlim=c(0,1),ylim=c(0,1))
set.colorbar(cbx=c(0, 1), cby=c(-.3, -.4)) # bottom
set.colorbar(cby=c(0, 1), cbx=c(-.4, -.3)) # left
set.colorbar(cbx=c(0, 1), cby=c(1.2, 1.3)) # top
set.colorbar(cby=c(0, 1), cbx=c(1.2, 1.3)) # right

## Example 2: use cbpos
par(mar=c(8,8,8,8))
plot(0.5,0.5,xlim=c(0,1),ylim=c(0,1))
set.colorbar(cbpos='b') # bottom
set.colorbar(cbpos='l') # left
set.colorbar(cbpos='t') # top
set.colorbar(cbpos='r') # right

## Example 3: interactive placement
# par(mar=c(8,8,8,8))
# plot(0.5,0.5,xlim=c(0,1),ylim=c(0,1))
# cb <- set.colorbar() # interactive
# plot(0.5,0.5,xlim=c(0,1),ylim=c(0,1))
# set.colorbar(cbx=cb$cbx, cby=cb$cby) # reuse stored colorbar positions
```

Description

Plots spatial data (e.g. 2D oceanographic data). Valid input data are objects of class 'Raster' ('RasterLayer', 'RasterStack' or 'RasterBrick'), 'ncdf4' (already loaded netcdf files) or a character strings indicating 'bathy' metric data, 'gz'- or '.nc-files' (netcdf). See also [name_split](#) for further information on '.gz'-file nomenclature.

Usage

```
## S4 method for signature 'bathy'
v(obj, v_area, lon, lat, resolution=4, keep=F,
  savename.bathy, folder.bathy=".", adaptive.vals=T, cb.title, show.colorbar=T,...)
```

```

## S4 method for signature 'nc'
v(obj, varname, t=1, layer=t, adaptive.vals=T, dates,
  cb.xlab=varname, lonname="lon", latname='lat', show.colorbar=T, ...)

## S4 method for signature 'ncdf4'
v(obj, varname, t=1, layer=t, adaptive.vals=T, dates,
  cb.xlab=varname, lonname="lon", latname='lat', show.colorbar=T, ...)

## S4 method for signature 'RasterLayer'
v(obj, varname, t=1, layer=t, ...)

## S4 method for signature 'RasterBrick'
v(obj, varname, t=1, layer=t, ...)

## S4 method for signature 'RasterStack'
v(obj, varname, t=1, layer=t, ...)

## S4 method for signature 'gz'
v(obj, v_area, adaptive.vals=F, show.colorbar=T, ...)

```

Arguments

obj	object of class 'Raster' ('RasterLayer', 'RasterStack' or 'RasterBrick'), 'ncdf4' or a character string indicating, 'bathy' metric data, '.gz'- or '.nc'-files to plot.
v_area	character string identifying the region that should be plotted, or in case of obj == 'bathy', also a Raster* or Extent object. If missing, region is derived from the '.gz'-filename. See region_definitions for area definitions and use add.region to add new regions.
adaptive.vals	sets minimum and maximum z-value according to the '.gz'-files value range. (ATTENTION! minv and maxv are disregarded if set!). (default is TRUE for non-'.gz'-files. If FALSE or not set, default value from the parameter_definitions -dataset will be applied according to the param-value.
t, layer	layer/time stemp to select in multi-layer files/objects (e.g. ncdf4, RasterStack).
dates	vector of type 'character' indicating dates per layer, used to define the title of the colorbar. Argument is omitted for '.gz'-files but date-information is derived from the filename. For '.nc'-files or 'ncdf4'-objects, date information is derived from the time-vector. For raster -objects the layer name is applied.
varname	character string indicating the name of the variable to plot. For '.nc'-files or 'ncdf4'-objects, this name must correspond to a variable name defined in the file/object. Sets also colorbar-title for non-'.gz'-files if cb.xlab is missing.
cb.title	character string indicating the title of the colorbar (default is set to date information/empty string if date information is missing.)
cb.xlab	character string indicating the x-axis label of the colorbar and cb.xlab.line its placement line (default is 0). If not defined, it will be set to varname for raster , ncdf4-objects and '.nc'-files or for '.gz'-files to a predefined title in the parameter_definitions -dataset according to the param-value.

lonname	character string indicating the name of the longitude-variable of ncdf4-objects and '.nc'-files to plot (default is 'lon')
latname	character string indicating the name of the latitude-variable of ncdf4-objects and '.nc'-files to plot (default is 'lat')
lon	Vector returning longitude coordinates of the area to be plotted, only valable for <code>obj == 'bathy'</code> .
lat	Vector returning latitude coordinates of the area to be plotted, only valable for <code>obj == 'bathy'</code> .
resolution	resolution of the bathymetric grid, in minutes (default is 4), only valable for <code>obj == 'bathy'</code> .
keep	whether to write the data downloaded from NOAA into a file (default is FALSE), only valable for <code>obj == 'bathy'</code> .
savename.bathy	savename for the bathymetric data file, if not specified set to type 'bathy_lon-lat_res.resolution.dat' or 'bathy_v_area_res.resolution.dat', only valable for <code>obj == 'bathy'</code> .
folder.bathy	directory where bathymetric data should be saved (default is current working directory), only valable for <code>obj == 'bathy'</code> .
show.colorbar	weather a colorbar should be plotted for image plots(default is T).
...	additional arguments to be passed: region see <code>v_area</code> . minv, maxv minimum and maximum z-value to be plotted. If not set, default value from the parameter_definitions -dataset will be applied. Argument is overwritten by <code>adaptive.vals</code> and <code>zlim</code> . replace.na whether missing values should be replaced by minimum values (default is FALSE.) param character string indicating the parameter name for the dataset treatment. See <code>parameter_definitions</code> for available parameters. For '.gz'-files, param is derived from the filename. For non-'.gz'-files this value is non-obligatory, but can replace the <code>varname</code> -argument and vise versa. See examples. main an overall title for the plot: see title . cbpos letter ("b", "l", "t", "r") indicating the position of the colorbar (bottom, left, top, right). Overwrites <code>cbx</code> and <code>cby</code> values. cbx the horizontal limits (x1, x2) of the colorbar. If missing and the value can not be reconstructed by the region information (e.g. <code>v_area</code> , '.gz'-file), the user will be asked for manual colorbar placement. cby the vertical limits (y1, y2) of the colorbar. If missing and the value can not be reconstructed by the region information (e.g. <code>v_area</code> , '.gz'-file), the user will be asked for manual colorbar placement. nticks number of tick marks for the colorbar (default is 5). pal color map to be plotted (default is the 'jet'-colormap, or in case of '.gz'-files derived from the parameter_definitions -dataset. See cmap for available color maps and parameter_definitions for predefined colormaps for different parameters.)

sidelabels whether an additional y-axis label and title should be added to the plot device (default is FALSE). If TRUE, y-axis label is defined by Ylab, the additional title is derived from the date-information and gives the month information.

Ylab an additional title for the y axis (default is date information), only used when sidelabels is set TRUE. Default value is year-information.

axeslabels whether axeslabels should be shown (default is TRUE, set as 'longitude' and 'latitude')

subplot whether '.gz'-file will be plotted as a sub plot to an existing plot device (default is FALSE; see: [par](#))

width, height the width and height of the plotting window, in inches. For '.gz'-files, default values are derived from the region-name as indicated by the filename. See [region_definitions](#) for predescribed definitions and use [add.region](#) to add new region definitions.

figdim numeric vector indicating the width and height of the plot device in inches. For '.gz'-files, default values are derived from the region-name as indicated by the filename. Value is overwritten if both, width and height are provided. See [region_definitions](#) for predescribed definitions and use [add.region](#) to add new region definitions.

xpos integer: initial position of the top left corner of the figure window on the pc-screen, given in pixels. Negative values are from the opposite corner. (default is -1). Disregarded under Mac OS and if Save is set TRUE.

Save whether the a plot device should be saved automatically as an image file of type fileformat in a folder specified by plotfolder (default is FALSE)

plotfolder directory where images should be saved (default is current working directory).

plotname the name of the output file(s). If not set, value will be derived from the provided file information (For '.gz'-files, default plotname is equal to the '.gz'-filename, replacing the '.gz'-fileformat-suffix with the defined image-fileformat).

fileformat fielformat of image file to be saved (only png and eps are accepted; default is png).

suffix suffix to be added to the image filename, before the filetype specification (e.g. '...suffix.png').

v_image whether an image-plot should be plotted (default is TRUE)

v_contour whether contour lines should be plotted (default is FALSE). If levels are specified, v_contour is set TRUE.

levels numeric vector of levels at which to draw contour lines.

contour.labels a vector giving the labels for the contour lines. By default levels are used as labels.

v_arrows whether current or wind vectors should be plotted (default is TRUE; Argument is disregarded for non-.gz-files and omitted if non current or wind data-files are provided)

scale_arrow scale factor needed for current and wind vector plots (default is 1; Argument is disregarded for non-.gz-files and omitted if no current or wind data-files are provided, indicated by the param-argument (valid

param-definitions are: 'uz' and 'vz', for current data, 'wu' and 'wz' for wind data))

terrain whether the to keep terrain data (default is FALSE). If set FALSE and visualize is TRUE, grid command in [plotmap](#) is disabled!

... Additional arguments to be passed to [plotmap](#) (bwd, fill, col, border, grid, grid.res, axeslabels, ticklabels, cex.lab, cex.ticks).

Details

v uses the maps and maptools functions to plot the landmask. See [clim_plot](#) for aligned plots of satellite-data climatologies.

Author(s)

Robert K. Bauer

References

Bauer, R. K., Stepputtis, D., Grawe, U., Zimmermann, C., and Hammer, C. 2013. Wind-induced variability in coastal larval retention areas: a case study on Western Baltic spring-spawning herring. Fisheries Oceanography, 22: 388-399.

See Also

[clim_plot](#), [readbin](#), [name_split](#), [regions](#), [plotmap](#), [v](#)

Examples

```
##### simple example section:

## Example 1: load & plot a sample Raster-object
setwd(system.file("test_files", package="oceanmap"))
load("medw4_modis_sst2_4km_1d_20020705_20020705.r2010.0.qual0.Rdata", verbose=TRUE)
dat <- raster::crop(dat, extent(c(0,10,40,44))) ## crop data, xlim/ylim not yet implemented in v()
print(dat)
v(dat, main="Raster-object", cbpos='r')

## Example 2: load & plot sample netcdf-file ('.nc'-file)
setwd(system.file("test_files", package="oceanmap"))
nfiles <- Sys.glob('*.*.nc') # load list of sample-'.nc'-files
head(nfiles)

### option a) load netcdf-file with ncdf4-package and plot it
library('ncdf4')
ncdf <- nc_open(nfiles[1])
print(ncdf)
v(obj = ncdf, cbpos="r")

### option b) load and plot netcdf-file as RasterStack object
nc <- nc2raster(nfiles[1])
```

```

v(nc,cbpos="r") # plot RasterStack object

### option c) plot netcdf-file directly
v(nfiles[1], cbpos="r")
v(nfiles[1], cbpos="r", replace.na=TRUE)

##### plot multiple layers:
par(mfrow=c(2,2))
v(nfiles[1], t=1:4, cbpos="r", replace.na=TRUE, subplot = TRUE)

# ## Example 2: load & plot bathymetry data from the NOAA-ETOPO1 database
# par(mfrow=c(2,1))
# bathy <- get.bathy("medw4", terrain=T, res=3, keep=T, visualize=T, subplot = TRUE, grid=F)
# # load('bathy_medw4_res.3.dat', verbose = T); bathy <- h
# v(bathy, param="bathy", subplot = TRUE, terrain=F, levels=c(200,2000)) # show contours
#
# ## b) only contour lines:
# par(mfrow=c(1,2))
# h <- get.bathy("lion", terrain=F, res=3, visualize=T,
#               subplot=T, v_image = FALSE, levels=c(200,2000))
#
# ## use v-function for same plot but on subregion:
# v(h, v_area = "survey", param="bathy",
#   subplot=T, v_image = FALSE, levels=c(200,2000))

## Example 3: plot sample-'.gz'-file
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('*.*gz')
v(gz.files[2]) ## plot content of gz-file

## Example 4: load sample-'.gz'-file manually as Raster-object and plot it
obj <- readbin(gz.files[2], area='lion')
par(mfrow=c(1,2))
v(obj, param="sst", subplot = TRUE)
v(obj, param="Temp", subplot = TRUE) ## note unset "pal" (colormap) for unknown "param"-values!

## Example 5: available color maps
data('cmap') # load color maps data
names(cmap) # list available color maps

setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('*.*gz')
figure(width=15, height=15)
par(mfrow=c(4,5))
for(n in names(cmap)) v(gz.files[2], v_area='lion', subplot=TRUE,
                      pal=n, adaptive.vals=TRUE, main=n)

## define new color maps from blue to red to white:

```

```

n <- colorRampPalette(c('blue','red','white'))(100)
v(gz.files[2], v_area='lion', subplot=TRUE,
  pal=n, adaptive.vals=TRUE, main="own colormap")

## Example 6: available parameters
data(parameter_definitions)
names(parameter_definitions)
# ?parameter_definitions

setwd(system.file("test_files", package="oceanmap"))
figure(width=12, height=6.2)
par(mfrow=c(2,3))
v('*sst2*707*', v_area="medw4", main="sst", subplot=TRUE)
v('*chla*531*', v_area="medw4", main="chla", subplot=TRUE)
v('*chlgrad*', v_area="medw4", main="chlgrad", subplot=TRUE)
v('*p100*', v_area="medw4", main="p100 (oceanic fronts)", subplot=TRUE)
v('*sla*', v_area="medw4", main="sla", subplot=TRUE)
# h <- get.bathy("medw4", visualize=TRUE, terrain=F, res=4, subplot=TRUE, main="bathy")

##### advanced example section:

## Example I: plot bathymetry using a v_area-keyword
## requires server connection!
# par(mfrow=c(2,1))
# v("bathy", "lion", res=4, keep=TRUE, border='grey', subplot=TRUE,
#   main='Gulf of Lions bathymetry', cb.title="resolution 4 min")

# v("bathy", "lion", res=1, keep=TRUE, border='grey', subplot=TRUE,
#   cb.title="resolution 1 min") # can take some time depending on server connection!

## Example II: plot bathymetry of the Baltic Sea defined by longitude and latitude coordinates
## requires server connection!
lon <- c(9, 31)
lat <- c(53.5, 66)
#v("bathy", lon=lon, lat=lat, main="Baltic Sea")

## Example III: plot landmask of the Baltic Sea defined by an extent- or raster-object
## requires server connection!
library('raster')
ext <- extent(lon, lat)
# v("bathy", ext, main="Baltic Sea", res=4, levels=200) # extent-object

## Example IV: plot '.gz'-files, following default plot-procedure
owd <- getwd()
setwd(system.file("test_files", package="oceanmap"))
check_gzfiles() # return file summary-table
gz.files <- Sys.glob('*.*gz') # load sample-'.gz'-files
v(gz.files[1:4])
v(gz.files[4], bwd=2)

```

```

## Example V: plot climatologies from '.gz'-files
##           (ATTENTION: not working for non-'gz'-files, requiring ImageMagick)
clim_plot('*1s*.gz',bwd=0.7,adaptive.vals=TRUE,plotname="seasonal_climatology.png")

## Example VI: plot subregion of gz-files as subplots
graphics.off()
par(mfrow=c(2,1))
v(gz.files[1:2],v_area='lion',subplot=TRUE) # run ?region_definitions to see predefined regions

## Example VII: plot subregion of raster file

# all manual:
obj <- readbin(gz.files[2],area='lion')
dev.new()
ticks <- seq(20,30,5)
par(mar=c(5,4,5,8))
image(obj,zlim=range(ticks),col=cmap$jet)
plotmap('lion',add=TRUE) # add landmask
# set.colorbar(ticks=ticks,cb.title='cb.title',cb.xlab='cb.xlab')

# using v, reconstructing region information
obj <- readbin(gz.files[2],area='lion')
v(obj,varname="sst2",cb.title='cb.title',cb.xlab='cb.xlab')

# using v for another subregion
ncorse <- crop(obj,extent(6,9,40,42))
# v(ncorse,grid.res=1)
# v(ncorse,zlim=c(20,30),cbx=c(8.3,8.9),cby=c(40.7,40.8)) # skipping colorbar widget

## Example VIII: Add region by supplying raster-object, colorbar positions and running the widget
#add.region(ncorse,cbx=c(8.3,8.9),cby=c(40.7,40.8))

## Example IX: plot netcdf-files ('.nc'-files)
nfiles <- Sys.glob('*.*.nc') # load sample-'.nc'-files
head(nfiles)

## plot herring larval dispersal from Bauer et al. (2013)
# par(mfrow=c(2,2))
# v(nfiles[1], subplot=TRUE, t=1:4,minv=0, maxv=1000, adaptive.vals=FALSE, replace.na=TRUE)
# par(new=TRUE,mfrow=c(1,1))
# empty.plot(main='herring larval dispersal in the Greifswald lagoon, Germany')
# mtext('see Bauer et al. (2013) as reference')

# plot bathymetric data (obtained from the Leibniz Institute for Baltic Sea Research Warnemuende)
# v(nfiles[2],varname='bathymetry') # following default plot-procedure
# v(nfiles[2],varname='bathymetry',pal='haxbyrev',Log=TRUE, cb.xlab='depth [log m]',levels=50)

```

v-class	<i>v-classes</i>
---------	------------------

Description

internal dummy classes used by [v](#).

writebin	<i>Saves geographic data as byte file ('.gz')</i>
----------	---

Description

Saves geographic data as byte file, in gzip compressed format ('.gz'). **ATTENTION!!** Only 2D (one layer) can be stored!

Usage

```
writebin(satdata, filename, param)
```

Arguments

satdata	one layer- raster -object or matrix holding spatial data.
param	character string indicating the parameter name for the dataset treatment. See parameter_definitions for available parameters.
filename	character string naming the '.gz'-file to be created.

Author(s)

Robert K. Bauer

See Also

[readbin](#), [regions](#), [crop](#), [raster2matrix](#), [param_unconvert](#)

Examples

```
## Example for selecting wrong area definition when saving files
setwd(system.file("test_files", package="oceanmap"))
gz.files <- Sys.glob('med4*.gz') # load sample-med4'.gz'-files
v(gz.files[1])

fname <- name_split(gz.files[1])
param <- fname$parameter
gz <- readbin(gz.files[1])
dim(gz)
v(gz.files[1])
```

```
### reset region name
fname$area <- 'med9'
fname <- name_join(fname)
# writebin(gz,fname,param=param)
# v(fname)
# system(paste('rm', fname))

### multi layer raster file
gz2 <- stack(gz,gz)
# writebin(gz2,rep(gz.files[1],2),param) # error message since multi layer
# writebin(gz,gz.files[1],param) # single layer raster file
# v(gz.files[1])
```

Index

- *Topic **bathymetry**
 - get.bathy, 16
 - v, 37
- *Topic **colorbar**
 - cmap, 12
 - set.colorbar, 35
- *Topic **image plot**
 - get.bathy, 16
 - set.colorbar, 35
 - v, 37
- *Topic **parameter_definitions**
 - param_convert, 26
 - parameter_definitions, 25
 - readbin, 31
 - writebin, 45
- *Topic **region_definitions**
 - add.region, 3
 - area_extrac, 6
 - delete.region, 13
 - region_definitions, 33
- *Topic **widget**
 - set.colorbar, 35
 - .get.worldmap, 2
- add.region, 3, 6, 10, 13, 14, 16, 17, 24, 27, 31–34, 38, 40
- area_extrac, 6
- bathy-class (v-class), 45
- bindate2main (bindate2Title), 7
- bindate2Title, 7
- bindate2ylab (bindate2Title), 7
- check_gzfiles, 8, 9, 20, 21
- check_ts, 9, 9
- clim_plot, 10, 12, 41
- close_fig, 11, 16, 24
- cmap, 10, 12, 36, 39
- cmap_topo (cmap), 12
- crop, 6, 31, 45
- data.frame, 20, 21
- delete.region, 5, 13, 27, 32, 33
- empty.plot, 14
- extent, 3, 4, 27
- fields, 31
- figure, 11, 12, 15, 24
- get.bathy, 12, 16, 17, 24
- get.gz.info (name_split), 20
- gz-class (v-class), 45
- image, 12
- image.plot, 12, 31
- internal.datasets, 18
- matrix, 31, 45
- matrix2raster, 18
- medm9_proj (internal.datasets), 18
- name_join, 19, 21
- name_split, 7, 9, 11, 20, 20, 21, 37, 41
- nc-class (v-class), 45
- nc2raster, 22
- nc2time, 23
- ncdf4-class (v-class), 45
- oceanmap, 24
- par, 40
- param_convert, 25, 26, 31
- param_unconvert, 6, 25, 26, 45
- param_unconvert (param_convert), 26
- parameter_definitions, 25, 31, 36, 38, 39
- plot, 14
- plot.window, 27
- plotmap, 3, 5, 11, 17, 24, 27, 33, 34, 41
- range, 18
- raster, 24, 31, 38, 45

`raster2array (raster2matrix)`, 30
`raster2matrix`, 6, 30, 31, 45
`readbin`, 6, 11, 18, 25, 26, 30, 31, 41, 45
`region_definitions`, 3, 5, 6, 8, 10, 13, 14, 16, 17, 27, 31, 32, 33, 38, 40
`regions`, 3, 5, 6, 11, 14, 17, 28, 31, 32, 33, 41, 45
`regions.dim.bathy (internal.datasets)`, 18

`set.colorbar`, 24, 27, 35
`set.colorbarp (set.colorbar)`, 35

`text`, 36
`title`, 39

`v`, 3, 5, 7, 11, 12, 17, 24, 25, 27, 28, 33, 36, 37, 41, 45
`v.bathy-method (v)`, 37
`v.character-method (v)`, 37
`v.gz-method (v)`, 37
`v.nc-method (v)`, 37
`v.ncdf4-method (v)`, 37
`v.RasterBrick-method (v)`, 37
`v.RasterLayer-method (v)`, 37
`v.RasterStack-method (v)`, 37
`v-class`, 45
`v.bathy (v)`, 37
`v.gz (v)`, 37
`v.plot (v)`, 37
`v.raster (v)`, 37

`worldHires`, 2, 3
`writebin`, 4, 6, 14, 17, 25, 26, 30, 31, 45