

MplusAutomation Examples

Michael N. Hallquist

Package version 0.3-1

Contents

1 Overview	2
2 Installing and loading the package	2
3 Running batches of Mplus models	2
3.1 Basic use of runModels	2
3.2 Advanced use of runModels	3
3.2.1 Recursing through subdirectories	3
3.2.2 Logging the outcome of runModels	3
3.2.3 Skipping models with existing output files	3
3.2.4 Displaying R output in the console	4
4 User-friendly interface to runModels	4
5 Extracting model summary statistics	4
5.1 Listing of summary statistics extracted by extractModelSummaries	5
6 Extracting model parameters	6
7 Summarizing model fit statistics in tabular form	6
7.1 Displaying the summary table on the screen	6
7.2 Creating a summary table in HTML	7
7.3 Creating a summary table in LaTeX	7
8 Creating a group of models from an Mplus template file (createModels)	7
8.1 Init section	8
8.1.1 Required init definitions	9
8.2 Tag types	10
8.2.1 Simple tags	10
8.2.2 List tags	11

8.2.3	Iterator tags	12
8.2.4	Conditional tags	12
8.3	A Complete Example	12
8.4	Caveats and limitations	14
8.4.1	Circular tag definition	14
8.4.2	Conditional logic for multiple conditions	14

1 Overview

This guide provides examples of how to use the functions in the `MplusAutomation` package. The package is designed to automate three major aspects of latent variable modeling in Mplus: 1) creating related groups of models, 2) running batches of models, and 3) extracting and tabulating model parameters and fit statistics.

The guide tries to make few assumptions about the user's familiarity with the R environment, as many Mplus user's may be unfamiliar with R. Note that the `MplusAutomation` package was written to be compatible with Mplus version 5.21 or later. Although many functions are likely to work with earlier versions, there are also known incompatibilities (e.g., extraction of standardized estimates using `extractModelParameters`).

Note: some examples herein reference examples from the Mplus User's Guide. The input and output files for these examples are assumed to reside in the directory: `C:\Program Files\Mplus\Mplus Examples\User's Guide Examples`. If you have installed Mplus to a different location, please use the correct directory in the code below.

2 Installing and loading the package

The package was built using R 2.11.0, although it should be compatible with older versions of R. To obtain R 2.11.0 for Windows, follow this link: <http://cran.r-project.org/bin/windows/base/R-2.11.0-win32.exe>

After installing the program and launching R, type the following at the command line:

```
> install.packages("MplusAutomation", .Library)
```

Depending on which version of Windows you're using, you may need to run R as an administrator (right-click, Run as administrator).

To load the `MplusAutomation` package so that its functions are available to use, type:

```
library(MplusAutomation)
```

3 Running batches of Mplus models

A major purpose of the `MplusAutomation` package is to allow for easy runs of batches/groups of Mplus models. Oftentimes, one wants to compare a group of related models, such as testing for different forms of measurement invariance. Depending on the complexity of the models, Mplus can take several minutes to many hours to run each model. The `runModels` routine is designed to run a group of related models located within a directory (or nested subdirectories).

3.1 Basic use of `runModels`

As an example, say that we want to run all of the models used in the Mplus 5.1 Addendum: <http://statmodel.com/download/examples1.pdf>. The input files for these are located in: `C:\Program Files\Mplus\Mplus Examples\Addendum Examples`.

To run this batch, enter this at the command line:

```
> runModels("C:/Program Files/Mplus/Mplus Examples/Addendum Examples")
```

Note that you need to use forward slashes ("/"), not backslashes("\") in the path name. Alternatively, you could use double backslashes (e.g., "C:\\Program Files" etc.).

3.2 Advanced use of runModels

3.2.1 Recursing through subdirectories

Sometimes it is useful to organize models into one or more subdirectories where each subdirectory contains models for a particular outcome or analytic approach. For example, if one were contrasting latent class analysis (LCA) with confirmatory factor analysis (CFA), one could place all LCA models in a single directory and place CFA models in a different directory. This might yield a file structure like this:

```
ComparingLCAvCFA/LCA/1-class LCA.inp
ComparingLCAvCFA/LCA/2-class LCA.inp
ComparingLCAvCFA/LCA/3-class LCA.inp
```

```
ComparingLCAvCFA/CFA/1-factor CFA.inp
ComparingLCAvCFA/CFA/2-factor CFA.inp
ComparingLCAvCFA/CFA/3-factor CFA.inp
```

In this case, all Mplus files for the larger project are housed within a parent directory, `ComparingLCAvCFA`. To run all models within `ComparingLCAvCFA`, including models within any subdirectories (including LCA and CFA), use the `recursive` parameter of `runModels`.

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE)
```

3.2.2 Logging the outcome of runModels

The `logFile` parameter of `runModels` allows the user to specify a text file containing the results of `runModels`. Included in the log file are the parameters passed to the function, the date when the batch started, which models were run (and which were skipped), and any actions taken if the R process was interrupted (e.g., terminating the Mplus process). By default, `runModels` will create a log file in the same directory as the models to be run, `directory`, called `Mplus Run Models.log`. To change the name or location of this file, specify the `logFile` parameter, such as in this example:

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE, logFile="C:/CFALCA-Comparison-Log.txt")
```

Here, the file `C:/CFALCA-Comparison-Log.txt` will be created in the directory `C:/`.

To specify that no log file should be created, pass `logFile=NULL` to `runModels`.

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE, logFile=NULL)
```

3.2.3 Skipping models with existing output files

Sometimes it is useful to skip models that have already been run to avoid the computing time associated with running all input files within a directory. The `replaceOutfile` parameter allows one to specify which models should be re-run, where models that have an output with the same filename as the input file are considered to have been run. By default, `replaceOutfile="always"`, meaning that all input files will be run, regardless of whether they have a matching output file.

To skip any model that already has an existing output file, pass `replaceOutfile="never"` to `runModels`, such as in this example:

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE, replaceOutfile="never")
```

Oftentimes, after a model or group of models has been run, it is necessary to modify some aspects of the parameterization to improve model fit or address estimation problems. In such cases, output files are inspected and the corresponding input

files are modified. In such cases, one may only want to run models that have been updated, but not to re-run models that completed successfully. This can be accomplished by passing `replaceOutfile="modifiedDate"` to `runModels`. The "modifiedDate" determines whether there is an existing output file for a given input file. If there is, it checks to see whether the date the input file was modified is *newer* than the output file. If the input file is newer, then the model is run. Otherwise, it is skipped. Here is an example:

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE, replaceOutfile="modifiedDate")
```

3.2.4 Displaying R output in the console

When models are run by the Mplus Windows program (MplusWin.exe), a separate DOS window appears that documents the TECH8 progress of the model, which represents the progress toward maximum-likelihood convergence for the model (including random starts and final stage optimizations for some models). To display the same TECH8 output for models run by `runModels`, pass `showOutput=TRUE` to the `runModels` function.

```
> runModels("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE, showOutput=TRUE)
```

If the R session was started through the R GUI (Rgui.exe), the output will be displayed within the R window. If the R session was started using Rterm (the R terminal), a separate DOS window will display the output, as occurs using the built-in Mplus Windows program.


By default, the output is not shown, `showOutput=FALSE`.

4 User-friendly interface to runModels

A wrapper function, `runModels_Interactive`, is included in the `MplusAutomation` package, which provides a simple dialog box for specifying which models to run. To start the interface, type the following:

```
> runModels_Interactive()
```

The picture below documents the appearance of this interface:



Although one can provide parameters to the function to set the initial states of the interface, it is rarely necessary to do so, so the syntax above should suffice.

5 Extracting model summary statistics

Another major purpose of the package is to allow for easy extraction of model summary statistics from a group of models. Such summary statistics include items such as log-likelihood values, root mean squared error of approximation (RMSEA),

and Akaike's Information (AIC).

The `extractModelSummaries` function is designed to extract model summaries from a group of models located within a directory (or nested within subdirectories). This function returns a `data.frame` containing one row per model, with columns representing several fit statistics.

A basic call to the function includes the directory containing output files to be parsed:

```
> mySummaries <- extractModelSummaries("C:/Data_Analysis/ComparingLCAvCFA", recursive=TRUE)
```

Now, the variable `mySummaries` is a `data.frame` containing summary statistics about models contained in the `ComparingLCAvCFA` directory.

As with `runModels`, `extractModelSummaries` includes a `recursive` parameter that specifies whether to parse output files located in subdirectories beneath the target directory (defaults to `FALSE`).

In addition, `extractModelSummaries` also includes a parameter, `filefilter`, that allows the user to parse only files matching certain search criteria. `filefilter` accepts a Perl-compatible regular expression string. If you're unfamiliar with regular expressions in Perl, I suggest these two websites:

<http://www.pcre.org/pcre.txt>

<http://www.regular-expressions.info/>

Note that many regular expression in Perl rely on backslashes (`\`) for defining character classes, escaping certain characters, and so on. In R, backslashes contained in strings must be doubled (i.e., `\\`).

Here is an example of filtering only files that match "ex4" followed by any characters. Note that the function automatically searches only files with the `.out` extension, so it isn't necessary to include `.out` in the file filter.

```
summaryStats <- extractModelSummaries("C:/Program Files/Mplus/Mplus Examples/User's Guide  
Examples/Outputs", filefilter="ex4.*")
```

Here is a more complex filter that matches filenames that begin with the digits 1, 2, or 3 (for 1-class, 2-class, or 3-class output files) and also contain the text "Threshold":

```
summaryStats <- extractModelSummaries("C:/Data_Analysis/Multiclass Models",  
filefilter="[123]{1}-class.*Threshold.*")
```

5.1 Listing of summary statistics extracted by `extractModelSummaries`

As of this version of the package (0.3-1), the following summary statistics are automatically extracted, when available:

- **Title:** Title for the model, specified by the `TITLE:` command
- **Filename:** Filename of the output file
- **InputInstructions:** A string containing the full input syntax for the model
- **Estimator:** Estimator used for the model (e.g., ML, MLR, WLSMV, etc.)
- **LL:** Log-likelihood of the model
- **BIC:** Bayesian Information Criterion
- **aBIC:** Sample-Size-Adjusted BIC (Schlove, 1987)
- **AIC:** Akaike's Information Criterion
- **AICC:** Corrected AIC, based on Sugiura (1978) and recommended by Burnham & Anderson (2002)
- **Parameters:** Number of parameters estimated by the model
- **Observations:** The number of observations for the model (does not support multiple-groups analysis at this time)
- **CFI:** Confirmatory Fit Index
- **TLI:** Tucker-Lewis Index
- **RMSEA_Estimate:** Point estimate of root mean squared error of approximation
- **RMSEA_90CI_LB:** Lower bound of the 90% Confidence Interval around the RMSEA estimate
- **RMSEA_90CI_UB:** Upper bound of the 90% Confidence Interval around the RMSEA estimate
- **RMSEA_pLT05:** Probability that the RMSEA estimate falls below .05, indicating good fit

- **ChiSqM_Value**: Model chi-squared value
- **ChiSqM_DF**: Model chi-squared degrees of freedom
- **ChiSqM_PValue**: Model chi-squared p value
- **BLRT_KM1LL**: Log-likelihood of the K-1 model (one less class) for the Bootstrapped Likelihood Ratio Test (TECH14)
- **BLRT_PValue**: P-value of the Bootstrapped Likelihood Ratio Test (TECH14) testing whether the K class model is significantly better than K-1
- **BLRT_Numdraws**: The number of bootstrapped samples used in the Bootstrapped Likelihood Ratio Test
- **SRMR**: Standardized root mean square residual
- **WRMR**: Weighted root mean square residual
- **ChiSqBaseline_Value**: Baseline (unstructured) chi-squared value
- **ChiSqBaseline_DF**: Baseline (unstructured) chi-squared degrees of freedom
- **ChiSqBaseline_PValue**: Baseline (unstructured) chi-squared p value

The `extractModelSummaries` function is designed to work in conjunction with functions that generate tables of summary statistics.

6 Extracting model parameters

The `extractModelParameters` function extracts the model parameters from the MODEL RESULTS section of a given Mplus output file. Parameters include the parameter estimate, std. err, param/s.e., and two-tailed p-value. Model results are returned as a `data.frame` object.

Example:

```
modelResults <- extractModelParameters("C:/Data_Analysis/Mplus Output.out", "stdyx")
```

This call will return a `data.frame` object with all model parameters from the STDYX standardization section of the output.

This function returns a `data.frame` containing the model parameters for the section specified above. Variables include

1. **paramHeader**: The header that begins a given parameter set. Example: "FACTOR1 BY"
2. **param**: The particular parameter being measured (within **paramHeader**). Example: "ITEM1"
3. **paramest**: Parameter estimate value
4. **se**: Standard error of the estimate
5. **est_se**: Quotient of **paramest/se**, representing z-test/t-test in large samples
6. **pval**: Two-tailed p-value for the **est_se** quotient

7 Summarizing model fit statistics in tabular form

Once summary statistics for a group of models have been extracted, it is often useful to display them in tabular form to compare fit among models, sorted by a particular criterion (e.g., AIC).

The `MplusAutomation` package provides three routines for tabulating model summary statistics. At this time, there are three table-generating functions, which are detailed below: `showSummaryTable`, `HTMLSummaryTable`, `LatexSummaryTable`.

As their names suggest, these functions can create tables for on-screen display (`showSummaryTable`), as an HTML file containing the table (`HTMLSummaryTable`), or as a LaTeX-formatted table (`LatexSummaryTable`).

7.1 Displaying the summary table on the screen

The `showSummaryTable` function is designed to display a summary table of model fit statistics on the screen. The function expects a model list created by `extractModelSummaries` and allows the user to specify which columns should be included in the table.

Here is a simple example of using `showSummaryTable` by specifying which columns to keep in the table:

```
showSummaryTable(summaryStats, keepCols=c("Title", "LL", "AIC", "BIC", "CFI"), sortBy="AIC")
```

And another example specifying that all columns in the model list should be displayed *except* those specified:

```
showSummaryTable(summaryStats, dropCols=c("InputInstructions", "Observations", "Parameters"),
  sortBy="CFI")
```

7.2 Creating a summary table in HTML

The `HTMLSummaryTable` function creates an HTML file containing a summary table of model fit statistics. Its syntax is very similar to `showSummaryTable`, including parameters such as `dropCols`, `keepCols`, and `sortBy`. Two parameters distinguish it from other summary functions: `filename` and `display`.

The `filename` parameter specifies the path and filename of the HTML file to be created. `display` specifies whether to display the HTML summary table in the web browser after it is created. Here is a simple of using the function:

```
HTMLSummaryTable(summaryStats, filename="C:/MyModelSummary.html", display=TRUE, keepCols=c("Title",
  "LL", "AIC", "BIC", "AICC"), sortBy="AIC")
```

7.3 Creating a summary table in LaTeX

One major strength of R is its ability to be interwoven with LaTeX, an advanced typesetting language. The most frequently used approach for combining R and LaTeX is Sweave (<http://www.stat.uni-muenchen.de/~leisch/Sweave/>), a built-in R function that runs R code embedded in a LaTeX document, thereby permitting the creation of advanced automated reports.

Mplus model fit summary tables can be formatted in LaTeX using the `LatexSummaryTable` function. Unlike `showSummaryTable` and `HTMLSummaryTable`, `LatexSummaryTable` returns a value, specifically the LaTeX syntax for the summary table. Here is a simple example of the function

```
myLatexTable <- LatexSummaryTable(summaryStats, keepCols=c("Title", "BIC", "Parameters"),
  sortBy="Parameters",
  caption="Comparing CFA vs. LCA according to number of parameters", label="CFALCATAB")
```

Note that `LatexSummaryTable` supports two distinct parameters relative to other summary table functions: `caption` and `label`. These allow the user to set the caption and label properties of the table, which are used in LaTeX for displaying a caption with the table and for allowing the table to be easily referenced in other parts of document, respectively. See http://en.wikibooks.org/wiki/LaTeX/Tables#The_table_environment_-_captioning_etc for further details about LaTeX tables.

The LaTeX syntax for a summary table could be included in an Sweave document in the following way:

```
<<echo=TRUE, results=tex>>=
myLatexTable <- LatexSummaryTable(summaryStats, keepCols=c("Title", "BIC", "Parameters"),
  sortBy="Parameters", caption="Comparing CFA vs. LCA according to number of parameters",
  label="CFALCATAB")
```

```
print(myLatexTable)
```

```
@
```

See the Sweave manual for more details about combining LaTeX with R.

8 Creating a group of models from an Mplus template file (createModels)

The third major focus of the `MplusAutomation` package is to provide tools that automate the process of creating input files for a related group of models. Perhaps the simplest example of a related group of models is latent class analysis, where one

runs a certain model with different numbers of classes, but the input files are otherwise the same.

The `createModels` function converts a single Mplus template file into a set of related Mplus input files. The template language is a simple extension of the Mplus language that allows dynamic values to be inserted into Mplus syntax files while reusing most of the code. The basic notion for template files is that multiple input files are created by looping over one or more variables (called "iterators") and substituting specific values that change for each model, thereby allowing for the creation of related input files that share much of the code. As a basic example, one might iterate over a set of outcome variables (e.g., positive emotions, negative emotions, and conscientiousness) in a growth model where the dataset remains fixed, but the outcome variables change.

Mplus template syntax files are divided into two sections: the init section and the body section. The init section consists of definitions for variables to be inserted in the Mplus syntax, instructions for determining the filename and directory for created input files, and the variables to loop over to create multiple Mplus input files. The body section consists of Mplus syntax with template tags included where certain variables will change (e.g., the number of classes, names of outcome variables, etc.). Tags in Mplus syntax language are demarcated by double brackets. For example, the tag `[[outcomeName]]` requests that the value of `outcomeName` provided in the init section be inserted into the Mplus syntax file.

Before we get into details, a particularly simple example may make the general concepts more tangible. This example is adapted from Mplus User's Guide Example 7.3: LCA with binary latent class indicators using automatic starting values with random starts.

```
[[init]]
iterators = classes;
classes = 1:7;
filename = "[[classes]]-class LCA 7.3.inp";
outputDirectory = "C:/Mplus_Automation/LCA Outputs";
[/init]]
```

```
TITLE: this is an example of a LCA with binary
latent class indicators using automatic
starting values with random starts
DATA: FILE IS ex7.3.dat;
VARIABLE: NAMES ARE u1-u4 x1-x10;
USEVARIABLES = u1-u4;
CLASSES = c ([[classes]]);
CATEGORICAL = u1-u4;
AUXILIARY = x1-x10 (e);
ANALYSIS: TYPE = MIXTURE;
OUTPUT: TECH1 TECH8 TECH10;
```

The above template file instructs the `createModels` function to loop over a variable called `classes`. The `classes` variable is defined as the integers from 1-7 (the colon in 1:7 indicates a sequence). Files should be named according to the number of classes, so when `classes = 5`, then `filename = "[[classes]]-class LCA 7.3.inp"`; will evaluate to `5-class LCA 7.3.inp`. All files will be saved in the directory `C:/Mplus_Automation/LCA Outputs`. Note that R uses forward slashes, not backslashes, to indicate directory paths.

In the body section of this simple example, the only thing that changes is the definition `CLASSES = c ([[classes]])`. And because `classes` was defined as the integers from 1-7, 7 Mplus input files will be created by `createModels` with the major difference being the number of classes. As `createModels` loops over the `classes` variable, the current value of `classes` is inserted in the body section.

8.1 Init section

The init section consists of variable definitions that are used to specify which variables are iterators, the number of iterations/models to loop over, the filenames and directories for the input files created by `createModels`, and the fields to be inserted in the body section where template tags are specified. Variable definitions in the iterator section use the syntax `variable = value;`. Variable names are case-sensitive and value fields can span multiple lines. All definitions must be terminated by a semicolon. In cases where the variable's value is a series of items (e.g., `outcome1`, `outcome2`, `outcome3`, these should be specified as a space-separated list (either using spaces or tabs). For example, if one wants to link a particular variable to an iterator and for the value of that list to be included in the body section, the definitions might look something

like:

```
[[init]]
iterators = outcome;
outcome = 1:4;
outcomeNames#outcome = Conscien Extraver Agreeabl Openness;
filename = "CFA for [[outcomeNames#outcome]].inp";
outputDirectory = C:/;
[[/init]]
```

Here, four input files will be created corresponding to four different outcome variables: Conscien, Extraver, Agreeabl, and Openness (which are all presumably defined in the body section of the template). The main point here is that the `outcomeNames` variable is defined as a four-item list, not as a single value. In cases where the values of a variable need to contain spaces, be sure to include the values in double quotes. For example, we might modify the `outcomeNames` field to be:

```
outcomeNames#outcome = "Conscientiousness Score" "Extraversion Score" "Agreeableness Score" "Openness Score";
```

This point deserves a emphasis: **spaces are assumed to specify distinct values unless they are enclosed in double quotes**. This behavior is similar to the Mplus language, where syntax such as `VARIABLES = var1 var2 var3;` defines three distinct variable names. Even where a given variable in the `init` section has only one value (such as `filename` above), double quotes must be used if the spaces are to be included in the created files, rather than being interpreted as a list.

8.1.1 Required init definitions

Three variables must be defined for all Mplus template files.

First, the `iterators` variable defines which variables in the `init` section are iterators (i.e., integer variables to be looped over to create the input files). Iterators will be looped over in the order specified by the definition of `iterators`. Here is an example of three iterators that will create a total of 60 files ($4 \times 5 \times 3$).

```
[[init]]
iterators = outcome model classes;
outcome = 1:4;
model = 1:5;
classes = 2 3 4;
filename = "[[classes]]-class Model.inp";
outputDirectory = C:/Data/[[outcome]]/[[model]];
[[/init]]
```

In the above example, the program will loop over `outcome`, `model`, and `classes` in that order. So the first file to be created would be `outcome=1, model=1, classes=1`, the second model would be `outcome=1, model=1, classes=2`, etc. For the more technical reader, iterators are processed recursively from left to right (here, `classes` within `model` within `outcome`). The top-most iterator is `outcome` and the bottom-most is `classes`. Don't worry too much about this, though. In most cases, the ordering does not matter much and one generally will not have to think about how the program handles the iterators.

The **second** required `init` variable is `filename`. This variable defines the filenames for input files created by the `createModels` function. In general, these should end in ".inp" to be consistent with Mplus conventions. Other tags can be (and probably should be) included in the filename definition. The idea is that the combination of `filename` and `outputDirectory` should define a unique file/path for *each* input file created by the `createModels` function. Remember that if your filename contains any spaces, please use double quotes.

The **third** required `init` variable is `outputDirectory`. This variable defines the directory (or directories) where input files should be saved. **Please note:** If directories specified by `outputDirectory` do not exist, the `createModels` function will create them, so be careful that the path is correct. If no output directory is specified, `createModels` will place the input files in the R working directory (viewable by `getwd()` and settable by `setwd()`), but it is preferable always to specify an output directory. If an `outputDirectory` is not an absolute path (i.e., one that begins with a drive letter, such as `C:\`), then the top level of the output directory will be placed within the R working directory. Consider this value of `outputDirectory`:

```
[[init]]
iterators = outcome model;
outcome = 1:2;
model = 1:3;
```

```

outcomeName#outcome = Outcome1 Outcome2;
modelName#model = Model1 Model2 Model3;
outputDirectory = "C:/CFA/[[outcomeName#outcome]]/[[modelName#model]]";
filename="testfile.inp"
[[/init]]

```

The above syntax will create the following directory structure:

```

CFA/
CFA/Outcome1/Model1
CFA/Outcome1/Model2
CFA/Outcome1/Model3
CFA/Outcome2/Model1
CFA/Outcome2/Model2
CFA/Outcome2/Model3

```

It is generally recommended that users specify an absolute path (i.e., one that begins with a drive letter such as C:/) for `outputDirectory` to avoid any confusion about where the files will be saved. Note that it is typical to include tags in the definition of `outputDirectory` to allow for dynamic naming of the directories according to the model file being created. Consider this example, which defines both `filename` and `outputDirectory` to create a set of unique files:

```

[[init]]
iterators = outcome model;
outcome = 1:5;
model = 1:3;
outcomeDirNames#outcome = Conscientiousness Extraversion Agreeableness Openness Neuroticism;
modelName#model = Poisson "Negative Binomial" "Negative Binomial Hurdle";
filename = "[[modelName#model]] Growth Model.inp";
outputDirectory = "Template Output/[[outcomeDirNames#outcome]]";
[[/init]]

```

In this case, because the `outputDirectory` is not an absolute path (i.e., does not begin with a drive letter), a directory called "Template Output" will be created within the R working directory (`getwd`). Five subdirectories within "Template Output" will be created: "Conscientiousness", "Extraversion", "Agreeableness", "Openness", and "Neuroticism". Within each of those directories, three files will be created: "Poisson Growth Model.inp", "Negative Binomial Growth Model.inp", and "Negative Binomial Hurdle Growth Model.inp". The idea is that as `createModels` iterates over `outcome` and `model`, the appropriate values of `outcomeDirNames` and `modelName` will be inserted. As described in the *list tag* section below, the `#` separating the `modelName` and `model` terms indicates that with each iteration of `model`, the matching element of the `modelName` variable will be inserted.

8.2 Tag types

There are four types of tags supported by the Mplus template language.

1. *simple*: A value defined in the init section is substituted wherever the simple tag occurs in the body section, unrelated to the status of an iterator.
2. *list*: A certain element from a list of values is substituted depending on the value of the specified iterator.
3. *iterator*: The numeric value of the iterator is substituted.
4. *conditional*: A certain block of code is included only if a condition is met (e.g., `classes > 1`).

8.2.1 Simple tags

Simple tags refer to variables that are defined in the init section, but that do not change with respect to an iterator. In practice, these are often less useful than list tags. But simple tags are useful when a certain variable/word occurs in several places in the input file and might need to be changed throughout the model. In essence, a simple tag can act as a find/replace function: the value is defined once in the init section and is inserted in the body section wherever the tag occurs.

Here is a simple tag example that uses simple tags to specify the time scores in a latent growth curve model:

```
[[init]]
iterators = model;
model = 1:3;
t1ModelNames#model = Outcome1_t1 Outcome2_t1 Outcome3_t1;
t2ModelNames#model = Outcome1_t2 Outcome2_t2 Outcome3_t2;
t3ModelNames#model = Outcome1_t3 Outcome2_t3 Outcome3_t3;
time1 = 0;
time2 = 1;
time3 = 3;
outputDirectory=output;
filename=[modelOutcome#model].inp;
[/init]]
TITLE: [modelOutcomes#model] Latent Growth Curve Model
DATA: FILE = "testData.dat";
VARIABLE: NAMES ARE id outcome1 outcome2 outcome3 covariate1;
MODEL: i s | [[t1ModelNames#model]]@[[time1]] [[t2ModelNames#model]]@[[time2]]
        [[t3ModelNames#model]]@[[time3]];
PLOT: TYPE=PLOT3;
        SERIES=[[t1ModelNames#model]] ([[time1]]) [[t2ModelNames#model]] ([[time2]])
        [[t3ModelNames#model]] ([[time3]]);
        i s ON covariate1;
```

The key idea with respect to simple tags is that the time scores are inserted both for the model and plot sections. Then if one wanted to change the time scores, these would be included in both sections. This is a bit contrived since one could easily use the command `SERIES=[[t1ModelNames#model]]-[[t3ModelNames#model]] (s);`.

8.2.2 List tags

List tags are used to insert a given value from a list init variable (i.e., one that has more than one element) depending on the value of the related iterator. List init variables are always linked to a particular iterator and should have the same number of elements as that iterator. To indicate that a list tag is tied to a certain iterator, include the suffix `#<iterator>` after the variable name, where `<iterator>` is the iterator of interest. For example, if one is creating a template file to iterate over 3 variables in a growth model, this can be accomplished with a single iterator variable (e.g., `outcome`). When defining the variable names to be used in the Mplus syntax, list tags could be used as follows:

```
[[init]]
iterators = outcome;
outcome = 1:3;
modelName#outcome = "Outcome 1" "Outcome 2" "Outcome 3";
wave1Name#outcome = outcome1_w1 outcome2_w1 outcome3_w1;
wave2Name#outcome = outcome1_w2 outcome2_w2 outcome3_w2;
wave3Name#outcome = outcome1_w3 outcome2_w3 outcome3_w3;
outputDirectory=test;
filename="[modelName#outcome] Growth Model.inp";
[/init]]
TITLE: [modelName#outcome] Growth Model
DATA: FILE = "testData.dat";
VARIABLE: NAMES ARE id outcome1_w1 outcome1_w2 outcome1_w3
        outcome2_w1 outcome2_w2 outcome2_w3
        outcome3_w1 outcome3_w2 outcome3_w3;

        USEVARIABLES ARE [[wave1Name#outcome]] [[wave2Name#outcome]] [[wave3Name#outcome]];
MODEL:
        i s | [[wave1Name#outcome]]@0 [[wave2Name#outcome]]@1 [[wave3Name#outcome]]@2;
```

In this simple example, there are four list tags tied to the `outcome` iterator. One list tag, `modelName#outcome` defines the descriptive names for each model used in the title and filename. The other list tags (`wave1Name#outcome`, `wave2Name#outcome`, `wave3Name#outcome`) are used to specify the variable names at each wave for the current value of the `outcome` iterator.

8.2.3 Iterator tags

Iterator tags are used to insert the numeric value of a given iterator into the body section (or another init variable). These are most useful when the numeric value of the iterator conveys some useful meaning, as in the case of multiple latent classes in mixture modeling or measurement occasions in growth modeling.

An iterator tag example was given above, where Mplus User's Guide Example 7.3 was adapted to create a set of related models spanning 1-7 classes. The relevant line for an iterator tag was:

```
CLASSES = c ([[classes]]);
```

Here, the numeric value of the classes iterator (which ranged from 1 to 7) is inserted in the Mplus syntax in place of the `[[classes]]` tag.

8.2.4 Conditional tags

Conditional tags are used to specify the conditions under which a certain block of Mplus syntax should be included or excluded from generated input files. Unlike the other types of tags, conditional tags themselves do not substitute particular values into the input file. Rather, there is always an opening tag and a closing conditional tag that define a pair, and the syntax between these tags is included provided the condition is met.

The basic syntax for a conditional tag is: `[[<varname> <operator> <value>]]` where `varname` is the variable whose condition is to be checked, `operator` is a logical operator (currently supported are `==`, `!=`, `<`, `>`, `<=`, and `>=`, for "equal to", "not equal to", "less than", "greater than", "less than or equal to", and "greater than or equal to", respectively), and `value` is a numeric value or character string to be compared against. The closing tag is always identical to the opening tag, except that it is prefixed by a single forward slash (drawing from basic HTML/XML syntax). Here is a simple excerpt demonstrating a conditional tag:

```
[[init]]
iterators=model;
model=1:5;
var1=test1;
var2=test2;
var3=test3;
[[/init]]
[[model > 2]]
COUNT ARE [[var1]] [[var2]] [[var3]];
[[/model > 2]]
```

The closing tag must match the opening tag exactly (at this point, even use of spaces). Conditional tags may be placed on separate rows or may be placed on the same row as the syntax to be included/excluded. Multiple conditional tags may be placed on the same row. As further described in the caveats/limitations section below, only one condition may be checked using a conditional tag, but multiple conditions may be checked by nesting two tags. If the value to be checked (i.e., on the right side of the comparator) is a character string, enclose it in double quotes, such as:

```
[[modelName#model != "Poisson GMM"]]
!Mplus code specific to non-Poisson GMM models here
[[/modelName#model != "Poisson GMM"]]
```

8.3 A Complete Example

Here, we provide a complex complete example of a template file that generates 480 input files in numerous subfolders. This is probably overkill for most applications, but it gives a sense of what the language is capable of. The application here is growth mixture modeling for symptoms of DSM-IV personality disorders over time. There are 10 personality disorders and two groups of participants: high risk and low risk. In addition, one question of interest is whether a class constrained to 0 at the first measurement occasion with 0 growth captures a subgroup of participants. In addition, one might be interested in comparing whether these count data are better modeled by a continuous normal model versus a Poisson model, and whether Poisson GMM provides a better fit than Poisson latent class growth analysis (LCGA). All of these considerations are reflected in this single template file. As a sane default, we chose to generate models that vary between 1 and 4 latent trajectory classes.

```

[[init]]
iterators = outcome group model classes zeroclass;
outcome = 1:10;
group = 2 5;
model = 1:3;
classes = 1:4;
zeroclass = 1:2;

outcomenames#outcome = Paranoid Schizoid Schizotypal Antisocial
    Borderline Histrionic Narcissistic Avoidant Dependent OCPD;

groupnames#group = "Low Risk" "High Risk";

modelnames#model = "Normal LGCM" "Poisson GMM" "Poisson LCGA";

zeroclassnames#zeroclass = "" " with zero class";

#wave names are with respect to the outcome iterator
w1name#outcome = Paran1 Szoid1 Sztyp1 Anti1 Border1 Hist1
    Narc1 Avoid1 Depend1 OCPD1;
w2name#outcome = Paran2 Szoid2 Sztyp2 Anti2 Border2 Hist2
    Narc2 Avoid2 Depend2 OCPD2;
w3name#outcome = Paran3 Szoid3 Sztyp3 Anti3 Border3 Hist3
    Narc3 Avoid3 Depend3 OCPD3;

filename = "[[classes]]-class [[groupnames#group]] [[outcomenames#outcome]]
    [[modelnames#model]] [[zeroclassnames#zeroclass]].inp";
outputDirectory = "PD
    GMM/[[outcomenames#outcome]]/[[groupnames#group]]/Unconditional_Models/[[modelnames#model]]";
[[/init]]

TITLE: [[classes]]-class [[outcomenames#outcome]] [[groupnames#group]] [[modelnames#model]]
    Unconditional Model[[zeroclassnames#zeroclass]]
DATA: FILE = "personality_mplus.dat";
VARIABLE: NAMES ARE
    id group sex age Paran1 Szoid1 Sztyp1 Anti1 Border1 Hist1 Narc1 Avoid1 Depend1
        OCPD1 PaAg1 Sadist1 SelfDef1 Paran2 Szoid2 Sztyp2 Anti2 Border2 Hist2 Narc2
        Avoid2 Depend2 OCPD2 Paran3 Szoid3 Sztyp3 Anti3 Border3 Hist3 Narc3 Avoid3
        Depend3 OCPD3;

MISSING ARE .;
USEVARIABLES ARE [[w1name#outcome]] [[w2name#outcome]] [[w3name#outcome]];
USEOBSERVATIONS ARE group EQ [[group]]; ![[groupnames#group]] Only

[[model > 1]]
COUNT ARE [[w1name#outcome]] [[w2name#outcome]] [[w3name#outcome]];
[[/model > 1]]
CLASSES = c ([[classes]]);

ANALYSIS:
    TYPE = MIXTURE;
    STARTS = 1000 10;
    K-1STARTS = 750 6;
    PROCESSORS = 4;
    [[model = 2]]
    ALGORITHM = INTEGRATION;
    [[/model = 2]]

MODEL:

%OVERALL%

```

```

Int Slope | [[w1name#outcome]]@0 [[w2name#outcome]]@0.97 [[w3name#outcome]]@2.77;

[[classes > 1]]
[[zeroclass = 2]]
!creates a class with all zeros at all time points
[[model=1]]
%c#2%
[Int@0 Slope@0];
Int@0 Slope@0;
[[/model=1]]
[[model>1]]
%c#2%
[Int@-15 Slope@-15];
Int@0 Slope@0;
[[/model>1]]
[[/zeroclass = 2]]
[[/classes > 1]]

PLOT:
    Type = PLOT3;
    Series = [[w1name#outcome]] (0) [[w2name#outcome]] (0.97) [[w3name#outcome]] (2.77);
OUTPUT: TECH1 TECH4 [[model != 1]]TECH10 [[/model != 1]] [[classes > 1]]TECH11 TECH14 [[/classes >
1]]STANDARDIZED RESIDUAL;

```

Rather than detailing this file line-by-line, a few points will be highlighted. First note that the `group` iterator has values of 2 and 5, which are non-contiguous and do not start at zero. This is fine for iterators, but note that the `groupnames#group` list variable has two elements (not 5). The essential idea is that iterators can take on any values (assuming they are unique) and the elements of the corresponding list tag should match one-to-one with the order of values (left to right) of the iterator.

Second, notice that conditional tags are used to specify that the numerical integration algorithm should only be used for model 2, which refers to Poisson GMM, whereas Poisson LCGA and Normal GMM do not require these features. Third, notice how two conditional tags are used on the last line to indicate when TECH10, TECH11, TECH14 should be included in the model estimation (TECH10 is only relevant for count outcomes and TECH11 and TECH14 are only relevant for multi-class models). Lastly, notice how nested conditional tags are used to specify a large block of code that is included only when creating a model with `classes > 1` and `zeroclass = 2`. Here, `zeroclass = 2` refers to models where an all-zero class is desired, whereas `zeroclass = 1` indicates no zero class.

8.4 Caveats and limitations

8.4.1 Circular tag definition

Although it is frequently useful to define init variables that include tags, be careful not to define two variables whose definitions depend on each other. This situation will result in a repetitive loop that cannot adequately resolve the tags (the program will inform you of this error). Here is an example of circular init variable definition:

```

iterators = model;
model = 1:3;
A = a_test1 a_test2 "a_test3[[B#model]]";
B = "b_test1 [[A#model]]" "b_test2 [[A#model]]" "b_test3 [[A#model]]";

```

In this case, both list variables are defined with respect to the `model` iterator. When `model` is 3, the tag cannot be resolved because the tags are circularly defined.

8.4.2 Conditional logic for multiple conditions

At this point, conditional tags only support checking the status of a single proposition (e.g., `model != 1`). In some cases, it is useful to only include a certain piece of Mplus syntax when two or more conditions are met. The workaround in the current version of MplusAutomation is to define two conditional tags, such as this example:

```
[[model > 1]]  
[[classes != 1]]  
var3@0; !Mplus code here  
[[/classes]]  
[[/model > 1]]
```

Checking for multiple conditions is on the short list of "to do" items and statements such as `[[model > 1 && classes != 1]]` should be available in a future version of the package.