

Package ‘MSbox’

July 21, 2025

Type Package

Title Mass Spectrometry Tools

Version 1.4.8

Author Yonghui Dong

Maintainer Yonghui Dong <yonghui.dong@gmail.com>

Description Common mass spectrometry tools described in John Roboz (2013) <doi:10.1201/b15436>. It allows checking element isotopes, calculating (isotope labelled) exact monoisotopic mass, m/z values and mass accuracy, and inspecting possible contaminant mass peaks, examining possible adducts in electrospray ionization (ESI) and matrix-assisted laser desorption ionization (MALDI) ion sources.

Depends R (>= 3.5.0)

Imports stringr, crayon, xml2, stats

License GPL-2

URL <https://github.com/YonghuiDong/MSbox>

BugReports <https://github.com/YonghuiDong/MSbox/issues/new>

Encoding UTF-8

RoxygenNote 7.2.2

NeedsCompilation no

Repository CRAN

Date/Publication 2022-12-08 14:42:31 UTC

Contents

adduct	2
contam	3
describe	3
doStat	4
E_iso	4

getCV	5
getFC	6
getMax	6
getP	7
Iso_mass	7
Iso_mz	8
mass	8
mz	9
ppm	10
searchDB	10
what	11
Index	12

adduct	<i>Common adducts</i>
--------	-----------------------

Description

calculate common adduct ions in positive or negative ion mode

Usage

```
adduct(F, mode = c("+", "-"))
```

Arguments

F	chemical formula, case insensitive
mode	ionization mode, either positive '+' or negative '-'

Author(s)

Yonghui Dong

Examples

```
adduct('C1H4', mode = '-')
adduct('C1h4', mode = '+')
```

contam	<i>Contaminants in MS</i>
--------	---------------------------

Description

check the possible contaminants

Usage

```
contam(mz, mode = NULL, ppm = 10)
```

Arguments

mz	suspected m/z value
mode	ionization mode, either positive '+' or negative '-'
ppm	mass tolerance, default value = 10

Author(s)

Yonghui Dong

Examples

```
contam(33.0335, ppm = 10, mode = '+')  
contam(44.998, ppm = 10, mode = '-')
```

describe	<i>Get the compound information</i>
----------	-------------------------------------

Description

get compound formula and structure from <https://cactus.nci.nih.gov/chemical/structure>

Usage

```
describe(chem, representation = "formula", info = FALSE)
```

Arguments

chem	chemical name of the compound
representation	representation methods, formula is default
info	extra molecular information that users can query

Author(s)

Yonghui Dong

Examples

```
## Not run:
describe('malic acid', "formula")
describe(c('malic acid', 'citric acid', 'tartaric acid'), "smiles")

## End(Not run)
```

doStat*Performing statistics*

Description

performing statistics, including calculating fold change, p-values and VIP values

Usage

```
doStat(x, Group = NULL)
```

Arguments

x	sample ion intensity matrix, row sample, column feature.
Group	sample group information

Value

a dataframe with statistical information

Examples

```
dat <- matrix(runif(2*300), ncol = 2, nrow = 300)
rownames(dat) <- 1:dim(dat)[1]
myGroup <- rep_len(LETTERS[1:3], 300)
ret <- doStat(dat, Group = myGroup)
```

E_iso*Element isotopes*

Description

check element isotope information

Usage

```
E_iso(S)
```

Arguments

S element, can be element symbol (i.e. C) or full name (i.e. Carbon). Both Element symbol and full name are case insensitive.

Author(s)

Yonghui Dong

Examples

```
E_iso('Na') # element symbol
E_iso('nA') # element symbol, case insensitive
E_iso('Carbon') # element full name
E_iso('carBon') # element full name, case insensitive
```

getCV

Calculate coefficient of variation (CV)

Description

Calculate coefficient of variation (CV), also known as relative standard deviation (RSD) among different sample groups

Usage

```
getCV(x, Group = NULL)
```

Arguments

x sample ion intensity matrix, row sample, column feature.
Group sample group information

Value

a dataframe with mean values and cv

Examples

```
dat <- matrix(runif(2*300), ncol = 2, nrow = 300)
myGroup <- rep_len(LETTERS[1:2], 300)
ret <- getCV(dat, Group = myGroup)
```

getFC	<i>calculate fold change</i>
-------	------------------------------

Description

calculate fold change among different samples.

Usage

```
getFC(x, Group = NULL)
```

Arguments

x	sample ion intensity matrix, row sample, column feature.
Group	sample group information

Value

a dataframe with mean values and fold changes

Examples

```
dat <- matrix(runif(2*300), ncol = 2, nrow = 300)
myGroup <- rep_len(LETTERS[1:2], 300)
ret <- getFC(dat, Group = myGroup)
```

getMax	<i>Get the sample name which has the max ion intensity</i>
--------	--

Description

get the sample name which has the max ion intensity

Usage

```
getMax(x)
```

Arguments

x	sample ion intensity matrix, row sample, column feature.
---	--

Value

a data frame

Examples

```
dat <- cbind.data.frame(mz = c(100, 101, 300), mz2 = c(0, 0, 1), mz3 = c(1, 9, 1))
rownames(dat) <- c("A", "B", "C")
out <- getMax(dat)
```

getP

get p-values

Description

get p-values from Post Hoc analysis

Usage

```
getP(x, Group = NULL)
```

Arguments

x	sample ion intensity matrix, row sample, column feature.
Group	sample group information

Value

a data frame

Examples

```
dat <- matrix(runif(2*300), ncol = 2, nrow = 300)
myGroup <- rep_len(LETTERS[1:3], 300)
out <- getP(dat, Group = myGroup)
```

Iso_mass

Isotope labelled molecular mass

Description

Calculate isotope labelled molecular mass

Usage

```
Iso_mass(F, iso)
```

Arguments

F	chemical formula, case insensitive
iso	labelled elements, case insensitive

Author(s)

Yonghui Dong

Examples

```
Iso_mass(F = 'C7H6O4', iso = '[13]C2[2]H3') # Two 13C and three 2H are labled
```

Iso_mz	<i>Isotope labelled molecular mass</i>
--------	--

Description

Calculate isotope labelled m/z

Usage

```
Iso_mz(F, iso, z)
```

Arguments

F	chemical formula, case insensitive
iso	labelled elements, case insensitive
z	charge

Author(s)

Yonghui Dong

Examples

```
Iso_mz(F = 'C7H6O4', iso = '[13]C2[2]H3', z = -1) # Two 13C and three 2H are labled
```

mass	<i>molecular mass</i>
------	-----------------------

Description

calculate accurate molecular mass

Usage

```
mass(F, caseSensitive = FALSE)
```

Arguments

<code>F</code>	chemical formula, case insensitive
<code>caseSensitive</code>	if case sensitive is 'FALSE' (default), the elements are separated by numbers. for instance, Carbon dioxide can be written as 'c1o2' or any combination of the two elements in lower or upper cases. However, the number of elements should be clearly stated in the chemical formula. if case sensitive is 'TRUE', the elements are separated by upper case letters. For instance, Carbon dioxide must be written as 'C1O2' or 'CO2'. You don't need to write the number of the element if it is 1.

Author(s)

Yonghui Dong

Examples

```

mass('C7h7o1')
mass('C7H7O', caseSensitive = TRUE)
mass(c('C7H7O4', 'C'), caseSensitive = TRUE) # vector input
mass(c('c7h7O4', 'c1'))

```

mz

*Calculate accurate mass-to-charge ratio***Description**

Calculate accurate mass-to-charge ratio (m/z)

Usage

```
mz(m, z, caseSensitive = FALSE)
```

Arguments

<code>m</code>	chemical formula of an ion, case insensitive
<code>z</code>	charge
<code>caseSensitive</code>	if case sensitive is 'FALSE' (default), the elements are separated by numbers. for instance, Carbon dioxide can be written as 'c1o2' or any combination of the two elements in lower or upper cases. However, the number of elements should be clearly stated in the chemical formula. if case sensitive is 'TRUE', the elements are separated by upper case letters. For instance, Carbon dioxide must be written as 'C1O2' or 'CO2'. You don't need to write the number of the element if it is 1.

Author(s)

Yonghui Dong

Examples

```
mz('C7h7o1', z = 1)
mz('C7H7O', z = 1, caseSensitive = TRUE)
mz(c('C7H7O4', 'C'), z = -1, caseSensitive = TRUE) # vector input
mz(c('c7h7O4', 'c1'), z = -1)
```

ppm	<i>mass accuracy</i>
-----	----------------------

Description

calculate the mass accuracy of measured m/z. lazy input allowed

Usage

```
ppm(m, t, lazy = TRUE)
```

Arguments

m	measured m/z
t	theoretical m/z
lazy	if lazy input is allowed

Author(s)

Yonghui Dong

Examples

```
ppm(155.03383, 155.03388) # with m/z value
ppm(155.03383, .03388) # lazy input when the integer parts of m and t are the same
ppm(155.03384, mz('C7H7O4', z = 1)) # with ion formula
```

searchDB	<i>Search in customized database</i>
----------	--------------------------------------

Description

search in customized database based on accurate m/z and RT

Usage

```
searchDB(DF, DB, ppm = 5, RT = 0.2, useRT = FALSE)
```

Arguments

DF	input file, should contain at least a column named mz
DB	database, should contain at least a column named mz
ppm	mass tolerance, default 5ppm
RT	retention time tolerance, default 0.2min
useRT	should RT be considered during database search?

Author(s)

Yonghui Dong

Examples

```
DF <- cbind.data.frame(mz = c(100.001, 100.1), RT = c(10, 11))
DB <- cbind.data.frame(mz = c(100.001, 100.1), RT = c(10, 12.1))
searchDB(DF, DB, ppm = 5, RT = 0.2, useRT = TRUE)
```

what	<i>search for m/z in from the idiom metabolomics database</i>
------	---

Description

tentative metabolite identification based on m/z value search

Usage

```
what(myMZ, mode = NULL, ppm = 5, useDB = "HMDB")
```

Arguments

myMZ	m/z values
mode	ionization mode, either positive '+' or negative '-'
ppm	mass tolerance, default value = 10
useDB	which database to use, HMDB or KEGG? default is HMDB

Author(s)

Yonghui Dong

Examples

```
a = what(133.014, mode = '-', ppm = 10)
```

Index

adduct, [2](#)

contam, [3](#)

describe, [3](#)

doStat, [4](#)

E_iso, [4](#)

getCV, [5](#)

getFC, [6](#)

getMax, [6](#)

getP, [7](#)

Iso_mass, [7](#)

Iso_mz, [8](#)

mass, [8](#)

mz, [9](#)

ppm, [10](#)

searchDB, [10](#)

what, [11](#)