

Package ‘R2sample’

July 21, 2025

Title Various Methods for the Two Sample Problem

Version 4.1.0

Description The routine `twosample_test()` in this package runs the two sample test using various test statistic. The p values are found via permutation or large sample theory. The routine `twosample_power()` allows the calculation of the power in various cases, and `plot_power()` draws the corresponding power graphs. The routine `run.studies` allows a user to quickly study the power of a new method and how it compares to some of the standard ones.

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 7.3.2

LinkingTo Rcpp

Imports Rcpp, parallel, shiny, ggplot2, stats, graphics,
microbenchmark

Suggests rmarkdown, knitr, testthat (>= 3.0.0)

VignetteBuilder knitr

Depends R (>= 3.5)

LazyData true

NeedsCompilation yes

Author Wolfgang Rolke [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-3514-726X>>)

Maintainer Wolfgang Rolke <wolfgang.rolke@upr.edu>

Repository CRAN

Date/Publication 2025-06-16 18:30:06 UTC

Contents

asymptotic_pvalues	2
case.studies	3
chi_power	3

myTS2	4
plot_power	5
powerR	5
power_newtest	6
power_studies_results	7
pvaluecdf	7
run.studies	8
run_shiny	9
signif.digits	10
timecheck	10
twosample_power	11
twosample_test	12
twosample_test_adjusted_pvalue	14
Index	16

asymptotic_pvalues	<i>This function finds the p values of several tests based on large sample theory</i>
--------------------	---

Description

This function finds the p values of several tests based on large sample theory

Usage

```
asymptotic_pvalues(x, n, m)
```

Arguments

x	a vector of test statistics
n	size of sample 1
m	size of sample 2

Value

A vector of p values.

case.studies	<i>This function creates the functions needed to run the various case studies.</i>
--------------	--

Description

This function creates the functions needed to run the various case studies.

Usage

```
case.studies(which, nsample = 500)
```

Arguments

which	name of the case study.
nsample	=500, sample size.

Value

a list of functions

chi_power	<i>This function runs the chi-square test for continuous or discrete data</i>
-----------	---

Description

This function runs the chi-square test for continuous or discrete data

Usage

```
chi_power(  
  rxy,  
  alpha = 0.05,  
  B = 1000,  
  xparam,  
  yparam,  
  nbins = c(50, 10),  
  minexpcount = 5,  
  typeTS  
)
```

Arguments

rx	a function to generate data
alpha	=0.05 type I error probability of test
B	=1000 number of simulation runs
xparam	vector of parameter values
yparam	vector of parameter values
nbins	=c(50, 10) number of desired bins
minexpcount	=5 smallest number of counts required in each bin
typeTS	type of problem, continuous/discrete, with/without weights

Value

A matrix of power values

myTS2	<i>a local function needed for the vignette</i>
-------	---

Description

a local function needed for the vignette

Usage

```
myTS2(x, y, vals)
```

Arguments

x	An integer vector.
y	An integer vector.
vals	A numeric vector with the values of the discrete rv.

Value

A vector with test statistics

plot_power	<i>This function draws the power graph, with curves sorted by the mean power and smoothed for easier reading.</i>
------------	---

Description

This function draws the power graph, with curves sorted by the mean power and smoothed for easier reading.

Usage

```
plot_power(pwr, xname = " ", title = " ", Smooth = TRUE, span = 0.25)
```

Arguments

pwr	a matrix of power values, usually from the twosample_power command
xname	Name of variable on x axis
title	(Optional) title of graph
Smooth	=TRUE lines are smoothed for easier reading
span	=0.25bandwidth of smoothing method

Value

plt, an object of class ggplot.

powerR	<i>Find the power of two sample tests using Rcpp and parallel computing.</i>
--------	--

Description

Find the power of two sample tests using Rcpp and parallel computing.

Usage

```
powerR(
  rxy,
  xparam,
  yparam,
  TS,
  typeTS,
  TSextra,
  alpha = 0.05,
  B = 1000,
  SuppressMessages,
  maxProcessor
)
```

Arguments

rx	function to generate a list with data sets x, y and (optional) vals, weights
param	first argument passed to rx
yparam	second argument passed to rx
TS	test statistic
typeTS	which format has TS?
TSextra	list of items passed TS
alpha	=0.05, the level of the hypothesis test
B	= 1000 number of simulation runs
SuppressMessages	= FALSE print informative messages?
maxProcessor	maximum number of cores to use. If maxProcessor=1 no parallel computing is used.

Value

A numeric vector of power values.

power_newtest	<i>Power for tests with p values</i>
---------------	--------------------------------------

Description

This function estimates the power of test routines that calculate p value(s)

Usage

```
power_newtest(TS, f, param_alt, TSextra, alpha = 0.05, B = 1000)
```

Arguments

TS	routine to calculate test statistics.
f	routine that generates data.
param_alt	values of parameter under the alternative hypothesis.
TSextra	list passed to TS.
alpha	=0.05 type I error.
B	= 1000 number of simulation runs to estimate the power.

Value

A matrix of power values

power_studies_results	<i>power_studies_results</i>
-----------------------	------------------------------

Description

the results of the included power studies

Usage

power_studies_results

Format

'power_studies_results':
A list of matrices with powers

pvaluecdf	<i>pvaluecdf</i>
-----------	------------------

Description

data to draw a graph in vignette

Usage

pvaluecdf

Format

'pvaluecdf':
A matrix

run.studies

Power Comparisons

Description

This function runs the case studies included in the package and compares the power of a new test to those included.

Usage

```
run.studies(
  TS,
  study,
  TSextra,
  With.p.value = FALSE,
  BasicComparison = TRUE,
  nsample = 500,
  alpha = 0.05,
  param_alt,
  maxProcessor,
  SuppressMessages = FALSE,
  B = 1000
)
```

Arguments

TS	routine to calculate test statistics.
study	either the name of the study, or its number. If missing all the studies are run.
TSextra	list passed to TS.
With.p.value	=FALSE does user supplied routine return p values?
BasicComparison	=TRUE if true compares tests on one default value of parameter of the alternative distribution.
nsample	= 500, desired sample size.
alpha	=0.05 type I error
param_alt	(list of) values of parameter under the alternative hypothesis. If missing included values are used.
maxProcessor	number of cores to use for parallel programming
SuppressMessages	= FALSE print informative messages?
B	= 1000

Details

For details consult vignette("R2sample", "R2sample")

Value

A (list of) matrices of power values.

Examples

```
#The new test is a simple chisquare test:
chitest = function(x, y, TSextra) {
  nbins=TSextra$nbins
  nx=length(x);ny=length(y);n=nx+ny
  xy=c(x,y)
  bins=quantile(xy, (0:nbins)/nbins)
  Ox=hist(x, bins, plot=FALSE)$counts
  Oy=hist(y, bins, plot=FALSE)$counts
  tmp=sqrt(sum(Ox)/sum(Oy))
  chi = sum((Ox/tmp-Oy*tmp)^2/(Ox+Oy))
  pval=1-pchisq(chi, nbins-1)
  out=ifelse(TSextra$statistic,chi,pval)
  names(out)="ChiSquare"
  out
}
TSextra=list(nbins=5,statistic=FALSE) # Use 5 bins and calculate p values
run.studies(chitest,TSextra=TSextra, With.p.value=TRUE, B=100)
```

run_shiny

Runs the shiny app associated with R2sample package

Description

Runs the shiny app associated with R2sample package

Usage

```
run_shiny()
```

Value

No return value, called for side effect of opening a shiny app

signif.digits	<i>This function does some rounding to nice numbers</i>
---------------	---

Description

This function does some rounding to nice numbers

Usage

```
## S3 method for class 'digits'  
signif(x, d = 4)
```

Arguments

x	a list of two vectors
d	=4 number of digits to round to

Value

A list with rounded vectors

timecheck	<i>test function</i>
-----------	----------------------

Description

test function

Usage

```
timecheck(dta, TS, typeTS, TSextra)
```

Arguments

dta	data set
TS	test statistics
typeTS	format of TS
TSextra	additional info TS

Value

Mean computation time

twosample_power	<i>Power estimation for two-sample methods</i>
-----------------	--

Description

Find the power of various two sample tests using Rcpp and parallel computing.

Usage

```
twosample_power(
  f,
  ...,
  TS,
  TSextra,
  With.p.value = FALSE,
  alpha = 0.05,
  B = 1000,
  nbins = c(50, 10),
  minexpcount = 5,
  UseLargeSample,
  samplingmethod = "Binomial",
  rnull,
  SuppressMessages = FALSE,
  maxProcessor
)
```

Arguments

f	function to generate a list with data sets x, y and (optional) vals, weights
...	additional arguments passed to f, up to 2
TS	routine to calculate test statistics for non-chi-square tests
TSextra	additional info passed to TS, if necessary
With.p.value	=FALSE does user supplied routine return p values?
alpha	=0.05, the level of the hypothesis test
B	=1000, number of simulation runs.
nbins	=c(50,10), number of bins for chi large and chi small.
minexpcount	=5 minimum required count for chi square tests
UseLargeSample	should p values be found via large sample theory if n,m>10000?
samplingmethod	"Binomial" or independence in discrete data case
rnull	a function that generates data from a model, possibly with parameter estimation.
SuppressMessages	= FALSE print informative messages?
maxProcessor	maximum number of cores to use. If maxProcessor=1 no parallel computing is used.

Details

For details consult vignette("R2sample","R2sample")

This routine runs a number of different two-sample tests for univariate data, either discrete or continuous. The user can also provide their own test method.

Value

A numeric vector of power values.

Examples

```
# Power of standard normal vs. normal with mean mu.
f1=function(mu) list(x=rnorm(25), y=rnorm(25, mu))
#Power of uniform discrete distribution vs. with different probabilities.
twosample_power(f1, mu=c(0,2), B=100, maxProcessor = 1)
f2=function(n, p) list(x=table(sample(1:5, size=1000, replace=TRUE)),
  y=table(sample(1:5, size=n, replace=TRUE,
    prob=c(1, 1, 1, 1, p))), vals=1:5)
twosample_power(f2, n=c(1000, 2000), p=c(1, 1.5), B=100, maxProcessor = 1)
# Compare power of a new test with those in package:
myTS=function(x,y) {z=c(mean(x)-mean(y),sd(x)-sd(y));names(z)=c("M","S");z}
cbind(twosample_power(f1, mu=c(0,2), TS=myTS,B=100, maxProcessor = 1),
  twosample_power(f1, mu=c(0,2), B=100, maxProcessor = 1))
# Power estimation if routine returns a p value
myTS2=function(x, y) {out=ks.test(x,y)$p.value; names(out)="KSp"; out}
twosample_power(f1, c(0,1), TS=myTS2, With.p.value = TRUE, B=100)
```

twosample_test

Tests for the univariate two-sample problem

Description

This function runs a number of two sample tests using Rcpp and parallel computing.

Usage

```
twosample_test(
  x,
  y,
  vals = NA,
  TS,
  TSextra,
  wx = rep(1, length(x)),
  wy = rep(1, length(y)),
  B = 5000,
  nbins = c(50, 10),
  minexpcount = 5,
```

```

    maxProcessor,
    UseLargeSample,
    samplingmethod = "Binomial",
    rnull,
    SuppressMessages = FALSE,
    doMethods = "all"
  )

```

Arguments

<code>x</code>	a vector of numbers if data is continuous or of counts if data is discrete or a list with the data
<code>y</code>	a vector of numbers if data is continuous or of counts if data is discrete.
<code>vals</code>	=NA, a vector of numbers, the values of a discrete random variable. NA if data is continuous data.
<code>TS</code>	routine to calculate test statistics for non-chi-square tests
<code>TSextra</code>	additional info passed to TS, if necessary
<code>wx</code>	A numeric vector of weights of x.
<code>wy</code>	A numeric vector of weights of y.
<code>B</code>	=5000, number of simulation runs for permutation test
<code>nbins</code>	=c(50,10), number of bins for chi square tests.
<code>minexpcount</code>	=5, minimum required expected counts for chi-square tests.
<code>maxProcessor</code>	maximum number of cores to use. If missing (the default) no parallel processing is used.
<code>UseLargeSample</code>	should p values be found via large sample theory if n,m>10000?
<code>samplingmethod</code>	="Binomial" or "independence" for discrete data
<code>rnull</code>	a function that generates data from a model, possibly with parameter estimation.
<code>SuppressMessages</code>	= FALSE print informative messages?
<code>doMethods</code>	="all" a vector of codes for the methods to include. If "all", all methods are used.

Details

For details consult `vignette("R2sample","R2sample")`

Value

A list of two numeric vectors, the test statistics and the p values.

Examples

```

R2sample::twosample_test(rnorm(1000), rt(1000, 4), B=1000)
myTS=function(x,y) {z=c(mean(x)-mean(y),sd(x)-sd(y));names(z)=c("M","S");z}
R2sample::twosample_test(rnorm(1000), rt(1000, 4), TS=myTS, B=1000)
vals=1:5

```

```
x=table(sample(vals, size=100, replace=TRUE))
y=table(sample(vals, size=100, replace=TRUE, prob=c(1,1,3,1,1)))
R2sample::twosample_test(x, y, vals)
```

twosample_test_adjusted_pvalue

Adjusted p values for simultaneous testing in the two-sample problem.

Description

This function runs a number of two sample tests using Rcpp and parallel computing and then finds the correct p value for the combined tests.

Usage

```
twosample_test_adjusted_pvalue(
  x,
  y,
  vals = NA,
  TS,
  TSextra,
  wx = rep(1, length(x)),
  wy = rep(1, length(y)),
  B = c(5000, 1000),
  nbins = c(50, 10),
  minexpcount = 5,
  samplingmethod = "independence",
  rnull,
  SuppressMessages = FALSE,
  doMethods
)
```

Arguments

x	a vector of numbers if data is continuous or of counts if data is discrete, or a list with the data.
y	a vector of numbers if data is continuous or of counts if data is discrete.
vals	=NA, a vector of numbers, the values of a discrete random variable. NA if data is continuous data.
TS	routine to calculate test statistics for non-chi-square tests
TSextra	additional info passed to TS, if necessary
wx	A numeric vector of weights of x.
wy	A numeric vector of weights of y.
B	=c(5000, 1000), number of simulation runs for permutation test
nbins	=c(50,10), number of bins for chi square tests.

minexpcount = 5, minimum required expected counts for chi-square tests
samplingmethod = "independence" or "Binomial" for discrete data
rnull routine for parametric bootstrap
SuppressMessages
= FALSE print informative messages?
doMethods = "all" a vector of codes for the methods to include. If "all", all methods are used.

Details

For details consult vignette("R2sample","R2sample")

Value

A list of two numeric vectors, the test statistics and the p values.

Examples

```
x=rnorm(100)
y=rt(200, 4)
R2sample::twosample_test_adjusted_pvalue(x, y, B=c(500, 500))
vals=1:5
x=table(c(1:5, sample(1:5, size=100, replace=TRUE)))-1
y=table(c(1:5, sample(1:5, size=100, replace=TRUE, prob=c(1,1,3,1,1))))-1
R2sample::twosample_test_adjusted_pvalue(x, y, vals, B=c(500, 500))
```

Index

* **datasets**

- power_studies_results, [7](#)
- pvaluecdf, [7](#)

asymptotic_pvalues, [2](#)

case.studies, [3](#)

chi_power, [3](#)

myTS2, [4](#)

plot_power, [5](#)

power_newtest, [6](#)

power_studies_results, [7](#)

powerR, [5](#)

pvaluecdf, [7](#)

run.studies, [8](#)

run_shiny, [9](#)

signif.digits, [10](#)

timecheck, [10](#)

twosample_power, [11](#)

twosample_test, [12](#)

twosample_test_adjusted_pvalue, [14](#)