

Package ‘RPublica’

July 21, 2025

Type Package

Title ProPublica API Client

Version 0.1.3

Date 2015-12-22

Maintainer Thomas J. Leeper <thosjleeper@gmail.com>

Imports jsonlite, httr, curl

Description

Client for accessing data journalism APIs from ProPublica <<http://www.propublica.org/>>.

License GPL-2

URL <https://github.com/rOpenGov/RPublica>

BugReports <https://github.com/rOpenGov/RPublica/issues>

NeedsCompilation no

Author Thomas J. Leeper [aut, cre],
Jeroen Ooms [ctb]

Repository CRAN

Date/Publication 2015-12-22 14:36:42

Contents

RPublica-package	2
committee	2
filing	3
forensics	3
market	4
nonprofitexplorer	5
ppQuery	6
station	6

Index	7
--------------	----------

RPublica-package

ProPublica API Client

Description

Client for accessing ProPublica's data journalism APIs.

Author(s)

Thomas J. Leeper

Maintainer: Thomas J. Leeper <thosjleeper@gmail.com>

References

APIs:

[Nonprofit Explorer](#)

[Forensics](#)

[Free the Files](#)

committee

Retrieve committees or committee

Description

Retrieve available committees, or a specific committee

Usage

```
committee(slug = NULL, ...)
```

Arguments

slug An optional character string containing a “slug” referring to a political committee.

... Arguments passed to [GET](#).

Author(s)

Thomas J. Leeper

Examples

```
## Not run: committee('obama-for-america')
```

filing	<i>Retrieve filing</i>
--------	------------------------

Description

Retrieve a specific filing, by ID

Usage

filing(id, ...)

Arguments

- id A character string containing a filing identification number.
- ... Arguments passed to [GET](#).

Author(s)

Thomas J. Leeper

Examples

```
## Not run: filing(51212)
```

forensics	<i>Forensics API</i>
-----------	----------------------

Description

Retrieve details about a given state or system

Usage

geos(state=NULL, ...)

systems(id, ...)

Arguments

- state An optional character string containing a two-letter state postal code. If NULL, results for all available states are returned.
- id The identification number for a particular medical examiner or coroner system.
- ... Arguments passed to [GET](#).

Author(s)

Thomas J. Leeper

References

[API Documentation](#)

Examples

```
## Not run: geos('ny')  
## Not run: systems(36)
```

market	<i>Retrieve market or markets</i>
--------	-----------------------------------

Description

Retrieve available markets, or a specific market

Usage

```
market(slug = NULL, ...)
```

Arguments

slug	An optional character string containing a “slug” referring to a media market.
...	Arguments passed to GET .

Author(s)

Thomas J. Leeper

Examples

```
## Not run: market('new-york')
```

nonprofitexplorer	<i>Nonprofit Explorer</i>
-------------------	---------------------------

Description

Search for and retrieve nonprofit data

Usage

```
np_search(q=NULL, order=NULL, sort=NULL, state=NULL, ntee=NULL, subsection=NULL, ...)
```

```
np_org(ein, ...)
```

Arguments

q	A character string containing a search query.
order	A character string containing a field by which to order the results. One of “name”, “city”, “state”, “c_code”, “fiscalyr”, “revenue”, “expenses”, “assets”, “liabilities”, “pct_officer_compt”. The ascending or descending sort by this parameter is controlled by sort.
sort	One of “asc” or “desc”, controlling the order of the results (according the the ordering given in order).
state	A two-letter state postal abbreviation code for a U.S. state or territory. Use “ZZ” for foreign organizations.
ntee	A numeric value (between 1 and 10) containing a National Taxonomy of Exempt Entities (NTEE) Major Group code.
subsection	A numeric value (between 2 and 92) referring to a subsection of tax code section 501(c).
ein	An employer identification number (EIN).
...	Arguments passed to GET .

Value

A list containing the API response.

Author(s)

Thomas J. Leeper

References

[API Documentation](#)

Examples

```
## Not run: np_search('propublica')  
## Not run: np_org(142007220)
```

ppQuery	API Query
Description Execute an API query	
Usage ppQuery(op, baseUrl, args = NULL, ...)	
Arguments	
op	A character string containing an API operation, and associated arguments.
baseUrl	The base URL for conducting the API query.
args	A character string containing additional URL-encoded parameters.
...	Arguments passed to GET .
Author(s) Thomas J. Leeper	
station	Retrieve station
Description Retrieve station	
Usage station(callsign, ...)	
Arguments	
callsign	A character string containing a station callsign.
...	Arguments passed to GET .
Author(s) Thomas J. Leeper	
Examples ## Not run: station('WEWS-TV')	

Index

* **package**

RPublica-package, [2](#)

committee, [2](#)

filing, [3](#)

forensics, [3](#)

geos (forensics), [3](#)

GET, [2–6](#)

market, [4](#)

nonprofitexplorer, [5](#)

np_org (nonprofitexplorer), [5](#)

np_search (nonprofitexplorer), [5](#)

ppQuery, [6](#)

RPublica (RPublica-package), [2](#)

RPublica-package, [2](#)

station, [6](#)

systems (forensics), [3](#)