

Package ‘Rpolyhedra’

July 21, 2025

Type Package

Title Polyhedra Database

Version 0.5.6

Language en-US

Maintainer Alejandro Baranek <abaranek@dc.uba.ar>

Description

A polyhedra database scraped from various sources as R6 objects and 'rgl' visualizing capabilities.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

Depends R (>= 3.5.0)

Imports R6, geometry, rgl, stringr, XML, digest, lgr, dplyr, jsonlite

Suggests testthat, knitr, pkgdown, rmarkdown, covr, codemetar

Collate 'Rpolyhedra-package.R' 'polyhedra-lib.R' 'ledger-lib.R'
'db-lib.R' 'env-lib.R' 'package-lib.R' 'serialization-lib.R'
'public-lib.R' 'test-lib.R' 'zzz.R'

BugReports <https://github.com/ropensci/Rpolyhedra/issues>

URL <https://docs.ropensci.org/Rpolyhedra/>,
<https://github.com/ropensci/Rpolyhedra>

StagedInstall TRUE

NeedsCompilation no

Author Alejandro Baranek [aut, com, cre, cph],
Leonardo Belen [aut, com, cph],
qbotics [cph],
Barret Schloerke [rev],
Lijia Yu [rev]

Repository CRAN

Date/Publication 2024-11-06 15:10:02 UTC

Contents

Rpolyhedra-package	2
genLogger	3
getAvailablePolyhedra	4
getAvailableSources	5
getLogger	5
getPolyhedraObject	6
getPolyhedron	6
loggerSetupFile	7
mutate_cond	8
PolyhedraDatabase	8
Polyhedron	14
PolyhedronState	17
PolyhedronStateDefined	19
PolyhedronStateDeserializer	24
PolyhedronStateDmccooeyScraper	25
PolyhedronStateNetlibScraper	28
polyhedronToXML	31
scrapePolyhedra	31
scrapePolyhedraSources	32
switchToFullDatabase	33
Index	34

Rpolyhedra-package	<i>Rpolyhedra: Polyhedra Database</i>
--------------------	---------------------------------------

Description

A polyhedra database scraped from various sources as R6 objects and 'rgl' visualizing capabilities.

Details

A polyhedra database scraped from:

- <http://paulbourke.net/dataformats/phd/>: PHD files as R6 objects and 'rgl' visualizing capabilities. The PHD format was created to describe the geometric polyhedra definitions derived mathematically <<https://netlib.org/polyhedra/>> by Andrew Hume and by the Kaleido program of Zvi Har'El.
- <http://dmccooey.com/Polyhedra/>: Polyhedra text datafiles.

Author(s)

Maintainer: Alejandro Baranek <abaranek@dc.uba.ar> [compiler, copyright holder]

Authors:

- Leonardo Belen <leobelen@gmail.com> [compiler, copyright holder]

Other contributors:

- qbotics <qbotics6@gmail.com> [copyright holder]
- Barret Schloerke <schloerke@gmail.com> [reviewer]
- Lijia Yu <yu@lijiayu.net> [reviewer]

See Also

Useful links:

- <https://docs.ropensci.org/Rpolyhedra/>
- <https://github.com/ropensci/Rpolyhedra>
- Report bugs at <https://github.com/ropensci/Rpolyhedra/issues>

genLogger

genLogger

Description

Returns a configured logger with threshold according r6 object. This function is usually called in class constructors

Usage

```
genLogger(r6.object)
```

Arguments

r6.object an r6.object

Author(s)

ken4rab

getAvailablePolyhedra *Get available polyhedra*

Description

Gets the list of names of available polyhedra and its status in the polyhedra database, which can be later called with getPolyhedron

Usage

```
getAvailablePolyhedra(sources, search.string)
```

Arguments

sources	A string vector containing the source, which can be obtained from getAvailableSources().
search.string	A search string

Value

polyhedra names vector

See Also

getAvailableSources

Examples

```
# gets all polyhedra in the database
available.polyhedra <- getAvailablePolyhedra()

# returns all polyhedra from a given source, in this case, netlib
available.netlib.polyhedra <- getAvailablePolyhedra(sources = "netlib")

# search within the polyhedron names

cube <- getAvailablePolyhedra(sources = "netlib", search.string = "cube")
cube
```

getAvailableSources	<i>Get available sources</i>
---------------------	------------------------------

Description

Gets the list of names of available sources in database to be used later as references to the package.

Usage

```
getAvailableSources()
```

Value

sources string vector, which can be obtained from getAvailableSources()

See Also

getAvailablePolyhedra, getPolyhedron

Examples

```
# gets all sources in the database
available.sources <- getAvailableSources()

# returns all polyhedra from all sources
available.polyhedra <- getAvailablePolyhedra(sources = available.sources)

# search within the polyhedron names from all sources
cubes <- getAvailablePolyhedra(
  sources = available.sources,
  search.string = "cube"
)
cubes
```

getLogger	<i>getLogger</i>
-----------	------------------

Description

Returns the configured lgr of an r6 object. If the object don't have a lgr or is not initialized returns an error

Usage

```
getLogger(r6.object)
```

Arguments

`r6.object` an `r6.object`

Author(s)

ken4rab

`getPolyhedraObject` *Get a polyhedra object*

Description

Return the polyhedra database handler.

Usage

```
getPolyhedraObject()
```

Value

`.polyhedra`

See Also

`PolyhedraDatabase`

`getPolyhedron` *Get polyhedron*

Description

Gets a polyhedron from the database. It returns an R6 Class with all its characteristics and functions. The object returned, of type `Polyhedron`, allows to the user to get access to all the functionality provided.

Usage

```
getPolyhedron(source = "netlib", polyhedron.name)
```

Arguments

`source` string vector, which can be obtained from `getAvailableSources()`
`polyhedron.name` a valid name of a polyhedron in the database. Current names can be found with `getAvailablePolyhedra()`

Value

polyhedron R6 object

See Also

getAvailablePolyhedra, getAvailableSources

Examples

```
tetrahedron <- getPolyhedron(
  source = "netlib",
  polyhedron.name = "tetrahedron"
)

# returns name of polyhedra
tetrahedron$getName()

# polyhedron state
tetrahedron.state <- tetrahedron$getState()

# Johnson symbol and Schlafli symbol
tetrahedron.state$getSymbol()

# vertex data.frame
tetrahedron.state$getVertices()

# List of faces of solid representation (3D)
tetrahedron.state$getSolid()

# List of faces of net representation (2D)
tetrahedron.state$getNet()
```

loggerSetupFile	<i>loggerSetupFile</i>
-----------------	------------------------

Description

loggerSetupFile

Usage

```
loggerSetupFile(log.file, default.threshold = "info", append = TRUE)
```

Arguments

log.file	log path for logging file
default.threshold	threshold for setting root. Default = "info"
append	if set to FALSE, cleanup all previous logs

Author(s)

kenarab

mutate_cond	<i>mutate_cond</i>
-------------	--------------------

Description

mutate_cond

Usage

```
mutate_cond(.data, condition, ..., envir = parent.frame())
```

Arguments

- | | |
|-----------|---|
| .data | data frame to apply the mutate |
| condition | condition to conditionally apply mutate |
| ... | mutation function |
| envir | environment to apply condition |

PolyhedraDatabase	<i>Polyhedra database</i>
-------------------	---------------------------

Description

Scrapes all polyhedra in data folder to save a representation which is accessible by the final users upon call to getPolyhedron().

Public fields

- version version of database file
- polyhedra.rds.file path of rds database file
- sources.config Sources configuration for scraping different sources
- ledger rr ledger of scraping process
- logger class logger

Methods

Public methods:

- `PolyhedraDatabase$new()`
- `PolyhedraDatabase$getVersion()`
- `PolyhedraDatabase$configPolyhedraRDSPath()`
- `PolyhedraDatabase$existsSource()`
- `PolyhedraDatabase$addSourceConfig()`
- `PolyhedraDatabase$existsPolyhedron()`
- `PolyhedraDatabase$getPolyhedraSourceDir()`
- `PolyhedraDatabase$getPolyhedronFilename()`
- `PolyhedraDatabase$getPolyhedron()`
- `PolyhedraDatabase$addPolyhedron()`
- `PolyhedraDatabase$configPolyhedraSource()`
- `PolyhedraDatabase$saveRDS()`
- `PolyhedraDatabase$cover()`
- `PolyhedraDatabase$scrape()`
- `PolyhedraDatabase$testRR()`
- `PolyhedraDatabase$generateTestTasks()`
- `PolyhedraDatabase$schedulePolyhedraSources()`
- `PolyhedraDatabase$getAvailableSources()`
- `PolyhedraDatabase$getAvailablePolyhedra()`
- `PolyhedraDatabase$clone()`

Method `new()`: Create a new `PolyhedraDatabase` object.

Usage:

```
PolyhedraDatabase$new()
```

Returns: A new 'PolyhedraDatabase' object.

Method `getVersion()`: get the version of the current object.

Usage:

```
PolyhedraDatabase$getVersion()
```

Returns: Database version

Method `configPolyhedraRDSPath()`: sets the path of the RDS object

Usage:

```
PolyhedraDatabase$configPolyhedraRDSPath()
```

Returns: Database version

Method `existsSource()`: Determines if the source exists on the database

Usage:

```
PolyhedraDatabase$existsSource(source)
```

Arguments:

source source description

Returns: boolean value

Method addSourceConfig(): add source.config to the database

Usage:

```
PolyhedraDatabase$addSourceConfig(source.config)
```

Arguments:

source.config SourceConfig object able to scrape source polyhedra definitions

Returns: PolyhedraDatabase object

Method existsPolyhedron(): Determines if the database includes a polyhedron which name matches the parameter value

Usage:

```
PolyhedraDatabase$existsPolyhedron(source = "netlib", polyhedron.name)
```

Arguments:

source source description

polyhedron.name polyhedron description

Returns: boolean value

Method getPolyhedraSourceDir(): gets polyhedra sources folder

Usage:

```
PolyhedraDatabase$getPolyhedraSourceDir(source, create.dir = TRUE)
```

Arguments:

source source description

create.dir if dir does not exists, create it

Returns: string with polyhedra sources path

Method getPolyhedronFilename(): gets the filename of the polyhedron matching parameter.

Usage:

```
PolyhedraDatabase$getPolyhedronFilename(source, polyhedron.name, extension)
```

Arguments:

source source description

polyhedron.name polyhedron description

extension extension of the polyhedron filename

Returns: string with polyhedron filename

Method getPolyhedron(): gets polyhedron object which name matches the parameter value

Usage:

```
PolyhedraDatabase$getPolyhedron(
  source = "netlib",
  polyhedron.name,
  strict = FALSE
)
```

Arguments:

source source description
 polyhedron.name polyhedron description
 strict halts execution if polyhedron not found

Returns: Polyhedron object

Method addPolyhedron(): add polyhedron object to the database

Usage:

```
PolyhedraDatabase$addPolyhedron(
  source = "netlib",
  source.filename,
  polyhedron,
  overwrite = FALSE,
  save.on.change = FALSE
)
```

Arguments:

source source description
 source.filename filename of the polyhedron source definition
 polyhedron polyhedron object
 overwrite overwrite exiting definition
 save.on.change saves Database state after operation

Returns: Polyhedron object

Method configPolyhedraSource(): Process parameter filenames using source.config parameter

Usage:

```
PolyhedraDatabase$configPolyhedraSource(
  source.config,
  source.filenames = NULL,
  max.quant = 0,
  save.on.change = FALSE
)
```

Arguments:

source.config source configuration for scraping files
 source.filenames filenames of the polyhedron source definition
 max.quant maximum filenames to process
 save.on.change saves Database state after operation

Returns: Modified 'PolyhedraDatabase' object.

Method saveRDS(): saveRDS

Usage:

```
PolyhedraDatabase$saveRDS(save.on.change = TRUE)
```

Arguments:

`save.on.change` saves Database state after operation

Returns: saveRDS return status

Method `cover()`: Cover objects and applies `covering.code` parameter

Usage:

```
PolyhedraDatabase$cover(
  mode,
  sources = names(self$sources.config),
  covering.code,
  polyhedra.names = NULL,
  max.quant = 0,
  save.on.change = FALSE,
  seed = NULL
)
```

Arguments:

`mode` covering mode. Available values are "scrape.queued", "scrape.retry", "skipped", "test"

`sources` sources names

`covering.code` code for applying in covering

`polyhedra.names` polyhedra names to cover (optional)

`max.quant` maximum numbers of polyhedra to cover

`save.on.change` saves Database state after operation

`seed` seed for deterministic random generator

Returns: A list with resulting objects covered

Method `scrape()`: Scrape polyhedra queued sources

Usage:

```
PolyhedraDatabase$scrape(
  mode = "scrape.queued",
  sources = names(self$sources.config),
  max.quant = 0,
  time2scrape.source = 30,
  save.on.change = FALSE,
  skip.still.queued = FALSE
)
```

Arguments:

`mode` covering mode. Available values are "scrape.queued", "scrape.retry", "skipped", "test"

`sources` sources names

`max.quant` maximum numbers of polyhedra to cover

`time2scrape.source` maximum time to spend scraping each source

`save.on.change` saves Database state after operation

`skip.still.queued` Flag unscraped files with status 'skipped'

`covering.code` code for applying in covering

`polyhedra.names` polyhedra names to cover (optional)

Returns: A list with resulting objects covered

Method testRR(): testRR*Usage:*

```
PolyhedraDatabase$testRR(sources = names(self$sources.config), max.quant = 0)
```

Arguments:

sources sources names

max.quant maximum numbers of polyhedra to cover

Returns: A list with resulting objects tested**Method** generateTestTasks(): generate Test tasks for selected polyhedra*Usage:*

```
PolyhedraDatabase$generateTestTasks(
  sources = names(self$sources.config),
  polyhedra.names = NULL,
  TestTaskClass,
  max.quant = 0
)
```

Arguments:

sources sources names

polyhedra.names polyhedra names to cover (optional)

TestTaskClass an R6 TestTaskClass class

max.quant maximum numbers of polyhedra to cover

Returns: A list with resulting TestTasks generated**Method** schedulePolyhedraSources(): Schedules polyhedra sources for scraping*Usage:*

```
PolyhedraDatabase$schedulePolyhedraSources(
  sources.config = getPackageEnvir(".available.sources"),
  source.filenames = NULL,
  max.quant = 0,
  save.on.change = FALSE
)
```

Arguments:

sources.config sources configurations for scraping files

source.filenames filenames of the polyhedron source definition

max.quant maximum filenames to process

save.on.change saves Database state after operation

Returns: Modified 'PolyhedraDatabase' object.**Method** getAvailableSources(): Returns available sources in current database*Usage:*

```
PolyhedraDatabase$getAvailableSources()
```

Returns: A vector with names of available sources

Method `getAvailablePolyhedra()`: Retrieves all polyhedron within the source those names match with `search.string`

Usage:

```
PolyhedraDatabase$getAvailablePolyhedra(
  sources = self$getAvailableSources(),
  search.string = NULL,
  ignore.case = TRUE
)
```

Arguments:

`sources` sources names
`search.string` string for matching polyhedron names
`ignore.case` ignore case in search string

Returns: A list with resulting objects covered

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PolyhedraDatabase$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Polyhedron

Polyhedron

Description

Polyhedron container class, which is accessible by the final users upon call

Public fields

`file.id` Polyhedron file.id
`state` Polyhedron state
`logger` class logger

Methods

Public methods:

- [Polyhedron\\$new\(\)](#)
- [Polyhedron\\$scrapeNetlib\(\)](#)
- [Polyhedron\\$scrapeDmccooey\(\)](#)
- [Polyhedron\\$deserialize\(\)](#)
- [Polyhedron\\$getName\(\)](#)
- [Polyhedron\\$getState\(\)](#)
- [Polyhedron\\$getSolid\(\)](#)

- `Polyhedron$isChecked()`
- `Polyhedron$getRGLModel()`
- `Polyhedron$exportToXML()`
- `Polyhedron$getErrors()`
- `Polyhedron$checkProperties()`
- `Polyhedron$clone()`

Method `new()`: Create a polyhedronState object

Usage:

`Polyhedron$new(file.id, state = NULL)`

Arguments:

`file.id` the file id

`state` polyhedron state object

Returns: A new Polyhedron object.

Method `scrapeNetlib()`: scrape Netlib polyhedron definition

Usage:

`Polyhedron$scrapeNetlib(netlib.p3.lines)`

Arguments:

`netlib.p3.lines` vector with netlib definition lines

Returns: A new PolyhedronStateDefined object.

Method `scrapeDmccoey()`: scrape Dmccoey polyhedron definition

Usage:

`Polyhedron$scrapeDmccoey(polyhedra.dmccoey.lines)`

Arguments:

`polyhedra.dmccoey.lines` vector with Dmccoey definition lines

Returns: A new PolyhedronStateDefined object.

Method `deserialize()`: deserialize a polyhedron state definition

Usage:

`Polyhedron$deserialize(serialized.polyhedron)`

Arguments:

`serialized.polyhedron` a serialized version of a polyhedron state

Returns: A new PolyhedronStateDefined object.

Method `getName()`: get Polyhedron name

Usage:

`Polyhedron$getName()`

Returns: string with polyhedron name

Method `getState()`: Gets polyhedron state

Usage:

Polyhedron\$getState()

Returns: A new PolyhedronState object.

Method getSolid(): Gets a solid definition

Usage:

Polyhedron\$getSolid()

Returns: A list of vertex vectors composing polyhedron faces.

Method isChecked(): checks Edges consistency

Usage:

Polyhedron\$isChecked()

Returns: A boolean value

Method getRGLModel(): Return an 'rgl' model with an optional transformation described by transformation.matrix parameter

Usage:

Polyhedron\$getRGLModel(transformation.matrix = NULL)

Arguments:

transformation.matrix transformation matrix parameter

Returns: An tmesh3d object

Method exportToXML(): exports an XML definition of current polyhedron

Usage:

Polyhedron\$exportToXML()

Returns: A character object with the XML definition

Method getErrors(): returns the errors found when processing current polyhedron

Usage:

Polyhedron\$getErrors()

Returns: a data.frame with polyhedron errors

Method checkProperties(): check properties of current polyhedron

Usage:

Polyhedron\$checkProperties(expected.vertices, expected.faces)

Arguments:

expected.vertices expected vertices number

expected.faces expected faces number

Returns: Unmodified polyhedron object

Method clone(): The objects of this class are cloneable with this method.

Usage:

Polyhedron\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

ken4rab

PolyhedronState

*PolyhedronState***Description**

This abstract class provide the basis from which every polyhedron state class derivate.

Public fields

source polyhedron definition source

file.id polyhedron file id

errors Errors string

logger class logger

Methods**Public methods:**

- [PolyhedronState\\$new\(\)](#)
- [PolyhedronState\\$addError\(\)](#)
- [PolyhedronState\\$scrape\(\)](#)
- [PolyhedronState\\$getName\(\)](#)
- [PolyhedronState\\$getSolid\(\)](#)
- [PolyhedronState\\$checkEdgesConsistency\(\)](#)
- [PolyhedronState\\$applyTransformationMatrix\(\)](#)
- [PolyhedronState\\$buildRGL\(\)](#)
- [PolyhedronState\\$exportToXML\(\)](#)
- [PolyhedronState\\$clone\(\)](#)

Method new(): Create a polyhedronState object

Usage:

```
PolyhedronState$new(source, file.id)
```

Arguments:

source the source file

file.id the file id

Returns: A new PolyhedronState object. '@description Adds an error to the error string and log it as info

Method addError():

Usage:

PolyhedronState\$addError(current.error)

Arguments:

current.error the error to add

Method scrape(): Scrapes the polyhedra folder files

Usage:

PolyhedronState\$scrape()

Method getName(): Get Polyhedron name

Usage:

PolyhedronState\$getName()

Returns: string with polyhedron name

Method getSolid(): Returns the object corresponding to the solid

Usage:

PolyhedronState\$getSolid()

Method checkEdgesConsistency(): Checks edge consistency

Usage:

PolyhedronState\$checkEdgesConsistency()

Method applyTransformationMatrix(): Apply transformation matrix to polyhedron

Usage:

PolyhedronState\$applyTransformationMatrix(transformation.matrix)

Arguments:

transformation.matrix the transformation matrix to apply to the polyhedron

Method buildRGL(): Creates a 'rgl' representation of the object

Usage:

PolyhedronState\$buildRGL(transformation.matrix)

Arguments:

transformation.matrix the transformation matrix to apply to the polyhedron

Method exportToXML(): Gets an XML representation out of the polyhedron object

Usage:

PolyhedronState\$exportToXML()

Method clone(): The objects of this class are cloneable with this method.

Usage:

PolyhedronState\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

ken4rab

PolyhedronStateDefined

PolyhedronStateDefined

Description

Polyhedron State scraped and defined

Super class

`Rpolyhedra::PolyhedronState` -> PolyhedronStateDefined

Public fields

`file.id` polyhedron filename in original
`source` polyhedron definition source (netlibldmccoey)
`name` polyhedron name (netlibldmccoey)
`symbol` the eqn(1) input for two symbols separated by a tab; the Johnson symbol, and the Schlafli symbol (netlib)
`dual` the name of the dual polyhedron optionally followed by a horizontal tab and the number of the dual (netlib)
`sfaces` polyhedron solid face list (netlib)
`svertices` polyhedron solid vertices list (netlib)
`vertices` Polyhedron vertices list (netlibldmccoey)
`vertices.centered` centered vertices for applying transformation matrices
`net` polyhedron 2D net model with vertices defined for a planar representation (netlib)
`solid` polyhedron list of edges which generate a solid (netlibldmccoey)
`hinges` Polyhedron hinge list (netlib)
`dih` Dih attribute (netlib)
`edges` polyhedron edges (netlibldmccoey)
`transformation.matrix` transformation matrix for calculations and visualizing polyhedron

Methods

Public methods:

- `PolyhedronStateDefined$new()`
- `PolyhedronStateDefined$scrape()`
- `PolyhedronStateDefined$saveToJson()`
- `PolyhedronStateDefined$getName()`
- `PolyhedronStateDefined$getSymbol()`
- `PolyhedronStateDefined$adjustVertices()`

- PolyhedronStateDefined\$getVertices()
- PolyhedronStateDefined\$getNet()
- PolyhedronStateDefined\$getSolid()
- PolyhedronStateDefined\$inferEdges()
- PolyhedronStateDefined\$checkEdgesConsistency()
- PolyhedronStateDefined\$triangulate()
- PolyhedronStateDefined\$getConvHull()
- PolyhedronStateDefined\$calculateMassCenter()
- PolyhedronStateDefined\$getNormalizedSize()
- PolyhedronStateDefined\$getTransformedVertices()
- PolyhedronStateDefined\$resetTransformationMatrix()
- PolyhedronStateDefined\$applyTransformationMatrix()
- PolyhedronStateDefined\$buildRGL()
- PolyhedronStateDefined\$exportToXML()
- PolyhedronStateDefined\$expectEqual()
- PolyhedronStateDefined\$serialize()
- PolyhedronStateDefined\$clone()

Method new(): object initialization routine

Usage:

```
PolyhedronStateDefined$new(
  source,
  file.id,
  name,
  vertices,
  solid,
  net = NULL,
  symbol = "",
  dual = NULL,
  sfaces = NULL,
  svertices = NULL,
  hinges = NULL,
  dihed = NULL,
  normalize.size = TRUE
)
```

Arguments:

source the library to use
 file.id identifier of the definition file.
 name the polyhedron name
 vertices the vertices
 solid the solid object
 net the net
 symbol the symbol
 dual whether it is dual or not

sfaces the solid faces
svertices the solid vertices
hinges the hinges
dih the dih
normalize.size whether it has to normalize the size or not

Returns: A new PolyhedronStateDefined object.

Method scrape(): scrape polyhedron. As the state is defined this functions do nothing

Usage:

PolyhedronStateDefined\$scrape()

Returns: current object

Method saveToJson(): saves the state to a JSON file

Usage:

PolyhedronStateDefined\$saveToJson(pretty = FALSE)

Arguments:

pretty whether json output is pretty or not

Returns: a json object

Method getName(): get Polyhedron name

Usage:

PolyhedronStateDefined\$getName()

Returns: string with polyhedron name

Method getSymbol(): get Polyhedron symbol

Usage:

PolyhedronStateDefined\$getSymbol()

Returns: string with polyhedron symbol

Method adjustVertices(): adjust polyhedron Vertices

Usage:

PolyhedronStateDefined\$adjustVertices(normalize.size = TRUE)

Arguments:

normalize.size whether it has to normalize the size or not

Returns: modified PolyhedronStateDefined object.

Method getVertices(): Get the polyhedron state

Usage:

PolyhedronStateDefined\$getVertices(solid = FALSE)

Arguments:

solid toggles the production of solid vertices.

Method getNet(): Gets the net property

Usage:

PolyhedronStateDefined\$getNet()

Method getSolid(): Gets the solid property

Usage:

PolyhedronStateDefined\$getSolid()

Method inferEdges(): Infer edges

Usage:

PolyhedronStateDefined\$inferEdges(force.recalculation = FALSE)

Arguments:

force.recalculation forces the recalculation of the edges

Method checkEdgesConsistency(): Checks edges consistency

Usage:

PolyhedronStateDefined\$checkEdgesConsistency()

Method triangulate(): Triangulates the polyhedron

Usage:

PolyhedronStateDefined\$triangulate(force = FALSE)

Arguments:

force forces the triangulation.

Method getConvHull(): Gets the convex hull

Usage:

```
PolyhedronStateDefined$getConvHull(
  transformation.matrix = self$transformation.matrix,
  vertices.id.3d = private$vertices.id.3d
)
```

Arguments:

transformation.matrix the transformation matrix

vertices.id.3d the vertices ids

Returns: the convex hull

Method calculateMassCenter(): Calculates the center of mass.

Usage:

```
PolyhedronStateDefined$calculateMassCenter(
  vertices.id.3d = private$vertices.id.3d,
  applyTransformation = TRUE
)
```

Arguments:

vertices.id.3d the vertices ids

applyTransformation does it need to apply transformations?

Method getNormalizedSize(): Gets the normalized size

Usage:

```
PolyhedronStateDefined$getNormalizedSize(size)
```

Arguments:

size the object's size

Method getTransformedVertices(): Gets the transformed vertices

Usage:

```
PolyhedronStateDefined$getTransformedVertices(  
  vertices = self$vertices.centered,  
  transformation.matrix = self$transformation.matrix  
)
```

Arguments:

vertices input vertices

transformation.matrix the transformation matrix

Method resetTransformationMatrix(): Resets the transformation matrix

Usage:

```
PolyhedronStateDefined$resetTransformationMatrix()
```

Method applyTransformationMatrix(): Apply transformation matrix to polyhedron

Usage:

```
PolyhedronStateDefined$applyTransformationMatrix(transformation.matrix)
```

Arguments:

transformation.matrix the transformation matrix to apply to the polyhedron

Returns: an applied transformation.matrix

Method buildRGL(): Build 'rgl'

Usage:

```
PolyhedronStateDefined$buildRGL(transformation.matrix = NULL)
```

Arguments:

transformation.matrix the transformation matrix

Method exportToXML(): Exports the object to XML format

Usage:

```
PolyhedronStateDefined$exportToXML()
```

Method expectEqual(): Determines if a polyhedron is equal to this one.

Usage:

```
PolyhedronStateDefined$expectEqual(polyhedron)
```

Arguments:

polyhedron the polyhedron to compare to.

Method `serialize()`: Serialize the object.

Usage:

`PolyhedronStateDefined$serialize()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`PolyhedronStateDefined$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Author(s)

ken4rab

PolyhedronStateDeserializer

PolyhedronStateDeserializer

Description

Polyhedron state for deserialize from database

Super class

`Rpolyhedra::PolyhedronState` -> PolyhedronStateDeserializer

Public fields

`serialized.polyhedron` polyhedron definition serialized

Methods

Public methods:

- `PolyhedronStateDeserializer$new()`
- `PolyhedronStateDeserializer$scrape()`
- `PolyhedronStateDeserializer$clone()`

Method `new()`: Initialize PolyhedronStateDeserializer object

Usage:

`PolyhedronStateDeserializer$new(serialized.polyhedron)`

Arguments:

`serialized.polyhedron` a serialized polyhedron

Returns: A new PolyhedronStateDeserializer object.

Method scrape(): Generates a PolyhedronStateDefined from a serialized polyhedron

Usage:

PolyhedronStateDeserializer\$scrape()

Returns: A new PolyhedronStateDefined object.

Method clone(): The objects of this class are cloneable with this method.

Usage:

PolyhedronStateDeserializer\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

ken4rab

PolyhedronStateDmccooeyScraper

PolyhedronStateDmccooeyScraper

Description

Scrapes polyhedra from a dmccooey file format

Super class

[Rpolyhedra::PolyhedronState](#) -> PolyhedronStateDmccooeyScraper

Public fields

regexp.values.names regexp for scraping values names

regexp.rn regexp for scraping real numbers

regexp.values regexp for scraping values

regexp.vertex regexp for scraping vertices

regexp.faces regexp for scraping faces

polyhedra.dmccooey.lines dmccooey polyhedra definition lines

labels.map labels map where values are

values labels map where values are

vertices specification

vertices.replaced 3D values

faces definition

Methods

Public methods:

- [PolyhedronStateDmccooeyScraper\\$new\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$setupRegexp\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$scrapeValues\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$scrapeVertices\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$scrapeFaces\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$scrape\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$getName\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$applyTransformationMatrix\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$buildRGL\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$exportToXML\(\)](#)
- [PolyhedronStateDmccooeyScraper\\$clone\(\)](#)

Method `new()`: Initialize Dmccooey scraper

Usage:

```
PolyhedronStateDmccooeyScraper$new(file.id, polyhedra.dmccooey.lines)
```

Arguments:

`file.id` identifier of the definition file.

`polyhedra.dmccooey.lines` raw Dmccooey definition file lines

Returns: A new PolyhedronStateDmccooeyScraper object.

Method `setupRegexp()`: setupRegexp for Dmccooey definition

Usage:

```
PolyhedronStateDmccooeyScraper$setupRegexp()
```

Returns: This PolyhedronStateDmccooeyScraper object with regexp defined.

Method `scrapeValues()`: scrape values from Dmccooey definition

Usage:

```
PolyhedronStateDmccooeyScraper$scrapeValues(values.lines)
```

Arguments:

`values.lines` values definitions in Dmccooey source

Returns: This PolyhedronStateDmccooeyScraper object with values defined.

Method `scrapeVertices()`: scrape polyhedron vertices from definition

Usage:

```
PolyhedronStateDmccooeyScraper$scrapeVertices(vertices.lines)
```

Arguments:

`vertices.lines` vertices definitions in Dmccooey source

Returns: This PolyhedronStateDmccooeyScraper object with faces defined.

Method `scrapeFaces()`: scrape polyhedron faces from definition

Usage:

PolyhedronStateDmccoeyScraper\$scrapeFaces(faces.lines)

Arguments:

faces.lines face

Returns: This PolyhedronStateDmccoeyScraper object with faces defined.

Method scrape(): scrape Dmccoey polyhedron definition

Usage:

PolyhedronStateDmccoeyScraper\$scrape()

Returns: A new PolyhedronStateDefined object.

Method getName(): get Polyhedron name

Usage:

PolyhedronStateDmccoeyScraper\$getName()

Returns: string with polyhedron name

Method applyTransformationMatrix(): Apply transformation matrix to polyhedron

Usage:

PolyhedronStateDmccoeyScraper\$applyTransformationMatrix(transformation.matrix)

Arguments:

transformation.matrix the transformation matrix to apply to the polyhedron

Method buildRGL(): Creates a 'rgl' representation of the object

Usage:

PolyhedronStateDmccoeyScraper\$buildRGL(transformation.matrix)

Arguments:

transformation.matrix the transformation matrix to apply to the polyhedron

Method exportToXML(): serializes object in XML

Usage:

PolyhedronStateDmccoeyScraper\$exportToXML()

Method clone(): The objects of this class are cloneable with this method.

Usage:

PolyhedronStateDmccoeyScraper\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

ken4rab

PolyhedronStateNetlibScraper
PolyhedronStateNetlibScraper

Description

Scrapes polyhedra from a PHD file format.

Super class

[Rpolyhedra::PolyhedronState](#) -> PolyhedronStateNetlibScraper

Public fields

`netlib.p3.lines` The path to the PHD files
`labels.rows` Labels - row of appearance
`labels.map` Labels - Map of content
`errors` the errors found

Methods

Public methods:

- [PolyhedronStateNetlibScraper\\$new\(\)](#)
- [PolyhedronStateNetlibScraper\\$extractRowsFromLabel\(\)](#)
- [PolyhedronStateNetlibScraper\\$getLabels\(\)](#)
- [PolyhedronStateNetlibScraper\\$scrapeNet\(\)](#)
- [PolyhedronStateNetlibScraper\\$extractCFOutBrackets\(\)](#)
- [PolyhedronStateNetlibScraper\\$scrapeVertices\(\)](#)
- [PolyhedronStateNetlibScraper\\$setupLabelsOrder\(\)](#)
- [PolyhedronStateNetlibScraper\\$getDataFromLabel\(\)](#)
- [PolyhedronStateNetlibScraper\\$getName\(\)](#)
- [PolyhedronStateNetlibScraper\\$scrape\(\)](#)
- [PolyhedronStateNetlibScraper\\$applyTransformationMatrix\(\)](#)
- [PolyhedronStateNetlibScraper\\$buildRGL\(\)](#)
- [PolyhedronStateNetlibScraper\\$exportToXML\(\)](#)
- [PolyhedronStateNetlibScraper\\$clone\(\)](#)

Method `new()`: Initializes the object, taking the `file.id` and PDH file as parameters

Usage:

`PolyhedronStateNetlibScraper$new(file.id, netlib.p3.lines)`

Arguments:

`file.id` the file id

`netlib.p3.lines` the lines to add

Returns: A new PolyhedronStateNetlibScraper object.

Method `extractRowsFromLabel()`: Extracts data from the label, taking the label number and the expected label as parameters

Usage:

```
PolyhedronStateNetlibScraper$extractRowsFromLabel(label.number, expected.label)
```

Arguments:

`label.number` the label number

`expected.label` the expected label

Method `getLabels()`: get Labels from current netlib file description

Usage:

```
PolyhedronStateNetlibScraper$getLabels()
```

Returns: a list containing labels from netlib file description

Method `scrapeNet()`: scrape Net Model from netlib format

Usage:

```
PolyhedronStateNetlibScraper$scrapeNet(net.txt, offset = 0)
```

Arguments:

`net.txt` a vector containing net model in netlib format

`offset` in numbering vertices

Returns: a list containing a net model

Method `extractCFOutBrackets()`: Remove brackets for current field content

Usage:

```
PolyhedronStateNetlibScraper$extractCFOutBrackets(x)
```

Arguments:

`x` a string containing brackets

Returns: value

Method `scrapeVertices()`: scrape vertices described in netlib format

Usage:

```
PolyhedronStateNetlibScraper$scrapeVertices(vertices.txt)
```

Arguments:

`vertices.txt` vector containing netlib format vertices

Returns: data.frame containing netlib vertices

Method `setupLabelsOrder()`: setupLabelsOrder

Usage:

```
PolyhedronStateNetlibScraper$setupLabelsOrder()
```

Arguments:

`vertices.txt` vector containing netlib format vertices

Returns: data.frame containing netlib vertices

Method `getDataFromLabel()`: Get data from label specified as parameter

Usage:

`PolyhedronStateNetlibScraper$getDataFromLabel(label)`

Arguments:

`label` the label to get data from

Returns: value

Method `getName()`: get Polyhedron name

Usage:

`PolyhedronStateNetlibScraper$getName()`

Returns: string with polyhedron name

Method `scrape()`: scrape Netlib polyhedron definition

Usage:

`PolyhedronStateNetlibScraper$scrape()`

Returns: A new PolyhedronStateDefined object.

Method `applyTransformationMatrix()`: Apply transformation matrix to polyhedron

Usage:

`PolyhedronStateNetlibScraper$applyTransformationMatrix(transformation.matrix)`

Arguments:

`transformation.matrix` the transformation matrix to apply to the polyhedron

Method `buildRGL()`: Creates a 'rgl' representation of the object

Usage:

`PolyhedronStateNetlibScraper$buildRGL(transformation.matrix)`

Arguments:

`transformation.matrix` the transformation matrix to apply to the polyhedron

Method `exportToXML()`: serializes object in XML

Usage:

`PolyhedronStateNetlibScraper$exportToXML()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`PolyhedronStateNetlibScraper$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Author(s)

ken4rab

polyhedronToXML	<i>Polyhedron to XML</i>
-----------------	--------------------------

Description

Gets an XML representation out of the polyhedron object

Usage

```
polyhedronToXML(polyhedron.state.defined, is.transformed.vertices = TRUE)
```

Arguments

```
polyhedron.state.defined
                        the polyhedron to get a representation from
is.transformed.vertices
                        flag which states if vertices are in original position or transformationMatrix ap-
                        plied
```

Value

an XML document, ready to be converted to String with XML::saveXML()

Examples

```
# get the representation of a cube (netlib library)
XML::saveXML(polyhedronToXML(getPolyhedron("netlib", "cube")$state))
```

scrapePolyhedra	<i>Scrape polyhedra objects</i>
-----------------	---------------------------------

Description

Gets polyhedra objects from text files of different sources, scheduling and scraping using predefined configurations.

Usage

```
scrapePolyhedra(
  scrape.config,
  source.fileNames = NULL,
  sources.config = getUserEnvir(".available.sources"),
  logger = lgr
)
```

Arguments

`scrape.config` predefined configuration for scraping
`source.filenames` if not null specify which source filenames to scrape
`sources.config` the sources that will be used by the function
`logger` logger for inheriting threshold from calling class/function

Value

polyhedra db object

scrapePolyhedraSources

Scrape polyhedra sources

Description

Scrapes polyhedra objects from text files of different sources, in order to make them available to the package.

Usage

```

scrapePolyhedraSources(sources.config =
  getUserEnvir(".available.sources"),
  max.quant.config.schedule = 0,
  max.quant.scrape = 0, time2scrape.source = 30,
  source.filenames = NULL, retry.scrape = FALSE,
  logger = lgr)
  
```

Arguments

`sources.config` the sources that will be used by the function
`max.quant.config.schedule` number of files to schedule
`max.quant.scrape` number of files scrape
`time2scrape.source` time applied to scrape source
`source.filenames` if not null specify which source filenames to scrape
`retry.scrape` should it retry scrape?
`logger` logger for inheriting threshold from calling class/function

Value

polyhedra db object

switchToFullDatabase	<i>Switch to full database</i>
----------------------	--------------------------------

Description

Prompts user for changing database to fulldb in user filespace. Also, allows the user to switch back to the package database, which is a minimal one for testing purposes.

Usage

```
switchToFullDatabase(env = NA, logger = lgr)
```

Arguments

env	The environment to run on, can be PACKAGE,
logger	logger for inheriting threshold from calling class/function HOME or NA. If NA, it asks the user for a an Environment.

Value

.data.env

Index

genLogger, [3](#)
getAvailablePolyhedra, [4](#)
getAvailableSources, [5](#)
getLogger, [5](#)
getPolyhedraObject, [6](#)
getPolyhedron, [6](#)

loggerSetupFile, [7](#)

mutate_cond, [8](#)

PolyhedraDatabase, [8](#)
Polyhedron, [14](#)
PolyhedronState, [17](#)
PolyhedronStateDefined, [19](#)
PolyhedronStateDeserializer, [24](#)
PolyhedronStateDmccooeyScraper, [25](#)
PolyhedronStateNetlibScraper, [28](#)
polyhedronToXML, [31](#)

Rpolyhedra (Rpolyhedra-package), [2](#)
Rpolyhedra-package, [2](#)
Rpolyhedra::PolyhedronState, [19](#), [24](#), [25](#),
[28](#)

scrapePolyhedra, [31](#)
scrapePolyhedraSources, [32](#)
switchToFullDatabase, [33](#)