

Package ‘SeedMaker’

July 21, 2025

Title Generate a Collection of Seeds from a Single Seed

Version 1.0.0

Description A mechanism for easily generating and organizing a collection of seeds from a single seed, which may be subsequently used to ensure reproducibility in processes/pipelines that utilize multiple random components (e.g., trial simulation).

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

Suggests devtools (>= 2.4.5), knitr (>= 1.45), rmarkdown (>= 2.25), testthat (>= 3.2.0), usethis (>= 2.2.2)

Imports checkmate (>= 2.3.0), dplyr (>= 1.1.4), rlang (>= 1.1.2), tibble (>= 3.2.1), tidyr (>= 1.3.0)

URL <https://github.com/hdhshowalter/SeedMaker>

BugReports <https://github.com/hdhshowalter/SeedMaker/issues>

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Hollins Showalter [aut, cre],
Eli Lilly and Company [cph, fnd]

Maintainer Hollins Showalter <hollins.showalter@gmail.com>

Repository CRAN

Date/Publication 2025-01-17 09:00:02 UTC

Contents

seed_gen	2
seed_maker	3
Index	8

seed_gen	<i>Generate a vector of seeds</i>
----------	-----------------------------------

Description

seed_gen() generates a vector of seeds from a single seed.

Usage

```
seed_gen(seed, n, sample_vector = 1:1e+06)
```

Arguments

seed	A number, interpreted as an integer, or NULL (see set.seed()).
n	The number of seeds to generate.
sample_vector	The values from which to sample (without replacement).

Details

length(sample_vector) must be $\geq n$.

The values of sample_vector must be unique, positive integers.

Value

An integer vector containing n randomly drawn values from sample_vector.

Examples

```
seeds1 <- seed_gen(  
  seed = 1234,  
  n = 10  
)  
  
seeds2 <- seed_gen(  
  seed = 1234,  
  n = 10,  
  sample_vector = 1:100  
)
```

seed_maker

*Construct a list containing a collection of seeds***Description**

seed_maker() constructs a hierarchical list containing a collection of seeds from a single seed.

Usage

```
seed_maker(
  seed,
  level_names,
  n_per_level,
  sample_vector = rep(list(rlang::expr(1:1e+06)), length(level_names)),
  index_level = rep(TRUE, length(level_names)),
  flatten = FALSE
)
```

Arguments

seed	A number, interpreted as an integer, or NULL (see set.seed()).
level_names	A character vector, or list of character vectors, indicating the element name(s) to use for each level of the returned list.
n_per_level	An integer vector indicating the number of elements to produce at each level of the returned list.
sample_vector	A list of expressions that are evaluable as integer vectors indicating the values from which to sample (without replacement) at each level of the returned list.
index_level	A logical vector indicating whether to index the root name of a respective level.
flatten	"Flatten" the lowest level of the returned list into a named vector?

Details

length(level_names) must be equal to length(n_per_level) must be equal equal to length(sample_vector) must be equal to length(index_level). When these arguments are greater than length 1, the intermediate seeds used to produce the seeds at the lowest level of the returned list are not included therein. In other words, only the collection of seeds at the lowest list level are returned.

If level_names is a character vector, each of its elements is used as the root name for the list elements produced at the respective level. See seeds_list1 and seeds_list2 in **Examples**.

If level_names is a list of character vectors:

- The element contained in a length 1 vector is used as the root name for the list elements produced at the respective level.
- Elements contained in a vector that is greater than length 1 are used verbatim as the names for the list elements produced at the respective level. The corresponding value of n_per_level must match the length of the vector.

See `seeds_list3`, `seeds_list4`, and `seeds_list5` in **Examples**.

For each element, `i`, of `sample_vector`:

- `length(eval(sample_vector[[i]]))` must be $\geq n_per_level[i]$.
- The values of `eval(sample_vector[[i]])` must be unique, positive integers.

See `seeds_list6`, `seeds_list7`, and `seeds_list8` in **Examples**.

Element name indexing applies to root name-provided levels only. Thus, for each element, `i`, of `index_level`, if `length(level_names[[i]])` is greater than 1, the value of `index_level[i]` is ignored. Otherwise:

- When `index_level[i]` is `TRUE`, the element names at the respective level are indexed from `1 - n_per_level[i]`.
- When `index_level[i]` is `FALSE`, the element name at the respective level is used verbatim, so long as `n_per_level[i] = 1`, since suppressing element name indexing makes sense only for single-element levels.

See `seeds_list9`, `seeds_list10`, `seeds_list11`, `seeds_list12`, and `seeds_list13` in **Examples**.

When `flatten` is set to `TRUE`, each set of seeds at the lowest level of the returned list is converted into a named vector (versus remaining in the default structure, which is a list of single value elements). When only a single level is specified (via `level_names`, `n_per_level`, `sample_vector`, and `index_level` all being length 1), a named integer vector is returned instead of a list. See `seeds_flat1`, `seeds_flat2`, `seeds_flat5`, `seeds_flat9`, `seeds_flat10`, and `seeds_flat11` in **Examples**.

Value

When `flatten` is set to `FALSE`, a hierarchical list with `length(level_names)` levels containing a collection of seeds.

When `flatten` is set to `TRUE`, a hierarchical list with `length(level_names) - 1` level(s) containing a collection of seeds (where "0 levels" corresponds to a named integer vector - see **Details**).

Examples

```
seeds_list1 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
  n_per_level = c(10)
)

seeds_list2 <- seed_maker(
  seed = 1234,
  level_names = c("sim", "dataset"),
  n_per_level = c(10, 15)
)

seeds_list3 <- seed_maker(
  seed = 1234,
  level_names = list("sim", c("component_a", "component_b", "component_c")),
```

```
n_per_level = c(10, 3)
)

try(seeds_list4 <- seed_maker(
  seed = 1234,
  level_names = list("sim", c("component_a", "component_b", "component_c")),
  n_per_level = c(10, 4)
))

seeds_list5 <- seed_maker(
  seed = 1234,
  level_names = list(
    "sim",
    c("component_a", "component_b", "component_c"),
    "dataset"
  ),
  n_per_level = c(10, 3, 5)
)

seeds_list6 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
  n_per_level = c(10),
  sample_vector = list(1:100)
)

seeds_list7 <- seed_maker(
  seed = 1234,
  level_names = c("sim", "dataset"),
  n_per_level = c(10, 15),
  sample_vector = list(1:100, 1:1000)
)

seeds_list8 <- seed_maker(
  seed = 1234,
  level_names = list(
    "sim",
    c("component_a", "component_b", "component_c"),
    "dataset"
  ),
  n_per_level = c(10, 3, 5),
  sample_vector = list(1:100, 1:1000, 1:10000)
)

seeds_list9 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
  n_per_level = c(1)
)

try(seeds_list10 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
```

```

    n_per_level = c(10),
    index_level = FALSE
  ))

seeds_list11 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
  n_per_level = c(1),
  index_level = FALSE
)

seeds_list12 <- seed_maker(
  seed = 1234,
  level_names = list("sim", c("component_a", "component_b", "component_c")),
  n_per_level = c(1, 3),
  index_level = c(FALSE, TRUE)
)

seeds_list13 <- seed_maker(
  seed = 1234,
  level_names = list("sim", c("component_a", "component_b", "component_c")),
  n_per_level = c(1, 3),
  index_level = c(FALSE, FALSE)
)

identical(seeds_list12, seeds_list13)

seeds_flat1 <- seed_maker(
  seed = 1234,
  level_names = c("sim"),
  n_per_level = c(10),
  flatten = TRUE
)

is.list(seeds_flat1)
is.integer(seeds_flat1)

seeds_flat2 <- seed_maker(
  seed = 1234,
  level_names = c("sim", "dataset"),
  n_per_level = c(10, 15),
  flatten = TRUE
)

is.list(seeds_flat2$sim1)
is.integer(seeds_flat2$sim1)

seeds_flat5 <- seed_maker(
  seed = 1234,
  level_names = list(
    "sim",
    c("component_a", "component_b", "component_c"),
    "dataset"
  )
)

```

```
    ),
    n_per_level = c(10, 3, 5),
    flatten = TRUE
  )

  is.list(seeds_flat5$sim1$component_a)
  is.integer(seeds_flat5$sim1$component_a)

  seeds_flat9 <- seed_maker(
    seed = 1234,
    level_names = c("sim"),
    n_per_level = c(1),
    flatten = TRUE
  )

  is.list(seeds_flat9)
  is.integer(seeds_flat9)

  try(seeds_flat10 <- seed_maker(
    seed = 1234,
    level_names = c("sim"),
    n_per_level = c(10),
    index_level = FALSE,
    flatten = TRUE
  ))

  seeds_flat11 <- seed_maker(
    seed = 1234,
    level_names = c("sim"),
    n_per_level = c(1),
    index_level = FALSE,
    flatten = TRUE
  )

  is.list(seeds_flat11)
  is.integer(seeds_flat11)
```

Index

seed_gen, [2](#)
seed_maker, [3](#)
set.seed(), [2](#), [3](#)