

Package ‘SeuratExplorer’

July 21, 2025

Title An 'Shiny' App for Exploring scRNA-seq Data Processed in 'Seurat'

Version 0.1.0

Description A simple, one-command package which runs an interactive dashboard capable of common visualizations for single cell RNA-seq. 'SeuratExplorer' requires a processed 'Seurat' object, which is saved as 'rds' or 'qs2' file.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

Imports ggplot2, utils, Seurat, shiny, shinydashboard, DT, shinycssloaders, patchwork, tools, colourpicker, shinyWidgets, scales, SeuratObject, shinyjqui, shinyBS, ggalluvial, dplyr, ComplexHeatmap, qs2, circlize, reshape2, stats, htmltools

Depends R (>= 4.1.0)

Suggests BiocManager, DESeq2, MAST, roxygen2, devtools

NeedsCompilation no

Author Yongchao Zhang [aut, cre] (<https://github.com/fentouxungui>)

Maintainer Yongchao Zhang <zhangyongchao@nibs.ac.cn>

Repository CRAN

Date/Publication 2025-03-13 13:10:05 UTC

Contents

cellRatioPlot	2
explorer_body_ui	3
explorer_server	3
explorer_sidebar_ui	4
getColors	4
launchSeuratExplorer	5
server	5
top_genes	6
ui	6

Index[7](#)

cellRatioPlot	<i>plot cell percentage barplot</i>
---------------	-------------------------------------

Description

support facet, codes refer to: <https://github.com/junjunlab/scRNAtoolVis/blob/master/R/cellRatioPlot.R>, with modification

Usage

```
cellRatioPlot(  
  object = NULL,  
  sample.name = NULL,  
  sample.order = NULL,  
  celltype.name = NULL,  
  celltype.order = NULL,  
  facet.name = NULL,  
  facet.order = NULL,  
  col.width = 0.7,  
  flow.alpha = 0.25,  
  flow.curve = 0,  
  color.choice = NULL  
)
```

Arguments

object	an Seurat object
sample.name	x axis
sample.order	order for x axis
celltype.name	column fill by
celltype.order	order for fill by
facet.name	column name for facet
facet.order	the order for facet
col.width	column width, from 0-1
flow.alpha	transparency for flow
flow.curve	curve for flow
color.choice	color choice for fill

Value

a ggplot2 object

Examples

```
#NULL
```

explorer_body_ui	<i>generate the body UI for each menu item specified in explorer_sidebar_ui</i>
------------------	---

Description

generate the body UI for each menu item specified in explorer_sidebar_ui

Usage

```
explorer_body_ui(tab_list)
```

Arguments

tab_list a tag list for the body UI of shiny dashboard

Value

a filled tag list for body UI

Examples

```
tab_list <- list()
tab_list <- explorer_body_ui(tab_list = tab_list)
```

explorer_server	<i>server side functions related to explorer_sidebar_ui</i>
-----------------	---

Description

server side functions related to explorer_sidebar_ui

Usage

```
explorer_server(input, output, session, data, verbose = FALSE)
```

Arguments

input	server input
output	server output
session	server session
data	the Seurat object and related parameters
verbose	for debug use

Value

server side functions related to explorer_sidebar_ui

explorer_sidebar_ui	<i>some menu items of the dashboard sidebar</i>
---------------------	---

Description

to generate some menu items for the dashboard, which can be integrated to other packages, such as 'fentouxungui/SeuratExplorerServer' from github.

Usage

```
explorer_sidebar_ui()
```

Value

return some menu items for the dashboard

Examples

```
explorer_sidebar_ui()
```

getColors	<i>getColors</i>
-----------	------------------

Description

getColors

Usage

```
getColors(color.platte = NULL, choice = NULL, n = NULL)
```

Arguments

color.platte	predefined color list
choice	color name
n	how many colors to return

Value

a color list

Examples

```
# null
```

launchSeuratExplorer	<i>Launch shiny app</i>
----------------------	-------------------------

Description

Launch shiny app

Usage

```
launchSeuratExplorer(verbose = FALSE)
```

Arguments

verbose for debug use

Value

In-browser Shiny Application launch

Examples

```
if(interactive()){launchSeuratExplorer()}
```

server	<i>Server</i>
--------	---------------

Description

Server

Usage

```
server(input, output, session)
```

Arguments

input Input from the UI
output Output to send back to UI
session from shiny server function

Value

the server functions of shiny app

top_genes	<i>Find Top Genes by Cell</i>
-----------	-------------------------------

Description

for each cell, find genes that has high UMI percentage, for example, if a cell has 10000 UMIs, and the UMI percentage cutoff is set to 0.01, then all genes that has more than $10000 * 0.01 = 100$ UMIs is thought to be the highly expressed genes for this cell.summary those genes for each cluster, firstly get all highly expressed genes in a cluster, some genes may has less cells, then for each gene, count cells in which this genes is highly expressed, and also calculate the mean and median UMI percentage in those highly expressed cells.

Usage

```
top_genes(SeuratObj, expr.cut = 0.01, group.by)
```

Arguments

- | | |
|-----------|--|
| SeuratObj | Seurat object |
| expr.cut | UMI percentage cutoff, in a cell, if a gene with UMIs ratio more than this cutoff, this gene will be assigned to highly expressed gene for this cell |
| group.by | how to group cells |

Value

a data frame

ui	<i>UI</i>
----	-----------

Description

UI

Usage

```
ui()
```

Value

the UI part of the shiny app

Examples

```
ui()
```

Index

cellRatioPlot, [2](#)

explorer_body_ui, [3](#)

explorer_server, [3](#)

explorer_sidebar_ui, [4](#)

getColors, [4](#)

launchSeuratExplorer, [5](#)

server, [5](#)

top_genes, [6](#)

ui, [6](#)