

Package ‘ari’

July 22, 2025

Type Package

Title Automated R Instructor

Version 0.3.5

Description Create videos from 'R Markdown' documents, or images and audio files. These images can come from image files or HTML slides, and the audio files can be provided by the user or computer voice narration can be created using 'Amazon Polly'. The purpose of this package is to allow users to create accessible, translatable, and reproducible lecture videos. See <https://aws.amazon.com/polly/> for more information.

SystemRequirements ffmpeg (>= 3.2.4)

Depends R (>= 3.1.0)

Imports text2speech (>= 0.2.8), tuneR, webshot, purrr, rmarkdown, xml2, rvest, tools, progress, hms

Suggests testthat, grDevices, xaringan, knitr

License MIT + file LICENSE

URL <http://github.com/seankross/ari>

BugReports <http://github.com/seankross/ari/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

VignetteBuilder knitr

NeedsCompilation no

Author Sean Kross [aut, cre],
John Muschelli [ctb]

Maintainer Sean Kross <sean@seankross.com>

Repository CRAN

Date/Publication 2020-02-08 19:10:13 UTC

Contents

ari_burn_subtitles	2
ari_example	3
ari_narrate	3
ari_spin	4
ari_stitch	6
ari_talk	7
ffmpeg_codecs	8
ffmpeg_exec	9
set_audio_codec	10
Index	12

ari_burn_subtitles	<i>Burn Subtitles into a video</i>
--------------------	------------------------------------

Description

Burn Subtitles into a video

Usage

```
ari_burn_subtitles(video, srt, verbose = FALSE)
```

Arguments

- video Video in mp4 format
- srt Subtitle file in srt format
- verbose print diagnostic messages. If > 1, then more are printed

Value

Name of output video

Note

This needs ffmpeg that was compiled with --enable-libass as per <https://trac.ffmpeg.org/wiki/HowToBurnSubtitlesIntoVideo>

ari_example	<i>Get the path to an ari example file</i>
-------------	--

Description

This function allows you to quickly access files that are used in the ari documentation.

Usage

```
ari_example(path = NULL)
```

Arguments

path	The name of the file. If no argument is provided then all of the example files will be listed.
------	--

Value

A character string

Examples

```
ari_example("ari_intro.Rmd")
```

ari_narrate	<i>Create a video from slides and a script</i>
-------------	--

Description

ari_narrate creates a video from a script written in markdown and HTML slides created with [rmarkdown](#) or a similar package. This function uses [Amazon Polly](#) via [ari_spin](#).

Usage

```
ari_narrate(
  script,
  slides,
  output = tempfile(fileext = ".mp4"),
  voice = text2speech::tts_default_voice(service = service),
  service = "amazon",
  capture_method = c("vectorized", "iterative"),
  subtitles = FALSE,
  ...,
  verbose = FALSE,
  audio_codec = get_audio_codec(),
  video_codec = get_video_codec(),
  cleanup = TRUE
)
```

Arguments

script	Either a markdown file where every paragraph will be read over a corresponding slide, or an .Rmd file where each HTML comment will be used for narration.
slides	A path or URL for an HTML slideshow created with rmarkdown , xaringan , or a similar package.
output	The path to the video file which will be created.
voice	The voice you want to use. See tts_voices for more information about what voices are available.
service	speech synthesis service to use, passed to tts . Either "amazon" or "google".
capture_method	Either "vectorized" or "iterative". The vectorized mode is faster though it can cause screens to repeat. If making a video from an ioslides_presentation you should use "iterative".
subtitles	Should a .srt file be created with subtitles? The default value is FALSE. If TRUE then a file with the same name as the output argument will be created, but with the file extension .srt.
...	Arguments that will be passed to webshot .
verbose	print diagnostic messages. If > 1, then more are printed
audio_codec	The audio encoder for the splicing. If this fails, try copy.
video_codec	The video encoder for the splicing. If this fails, see <code>ffmpeg -codecs</code>
cleanup	If TRUE, interim files are deleted

Value

The output from [ari_spin](#)

Examples

```
## Not run:

#
ari_narrate(system.file("test", "ari_intro_script.md", package = "ari"),
            system.file("test", "ari_intro.html", package = "ari"),
            voice = "Joey")

## End(Not run)
```

ari_spin

Create a video from images and text

Description

Given equal length vectors of paths to images (preferably .jpgs or .pngs) and strings which will be synthesized by [Amazon Polly](#) or any other synthesizer available in [tts](#), this function creates an .mp4 video file where each image is shown with its corresponding narration. This function uses [ari_stitch](#) to create the video.

Usage

```
ari_spin(
  images,
  paragraphs,
  output = tempfile(fileext = ".mp4"),
  voice = text2speech::tts_default_voice(service = service),
  service = "amazon",
  subtitles = FALSE,
  ...
)
```

Arguments

images	A vector of paths to images.
paragraphs	A vector strings that will be spoken by Amazon Polly.
output	A path to the video file which will be created.
voice	The voice you want to use. See tts_voices for more information about what voices are available.
service	speech synthesis service to use, passed to tts . Either "amazon" or "google".
subtitles	Should a .srt file be created with subtitles? The default value is FALSE. If TRUE then a file with the same name as the output argument will be created, but with the file extension .srt.
...	additional arguments to ari_stitch

Details

This function needs to connect to [Amazon Web Services](#) in order to create the narration. You can find a guide for accessing AWS from R [here](#). For more information about how R connects to Amazon Polly see the `aws.polly` documentation [here](#).

Value

The output from [ari_stitch](#)

Examples

```
## Not run:

slides <- system.file("test", c("mab2.png", "mab1.png"),
  package = "ari")
sentences <- c("Welome to my very interesting lecture.",
  "Here are some fantastic equations I came up with.")
ari_spin(slides, sentences, voice = "Joey")

## End(Not run)
```

ari_stitch

Create a video from images and audio

Description

Given a vector of paths to images (preferably .jpgs or .pngs) and a flat list of [Waves](#) of equal length this function will create an .mp4 video file where each image is shown with its corresponding audio. Take a look at the [readWave](#) function if you want to import your audio files into R. Please be sure that all images have the same dimensions.

Usage

```
ari_stitch(
  images,
  audio,
  output = tempfile(fileext = ".mp4"),
  verbose = FALSE,
  cleanup = TRUE,
  ffmpeg_opts = "",
  divisible_height = TRUE,
  audio_codec = get_audio_codec(),
  video_codec = get_video_codec(),
  video_sync_method = "2",
  audio_bitrate = NULL,
  video_bitrate = NULL,
  pixel_format = "yuv420p",
  fast_start = TRUE,
  deinterlace = TRUE,
  stereo_audio = TRUE
)
```

Arguments

images	A vector of paths to images.
audio	A list of Waves from tuneR.
output	A path to the video file which will be created.
verbose	print diagnostic messages. If > 1, then more are printed
cleanup	If TRUE, interim files are deleted
ffmpeg_opts	additional options to send to ffmpeg. This is an advanced option, use at your own risk
divisible_height	Make height divisible by 2, which may be required if getting "height not divisible by 2" error.
audio_codec	The audio encoder for the splicing. If this fails, try copy.
video_codec	The video encoder for the splicing. If this fails, see ffmpeg -codecs

video_sync_method	Video sync method. Should be "auto" or "vfr" or a numeric. See https://ffmpeg.org/ffmpeg.html .
audio_bitrate	Bit rate for audio. Passed to -b:a.
video_bitrate	Bit rate for video. Passed to -b:v.
pixel_format	pixel format to encode for 'ffmpeg'.
fast_start	Adding 'faststart' flags for YouTube and other sites, see https://trac.ffmpeg.org/wiki/Encode/YouTube
deinterlace	should the video be de-interlaced, see https://ffmpeg.org/ffmpeg-filters.html , generally for YouTube
stereo_audio	should the audio be forced to stereo, corresponds to '-ac 2'

Details

This function uses **FFmpeg** which you should be sure is installed before using this function. If running `Sys.which("ffmpeg")` in your R console returns an empty string after installing FFmpeg then you should set the path to FFmpeg on your computer to an environmental variable using `Sys.setenv(ffmpeg = "path/to/ffmpeg")`. The environmental variable will always override the result of `Sys.which("ffmpeg")`.

Value

A logical value, with the attribute `outfile` for the output file.

Examples

```
## Not run:
if (ffmpeg_version_sufficient()) {
  result = ari_stitch(
    ari_example(c("mab1.png", "mab2.png")),
    list(tuneR::noise(), tuneR::noise()))
}

## End(Not run)
```

ari_talk

Create spoken audio files

Description

A simple function for demoing how spoken text will sound.

Usage

```
ari_talk(  
  paragraphs,  
  output = tempfile(fileext = ".wav"),  
  voice = text2speech::tts_default_voice(service = service),  
  service = "amazon"  
)
```

Arguments

- paragraphs A vector strings that will be spoken by Amazon Polly.
- output A path to the audio file which will be created.
- voice The voice you want to use. See [tts_voices](#) for more information about what voices are available.
- service speech synthesis service to use, passed to [tts](#) Either "amazon" or "google".

Value

A Wave output object, with the attribute out file of the output file name.

ffmpeg_codecs	<i>Get Codecs for ffmpeg</i>
---------------	------------------------------

Description

Get Codecs for ffmpeg

Usage

```
ffmpeg_codecs()  
  
ffmpeg_video_codecs()  
  
ffmpeg_audio_codecs()  
  
ffmpeg_muxers()  
  
ffmpeg_version()  
  
ffmpeg_version_sufficient()  
  
check_ffmpeg_version()
```

Value

A ‘data.frame’ of codec names and capabilities

Examples

```
## Not run:
if (ffmpeg_version_sufficient()) {
  ffmpeg_codecs()
  ffmpeg_video_codecs()
  ffmpeg_audio_codecs()
}

## End(Not run)
```

ffmpeg_exec

Get Path to ffmpeg Executable

Description

Get Path to ffmpeg Executable

Usage

```
ffmpeg_exec(quote = FALSE)

have_ffmpeg_exec()
```

Arguments

quote should [shQuote](#) be run before returning?

Value

The path to the ffmpeg executable, or an error.

Note

This looks using ‘Sys.getenv("ffmpeg")’ and ‘Sys.which("ffmpeg")’ to find ‘ffmpeg’. If ‘ffmpeg’ is not in your PATH, then please set the path to ‘ffmpeg’ using ‘Sys.setenv(ffmpeg = "/path/to/ffmpeg")’

Examples

```
## Not run:
if (have_ffmpeg_exec()) {
  ffmpeg_exec()
}

## End(Not run)
```

set_audio_codec	<i>Set Default Audio and Video Codecs</i>
-----------------	---

Description

Set Default Audio and Video Codecs

Usage

```
set_audio_codec(codec)

set_video_codec(codec = "libx264")

get_audio_codec()

get_video_codec()

audio_codec_encode(codec)

video_codec_encode(codec)
```

Arguments

codec	The codec to use or get for audio/video. Uses the 'ffmpeg_audio_codec' and 'ffmpeg_video_codec' options to store this information.
-------	--

Value

A 'NULL' output

See Also

[ffmpeg_codecs()] for options

Examples

```
## Not run:
if (have_ffmpeg_exec()) {
  print(ffmpeg_version())
  get_audio_codec()
  set_audio_codec(codec = "libfdk_aac")
  get_audio_codec()
  set_audio_codec(codec = "aac")
  get_audio_codec()
}
if (have_ffmpeg_exec()) {
  get_video_codec()
  set_video_codec(codec = "libx265")
  get_video_codec()
}
```

```
set_video_codec(codec = "libx264")
get_video_codec()
}
## empty thing
if (have_ffmpeg_exec()) {
  video_codec_encode("libx264")

  audio_codec_encode("aac")
}

## End(Not run)
```

Index

ari_burn_subtitles, [2](#)
ari_example, [3](#)
ari_narrate, [3](#)
ari_spin, [3](#), [4](#), [4](#)
ari_stitch, [4](#), [5](#), [6](#)
ari_talk, [7](#)
audio_codec_encode (set_audio_codec), [10](#)

check_ffmpeg_version (ffmpeg_codecs), [8](#)

ffmpeg_audio_codecs (ffmpeg_codecs), [8](#)
ffmpeg_codecs, [8](#)
ffmpeg_exec, [9](#)
ffmpeg_muxers (ffmpeg_codecs), [8](#)
ffmpeg_version (ffmpeg_codecs), [8](#)
ffmpeg_version_sufficient
 (ffmpeg_codecs), [8](#)
ffmpeg_video_codecs (ffmpeg_codecs), [8](#)

get_audio_codec (set_audio_codec), [10](#)
get_video_codec (set_audio_codec), [10](#)

have_ffmpeg_exec (ffmpeg_exec), [9](#)

ioslides_presentation, [4](#)

readWave, [6](#)
rmarkdown, [3](#), [4](#)

set_audio_codec, [10](#)
set_video_codec (set_audio_codec), [10](#)
shQuote, [9](#)

tts, [4](#), [5](#), [8](#)
tts_voices, [4](#), [5](#), [8](#)

video_codec_encode (set_audio_codec), [10](#)

Wave, [6](#)
webshot, [4](#)