

Package ‘blsR’

July 22, 2025

Title Make Requests from the Bureau of Labor Statistics API

Version 0.5.0

Description Implements v2 of the B.L.S. API for requests of survey information and time series data through 3-tiered API that allows users to interact with the raw API directly, create queries through a functional interface, and re-shape the data structures returned to fit common uses. The API definition is located at: <https://www.bls.gov/developers/api_signature_v2.htm>.

License MIT + file LICENSE

URL <https://github.com/groditi/blsR>

BugReports <https://github.com/groditi/blsR/issues>

Encoding UTF-8

RoxygenNote 7.2.3

Imports dplyr, httr, purrr, rlang, readr, stringr

Suggests testthat (>= 3.0.0), stringi, zoo, jsonlite

Config/testthat/edition 3

Depends R (>= 3.4)

NeedsCompilation no

Author Guillermo Roditi Dominguez [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-7127-8742>>)

Maintainer Guillermo Roditi Dominguez <guillermo@newriverinvestments.com>

Repository CRAN

Date/Publication 2023-07-05 04:33:14 UTC

Contents

bls-api-key	2
blsR	4
bls_request	6
data_as_table	7
data_as_tidy_table	8

get_all_surveys	9
get_latest_observation	10
get_n_series	10
get_n_series_table	12
get_popular_series	14
get_series	14
get_series_table	16
get_series_tables	17
get_survey_info	18
merge_tables	19
merge_tidy_tables	20
query_all_surveys	20
query_latest_observation	21
query_n_series	21
query_popular_series	22
query_series	23
query_survey_info	24
reduce_spanned_responses	24
span_request_queries	25
span_series_request	26
tidy_periods	26
tidy_table_as_zoo	27

Index 29

bls-api-key	<i>Managing API keys</i>
-------------	--------------------------

Description

It is strongly recommended users of the BLS API use an API key. This key can be stored as environment variable, BLS_API_KEY.

- `bls_get_key()` will retrieve the key, if set, or it will return NULL if the key has not been set or has been unset.
- `bls_set_key()` will set the key *for the current R session*. For persistence across sessions, set the environment variable. See the Persistence section for more information.
- `bls_unset_key()` will unset the key *for the current R session*.
- `bls_has_key()` returns TRUE if a key can be found. Otherwise it returns FALSE.

Usage

```
bls_set_key(key)
```

```
bls_unset_key()
```

```
bls_get_key()
```

```
bls_has_key()
```

Arguments

key	A valid BLS API key as a string. keys are typically 32 characters in length and a key with a different length will trigger a warning.
-----	---

Registering for and using an API key

Registering for an API key is not required to use the BLS API, but it is recommended you register for an API key and use it. Requests without a key are limited to 10 years of data per request, 25 series per query, and 25 queries per day. You can register for an API key at: <https://data.bls.gov/registrationEngine/>

Persistence

The preferred method to set the key is to set the BLS_API_KEY environment variable in an .Renviro file. The easiest way to do this is by calling `usethis::edit_r_enviro()`. Don't forget to restart R after setting the key.

See Also

Other blsR-utils: [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Other blsR-utils: [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Other blsR-utils: [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Other blsR-utils: [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Examples

```
has_key <- bls_has_key()

if(has_key){
  original_key <- bls_get_key()
  bls_unset_key()
}

#no initial key
bls_has_key()

# Set a session key
bls_set_key("XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX")

bls_has_key()
```

```
# Get session key
bls_get_key()

# Reset to original key
if(has_key) bls_set_key(original_key)
```

blsR

blsR: Retrieve Data From the U.S. Bureau Of Labor Statistics API

Description

blsR provides functions for retrieving and processing data from the BLS API. The functions are divided into 5 categories: query generators, query requests, the spanning functions, result processors, and the user-friendly simplified interface.

API Key and Definition

The API key is an optional argument, but it is recommended you register for an API key and use it. Requests without a key are limited to 10 years of data per request, 25 series per query, and 25 queries per day. You can register at: <https://data.bls.gov/registrationEngine/>

This implementation was based on the signatures available at: https://www.bls.gov/developers/api_signature_v2.htm

The B.L.S. Frequently asked questions is available at: https://www.bls.gov/developers/api_faqs.htm

General Workflow

This package was designed with a three-step workflow in mind:

- Identify which data you would like to retrieve and create a query.
- Make an http request to execute a query ([bls_request\(\)](#))
- Modify the response data to fit the user workflow

You can customize this workflow by creating your own query objects which consist of a target URL and an optional payload as documented in the API Spec. You may also want to create a custom results processor to shape the data to suit individual needs and wrap those into a single call like [get_series_table\(\)](#) does.

API Key Management

The preferred method to set the key is to set the BLS_API_KEY environment variable in an .Renviron file. To learn more, see [bls-api-key](#).

- [bls_has_key\(\)](#) - Check if an API key is set
- [bls_get_key\(\)](#) - Get an API key, if set
- [bls_set_key\(\)](#) - Set an API key for the *current session*
- [bls_unset_key\(\)](#) - Unset an API key for the *current session*

Query Generators

The query generators return a list suitable for passing to `bls_request()`. Most users should never need to access these functions directly but they are made available for advanced users and user-extensions.

- `query_series()` - Create a query for a single time series
- `query_n_series()` - Create a query to retrieve one or more time series and their catalog data
- `query_popular_series()` - Create a query to retrieve popular series
- `query_all_surveys()` - Create a query to retrieve all surveys
- `query_survey_info()` - Create a query to retrieve information about a survey
- `query_latest_observation()` - Create a Query to retrieve the latest observation for a time series

Query Requests

The query-requester functions will execute the query by making the API request and returning a minimally-processed response. These are likely to be the most suitable functions to use for users who want to access the raw results.

- `bls_request()` - Execute a query and return the unprocessed results
- `get_series()` - Create and execute query for a single time series
- `get_n_series()` - Create and execute a query to retrieve one or more time series and their catalog data
- `get_popular_series()` - Create and execute a query to retrieve popular series
- `get_all_surveys()` - Create and execute a query to retrieve all surveys
- `get_survey_info()` - Create and execute a query to retrieve information about a survey
- `get_latest_observation()` - Create and execute a query to retrieve the latest observation for a time series

Spanning functions

The spanning functions implement the behavior around breaking up a request that exceeds the API limits into multiple requests within the API limits and then reducing the results. Currently, spanning is only supported across time but there is plans to also support spanning across the number of series requested. These functions are low-level internal implementations and most users should never need to interact with them directly.

- `span_series_request()` - Breaks up a request into multiple queries, executes the queries, and returns the reduced results
- `span_request_queries()` - Breaks up a request into a list of queries
- `reduce_spanned_responses()` - Reduces a list of responses into one series list

Result Processors

The result-processor functions will transform the raw API response data structures into data structures more likely to be suitable for modern user workflows. The functions generally take as input the values returned by the query-requester functions and make transform the data to different formats or modify the output of another result-processor function.

- `data_as_table()` - Flatten the data list into a table
- `merge_tables()` - Merge multiple tables by period
- `tidy_periods()` - Transform periods to a more useful format
- `data_as_tidy_table()` - Flatten the data list and transform period data
- `merge_tidy_tables()` - Merge multiple tables with tidy period data
- `tidy_table_as_zoo()` - Turn a table produced by `data_as_tidy_table`, `merge_tidy_tables`, or `tidy_periods` as a zoo object, which can be further turned into an xts object

Simplified Interface

These functions simplify the query generation, execution, and response processing into a single function call, including extended request periods that have to be broken down into multiple API requests. For most common use cases these are likely to be the only functions needed.

- `get_series_table()` - Request one series and return a data table
- `get_series_tables()` - Request series and return list of data tables
- `get_n_series_table()` - Request series and return one table of values

bls_request

Retrieve Data From the U.S. Bureau Of Labor Statistics API v2

Description

`bls_request()` will execute queries against the BLS API. Queries are generated using one of the following query-generating functions: `query_series()`, `query_n_series()`, `query_popular_series()`, `query_all_surveys()`, `query_survey_info()`, `query_latest_observation()`. The result is the "Results" block as defined in the API v2 signatures at https://www.bls.gov/developers/api_signature_v2.htm

Usage

```
bls_request(
  query,
  api_key = bls_get_key(),
  user_agent = "http://github.com/groditi/blsR",
  process_response = .process_response,
  ...
)
```

Arguments

query	list generated by one of the query generating functions
api_key	Optional. An API key string. Defaults to the value returned by <code>bls_get_key()</code> . The preferred way to provide an API key is to use <code>bls_set_key()</code> or the BLS_API_KEY environment variable. Manually passing the key will be deprecated in future releases.
user_agent	string, optional
process_response	function, optional. processes the http response object. The default function will return the JSON payload parsed into a list
...	further arguments will be passed to process_response when called

Value

a list of information returned by the API request

See Also

Other blsR-requests: `get_all_surveys()`, `get_latest_observation()`, `get_n_series_table()`, `get_n_series()`, `get_popular_series()`, `get_series_tables()`, `get_series_table()`, `get_series()`, `get_survey_info()`, `reduce_spanned_responses()`, `span_series_request()`

Examples

```
## Not run:
library(blsR)
uer_query <- query_series('LNS14000000') #monthly unemployment rate series
uer_results <- bls_request(uer_query) #API response

## End(Not run)
```

data_as_table	<i>Convert a list of data entries as returned by BLS API to a table</i>
---------------	---

Description

Convert a list of data entries as returned by BLS API to a table

Usage

```
data_as_table(data, parse_values = TRUE)
```

Arguments

data	a list of individual datum entries as returned by the API
parse_values	optional boolean. If set to TRUE (default) it will attempt to parse the contents of value and cast numeric strings as numeric values. If set to FALSE it will retain value as a column of strings.

Details

currently data_as_table is very similar to `dplyr::bind_rows()`

Value

tibble flattening data into rows for entries and columns for fields

See Also

Other blsR-utils: `bls-api-key`, `data_as_tidy_table()`, `merge_tables()`, `merge_tidy_tables()`, `reduce_spanned_responses()`, `span_request_queries()`, `span_series_request()`, `tidy_periods()`, `tidy_table_as_zoo()`

Examples

```
## Not run:
series <- get_series('LNS14000001')
table <- data_as_table(series$data)

## End(Not run)
```

data_as_tidy_table	<i>Convert a list of data entries as returned by BLS API to a table</i>
--------------------	---

Description

Convert a list of data entries as returned by BLS API to a table

Usage

```
data_as_tidy_table(data, parse_values = TRUE)
```

Arguments

data	a list of individual datum entries as returned by the API
parse_values	optional boolean. If set to TRUE (default) it will attempt to parse the contents of value and cast numeric strings as numeric values. If set to FALSE it will retain value as a column of strings.

Details

An extension of `data_as_table` that replaces the BLS period format by removing columns period and periodName and adding month or quarter where appropriate.

Value

tibble flattening data into rows for entries and columns for fields

See Also

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Examples

```
## Not run:
series <- get_series('LNS14000001')
table <- data_as_tidy_table(series$data)

## End(Not run)
```

get_all_surveys	Create and execute a query to retrieve all surveys
-----------------	--

Description

Create and execute a query to retrieve all surveys

Usage

```
get_all_surveys(...)
```

Arguments

... additional arguments to pass to [bls_request\(\)](#)

Value

a table with a survey_abbreviation and survey_name columns

See Also

[query_all_surveys](#)

Other blsR-requests: [bls_request\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

```
get_latest_observation
```

Create and execute a query to retrieve the latest observation for a series

Description

Create and execute a query to retrieve the latest observation for a series

Usage

```
get_latest_observation(series_id, ...)
```

Arguments

<code>series_id</code>	BLS series ID
<code>...</code>	additional arguments to pass to bls_request()

Value

a datum in the form of a list

See Also

[query_latest_observation](#)

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

```
get_n_series
```

Create and execute a query to retrieve one or more time series and their catalog data

Description

Create and execute a query to retrieve one or more time series and their catalog data

Usage

```
get_n_series(
  series_ids,
  api_key = bls_get_key(),
  start_year = NULL,
  end_year = NULL,
  year_limit = NULL,
```

```

    span = TRUE,
    catalog = FALSE,
    calculations = FALSE,
    annualaverage = FALSE,
    aspects = FALSE,
    series_limit = NULL,
    ...
)

```

Arguments

<code>series_ids</code>	a list or character vector of BLS time-series IDs. If the items are named then the names will be used in the returned list
<code>api_key</code>	Optional. An API key string. Defaults to the value returned by <code>bls_get_key()</code> . The preferred way to provide an API key is to use <code>bls_set_key()</code> or the <code>BLS_API_KEY</code> environment variable. Manually passing the key will be deprecated in future releases.
<code>start_year, end_year</code>	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. <code>end_year</code> must be greater than <code>start_year</code>
<code>year_limit</code>	optional number of years to paginate request by. If not explicitly set, it will be set to 10 or 20 depending on if an <code>api_key</code> is available
<code>span</code>	when set to <code>TRUE</code> , requests where the number of years between <code>start_year</code> and <code>end_year</code> exceed <code>year_limit</code> will be performed as multiple requests automatically
<code>catalog</code>	boolean. If set to <code>TRUE</code> , element item in the list returned may include a named item <code>catalog</code> , a named list containing descriptive information about the series. Not all series have a catalog entry available.
<code>calculations</code>	boolean. If set to <code>TRUE</code> , each element in the data list for each series returned may include an additional named element <code>calculations</code> , a named list containing two items, <code>net_changes</code> and <code>pct_changes</code> , each of them a named list which may include items 1, 3, 6, 12 which represent 1, 3, 6, and 12 month net changes and percent changes respectively. Not all data series will have enough data points to include these calculations.
<code>annualaverage</code>	boolean. If set to <code>TRUE</code> , each data list may include an additional element for an annual average of the time series, which is usually presented as month 13 in monthly data. Not all data series support this feature.
<code>aspects</code>	boolean. If set to <code>TRUE</code> , each item in the data list for each series returned may include an additional named element <code>aspects</code> , which will be a named list. Not all data series support this feature.
<code>series_limit</code>	Maximum number of series to request in one API call when <code>span</code> is set to <code>TRUE</code> .
<code>...</code>	additional arguments to pass to <code>bls_request()</code>

Value

a list of series results. Each element of the returned list is a named list guaranteed to have two items, `SeriesID` and `data` and optionally `catalog`. The unnamed list `data` will have 0 or more elements,

each one a named list representing an observation in the time series. Each observation is guaranteed to include the elements year, period, periodName, value, and footnotes. Footnotes are a list of named lists. The rest are scalar values. If the the most recent observation is included, that observation will have an element named latest which will contain the text 'true'. If calculations or aspects were requested they will be present as named elements in each observation.

See Also

[query_n_series](#)

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

Examples

```
## Not run:
series_ids <- list(uer.men = 'LNS14000001', uer.women = 'LNS14000002')
uer_series <- get_n_series(series_ids, 'your-api-key-here' )

## End(Not run)
```

get_n_series_table	<i>Retrieve multiple time series in one API request and return a single tibble</i>
--------------------	--

Description

Retrieve multiple time series in one API request and return a single tibble

Usage

```
get_n_series_table(
  series_ids,
  api_key = bls_get_key(),
  start_year = NULL,
  end_year = NULL,
  year_limit = NULL,
  tidy = FALSE,
  parse_values = TRUE,
  ...
)
```

Arguments

series_ids	a list or character vector of BLS time-series IDs. If the items are named then the names will be used in the returned list
------------	--

api_key	Optional. An API key string. Defaults to the value returned by bls_get_key() . The preferred way to provide an API key is to use bls_set_key() or the BLS_API_KEY environment variable. Manually passing the key will be deprecated in future releases.
start_year, end_year	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year
year_limit	optional number of years to paginate request by. If not explicitly set, it will be set to 10 or 20 depending on if an api_key is available
tidy	optional boolean. Return will use tidy_periods() if true
parse_values	optional boolean. If set to TRUE (default) it will attempt to parse the contents of value and cast numeric strings as numeric values. If set to FALSE it will retain value as a column of strings.
...	Arguments passed on to get_n_series
series_limit	Maximum number of series to request in one API call when span is set to TRUE.
span	when set to TRUE, requests where the number of years between start_year and end_year exceed year_limit will be performed as multiple requests automatically

Value

a tibble of multiple merged time series

See Also

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

Examples

```
## Not run:
get_n_series_table(
  list(uer.men = 'LNS14000001', uer.women = 'LNS14000002'),
  start_year = 2005, end_year=2006
)

## End(Not run)
```

get_popular_series	Create and execute a query to retrieve popular series
--------------------	---

Description

Create and execute a query to retrieve popular series

Usage

```
get_popular_series(survey_id = NULL, ...)
```

Arguments

survey_id	BLS survey abbreviation (two letter code)
...	additional arguments to pass to bls_request()

Value

a character vector of series IDs

See Also

[query_popular_series](#)

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

get_series	Create and execute query for a single time series
------------	---

Description

Create and execute query for a single time series

Usage

```
get_series(
  series_id,
  start_year = NULL,
  end_year = NULL,
  year_limit = NULL,
  span = TRUE,
  api_key = bls_get_key(),
  ...
)
```

Arguments

<code>series_id</code>	Character scalar BLS series ID
<code>start_year, end_year</code>	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. <code>end_year</code> must be greater than <code>start_year</code>
<code>year_limit</code>	optional number of years to paginate request by. If not explicitly set, it will be set to 10 or 20 depending on if an <code>api_key</code> is available
<code>span</code>	when set to TRUE, requests where the number of years between <code>start_year</code> and <code>end_year</code> exceed <code>year_limit</code> will be performed as multiple requests automatically
<code>api_key</code>	Optional. An API key string. Defaults to the value returned by <code>bls_get_key()</code> . The preferred way to provide an API key is to use <code>bls_set_key()</code> or the BLS_API_KEY environment variable. Manually passing the key will be deprecated in future releases.
<code>...</code>	additional arguments to pass to <code>bls_request()</code>

Value

a single series result, in list form. The resulting list will have the following items:

- `seriesID`: a character vector of length 1 containing the `series_id`
- `data`: a list of lists containing the payload data. Each item of the list represents an observation. Each observation is a list with the following named items `year`, `period`, `periodName`, `value`, `footnotes`. Footnotes are a list. Additionally, the most recent observation will have an item named `latest` which will be marked as 'true'.

See Also

[query_series](#)

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

Examples

```
## Not run:
series <- get_series('LNS14000001')

## End(Not run)
```

get_series_table	<i>Retrieve a time series from BLS API as a tibble</i>
------------------	--

Description

Retrieve a time series from BLS API as a tibble

Usage

```
get_series_table(
  series_id,
  api_key = bls_get_key(),
  start_year = NULL,
  end_year = NULL,
  year_limit = NULL,
  parse_values = TRUE,
  ...
)
```

Arguments

series_id	Character scalar BLS series ID
api_key	Optional. An API key string. Defaults to the value returned by bls_get_key() . The preferred way to provide an API key is to use bls_set_key() or the BLS_API_KEY environment variable. Manually passing the key will be deprecated in future releases.
start_year, end_year	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year
year_limit	optional number of years to paginate request by. If not explicitly set, it will be set to 10 or 20 depending on if an api_key is available
parse_values	optional boolean. If set to TRUE (default) it will attempt to parse the contents of value and cast numeric strings as numeric values. If set to FALSE it will retain value as a column of strings.
...	additional arguments to pass to get_series

Value

a tibble of observations or NA if the request had zero results.

See Also

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

Examples

```
## Not run:
get_series_table('LNS14000001', 2005, 2006)

## End(Not run)
```

get_series_tables	<i>Retrieve multiple time series as in one API request as tibbles</i>
-------------------	---

Description

Retrieve multiple time series as in one API request as tibbles

Usage

```
get_series_tables(
  series_ids,
  api_key = bls_get_key(),
  start_year = NULL,
  end_year = NULL,
  year_limit = NULL,
  parse_values = TRUE,
  ...
)
```

Arguments

series_ids	a list or character vector of BLS time-series IDs. If the items are named then the names will be used in the returned list
api_key	Optional. An API key string. Defaults to the value returned by bls_get_key() . The preferred way to provide an API key is to use bls_set_key() or the BLS_API_KEY environment variable. Manually passing the key will be deprecated in future releases.
start_year, end_year	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year
year_limit	optional number of years to paginate request by. If not explicitly set, it will be set to 10 or 20 depending on if an api_key is available
parse_values	optional boolean. If set to TRUE (default) it will attempt to parse the contents of value and cast numeric strings as numeric values. If set to FALSE it will retain value as a column of strings.
...	Arguments passed on to get_n_series
series_limit	Maximum number of series to request in one API call when span is set to TRUE.
span	when set to TRUE, requests where the number of years between start_year and end_year exceed year_limit will be performed as multiple requests automatically

Value

a list of tibbles. Series requests which return observations will be a tibble. Series with no observations will be NA

See Also

Other blsR-requests: `bls_request()`, `get_all_surveys()`, `get_latest_observation()`, `get_n_series_table()`, `get_n_series()`, `get_popular_series()`, `get_series_table()`, `get_series()`, `get_survey_info()`, `reduce_spanned_responses()`, `span_series_request()`

Examples

```
## Not run:

blsr_set_key('your-api-key-here-xxxxxxxxxxxxxx')

get_series_tables(
  list(uer.men = 'LNS14000001', uer.women = 'LNS14000002')
)
get_series_tables(
  list(uer.men = 'LNS14000001', uer.women = 'LNS14000002'),
  2005, 2006
)

## End(Not run)
```

get_survey_info

Create and execute a query to retrieve information about a survey

Description

Create and execute a query to retrieve information about a survey

Usage

```
get_survey_info(survey_id, ...)
```

Arguments

survey_id BLS survey abbreviation (two letter code)
 ... additional arguments to pass to `bls_request()`

Value

a list of survey information

See Also

[query_survey_info](#)

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#)

merge_tables	<i>Turn a list of one or more series into a single table of time series data</i>
--------------	--

Description

`merge_tables()` turns a list of series as returned by [data_as_table\(\)](#) into a single tibble

Usage

```
merge_tables(tables, join_by = c("year", "period"))
```

Arguments

tables	a named list of tables with matching periodicity. Mixing data with different (monthly, quarterly, annual) periodicity is unsupported. The list names will be used as column names in the output.
join_by	an optional character vector of columns to use to join tables. The result will be sorted in ascending order using these columns.

Value

tibble

See Also

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

Examples

```
## Not run:
series_ids <- list(uer.men = 'LNS14000001', uer.women = 'LNS14000002')
uer_series <- get_n_series(series_ids, 'your-api-key-here' )
uer_tables <- lapply(uer_series, function(x) data_to_table(x$data))
big_table <- merge_tables(uer_tables)

## End(Not run)
```

merge_tidy_tables	<i>Turn a list of one or more series into a single table of time series data</i>
-------------------	--

Description

merge_tidy_tables() turns a list of series as returned by [data_as_tidy_table\(\)](#) into a single tibble

Usage

```
merge_tidy_tables(tidy_tables)
```

Arguments

tidy_tables a named list of tables with matching periodicity. Mixing data with different (monthly, quarterly, annual) periodicity is unsupported. The list names will be used as column names in the output.

Value

tibble

See Also

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

query_all_surveys	<i>Create a query to retrieve all surveys</i>
-------------------	---

Description

Create a query to retrieve all surveys

Usage

```
query_all_surveys()
```

Value

list of query parameters

See Also

Other blsR-queries: [query_latest_observation\(\)](#), [query_n_series\(\)](#), [query_popular_series\(\)](#), [query_series\(\)](#), [query_survey_info\(\)](#), [span_request_queries\(\)](#)

`query_latest_observation`*Create a Query to retrieve the latest observation for a time series*

Description

Create a Query to retrieve the latest observation for a time series

Usage

```
query_latest_observation(series_id)
```

Arguments

`series_id` BLS series ID

Value

list of query parameters

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_n_series\(\)](#), [query_popular_series\(\)](#), [query_series\(\)](#), [query_survey_info\(\)](#), [span_request_queries\(\)](#)

`query_n_series`*Create a query to retrieve one or more time series and their catalog data*

Description

Create a query to retrieve one or more time series and their catalog data

Usage

```
query_n_series(  
  series_ids,  
  start_year = NULL,  
  end_year = NULL,  
  catalog = FALSE,  
  calculations = FALSE,  
  annualaverage = FALSE,  
  aspects = FALSE  
)
```

Arguments

series_ids	Character vector of BLS series IDs
start_year, end_year	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year
catalog	boolean. If set to TRUE, element item in the list returned may include a named item catalog, a named list containing descriptive information about the series. Not all series have a catalog entry available.
calculations	boolean. If set to TRUE, each element in the data list for each series returned may include an additional named element calculations, a named list containing two items, net_changes and pct_changes, each of them a named list which may include items 1, 3, 6, 12 which represent 1, 3, 6, and 12 month net changes and percent changes respectively. Not all data series will have enough data points to include these calculations.
annualaverage	boolean. If set to TRUE, each data list may include an additional element for a an annual average of the time series, which is usually presented as month 13 in monthly data. Not all data series support this feature.
aspects	boolean. If set to TRUE, each item in the data list for each series returned may include an additional named element aspects, which will be a named list. Not all data series support this feature.

Value

list of query parameters

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_latest_observation\(\)](#), [query_popular_series\(\)](#), [query_series\(\)](#), [query_survey_info\(\)](#), [span_request_queries\(\)](#)

Examples

```
a <- query_n_series(c('LNS14000001', 'LNS14000002'))
b <- query_n_series(c('LNS14000001', 'LNS14000002'), start_year = 2005, end_year=2010)
c <- query_n_series(c('LNS14000001', 'LNS14000002'), 2005, 2010)
d <- query_n_series(c('LNS14000001', 'LNS14000002'), catalog=TRUE)
```

query_popular_series *Create a query to retrieve popular series*

Description

Create a query to retrieve popular series

Usage

```
query_popular_series(survey_id = NULL)
```

Arguments

survey_id BLS survey abbreviation (two letter code)

Value

list of query parameters

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_latest_observation\(\)](#), [query_n_series\(\)](#), [query_series\(\)](#), [query_survey_info\(\)](#), [span_request_queries\(\)](#)

Examples

```
popular_series_query <- query_popular_series()
popular_labor_force_series <- query_popular_series('LN')
```

query_series	<i>Create a query for a single time series</i>
--------------	--

Description

Create a query for a single time series

Usage

```
query_series(series_id, start_year = NULL, end_year = NULL)
```

Arguments

series_id Character scalar BLS series ID
 start_year, end_year numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year

Value

list of query parameters

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_latest_observation\(\)](#), [query_n_series\(\)](#), [query_popular_series\(\)](#), [query_survey_info\(\)](#), [span_request_queries\(\)](#)

Examples

```
unemployment_rate_query <- query_series('LNS14000000')
unemployment_rate_query <- query_series('LNS14000000', 2005, 2010)
```

query_survey_info	<i>Create a query to retrieve information about a survey</i>
-------------------	--

Description

Create a query to retrieve information about a survey

Usage

```
query_survey_info(survey_id)
```

Arguments

survey_id BLS survey abbreviation (two letter code)

Value

list of query parameters

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_latest_observation\(\)](#), [query_n_series\(\)](#), [query_popular_series\(\)](#), [query_series\(\)](#), [span_request_queries\(\)](#)

Examples

```
query_survey_info('LN')
```

reduce_spanned_responses	<i>Reduce the multiple spanned responses into a list of series</i>
--------------------------	--

Description

Reduce the multiple spanned responses into a list of series

Usage

```
reduce_spanned_responses(responses)
```

Arguments

responses a list of API responses as returned by [bls_request\(\)](#)

Value

series list

See Also

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [span_series_request\(\)](#)

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

span_request_queries *Generate multiple queries that don't exceed a year limit*

Description

Generate multiple queries that don't exceed a year limit

Usage

```
span_request_queries(start_year, end_year, year_limit, query_fn)
```

Arguments

start_year, end_year numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year

year_limit positive integer

query_fn a function or closure that takes two arguments, start_year and end_year, and returns a query (see [purrr::partial\(\)](#))

Value

a list of query objects in reverse chronological order

See Also

Other blsR-queries: [query_all_surveys\(\)](#), [query_latest_observation\(\)](#), [query_n_series\(\)](#), [query_popular_series\(\)](#), [query_series\(\)](#), [query_survey_info\(\)](#)

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

span_series_request	<i>Break up a long request into multiple API calls</i>
---------------------	--

Description

Break up a long request into multiple API calls

Usage

```
span_series_request(start_year, end_year, year_limit, query_fn, ...)
```

Arguments

start_year, end_year	numeric 4-digit years. While optional, they are strongly recommended. If one is provided, the other is mandatory. end_year must be greater than start_year
year_limit	positive integer
query_fn	a function or closure that takes two arguments, start_year and end_year, and returns a query (see purrr::partial())
...	additional arguments to pass to bls_request()

Value

a list of API responses (what comes back from bls_re)

See Also

Other blsR-requests: [bls_request\(\)](#), [get_all_surveys\(\)](#), [get_latest_observation\(\)](#), [get_n_series_table\(\)](#), [get_n_series\(\)](#), [get_popular_series\(\)](#), [get_series_tables\(\)](#), [get_series_table\(\)](#), [get_series\(\)](#), [get_survey_info\(\)](#), [reduce_spanned_responses\(\)](#)

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [tidy_periods\(\)](#), [tidy_table_as_zoo\(\)](#)

tidy_periods	<i>Clean the period information returned by BLS</i>
--------------	---

Description

Clean the period information returned by BLS

Usage

```
tidy_periods(table)
```

Arguments

table a tibble of the data slot in a series

Details

tidy_periods will return a tibble where the period and periodName columns have been deleted and replaced. Monthly periodicity data will have a new column month and quarterly data will have a new column quarter. Rows will be sorted from oldest to newest.

Value

a sorted tibble containing the period and the value

See Also

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_table_as_zoo\(\)](#)

Examples

```
## Not run:
series <- get_series('LNS14000001')
table <- data_as_table(series$data)
tidy_table <- tidy_periods(table)

## End(Not run)
```

tidy_table_as_zoo	<i>Convert a single series or n series tables into a zoo object</i>
-------------------	---

Description

Convert a single series or n series tables into a zoo object

Usage

```
tidy_table_as_zoo(table, index_function = .zoo_index_function)
```

Arguments

table a table of results

index_function optional closure. The closure argument is the table and it should return a vector of values compatible with a zoo index. The default function will return a vector of [zoo::yearmon\(\)](#) for monthly series and [zoo::yearqtr\(\)](#) for quarterly or annual series.

Details

A utility function to easily convert retrieved BLS series into zoo or xts objects.

Value

a zooobject

See Also

Other blsR-utils: [bls-api-key](#), [data_as_table\(\)](#), [data_as_tidy_table\(\)](#), [merge_tables\(\)](#), [merge_tidy_tables\(\)](#), [reduce_spanned_responses\(\)](#), [span_request_queries\(\)](#), [span_series_request\(\)](#), [tidy_periods\(\)](#)

Examples

```
## Not run:
series <- get_series('LNS14000001')
table <- data_as_tidy_table(series$data)
zoo_obj <- tidy_table_as_zoo(table)

## End(Not run)
```

Index

- * **blsR-queries**
 - query_all_surveys, 20
 - query_latest_observation, 21
 - query_n_series, 21
 - query_popular_series, 22
 - query_series, 23
 - query_survey_info, 24
 - span_request_queries, 25
- * **blsR-requests**
 - bls_request, 6
 - get_all_surveys, 9
 - get_latest_observation, 10
 - get_n_series, 10
 - get_n_series_table, 12
 - get_popular_series, 14
 - get_series, 14
 - get_series_table, 16
 - get_series_tables, 17
 - get_survey_info, 18
 - reduce_spanned_responses, 24
 - span_series_request, 26
- * **blsR-utils**
 - bls-api-key, 2
 - data_as_table, 7
 - data_as_tidy_table, 8
 - merge_tables, 19
 - merge_tidy_tables, 20
 - reduce_spanned_responses, 24
 - span_request_queries, 25
 - span_series_request, 26
 - tidy_periods, 26
 - tidy_table_as_zoo, 27
- bls-api-key, 2
- bls_get_key (bls-api-key), 2
- bls_get_key(), 4, 7, 11, 13, 15–17
- bls_has_key (bls-api-key), 2
- bls_has_key(), 4
- bls_request, 6, 9, 10, 12–16, 18, 19, 25, 26
- bls_request(), 4, 5, 9–11, 14, 15, 18, 25, 26
- bls_set_key (bls-api-key), 2
- bls_set_key(), 4, 7, 11, 13, 15–17
- bls_unset_key (bls-api-key), 2
- bls_unset_key(), 4
- blsR, 4
- data_as_table, 3, 7, 8, 9, 19, 20, 25–28
- data_as_table(), 6, 19
- data_as_tidy_table, 3, 8, 8, 19, 20, 25–28
- data_as_tidy_table(), 6, 20
- dplyr::bind_rows(), 8
- get_all_surveys, 7, 9, 10, 12–16, 18, 19, 25, 26
- get_all_surveys(), 5
- get_latest_observation, 7, 9, 10, 12–16, 18, 19, 25, 26
- get_latest_observation(), 5
- get_n_series, 7, 9, 10, 10, 13–19, 25, 26
- get_n_series(), 5
- get_n_series_table, 7, 9, 10, 12, 12, 14–16, 18, 19, 25, 26
- get_n_series_table(), 6
- get_popular_series, 7, 9, 10, 12, 13, 14, 15, 16, 18, 19, 25, 26
- get_popular_series(), 5
- get_series, 7, 9, 10, 12–14, 14, 16, 18, 19, 25, 26
- get_series(), 5
- get_series_table, 7, 9, 10, 12–15, 16, 18, 19, 25, 26
- get_series_table(), 4, 6
- get_series_tables, 7, 9, 10, 12–16, 17, 19, 25, 26
- get_series_tables(), 6
- get_survey_info, 7, 9, 10, 12–16, 18, 18, 25, 26
- get_survey_info(), 5
- merge_tables, 3, 8, 9, 19, 20, 25–28

`merge_tables()`, 6
`merge_tidy_tables`, 3, 8, 9, 19, 20, 25–28
`merge_tidy_tables()`, 6

`purrr::partial()`, 25, 26

`query_all_surveys`, 9, 20, 21–25
`query_all_surveys()`, 5, 6
`query_latest_observation`, 10, 20, 21, 22–25
`query_latest_observation()`, 5, 6
`query_n_series`, 12, 20, 21, 21, 23–25
`query_n_series()`, 5, 6
`query_popular_series`, 14, 20–22, 22, 23–25
`query_popular_series()`, 5, 6
`query_series`, 15, 20–23, 23, 24, 25
`query_series()`, 5, 6
`query_survey_info`, 19–23, 24, 25
`query_survey_info()`, 5, 6

`reduce_spanned_responses`, 3, 7–10, 12–16, 18–20, 24, 25–28
`reduce_spanned_responses()`, 5

`span_request_queries`, 3, 8, 9, 19–25, 25, 26–28
`span_request_queries()`, 5
`span_series_request`, 3, 7–10, 12–16, 18–20, 25, 26, 27, 28
`span_series_request()`, 5

`tidy_periods`, 3, 8, 9, 19, 20, 25, 26, 26, 28
`tidy_periods()`, 6, 13
`tidy_table_as_zoo`, 3, 8, 9, 19, 20, 25–27, 27
`tidy_table_as_zoo()`, 6

`zoo::yearmon()`, 27
`zoo::yearqtr()`, 27