

Package ‘bsTools’

July 22, 2025

Type Package

Title Create HTML Content with Bootstrap 5 Classes and Layouts

Version 1.0.5

Author Timothy Conwell

Maintainer Timothy Conwell <timconwell@gmail.com>

Description Functions are pre-configured to utilize Bootstrap 5 classes and HTML structures to create Bootstrap-styled HTML quickly and easily. Includes functions for creating common Bootstrap elements such as containers, rows, cols, navbars, etc. Intended to be used with the html5 package. Learn more at <<https://getbootstrap.com/>>.

License GPL (>= 2)

Encoding UTF-8

Depends R (>= 3.5.0), html5 (>= 1.0.0)

Imports toolbox

RoxygenNote 7.2.0

NeedsCompilation no

Repository CRAN

Date/Publication 2022-08-29 19:40:02 UTC

Contents

bs_accordion	3
bs_alert	4
bs_badge	5
bs_black	5
bs_blue	6
bs_breadcrumb	6
bs_card	7
bs_carousel	9
bs_clearfix	10
bs_col	11

bs_collapse	11
bs_col_break	12
bs_container	13
bs_cyan	13
bs_danger	14
bs_dark	14
bs_doc	14
bs_dropdown	15
bs_figure	17
bs_flexbox	18
bs_green	18
bs_img	19
bs_indigo	19
bs_info	20
bs_input	20
bs_light	21
bs_modal	22
bs_nav	23
bs_navbar	24
bs_offcanvas	26
bs_orange	27
bs_pagination	28
bs_pink	29
bs_primary	29
bs_purple	29
bs_red	30
bs_row	30
bs_secondary	31
bs_select	31
bs_spinner	32
bs_success	33
bs_table	33
bs_teal	34
bs_textarea	35
bs_toast	36
bs_toast_container	37
bs_toast_js	38
bs_warning	38
bs_white	39
bs_yellow	39
css_href_var	39
css_integrity_var	40
js_integrity_var	40
js_src_var	40

bs_accordion

*Create a Bootstrap accordion***Description**

Learn more at <https://getbootstrap.com/docs/5.1/components/accordion/>.

Usage

```
bs_accordion(
  id,
  items = list(),
  expand = c(),
  button_background_color = NULL,
  button_text_color = NULL,
  accordion_attr = list(class = "accordion"),
  item_attr = list(class = "accordion-item"),
  item_header_attr = list(class = "accordion-header"),
  button_attr = list(class = "accordion-button collapsed"),
  div_attr = list(class = "accordion-collapse collapse"),
  body_attr = list(class = "accordion-body")
)
```

Arguments

id	A string, the id to use for the accordion, must be unique within a page (if you have multiple accordions on a page).
items	A named list, names become the label for each panel, values should be the HTML content to display when the panel is toggled.
expand	A vector, the names or positions of panels that should be expanded by default.
button_background_color	A string vector, the color to apply to the background of the accordion toggle button. Recycles for each panel.
button_text_color	A string vector, the color to apply to the text of the accordion toggle button. Recycles for each panel.
accordion_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the accordion content.
item_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the accordion items.
item_header_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the accordion panel headers.
button_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the accordion panel header button items.

div_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the accordion panel content.
body_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the accordion panel content body.

Value

A string of HTML.

Examples

```
bs_accordion(
  id = "acc1",
  items = list(
    "One" = p("Check it out."),
    "Two" = p("Does it work?"),
    "Three" = p("I hope so.")
  )
)
```

bs_alert

Create a Bootstrap alert

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/alerts/>.

Usage

```
bs_alert(x, div_attr = c(class = "alert alert-primary"))
```

Arguments

x	A string, the HTML or text to display in the alert.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div containing the alert.

Value

A string of HTML.

Examples

```
bs_alert(
  "Hello"
)
```

`bs_badge`*Create a Bootstrap badge*

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/badge/>.

Usage

```
bs_badge(x, span_attr = c(class = "badge bg-secondary"))
```

Arguments

<code>x</code>	A string, the text to display in the badge (uses the <code></code> tag).
<code>span_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the span containing the badge text.

Value

A string of HTML.

Examples

```
bs_badge(  
  "Hello"  
)
```

`bs_black`*Hex code for bootstrap black color*

Description

"#000"

Usage

```
bs_black
```

Format

A string

bs_blue	Hex code for bootstrap blue color
---------	-----------------------------------

Description

"#0d6efd"

Usage

bs_blue

Format

A string

bs_breadcrumb	Create a Bootstrap breadcrumb
---------------	-------------------------------

Description

Create a Bootstrap breadcrumb

Usage

```
bs_breadcrumb(  
  items = list(),  
  active = NULL,  
  nav_attr = c(`aria-label` = "breadcrumb"),  
  ul_attr = c(class = "breadcrumb"),  
  li_attr = c(class = "breadcrumb-item"),  
  a_attr = NULL  
)
```

Arguments

- | | |
|--------|--|
| items | A list, creates nav elements. If a list item is named, names should be links and values should be text to display in the nav for that link. Names will be passed to the href attribute and values to the main content of the html5::a function which will be wrapped by the html5::li function, each of which have Bootstrap classes added by default. If an item in the list is not named, the item must be valid HTML with appropriate Bootstrap classes added manually. For example, to add a drop-down, add an unnamed item to the list with HTML defining the drop-down as the value of the item. |
| active | A integer, the position in items to make active. |

nav_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::nav</code> .
ul_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::ul</code> .
li_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::li</code> .
a_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::a</code> .

Value

A string of HTML.

Examples

```
bs_breadcrumb(
  items = list(
    "#" = "Option 1",
    "#" = "Option 2",
    "#" = "Option 3"
  ),
  active = 2
)
```

bs_card	<i>Create a Bootstrap card</i>
---------	--------------------------------

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/card/>.

Usage

```
bs_card(
  header = NULL,
  title = NULL,
  text = NULL,
  body,
  footer = NULL,
  img_src = NULL,
  img_alt = NULL,
  div_attr = c(class = "card"),
  header_attr = c(class = "card-header"),
  title_attr = c(class = "card-title"),
  text_attr = c(class = "card-text"),
  body_attr = c(class = "card-body"),
  footer_attr = c(class = "card-footer"),
```

```

img_attr = c(class = "card-img-top"),
header_func = h5,
title_func = h5,
text_func = h5,
img_left = FALSE,
img_right = FALSE,
img_col_attr = c(class = "col-md-6"),
body_col_attr = c(class = "col-md-6"),
img_horizontal_attr = c(class = "img-fluid")
)

```

Arguments

header	A string, the HTML to display in the header of the card.
title	A string, the HTML to display in the title of the card.
text	A string, the HTML to display in the text of the card.
body	A string, the HTML to display in the body of the card.
footer	A string, the HTML to display in the footer of the card.
img_src	A string, the path of an image to display with the card. Passed to "src" attribute of the tag.
img_alt	A string, the alt attribute of an image to display with the card. Passed to "alt" attribute of the tag.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the card content.
header_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the card header.
title_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the card title.
text_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the card text.
body_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the card body.
footer_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the card footer.
img_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the img tag if an image is to be displayed.
header_func	A html5 function to use for the header input.
title_func	A html5 function to use for the title input.
text_func	A html5 function to use for the text input.
img_left	TRUE/FALSE, if TRUE, places the image on the left of the card
img_right	TRUE/FALSE, if TRUE, places the image on the right of the card
img_col_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the column containing the img tag if an image is to be displayed horizontally.

- `body_col_attr` A named list or named vector, names are attribute names and values are attribute values. Added to the column containing the body if an image is to be displayed horizontally.
- `img_horizontal_attr` A named list or named vector, names are attribute names and values are attribute values. Added to the img tag if an image is to be displayed horizontally.

Value

A string of HTML.

Examples

```
bs_card(
  body = "This is a card"
)
```

bs_carousel	<i>Create a Bootstrap carousel</i>
-------------	------------------------------------

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/carousel/>.

Usage

```
bs_carousel(
  id,
  items = list(),
  carousel_attr = c(class = "carousel slide"),
  inner_attr = c(class = "carousel-inner"),
  item_attr = c(class = "carousel-item"),
  controls = TRUE
)
```

Arguments

- `id` A string, the id to use for the carousel div.
- `items` A list, entries should be HTML to display in the carousel.
- `carousel_attr` A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the carousel content.
- `inner_attr` A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the carousel items.
- `item_attr` A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping each carousel item.
- `controls` TRUE/FALSE, if TRUE, adds code to display arrows to click through the carousel.

Value

A string of HTML.

Examples

```
bs_carousel(  
  id = "c1",  
  items = list(  
    h1("First slide"),  
    h1("Second slide"),  
    h1("Third Slide")  
  )  
)
```

bs_clearfix

Create a div with class "clearfix"

Description

Learn more at <https://getbootstrap.com/docs/5.1/layout/columns/>.

Usage

```
bs_clearfix(..., clearfix_attr = c(class = "clearfix"))
```

Arguments

...	Valid string(s) of HTML.
clearfix_attr	A named list or named vector, names are attribute names and values are attribute values.

Value

A string of HTML.

Examples

```
bs_clearfix(  
  p("Test")  
)
```

`bs_col`*Create a Bootstrap col div*

Description

Learn more at <https://getbootstrap.com/docs/5.1/layout/columns/>.

Usage

```
bs_col(..., col_attr = c(class = "col"))
```

Arguments

<code>...</code>	A string or strings of HTML content to include in the col div.
<code>col_attr</code>	A named list or named vector, names are attribute names and values are attribute values.

Value

A string of HTML.

Examples

```
bs_col(p("Col 1"))
```

`bs_collapse`*Create a Bootstrap collapse*

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/collapse/>.

Usage

```
bs_collapse(  
  id,  
  button_label,  
  content,  
  button_attr = c(class = "btn btn-primary"),  
  content_attr = c(class = "collapse")  
)
```

Arguments

id	A string, the id to use for the collapse div.
button_label	A string, the text to display in the button controlling the collapsible content.
content	A string, the HTML to display or collapse.
button_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the button controlling the collapse.
content_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the collapsible content.

Value

A string of HTML.

Examples

```
bs_collapse(
  id = "collapse1",
  button_label = "Click to Expand",
  content = p("Hello")
)
```

bs_col_break

Create a div with class "w-100" to force columns onto a new line

Description

Learn more at <https://getbootstrap.com/docs/5.1/layout/columns/>.

Usage

```
bs_col_break(col_break_attr = c(class = "w-100"))
```

Arguments

col_break_attr	A named list or named vector, names are attribute names and values are attribute values.
----------------	--

Value

A string of HTML.

Examples

```
bs_col_break()
```

bs_container	Create a Bootstrap container div
--------------	----------------------------------

Description

Create a Bootstrap container div.

Usage

```
bs_container(..., container_attr = c(class = "container"))
```

Arguments

... A string or strings of HTML content to include in the container div.
container_attr A named list or named vector, names are attribute names and values are attribute values.

Details

Learn more at <https://getbootstrap.com/docs/5.1/layout/containers/>.

Value

A string of HTML.

Examples

```
bs_container(  
  div()  
)
```

bs_cyan	Hex code for bootstrap cyan color
---------	-----------------------------------

Description

"#0dcaf0"

Usage

```
bs_cyan
```

Format

A string

bs_danger	<i>Hex code for bootstrap danger color</i>
-----------	--

Description

"#dc3545"

Usage

bs_danger

Format

A string

bs_dark	<i>Hex code for bootstrap dark color</i>
---------	--

Description

"#212529"

Usage

bs_dark

Format

A string

bs_doc	<i>Create a HTML document preconfigured to load Bootstrap5 from the CDN</i>
--------	---

Description

Learn more at <https://getbootstrap.com/docs/5.1/getting-started/introduction/>.

Usage

```
bs_doc(
  head = NULL,
  body,
  body_attr = NULL,
  css_href = css_href_var,
  css_integrity = css_integrity_var,
  js_src = js_src_var,
  js_integrity = js_integrity_var
)
```

Arguments

head	A string of HTML that will be passed to the ... param of the <code>html5::head()</code> function.
body	A string of HTML that will be passed to the ... param of the <code>html5::body()</code> function.
body_attr	A named list or named vector, passed to the <code>attr</code> param of the <code>html5::body()</code> function.
css_href	The url of jsDelivr for the version of bootstrap css to include.
css_integrity	The integrity string for the version of bootstrap css to include.
js_src	The url of jsDelivr for the version of bootstrap js bundle to include.
js_integrity	The integrity string for the version of bootstrap js bundle to include.

Value

A string of HTML.

Examples

```
bs_doc(
  body = div(h1("Hello"), p("Welcome to this page. "))
)
```

bs_dropdown

Create a Bootstrap dropdown

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/dropdowns/>.

Usage

```
bs_dropdown(
  id,
  items = list(),
  button_label = "Dropdown Button",
  dropdown_attr = c(class = "dropdown"),
  button_attr = c(class = "btn btn-secondary dropdown-toggle"),
  ul_attr = c(class = "dropdown-menu"),
  li_attr = NULL,
  a_attr = c(class = "dropdown-item")
)
```

Arguments

<code>id</code>	A string, the id to use for the dropdown, must be unique within a page (if you have multiple dropdowns on a page).
<code>items</code>	A named list, names become the href for each item, values should be the text to display for each href. If an item is unnamed, the value does not get passed to the li/a tags and is instead displayed as-is (useful for displaying custom HTML content in the dropdown).
<code>button_label</code>	A string, the label to use for the dropdown toggle button.
<code>dropdown_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the dropdown elements.
<code>button_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the button controlling the dropdown toggle.
<code>ul_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the "ul" tag wrapping the dropdown nav elements.
<code>li_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the "li" tags wrapping the dropdown nav elements if the input list item is named.
<code>a_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Added to the "a" tags wrapping the dropdown nav elements if the input list item is named.

Value

A string of HTML.

Examples

```
bs_dropdown(
  id = "drop",
  items = list(
    "#" = "Home",
    "#" = "About",
    "#" = "Other"
  )
)
```

bs_figure*Create HTML figure tag configured with Bootstrap classes*

Description

Learn more at <https://getbootstrap.com/docs/5.1/content/figures/>.

Usage

```
bs_figure(  
  figure_attr = c(class = "figure"),  
  img_attr = c(src = "...", alt = "...", class = "figure-img img-fluid"),  
  figcaption_attr = c(class = "figure-caption"),  
  figcaption = NULL  
)
```

Arguments

figure_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::figure</code> .
img_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::img</code> .
figcaption_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::figcaption</code> .
figcaption	A string, gets passed to <code>html5::figcaption</code> .

Value

A string of HTML.

Examples

```
bs_figure(  
  img_attr = c(  
    "src" = "...",  
    "alt" = "...",  
    "class" = "figure-img img-fluid"  
  )  
)
```

bs_flexbox

Create a Bootstrap flexbox

Description

Learn more at <https://getbootstrap.com/docs/5.1/utilities/flex/>.

Usage

```
bs_flexbox(x, div_attr = c(class = "d-flex justify-content-center"))
```

Arguments

x A string, the HTML or text to display in the div.

div_attr A named list or named vector, names are attribute names and values are attribute values. Added to the div containing x. Defaults to center the content of x.

Value

A string of HTML.

Examples

```
bs_flexbox(
  p("Hello")
)
```

bs_green

Hex code for bootstrap green color

Description

"#198754"

Usage

```
bs_green
```

Format

A string

`bs_img`*Create HTML img tag configured with Bootstrap classes*

Description

Learn more at <https://getbootstrap.com/docs/5.1/content/images/>.

Usage

```
bs_img(img_attr = c(src = "...", alt = "...", class = "img"), center = FALSE)
```

Arguments

<code>img_attr</code>	A named list or named vector, names are attribute names and values are attribute values. Passed to the <code>attr</code> parameter of <code>html5::img</code> .
<code>center</code>	TRUE/FALSE, if TRUE, wraps img tag in a div with class "text-center".

Value

A string of HTML.

Examples

```
bs_img(  
  img_attr = c(  
    "src" = "...",  
    "alt" = "...",  
    "class" = "img"  
  )  
)
```

`bs_indigo`*Hex code for bootstrap indigo color*

Description

"#6610f2"

Usage

```
bs_indigo
```

Format

A string

bs_info	<i>Hex code for bootstrap info color</i>
---------	--

Description

"#0dcaf0"

Usage

bs_info

Format

A string

bs_input	<i>Create a HTML input tag configured with Bootstrap classes</i>
----------	--

Description

Learn more at <https://getbootstrap.com/docs/5.1/forms/overview/>.

Usage

```
bs_input(  
  id,  
  type = "text",  
  value = NULL,  
  placeholder = NULL,  
  label = NULL,  
  text = NULL,  
  required = FALSE,  
  div_attr = NULL,  
  input_attr = c(class = "form-control"),  
  label_attr = c(class = "form-label"),  
  text_attr = c(class = "form-text"),  
  inline = FALSE  
)
```

Arguments

id	A string, the id/name for the input, passed to the id and name attributes of the <input> tag.
type	A string, the type of input to create, passed to the type attribute of the <input> tag.

value	A string, the value of the input, passed to the value attribute of the <input> tag.
placeholder	A string, passed to the placeholder attribute of the <input> tag.
label	A string, passed to the <label> tag.
text	A string, text or HTML to display with the input and label tags.
required	TRUE/FALSE, if TRUE, will add the required attribute to the input tag.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, wrapping the input, label, and text.
input_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::input, but id (also name), type, value, and placeholder have their own parameters.
label_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::label.
text_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, which will display the text parameter.
inline	TRUE/FALSE, if TRUE, adds a div and classes to display the label, input, and text in the same line.

Value

A string of HTML.

Examples

```
bs_input(
  id = "example1",
  label = "Example Text Input"
)
```

bs_light

Hex code for bootstrap light color

Description

"#f8f9fa"

Usage

```
bs_light
```

Format

A string

bs_modal

*Create a Bootstrap modal***Description**

Learn more at <https://getbootstrap.com/docs/5.1/components/modal/>.

Usage

```
bs_modal(
  id,
  header = button(attr = c(type = "button", class = "btn-close", `data-bs-dismiss` =
    "modal", `aria-label` = "Close")),
  title = h5("Note"),
  body,
  footer = button(attr = c(type = "button", class = "btn btn-secondary",
    `data-bs-dismiss` = "modal"), "Close"),
  modal_attr = c(class = "modal", tabindex = "-1"),
  dialog_attr = c(class = "modal-dialog"),
  content_attr = c(class = "modal-content"),
  header_attr = c(class = "modal-header"),
  title_attr = c(class = "modal-title"),
  body_attr = c(class = "modal-body"),
  footer_attr = c(class = "modal-footer")
)
```

Arguments

id	A string, an id for the modal (to launch the modal, reference this id in the data-bs-target attribute of the HTML element that will launch the modal. See example below).
header	A string, likely HTML, that goes in the header div after the title.
title	A string, likely HTML, displayed as the title of the modal.
body	A string, likely HTML, displayed as the body of the modal.
footer	A string, likely HTML, displayed at the bottom of the modal.
modal_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the the div wrapping the dialog.
dialog_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the the div wrapping the content wrapper.
content_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the the div wrapping the content (header, body, footer).
header_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the the div wrapping the header.
title_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the the div wrapping the title.

body_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the body.
footer_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the footer.

Value

A string of HTML.

Examples

```
div(  
  button(  
    attr = c(  
      "type" = "button",  
      "class" = "btn btn-primary",  
      "data-bs-toggle" = "modal",  
      "data-bs-target" = "#modal1"  
    ),  
    "Launch Modal"  
  ),  
  bs_modal(  
    id = "modal1",  
    body = p("Here is the modal.")  
  )  
)
```

bs_nav

Create a Bootstrap nav

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/navs-tabs/>.

Usage

```
bs_nav(  
  items = list(),  
  vertical = FALSE,  
  nav_attr = c(class = "nav"),  
  ul_attr = c(class = "nav"),  
  li_attr = c(class = "nav-item"),  
  a_attr = c(class = "nav-link")  
)
```

Arguments

items	A list, creates nav elements. If a list item is named, names should be links and values should be text to display in the nav for that link. Names will be passed to the href attribute and values to the main content of the <code>html5::a</code> function which will be wrapped by the <code>html5::li</code> function, each of which have Bootstrap classes added by default. If an item in the list is not named, the item must be valid HTML with appropriate Bootstrap classes added manually. For example, to add a drop-down, add an unnamed item to the list with HTML defining the drop-down as the value of the item.
vertical	TRUE/FALSE, if TRUE, makes the nav vertical.
nav_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the <code>attr</code> parameter of <code>html5::nav</code> .
ul_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the <code>attr</code> parameter of <code>html5::ul</code> .
li_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the <code>attr</code> parameter of <code>html5::li</code> .
a_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the <code>attr</code> parameter of <code>html5::a</code> .

Value

A string of HTML.

Examples

```
bs_nav(
  items = list(
    "#" = "Option 1",
    "#" = "Option 2",
    "#" = "Option 3"
  )
)
```

bs_navbar

Create a Bootstrap navbar

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/navbar/>.

Usage

```
bs_navbar(
  id = toolbox::sampleStr(12, sample_chars = c(letters, LETTERS)),
  brand = list(),
  from_left = list(),
```

```

    from_right = list(),
    nav_attr = c(class = "navbar bg-primary navbar-dark navbar-expand-lg"),
    container_attr = c(class = "container-fluid"),
    div_attr = c(),
    brand_attr = c(class = "navbar-brand"),
    from_left_ul_attr = c(class = "navbar-nav me-auto"),
    from_right_ul_attr = c(class = "navbar-nav"),
    li_attr = c(class = "nav-item"),
    a_attr = c(class = "nav-link")
  )

```

Arguments

id	A string, used to control the collapse/expand functionality. Defaults to a random string.
brand	A named list of length 1, name should be a value suitable for the href attribute of <code>html5::a</code> and the value is the HTML or text to display in the a tag.
from_left	A list, creates navbar elements arranged to the left. If a list item is named, names should be links and values should be text to display in the navbar for that link. Names will be passed to the href attribute and values to the main content of the <code>html5::a</code> function which will be wrapped by the <code>html5::li</code> function, each of which have Bootstrap classes added by default. If an item in the list is not named, the item must be valid HTML with appropriate Bootstrap classes added manually. For example, to add a drop-down, add an unnamed item to the list with HTML defining the drop-down as the value of the item.
from_right	A list, creates navbar elements arranged to the right. If a list item is named, names should be links and values should be text to display in the navbar for that link. Names will be passed to the href attribute and values to the main content of the <code>html5::a</code> function which will be wrapped by the <code>html5::li</code> function, each of which have Bootstrap classes added by default. If an item in the list is not named, the item must be valid HTML with appropriate Bootstrap classes added manually. For example, to add a drop-down, add an unnamed item to the list with HTML defining the drop-down as the value of the item.
nav_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::nav</code> .
container_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::div</code> to be used as a container.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::div</code> wrapping the brand and left and right content.
brand_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::a</code> containing the brand href and text.
from_left_ul_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::ul</code> .

from_right_ul_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::ul</code> .
li_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::li</code> .
a_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::a</code> .

Value

A string of HTML.

Examples

```
bs_navbar(
  brand = list("#" = "Sample Brand"),
  from_left = list(
    "/" = "Home",
    "/about" = "About"
  ),
  from_right = list(
    "/options" = "Options"
  )
)
```

bs_offcanvas

Create a Bootstrap offcanvas

Description

Create a Bootstrap offcanvas

Usage

```
bs_offcanvas(
  id = "offcanvas",
  header,
  title = NULL,
  body,
  offcanvas_attr = c(class = "offcanvas offcanvas-start", tabindex = "-1",
    `aria-labelledby` = "offcanvasLabel"),
  header_attr = c(class = "offcanvas-header"),
  title_attr = c(class = "offcanvas-title", id = "offcanvasLabel"),
  body_attr = c(class = "offcanvas-body"),
  title_function = h5
)
```

Arguments

id	A string, the id for the div of the offcanvas.
header	A string, the HTML to display in the header of the offcanvas.
title	A string, the HTML to display in the title of the offcanvas.
body	A string, the HTML to display in the body of the offcanvas.
offcanvas_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the offcanvas content.
header_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the offcanvas header.
title_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the tag containing the offcanvas title.
body_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the offcanvas body.
title_function	A function, most likely from the html5 package, containing the attr parameter to be used to generate the title, defaults to h5.

Value

A string of HTML.

Examples

```
bs_offcanvas(  
  header = "Hello",  
  body = p("This is a offcanvas.")  
)
```

bs_orange	<i>Hex code for bootstrap orange color</i>
-----------	--

Description

"#fd7e14"

Usage

bs_orange

Format

A string

bs_pagination

*Create a Bootstrap pagination nav***Description**

Learn more at <https://getbootstrap.com/docs/5.1/components/pagination/>.

Usage

```
bs_pagination(
  items = list(),
  ul_attr = c(class = "pagination"),
  li_attr = c(class = "page-item"),
  a_attr = c(class = "page-link")
)
```

Arguments

items	A list, creates nav elements. If a list item is named, names should be links and values should be text to display in the pagination bar for that link. Names will be passed to the href attribute and values to the main content of the <code>html5::a</code> function which will be wrapped by the <code>html5::li</code> function, each of which have Bootstrap classes added by default. If an item in the list is not named, the item must be valid HTML with appropriate Bootstrap classes added manually.
ul_attr	A named list or named vector, names are attribute names and values are attribute values. Used for the "ul" tag wrapping the nav elements.
li_attr	A named list or named vector, names are attribute names and values are attribute values. Used for the "li" tags wrapping the nav elements if the input list item is named.
a_attr	A named list or named vector, names are attribute names and values are attribute values. Used for the "a" tags wrapping the nav elements if the input list item is named.

Value

A string of HTML.

Examples

```
bs_pagination(
  items = list(
    "#" = "Previous",
    "#" = "1",
    "#" = "2",
    "#" = "3",
    "#" = "Next"
  )
)
```

bs_pink	<i>Hex code for bootstrap pink color</i>
---------	--

Description`"#d63384"`**Usage**`bs_pink`**Format**

A string

bs_primary	<i>Hex code for bootstrap primary color</i>
------------	---

Description`"#0d6efd"`**Usage**`bs_primary`**Format**

A string

bs_purple	<i>Hex code for bootstrap purple color</i>
-----------	--

Description`"#6f42c1"`**Usage**`bs_purple`**Format**

A string

bs_red	<i>Hex code for bootstrap red color</i>
--------	---

Description

"#dc3545"

Usage

bs_red

Format

A string

bs_row	<i>Create a Bootstrap row div</i>
--------	-----------------------------------

Description

Learn more at <https://getbootstrap.com/docs/5.1/layout/grid/>.

Usage

```
bs_row(..., row_attr = c(class = "row"))
```

Arguments

...	A string or strings of HTML content to include in the row div.
row_attr	A named list or named vector, names are attribute names and values are attribute values.

Value

A string of HTML.

Examples

```
bs_row(  
  bs_col(p("Col 1")),  
  bs_col(p("Col 2"))  
)
```

bs_secondary	<i>Hex code for bootstrap secondary color</i>
--------------	---

Description

"#6c757d"

Usage

bs_secondary

Format

A string

bs_select	<i>Create a HTML select tag configured with Bootstrap classes</i>
-----------	---

Description

Learn more at <https://getbootstrap.com/docs/5.1/forms/overview/>.

Usage

```
bs_select(
  ...,
  id,
  label = NULL,
  text = NULL,
  multiple = FALSE,
  required = FALSE,
  div_attr = NULL,
  select_attr = c(class = "form-select"),
  label_attr = c(class = "form-label"),
  text_attr = c(class = "form-text")
)
```

Arguments

...	A string or strings of HTML to pass to <code>html5::select()</code> , most likely a sequence of option tags.
id	A string, the id/name for the select, passed to the <code>id</code> and <code>name</code> attributes of the <code><select></code> tag.
label	A string, the label to use for the select, passed to <code>html5::label()</code> .
text	A string, text or HTML to display with the select and label tags.

multiple	TRUE/FALSE, if TRUE, adds the "multiple" attribute to the select tag.
required	TRUE/FALSE, if TRUE, will add the required attribute to the select tag.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, wrapping the select, label, and text.
select_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::select.
label_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::label.
text_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, which will display the text parameter.

Value

A string of HTML.

Examples

```
bs_select(
  option(attr = c(value = 1), "Option One"),
  option(attr = c(value = 2), "Option Two"),
  id = "example1",
  label = "Example Select Input"
)
```

bs_spinner

Create a Bootstrap spinner

Description

Learn more at <https://getbootstrap.com/docs/5.1/components/spinners/>.

Usage

```
bs_spinner(div_attr = c(class = "spinner-border text-primary"))
```

Arguments

div_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div displaying the spinner.
----------	---

Value

A string of HTML.

Examples

```
bs_spinner()
```

bs_success	<i>Hex code for bootstrap success color</i>
------------	---

Description

"#198754"

Usage

```
bs_success
```

Format

A string

bs_table	<i>Create a HTML table configured with Bootstrap classes</i>
----------	--

Description

Learn more at <https://getbootstrap.com/docs/5.1/content/tables/>.

Usage

```
bs_table(
  x,
  id,
  headers = NULL,
  table_attr = list(class = "table"),
  thead_attr = NULL,
  tbody_attr = NULL,
  tr_attr = NULL,
  th_attr = list(scope = "col"),
  td_attr = NULL,
  wrapper_attr = NULL
)
```

Arguments

x	A data frame or list with entries of equal length.
id	A string, the id for the table.
headers	A vector of names to use as table headers instead of the list names (or 1, 2, 3, etc. if list is not named).
table_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of <code>html5::table</code> .

thead_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::thead.
tbody_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::tbody.
tr_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::tr.
th_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::th.
td_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::td.
wrapper_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div wrapping html5::table.

Value

A string of HTML.

Examples

```
bs_table(  
  id = "t1",  
  x = list(  
    col1 = c(1, 2, 3, 4, 5),  
    col2 = c("a", "b", "c", "d", "e"),  
    col3 = c(1, 2, 3, 4, 5),  
    col4 = c("test", "test", "test", "test", "test")  
  )  
)
```

bs_teal	<i>Hex code for bootstrap teal color</i>
---------	--

Description

"#20c997"

Usage

bs_teal

Format

A string

bs_textarea

*Create a HTML textarea tag configured with Bootstrap classes***Description**

Learn more at <https://getbootstrap.com/docs/5.1/forms/overview/>.

Usage

```
bs_textarea(
  id,
  value = NULL,
  label = NULL,
  placeholder = NULL,
  text = NULL,
  inline = FALSE,
  required = FALSE,
  div_attr = NULL,
  textarea_attr = c(class = "form-control"),
  label_attr = c(class = "form-label"),
  text_attr = c(class = "form-text")
)
```

Arguments

id	A string, the id/name for the textarea, passed to the id and name attributes of the <textarea> tag.
value	A string, the value of the textarea, passed to the value attribute of the <textarea> tag.
label	A string, the label to use for the textarea, passed to html5::label.
placeholder	A string, passed to the placeholder attribute of the <textarea> tag.
text	A string, text or HTML to display with the textarea and label tags.
inline	TRUE/FALSE, if TRUE, adds a div and classes to display the label and textarea and text in the same line.
required	TRUE/FALSE, if TRUE, will add the required attribute to the textarea tag.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, wrapping the textarea, label, and text.
textarea_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::textarea.
label_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::label.
text_attr	A named list or named vector, names are attribute names and values are attribute values. Passed to the attr parameter of html5::div, which will display the text parameter.

Value

A string of HTML.

Examples

```
bs_textarea(  
  id = "example1",  
  label = "Example Text Area Input"  
)
```

bs_toast	Create a Bootstrap toast
----------	--------------------------

Description

Create a Bootstrap toast

Usage

```
bs_toast(  
  id,  
  header,  
  body,  
  default_close_button = TRUE,  
  on_load = TRUE,  
  toast_attr = c(class = "toast", role = "alert", `aria-live` = "assertive",  
    `aria-atomic` = "true", `data-bs-autohide` = "false"),  
  header_attr = c(class = "toast-header"),  
  body_attr = c(class = "toast-body")  
)
```

Arguments

id	A string, the id for the div of the toast.
header	A string, the HTML to display in the header of the toast.
body	A string, the HTML to display in the body of the toast.
default_close_button	TRUE/FALSE, if TRUE, adds code to display the default toast close button, otherwise the close button should be added manually.
on_load	TRUE/FALSE, if TRUE, adds a script tag with javascript to show the toast by id on load.
toast_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the toast content.
header_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the toast header.
body_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping the toast body.

Value

A string of HTML.

Examples

```
bs_toast(  
  id = "toast1",  
  header = "Hello",  
  body = "This is a toast"  
)
```

bs_toast_container	Create a Bootstrap toast container
--------------------	------------------------------------

Description

Create a Bootstrap toast container

Usage

```
bs_toast_container(..., div_attr = c(class = "toast-container"))
```

Arguments

...	A string, the HTML to display in the toast container.
div_attr	A named list or named vector, names are attribute names and values are attribute values. Added to the div wrapping

Value

A string of HTML.

Examples

```
bs_toast_container(  
  bs_toast(  
    id = "toast1",  
    header = "Hello",  
    body = "This is a toast"  
  )  
)
```

bs_toast_js	Create a <code><script></code> tag to initialize the Bootstrap javascript for creating toasts. Must include in HTML document if using a toast.
-------------	--

Description

Create a `<script>` tag to initialize the Bootstrap javascript for creating toasts. Must include in HTML document if using a toast.

Usage

```
bs_toast_js()
```

Value

A string of HTML.

Examples

```
bs_toast_js()
```

bs_warning	Hex code for bootstrap warning color
------------	--------------------------------------

Description

```
#ffc107"
```

Usage

```
bs_warning
```

Format

A string

bs_white	<i>Hex code for bootstrap white color</i>
----------	---

Description

"#fff"

Usage

bs_white

Format

A string

bs_yellow	<i>Hex code for bootstrap yellow color</i>
-----------	--

Description

"#ffc107"

Usage

bs_yellow

Format

A string

css_href_var	<i>Variable for the CSS CDN link</i>
--------------	--------------------------------------

Description

"https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css"

Usage

css_href_var

Format

A string

css_integrity_var	<i>Variable for the CSS CDN integrity string</i>
-------------------	--

Description

"sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC"

Usage

css_integrity_var

Format

A string

js_integrity_var	<i>Variable for the JS CDN integrity string</i>
------------------	---

Description

"sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM"

Usage

js_integrity_var

Format

A string

js_src_var	<i>Variable for the JS CDN link</i>
------------	-------------------------------------

Description

"https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js"

Usage

js_src_var

Format

A string

Index

* datasets

- [bs_black, 5](#)
- [bs_blue, 6](#)
- [bs_cyan, 13](#)
- [bs_danger, 14](#)
- [bs_dark, 14](#)
- [bs_green, 18](#)
- [bs_indigo, 19](#)
- [bs_info, 20](#)
- [bs_light, 21](#)
- [bs_orange, 27](#)
- [bs_pink, 29](#)
- [bs_primary, 29](#)
- [bs_purple, 29](#)
- [bs_red, 30](#)
- [bs_secondary, 31](#)
- [bs_success, 33](#)
- [bs_teal, 34](#)
- [bs_warning, 38](#)
- [bs_white, 39](#)
- [bs_yellow, 39](#)
- [css_href_var, 39](#)
- [css_integrity_var, 40](#)
- [js_integrity_var, 40](#)
- [js_src_var, 40](#)

- [bs_accordion, 3](#)
- [bs_alert, 4](#)
- [bs_badge, 5](#)
- [bs_black, 5](#)
- [bs_blue, 6](#)
- [bs_breadcrumb, 6](#)
- [bs_card, 7](#)
- [bs_carousel, 9](#)
- [bs_clearfix, 10](#)
- [bs_col, 11](#)
- [bs_col_break, 12](#)
- [bs_collapse, 11](#)
- [bs_container, 13](#)
- [bs_cyan, 13](#)
- [bs_danger, 14](#)
- [bs_dark, 14](#)
- [bs_doc, 14](#)
- [bs_dropdown, 15](#)
- [bs_figure, 17](#)
- [bs_flexbox, 18](#)
- [bs_green, 18](#)
- [bs_img, 19](#)
- [bs_indigo, 19](#)
- [bs_info, 20](#)
- [bs_input, 20](#)
- [bs_light, 21](#)
- [bs_modal, 22](#)
- [bs_nav, 23](#)
- [bs_navbar, 24](#)
- [bs_offcanvas, 26](#)
- [bs_orange, 27](#)
- [bs_pagination, 28](#)
- [bs_pink, 29](#)
- [bs_primary, 29](#)
- [bs_purple, 29](#)
- [bs_red, 30](#)
- [bs_row, 30](#)
- [bs_secondary, 31](#)
- [bs_select, 31](#)
- [bs_spinner, 32](#)
- [bs_success, 33](#)
- [bs_table, 33](#)
- [bs_teal, 34](#)
- [bs_textarea, 35](#)
- [bs_toast, 36](#)
- [bs_toast_container, 37](#)
- [bs_toast_js, 38](#)
- [bs_warning, 38](#)
- [bs_white, 39](#)
- [bs_yellow, 39](#)

- [css_href_var, 39](#)
- [css_integrity_var, 40](#)

js_integrity_var, [40](#)

js_src_var, [40](#)