

Package ‘dartR.spatial’

July 22, 2025

Type Package

Title Applying Landscape Genomic Methods on 'SNP' and 'Silicodart'
Data

Version 0.78

Date 2023-11-15

Description Provides landscape genomic functions to analyse 'SNP' (single nuclear polymorphism) data, such as least cost path analysis and isolation by distance. Therefore each sample needs to have coordinate data attached (lat/lon) to be able to run most of the functions. 'dartR.spatial' is a package that belongs to the 'dartRverse' suit of packages and depends on 'dartR.base' and 'dartR.data'.

Revision Attractive Abalone

Encoding UTF-8

Depends R (>= 3.5), adegenet (>= 2.0.0), dartR.base, dartR.data

Imports methods, utils, crayon, StAMPP, raster, sp, tidyr, vegan,
MASS, ggplot2, data.table

Suggests mmmod, dismo, gdistance, gplots, rrBLUP, terra (>= 1.7-39),
sf, PopGenReport

License GPL (>= 3)

RoxygenNote 7.2.3

NeedsCompilation no

Author Bernd Gruber [aut, cre],
Arthur Georges [aut],
Jose L. Mijangos [aut],
Carlo Pacioni [aut],
Peter J. Unmack [ctb],
Oliver Berry [ctb]

URL <https://green-striped-gecko.github.io/dartR/>

BugReports <https://groups.google.com/g/dartr?pli=1>

Maintainer Bernd Gruber <bernd.gruber@canberra.edu.au>

Repository CRAN

Date/Publication 2023-11-15 00:50:02 UTC

Contents

gl.costdistances	2
gl.genleastcost	3
gl.grm2	5
gl.ibd	7
gl.kosman	9
gl.spatial.autoCorr	10
gl2shp	14
utils.spautocor	15
Index	17

gl.costdistances	<i>Calculates cost distances for a given landscape (resistance matrix)</i>
------------------	--

Description

Calculates a cost distance matrix, to be used with run.poppensim.

Usage

```
gl.costdistances(landscape, locs, method, NN, verbose = NULL)
```

Arguments

landscape	A raster object coding the resistance of the landscape [required].
locs	Coordinates of the subpopulations. If a genlight object is provided coordinates are taken from @other\$latlon and centers for population (pop(gl)) are calculated. In case you want to calculate costdistances between individuals redefine pop(gl) via: pop(gl)<- indNames(gl) [required].
method	Defines the type of cost distance, types are 'leastcost', 'rSPDistance' or 'commute' (Circuitscape type) [required].
NN	Number of next neighbours recommendation is 8 [required].
verbose	Verbosity: 0, silent or fatal errors; 1, begin and end; 2, progress log ; 3, progress and results summary; 5, full report [default 2, unless specified using gl.set.verbosity].

Value

A costdistance matrix between all pairs of locs.

Examples

```
data(possums.gl)
library(raster) #needed for that example
landscape.sim <- readRDS(system.file('extdata','landscape.sim.rdata',
package='dartR.data'))
#calculate mean centers of individuals per population
xy <- apply(possums.gl@other$xy, 2, function(x) tapply(x, pop(possums.gl),
mean))
cd <- gl.costdistances(landscape.sim, xy, method='leastcost', NN=8)
round(cd,3)
```

gl.genleastcost	<i>Performs least-cost path analysis based on a friction matrix</i>
-----------------	---

Description

This function calculates the pairwise distances (Euclidean, cost path distances and genetic distances) of populations using a friction matrix and a spatial genind object. The genind object needs to have coordinates in the same projected coordinate system as the friction matrix. The friction matrix can be either a single raster or a stack of several layers. If a stack is provided the specified cost distance is calculated for each layer in the stack. The output of this function can be used with the functions wassermann from package PopGenReport and lgrMMRR from package PopGenReport to test for the significance of a layer on the genetic structure.

Usage

```
gl.genleastcost(
  x,
  fric.raster,
  gen.distance,
  NN = NULL,
  pathtype = "leastcost",
  plotpath = TRUE,
  theta = 1,
  verbose = NULL
)
```

Arguments

x	A spatial gelight object. [required].
fric.raster	A friction matrix [required].
gen.distance	Specification which genetic distance method should be used to calculate pairwise genetic distances between populations ('D', 'Gst.Nei', 'Gst.Hedrick') or individuals ('kosman', 'propShared') [required].

NN	Number of neighbours used when calculating the cost distance (possible values 4, 8 or 16). As the default is NULL a value has to be provided if <code>pathtype='leastcost'</code> . NN=8 is most commonly used. Be aware that linear structures may cause artefacts in the least-cost paths, therefore inspect the actual least-cost paths in the provided output [default NULL].
pathtype	Type of cost distance to be calculated (based on function in the <code>gdistance</code> package. Available distances are 'leastcost', 'commute' or 'rSPDistance'. See functions in the <code>gdistance</code> package for further explanations. If the path type is set to 'leastcost' then paths and also pathlength are returned [default 'leastcost'].
plotpath	switch if least cost paths should be plotted (works only if <code>pathtype='leastcost'</code>). Be aware this slows down the computation, but it is recommended to do this to check least cost paths visually.
theta	value needed for <code>rSPDistance</code> function. See <code>rSPDistance</code> in package <code>gdistance</code> [default 1].
verbose	Verbosity: 0, silent or fatal errors; 1, begin and end; 2, progress log; 3, progress and results summary; 5, full report [default 2, unless specified using <code>gl.set.verbosity</code>].

Value

Returns a list that consists of four pairwise distance matrices (Euclidean, Cost, length of path and genetic) and the actual paths as spatial line objects.

Author(s)

Bernd Gruber (bugs? Post to <https://groups.google.com/d/forum/dartr>)

References

- Cushman, S., Wasserman, T., Landguth, E. and Shirk, A. (2013). Re-Evaluating Causal Modeling with Mantel Tests in Landscape Genetics. *Diversity*, 5(1), 51-72.
- Landguth, E. L., Cushman, S. A., Schwartz, M. K., McKelvey, K. S., Murphy, M. and Luikart, G. (2010). Quantifying the lag time to detect barriers in landscape genetics. *Molecular ecology*, 4179-4191.
- Wasserman, T. N., Cushman, S. A., Schwartz, M. K. and Wallin, D. O. (2010). Spatial scaling and multi-model inference in landscape genetics: *Martes americana* in northern Idaho. *Landscape Ecology*, 25(10), 1601-1612.

Examples

#this example takes about 20 seconds to run...

```
data(possums.gl)
library(raster) #needed for that example
landscape.sim <- readRDS(system.file('extdata','landscape.sim.rdata',
package='dartR.data'))
#use only 3 population (first 90 individuals) due to speed
glc <- gl.genleastcost(x=possums.gl,fric.raster=landscape.sim ,
gen.distance = 'D', NN=8, pathtype = 'leastcost',plotpath = TRUE)
```

```
#### run tests as implemented in PopGenreport (maybe need to install)
if (require("PopGenReport", quietly=TRUE)) {
  PopGenReport::wassermann(eucl.mat = glc$eucl.mat, cost.mat = glc$cost.mats,
    gen.mat = glc$gen.mat)
  lgrMMRR(gen.mat = glc$gen.mat, cost.mats = glc$cost.mats,
    eucl.mat = glc$eucl.mat)
}
```

gl.grm2

Calculates an identity by descent matrix

Description

This function calculates the mean probability of identity by state (IBS) across loci that would result from all the possible crosses of the individuals analyzed. IBD is calculated by an additive relationship matrix approach developed by Endelman and Jannink (2012) as implemented in the function [A.mat](#) (package rrBLUP).

Usage

```
gl.grm2(
  x,
  plotheatmap = TRUE,
  palette_discrete = NULL,
  palette_convergent = NULL,
  legendx = 0,
  legendy = 0.5,
  plot.file = NULL,
  plot.dir = NULL,
  verbose = NULL,
  ...
)
```

Arguments

<code>x</code>	Name of the genlight object containing the SNP data [required].
<code>plotheatmap</code>	A switch if a heatmap should be shown [default TRUE].
<code>palette_discrete</code>	the color of populations [gl.select.colors].
<code>palette_convergent</code>	A convergent palette for the IBD values [default convergent_palette].
<code>legendx</code>	x coordinates for the legend [default 0].
<code>legendy</code>	y coordinates for the legend [default 1].
<code>plot.file</code>	Name for the RDS binary file to save (base name only, exclude extension) [default NULL]

<code>plot.dir</code>	Directory in which to save files [default = working directory]
<code>verbose</code>	Verbosity: 0, silent or fatal errors; 1, begin and end; 2, progress log ; 3, progress and results summary; 5, full report [default 2 or as specified using <code>gl.set.verbosity</code>].
<code>...</code>	Parameters passed to function <code>A.mat</code> from package <code>rrBLUP</code> .

Details

Two or more alleles are identical by descent (IBD) if they are identical copies of the same ancestral allele in a base population. The additive relationship matrix is a theoretical framework for estimating a relationship matrix that is consistent with an approach to estimate the probability that the alleles at a random locus are identical in state (IBS).

This function also plots a heatmap, and a dendrogram, of IBD values where each diagonal element has a mean that equals $1+f$, where f is the inbreeding coefficient (i.e. the probability that the two alleles at a randomly chosen locus are IBD from the base population). As this probability lies between 0 and 1, the diagonal elements range from 1 to 2. Because the inbreeding coefficients are expressed relative to the current population, the mean of the off-diagonal elements is $-(1+f)/n$, where n is the number of loci. Individual names are shown in the margins of the heatmap and colors represent different populations.

Value

An identity by descent matrix

Author(s)

Custodian: Arthur Georges – Post to <https://groups.google.com/d/forum/dartR>

References

- Endelman, J. B. (2011). Ridge regression and other kernels for genomic selection with `r` package `rrblup`. *The Plant Genome* 4, 250.
- Endelman, J. B. , Jannink, J.-L. (2012). Shrinkage estimation of the realized relationship matrix. *G3: Genes, Genomics, Genetics* 2, 1405.

Examples

```
require(dartR.base)
gl.grm2(platypus.gl[1:10,1:100])
```

gl.ibd

*Performs isolation by distance analysis***Description**

This function performs an isolation by distance analysis based on a Mantel test and also produces an isolation by distance plot. If a genlight object with coordinates is provided, then an Euclidean and genetic distance matrices are calculated.'

Usage

```
gl.ibd(
  x = NULL,
  distance = "Fst",
  coordinates = "latlon",
  Dgen = NULL,
  Dgeo = NULL,
  Dgeo_trans = "Dgeo",
  Dgen_trans = "Dgen",
  permutations = 999,
  plot.out = TRUE,
  paircols = NULL,
  plot.theme = theme_dartR(),
  plot.file = NULL,
  plot.dir = NULL,
  verbose = NULL
)
```

Arguments

x	Genlight object. If provided a standard analysis on Fst/1-Fst and log(distance) is performed [required].
distance	Type of distance that is calculated and used for the analysis. Can be either population based 'Fst' [stamppFst], 'D' [stamppNeisD] or individual based 'propShared', [gl.propShared], 'euclidean' [gl.dist.ind, method='Euclidean'], 'kosman' [gl.kosman] [default "Fst"].
coordinates	Can be either 'latlon', 'xy' or a two column data.frame with column names 'lat','lon', 'x', 'y'). Coordinates are provided via gl@other\$latlon ['latlon'] or via gl@other\$xy ['xy']. If latlon data will be projected to meters using Mercator system [google maps] or if xy then distance is directly calculated on the coordinates.
Dgen	Genetic distance matrix if no genlight object is provided [default NULL].
Dgeo	Euclidean distance matrix if no genlight object is provided [default NULL].
Dgeo_trans	Transformation to be used on the Euclidean distances. See Dgen_trans [default "Dgeo"].

Dgen_trans	You can provide a formula to transform the genetic distance. The transformation can be applied as a formula using Dgen as the variable to be transformed. For example: <code>Dgen_trans = 'Dgen/(1-Dgen)'</code> . Any valid R expression can be used here [default 'Dgen', which is the identity function.]
permutations	Number of permutations in the Mantel test [default 999].
plot.out	Should an isolation by distance plot be returned [default TRUE].
paircols	Should pairwise dots colored by 'population'/individual pairs [default 'pop']. You can color pairwise individuals by pairwise population colors.
plot.theme	Theme for the plot. See details for options [default theme_dartR()].
plot.file	Name for the RDS binary file to save (base name only, exclude extension) [default NULL]
plot.dir	Directory in which to save files [default = working directory]
verbose	Verbosity: 0, silent or fatal errors; 1, begin and end; 2, progress log ; 3, progress and results summary; 5, full report [default 2 or as specified using <code>gl.set.verbosity</code>].

Details

Currently pairwise Fst and D between populations and 1-propShared and Euclidean distance between individuals are implemented. Coordinates are expected as lat long and converted to Google Earth Mercator projection. If coordinates are already projected, provide them at the `x@other$xy` slot.

You can provide also your own genetic and Euclidean distance matrices. The function is based on the code provided by the adegenet tutorial (<http://adegenet.r-forge.r-project.org/files/tutorial-basics.pdf>), using the functions `mantel` (package `vegan`), `stamppFst`, `stamppNeisD` (package `StAMPP`) and `gl.propShared` or `gl.dist.ind`. For transformation you need to have the `dismo` package installed. As a new feature you can plot pairwise relationship using double colored points (`paircols=TRUE`). Pairwise relationship can be visualised via populations or individuals, depending which distance is calculated. Please note: Often a problem arises, if an individual based distance is calculated (e.g. `propShared`) and some individuals have identical coordinates as this results in distances of zero between those pairs of individuals.

If the standard transformation $\log(D_{geo})$ is used, this results in an infinite value, because of trying to calculate $\log(0)$. To avoid this, the easiest fix is to change the transformation from $\log(D_{geo})$ to $\log(D_{geo}+1)$ or you could add some "noise" to the coordinates of the individuals (e.g. ± 1 m, but be aware if you use lat lon then you rather want to add ± 0.00001 degrees or so).

Value

Returns a list of the following components: `Dgen` (the genetic distance matrix), `Dgeo` (the Euclidean distance matrix), `Mantel` (the statistics of the Mantel test).

Author(s)

Bernd Gruber (bugs? Post to <https://groups.google.com/d/forum/dartr>)

References

Rousset, F. (1997). Genetic differentiation and estimation of gene flow from F-statistics under isolation by distance. *Genetics*, 145(4), 1219-1228.

See Also[mantel](#), [stampFst](#)**Examples**

```
#because of speed only the first 100 loci
ibd <- gl.ibd(bandicoot.gl[,1:100], Dgeo_trans='log(Dgeo)' ,
Dgen_trans='Dgen/(1-Dgen)')
#because of speed only the first 10 individuals)
ibd <- gl.ibd(bandicoot.gl[1:10,], distance='euclidean', paircols='pop',
Dgeo_trans='Dgeo')

#only first 100 loci
ibd <- gl.ibd(bandicoot.gl[,1:100], paircols='pop')
```

gl.kosman

*Calculates a Kosman distance matrix for each pair of individuals***Description**

This script calculates an individual based distance matrix.

Usage

```
gl.kosman(x, verbose = NULL)
```

Arguments

x	genlight/dartR object with a unique ploidy
verbose	verbosity of the function.

Value

returns a matrix of [dimensions nInd(x) x nInd(x)] of kosman distances between individuals,

Examples

```
#use only five individuals and seven loci
gg <- gl.kosman(possums.gl[1:5,14:21])
gg$kosman
gg$nloci
```

gl.spatial.autoCorr *Spatial autocorrelation following Smouse and Peakall 1999*

Description

Global spatial autocorrelation is a multivariate approach combining all loci into a single analysis. The autocorrelation coefficient "r" is calculated for each pair of individuals in each specified distance class. For more information see Smouse and Peakall 1999, Peakall et al. 2003 and Smouse et al. 2008.

Usage

```
gl.spatial.autoCorr(
  x = NULL,
  Dgeo = NULL,
  Dgen = NULL,
  coordinates = "latlon",
  Dgen_method = "Euclidean",
  Dgeo_trans = "Dgeo",
  Dgen_trans = "Dgen",
  bins = 5,
  reps = 100,
  plot.pops.together = FALSE,
  permutation = TRUE,
  bootstrap = TRUE,
  plot.theme = theme_dartR(),
  plot.colors.pop = NULL,
  CI.color = "red",
  plot.out = TRUE,
  plot.file = NULL,
  plot.dir = NULL,
  verbose = NULL
)
```

Arguments

x	Genlight object [default NULL].
Dgeo	Geographic distance matrix if no genlight object is provided. This is typically an Euclidean distance but it can be any meaningful (geographical) distance metrics [default NULL].
Dgen	Genetic distance matrix if no genlight object is provided [default NULL].
coordinates	Can be either 'latlon', 'xy' or a two column data.frame with column names 'lat','lon', 'x', 'y') Coordinates are provided via gl@other\$latlon ['latlon'] or via gl@other\$xy ['xy']. If latlon data will be projected to meters using Mercator system [google maps] or if xy then distance is directly calculated on the coordinates [default "latlon"].

Dgen_method	Method to calculate genetic distances. See details [default "Euclidean"].
Dgeo_trans	Transformation to be used on the geographic distances. See Dgen_trans [default "Dgeo"].
Dgen_trans	You can provide a formula to transform the genetic distance. The transformation can be applied as a formula using Dgen as the variable to be transformed. For example: Dgen_trans = 'Dgen/(1-Dgen)'. Any valid R expression can be used here [default 'Dgen', which is the identity function.]
bins	The number of bins for the distance classes (i.e. length(bins) == 1) or a vectors with the break points. See details [default 5].
reps	The number to be used for permutation and bootstrap analyses [default 100].
plot.pops.together	Plot all the populations in one plot. Confidence intervals from permutations are not shown [default FALSE].
permutation	Whether permutation calculations for the null hypothesis of no spatial structure should be carried out [default TRUE].
bootstrap	Whether bootstrap calculations to compute the 95% confidence intervals around r should be carried out [default TRUE].
plot.theme	Theme for the plot. See details [default NULL].
plot.colors.pop	A color palette for populations or a list with as many colors as there are populations in the dataset [default NULL].
CI.color	Color for the shade of the 95% confidence intervals around the r estimates [default "red"].
plot.out	Specify if plot is to be produced [default TRUE].
plot.file	Name for the RDS binary file to save (base name only, exclude extension) [default NULL] temporary directory (tempdir) [default FALSE].
plot.dir	Directory in which to save files [default = working directory]
verbose	Verbosity: 0, silent or fatal errors; 1, begin and end; 2,

Details

This function executes a modified version of spautocorr from the package PopGenReport. Differently from PopGenReport, this function also computes the 95% confidence intervals around the r via bootstraps, the 95 null hypothesis of no spatial structure and the one-tail test via permutation, and the correction factor described by Peakall et al 2003.

The input can be i) a genlight object (which has to have the latlon slot populated), ii) a pair of Dgeo and Dgen, which have to be either matrix or dist objects, or iii) a list of the matrix or dist objects if the analysis needs to be carried out for multiple populations (in this case, all the elements of the list have to be of the same class (i.e. matrix or dist) and the population order in the two lists has to be the same.

If the input is a genlight object, the function calculates the linear distance for Dgeo and the relevant Dgen matrix (see Dgen_method) for each population. When the method selected is a genetic similarity matrix (e.g. "simple" distance), the matrix is internally transformed with $1 - \text{Dgen}$ so that

positive values of autocorrelation coefficients indicates more related individuals similarly as implemented in GenAlEx. If the user provide the distance matrices, care must be taken in interpreting the results because similarity matrix will generate negative values for closely related individuals.

If $\max(D_{\text{geo}}) > 1000$ (e.g. the geographic distances are in thousands of metres), values are divided by 1000 (in the example before these would then become km) to facilitate readability of the plots.

If `bins` is of length = 1 it is interpreted as the number of (even) bins to use. In this case the starting point is always the minimum value in the distance matrix, and the last is the maximum. If it is a numeric vector of length > 1, it is interpreted as the breaking points. In this case, the first has to be the lowest value, and the last has to be the highest. There are no internal checks for this and it is user responsibility to ensure that distance classes are properly set up. If that is not the case, data that fall outside the range provided will be dropped. The number of bins will be $\text{length}(\text{bins}) - 1$.

The permutation constructs the 95% confidence intervals around the null hypothesis of no spatial structure (this is a two-tail test). The same data are also used to calculate the probability of the one-tail test (See references below for details).

Bootstrap calculations are skipped and NA is returned when the number of possible combinations given the sample size of any given distance class is < reps.

Methods available to calculate genetic distances for SNP data:

- "propShared" using the function `gl.propShared`.
- "grm" using the function `gl.grm2`.
- "Euclidean" using the function `gl.dist.ind`.
- "Simple" using the function `gl.dist.ind`.
- "Absolute" using the function `gl.dist.ind`.
- "Manhattan" using the function `gl.dist.ind`.

Methods available to calculate genetic distances for SilicoDART data:

- "Euclidean" using the function `gl.dist.ind`.
- "Simple" using the function `gl.dist.ind`.
- "Jaccard" using the function `gl.dist.ind`.
- "Bray-Curtis" using the function `gl.dist.ind`.

Plots and table are saved `plot.file` in `plot.dir` if specified.

Examples of other themes that can be used can be consulted in

- <https://ggplot2.tidyverse.org/reference/ggtheme.html> and
- <https://yutannihilation.github.io/allYourFigureAreBelongToUs/ggthemes/>

Value

Returns a data frame with the following columns:

1. Bin The distance classes
2. N The number of pairwise comparisons within each distance class

3. r.uc The uncorrected autocorrelation coefficient
4. Correction the correction
5. r The corrected autocorrelation coefficient
6. L.r The corrected autocorrelation coefficient lower limit (if bootstrap = TRUE)
7. U.r The corrected autocorrelation coefficient upper limit (if bootstrap = TRUE)
8. L.r.null.uc The uncorrected lower limit for the null hypothesis of no spatial autocorrelation (if permutation = TRUE)
9. U.r.null.uc The uncorrected upper limit for the null hypothesis of no spatial autocorrelation (if permutation = TRUE)
10. L.r.null The corrected lower limit for the null hypothesis of no spatial autocorrelation (if permutation = TRUE)
11. U.r.null The corrected upper limit for the null hypothesis of no spatial autocorrelation (if permutation = TRUE)
12. p.one.tail The p value of the one tail statistical test

Author(s)

Carlo Pacioni, Bernd Gruber & Luis Mijangos (Post to <https://groups.google.com/d/forum/dartr>)

References

- Smouse PE, Peakall R. 1999. Spatial autocorrelation analysis of individual multiallele and multilocus genetic structure. *Heredity* 82: 561-573.
- Double, MC, et al. 2005. Dispersal, philopatry and infidelity: dissecting local genetic structure in superb fairy-wrens (*Malurus cyaneus*). *Evolution* 59, 625-635.
- Peakall, R, et al. 2003. Spatial autocorrelation analysis offers new insights into gene flow in the Australian bush rat, *Rattus fuscipes*. *Evolution* 57, 1182-1195.
- Smouse, PE, et al. 2008. A heterogeneity test for fine-scale genetic structure. *Molecular Ecology* 17, 3389-3400.
- Gonzales, E, et al. 2010. The impact of landscape disturbance on spatial genetic structure in the Guanacaste tree, *Enterolobium cyclocarpum* (Fabaceae). *Journal of Heredity* 101, 133-143.
- Beck, N, et al. 2008. Social constraint and an absence of sex-biased dispersal drive fine-scale genetic structure in white-winged choughs. *Molecular Ecology* 17, 4346-4358.

Examples

```
require("dartR.data")
res <- gl.spatial.autoCorr(platypus.gl, bins=seq(0,10000,2000))
# using one population, showing sample size
test <- gl.keep.pop(platypus.gl,pop.list = "TENTERFIELD")
res <- gl.spatial.autoCorr(test, bins=seq(0,10000,2000),CI.color = "green")

test <- gl.keep.pop(platypus.gl,pop.list = "TENTERFIELD")
res <- gl.spatial.autoCorr(test, bins=seq(0,10000,2000),CI.color = "green")
```

gl2shp

*Converts a genlight object to ESRI shapefiles or kml files***Description**

This function exports coordinates in a genlight object to a point shape file (including also individual meta data if available). Coordinates are provided under `x@other$latlon` and assumed to be in WGS84 coordinates, if not proj4 string is provided.

Usage

```
gl2shp(
  x,
  type = "shp",
  proj4 = "+proj=longlat +ellps=WGS84 +datum=WGS84 +no_defs",
  outfile = "gl",
  outpath = tempdir(),
  verbose = NULL
)
```

Arguments

<code>x</code>	Name of the genlight object containing the SNP data and location data, lat longs [required].
<code>type</code>	Type of output 'kml' or 'shp' [default 'shp'].
<code>proj4</code>	Proj4string of data set (see spatialreference.org for projections) [default WGS84].
<code>outfile</code>	Name (path) of the output shape file [default 'gl']. shp extension is added automatically.
<code>outpath</code>	Path where to save the output file [default tempdir(), mandated by CRAN]. Use <code>outpath=getwd()</code> or <code>outpath='.'</code> when calling this function to direct output files to your working directory.
<code>verbose</code>	Verbosity: 0, silent or fatal errors; 1, begin and end; 2, progress log; 3, progress and results summary; 5, full report [default 2 or as specified using <code>gl.set.verbosity</code>].

Value

returns a SpatVector file

Author(s)

Bernd Guber (Post to <https://groups.google.com/d/forum/dartr>)

Examples

```
out <- gl2shp(testset.gl, outpath=tempdir())
```

utils.spautocor	<i>Spatial autocorrelation coefficient calculations</i>
-----------------	---

Description

Carries out calculation for spatial autocorrelation coefficient starting from a genetic and geographic distance matrix.

Usage

```
utils.spautocor(
  GD,
  GGD,
  permutation = FALSE,
  bootstrap = FALSE,
  bins = 10,
  reps
)
```

Arguments

GD	Genetic distance matrix.
GGD	Geographic distance matrix.
permutation	Whether permutation calculations for the null hypothesis of no spatial structure should be carried out [default TRUE].
bootstrap	Whether bootstrap calculations to compute the 95% confidence intervals around r should be carried out [default TRUE].
bins	The number of bins for the distance classes (i.e. <code>length(bins) == 1</code>) or a vector with the break points. See details [default 5].
reps	The number to be used for permutation and bootstrap analyses [default 100].

Details

The code of this function is based one `spautocorr` from the package `PopGenReport`, which has been modified to fix a few bugs (as of `PopGenReport` v 3.0.4 and allow calculations of bootstraps estimates.

See details from `gl.spatial.autoCorr` for a detailed explanation.

Value

Returns a data frame with the following columns:

1. Bin The distance classes
2. N The number of pairwise comparisons within each distance class
3. r_{uc} The uncorrected autocorrelation coefficient

if both `bootstap` and `permutation` are `FALSE` otherwise only r estimates are returned

Author(s)

Carlo Pacioni & Bernd Gruber

References

- Smouse PE, Peakall R. 1999. Spatial autocorrelation analysis of individual multiallele and multilocus genetic structure. *Heredity* 82: 561-573.
- Double, MC, et al. 2005. Dispersal, philopatry and infidelity: dissecting local genetic structure in superb fairy-wrens (*Malurus cyaneus*). *Evolution* 59, 625-635.
- Peakall, R, et al. 2003. Spatial autocorrelation analysis offers new insights into gene flow in the Australian bush rat, *Rattus fuscipes*. *Evolution* 57, 1182-1195.
- Smouse, PE, et al. 2008. A heterogeneity test for fine-scale genetic structure. *Molecular Ecology* 17, 3389-3400.
- Gonzales, E, et al. 2010. The impact of landscape disturbance on spatial genetic structure in the Guanacaste tree, *Enterolobium cyclocarpum*(Fabaceae). *Journal of Heredity* 101, 133-143.
- Beck, N, et al. 2008. Social constraint and an absence of sex-biased dispersal drive fine-scale genetic structure in white-winged choughs. *Molecular Ecology* 17, 4346-4358.

See Also

[gl.spatial.autoCorr](#)

Examples

```
# See gl.spatial.autoCorr
```


Index

*** inbreeding functions**

gl.grm2, [5](#)

A.mat, [5](#)

gl.costdistances, [2](#)

gl.dist.ind, [12](#)

gl.genleastcost, [3](#)

gl.grm2, [5](#)

gl.ibd, [7](#)

gl.kosman, [9](#)

gl.propShared, [12](#)

gl.spatial.autoCorr, [10](#), [16](#)

gl2shp, [14](#)

mantel, [8](#), [9](#)

rSPDistance, [4](#)

stampFst, [7–9](#)

stampNeisD, [7](#), [8](#)

utils.spautocor, [15](#)