

# Package ‘linkeR’

September 21, 2025

**Title** Link Interactive Plots and Tables in 'shiny' Applications

**Version** 0.1.2

**Description** Build powerful, linked-view dashboards in 'shiny' applications. With a declarative, one-line setup, you can create bidirectional links between interactive components. When a user interacts with one element (e.g., clicking a map marker), all linked components (such as 'DT' tables or other charts) instantly update. Supports 'leaflet' maps, 'DT' tables, and spatial data via 'sf' objects out-of-the-box, with an extensible API for custom components.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Imports** shiny (>= 1.5.0), magrittr (>= 2.0.0), later (>= 1.0.0)

**Suggests** leaflet, DT, sf, testthat (>= 3.0.0), knitr, plotly, bslib, rmarkdown

**Config/testthat.edition** 3

**VignetteBuilder** knitr

**URL** <https://epiforesite.github.io/linkeR/>,

<https://github.com/EpiForeSITE/linkeR/>

**BugReports** <https://github.com/EpiForeSITE/linkeR/issues/>

**NeedsCompilation** no

**Author** Jake Wagoner [aut, cre] (ORCID:  
<https://orcid.org/0009-0000-5053-2281>),  
Centers for Disease Control and Prevention's Center for Forecasting and  
Outbreak Analytics [fnd] (Cooperative agreement CDC-RFA-FT-23-0069)

**Maintainer** Jake Wagoner <jakew@sci.utah.edu>

**Repository** CRAN

**Date/Publication** 2025-09-21 14:10:02 UTC

## Contents

apply_default_leaflet_behavior . . . . .	2
create_link_registry . . . . .	3
linkeR-imports . . . . .	5
link_plots . . . . .	5
register_dt . . . . .	7
register_leaflet . . . . .	8
setup_datatable_observers . . . . .	10
setup_leaflet_observers . . . . .	11
update_dt_selection . . . . .	12
update_leaflet_selection . . . . .	13
<b>Index</b>	<b>15</b>

---

<b>apply_default_leaflet_behavior</b>	
	<i>Apply Default Leaflet Behavior for Selection Events</i>

---

### Description

`apply_default_leaflet_behavior` is a helper function that provides consistent default behavior for leaflet maps when handling selection events. It manages popup display and map navigation based on the selection state.

### Usage

```
apply_default_leaflet_behavior(map_proxy, selected_data, component_info)
```

### Arguments

- `map_proxy` A leaflet map proxy object used to update the map
- `selected_data` A data frame or list containing the selected row/item data. If NULL, indicates deselection occurred.
- `component_info` A list containing component configuration information:
  - shared\_id\_column** Character. Name of the column containing unique identifiers
  - config** List containing:
    - lng\_col** Character. Name of the longitude column
    - lat\_col** Character. Name of the latitude column
    - highlight\_zoom** Numeric. Zoom level to use when highlighting selection

## Details

When selected\_data is provided:

- Creates a popup with "Selected" header and ID information
- Sets map view to the selected location coordinates
- Applies the configured highlight zoom level

When selected\_data is NULL (deselection):

- Removes all existing popups from the map

## Value

Returns the modified map proxy object with updated view and popups

---

create\_link\_registry    *Create a Link Registry for 'shiny' Component Coordination*

---

## Description

create\_link\_registry creates a registry system that manages linked interactions between multiple 'shiny' components, allowing them to share selection state and coordinate their behavior.

## Usage

```
create_link_registry(session, on_selection_change = NULL)
```

## Arguments

session	A 'shiny' session object, required for server-side reactivity
on_selection_change	Optional callback function that gets called when selection changes. Should accept parameters: selected_id, selected_data, source_component_id, and session

## Details

The registry maintains a shared state across all registered components, automatically setting up observers to synchronize selections. When a selection changes in one component, all other registered components are updated to reflect the same selection.

Components are automatically cleaned up when re-registered to prevent memory leaks from orphaned observers.

## Value

A link\_registry object with the following methods:

**register\_component(session, component\_id, type, data\_reactive, shared\_id\_column, config)** Register a new component with the registry. Parameters:

- session: 'shiny' session object for namespacing. Can be global session in non-modular apps.
- component\_id: Unique string identifier for the component
- type: Component type (e.g., "table", "plot")
- data\_reactive: Reactive expression returning the component's data
- shared\_id\_column: Name of the column used for linking selections
- config: Optional list of component-specific configuration

**clear\_all()** Remove all registered components and reset shared state

**set\_selection(selected\_id, source\_component\_id)** Programmatically update the selection state

**get\_selection()** Get current selection as list with selected\_id and source

**get\_on\_selection\_change()** Return the on\_selection\_change callback function

**get\_components()** Get registry components info (for debugging)

**get\_shared\_state()** Get current shared state (for debugging)

## See Also

[setup\\_component\\_observers\(\)](#) for component observer setup

## Examples

```
# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create registry with optional callback
registry <- create_link_registry(
  session = session,
  on_selection_change = function(id, data, source, session) {
    message("Selection changed to ID: ", id, " from: ", source)
  }
)

# In a real app, you would register components like this:
# my_data <- reactive({ data.frame(id = 1:3, name = c("A", "B", "C")) })
# registry$register_component("table1", "table", my_data, "id")
# registry$register_component("plot1", "plot", my_data, "id")
```

---

linkeR-imports	<i>Package imports</i>
----------------	------------------------

---

### Description

Package imports

---

link_plots	<i>Simple Plot Linking Function for Non-Modular 'shiny' Apps</i>
------------	------------------------------------------------------------------

---

### Description

link\_plots provides a simple, one-line interface to link interactive components in a **single-file or non-modular 'shiny' application**. It automatically detects component types and sets up bidirectional linking.

### Usage

```
link_plots(  
  session,  
  ...,  
  shared_id_column,  
  leaflet_lng_col = "longitude",  
  leaflet_lat_col = "latitude",  
  leaflet_click_handler = NULL,  
  dt_click_handler = NULL,  
  on_selection_change = NULL  
)
```

### Arguments

session	The 'shiny' session object
...	Named arguments where names are component output IDs and values are reactive data frames. Each data frame must contain the shared_id_column. For leaflet maps: can be sf objects (coordinates auto-extracted) or regular data frames with longitude/latitude columns.
shared_id_column	Character string naming the column that contains unique identifiers present in all linked components.
leaflet_lng_col	Character string naming the longitude column for leaflet maps. Defaults to "longitude". For sf objects, this will be the name of the created column.
leaflet_lat_col	Character string naming the latitude column for leaflet maps. Defaults to "latitude". For sf objects, this will be the name of the created column.

**leaflet\_click\_handler**

Optional function that handles leaflet marker clicks. This will be used for both direct clicks and when other components select this marker. Function should accept (map\_proxy, selected\_data, session).

**dt\_click\_handler**

Optional function that handles DT row selections. This will be used for both direct clicks and when other components select this row. Function should accept (dt\_proxy, selected\_data, session).

**on\_selection\_change**

Optional callback function that gets called when selection changes. Function should accept parameters: (selected\_id, selected\_data, source\_component\_id, session)

## Details

This function is the fastest way to get started with linkeR and is ideal for straightforward dashboards.

For more complex applications that use '**shiny**' **Modules**, you should use the more robust pattern of creating a central registry with [create\\_link\\_registry\(\)](#) and passing it to your modules, where you will call [register\\_leaflet\(\)](#) or [register\\_dt\(\)](#) directly. This preserves module encapsulation and leads to more maintainable code. See the [modularized\\_example](#) for a complete example of this pattern.

## Value

Invisibly returns the created registry object

## Examples

```
# This example is for a single-file app.
# For modular apps, please see the "Using linkeR with Modules" vignette.
if (interactive()) {
  library(shiny)
  library(leaflet)
  library(DT)

  # Sample data
  sample_data <- data.frame(
    id = 1:10,
    name = paste("Location", 1:10),
    latitude = runif(10, 40.7, 40.8),
    longitude = runif(10, -111.95, -111.85),
    value = round(runif(10, 100, 1000))
  )

  ui <- fluidPage(
    titlePanel("linkeR Example"),
    fluidRow(
      column(6, leafletOutput("my_map")),
      column(6, DTOutput("my_table"))
    )
  )
}
```

`register_dt`

7

```
)  
)  
  
server <- function(input, output, session) {  
  my_data <- reactive({  
    sample_data  
  })  
  
  output$my_map <- renderLeaflet({  
    leaflet(my_data()) %>%  
    addTiles() %>%  
    addMarkers(  
      lng = ~longitude,  
      lat = ~latitude,  
      layerId = ~id,  
      popup = ~name  
    )  
  })  
  
  output$my_table <- renderDT({  
    datatable(my_data()[, c("name", "value")], selection = "single")  
  })  
  
  link_plots(  
    session,  
    my_map = my_data,  
    my_table = my_data,  
    shared_id_column = "id"  
  )  
}  
  
shinyApp(ui, server)  
}
```

---

`register_dt`

*Register a DT DataTable Component*

---

## Description

`register_dt` registers a DT datatable for linking with other components.

## Usage

```
register_dt(  
  session,  
  registry,  
  dt_output_id,  
  data_reactive,  
  shared_id_column,  
  click_handler = NULL  
)
```

## Arguments

<code>session</code>	'shiny' session object. The session from the module where the DT is used. This could be global session in non-modular apps.
<code>registry</code>	A link registry created by <code>create_link_registry()</code>
<code>dt_output_id</code>	Character string: the outputId of your <code>DT::DTOutput</code>
<code>data_reactive</code>	Reactive expression returning the data frame for the table
<code>shared_id_column</code>	Character string: name of the ID column
<code>click_handler</code>	Optional function: custom click handler for row selection, must have args (map_proxy, selected_data, session), overrides all default behavior

## Value

NULL (invisible). This function is called for its side effects of registering the component.

## Examples

```
# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create a registry
registry <- create_link_registry(session)

# Sample reactive data
my_data <- shiny::reactive({
  data.frame(
    id = 1:5,
    name = c("A", "B", "C", "D", "E"),
    value = 11:15
  )
})

# Register a DT component
register_dt(session, registry, "my_table", my_data, "id")

# Verify registration
print(registry$get_components())
```

## Description

`register_leaflet` registers a Leaflet map for linking with other components.

**Usage**

```
register_leaflet(
  session,
  registry,
  leaflet_output_id,
  data_reactive,
  shared_id_column,
  lng_col = "longitude",
  lat_col = "latitude",
  highlight_zoom = 12,
  click_handler = NULL
)
```

**Arguments**

session	'shiny' session object. The session from the module where the DT is used. This could be global session in non-modular apps.
registry	A link registry created by <a href="#">create_link_registry()</a>
leaflet_output_id	Character string: the outputId of your leafletOutput
data_reactive	Reactive expression returning the data frame for the map
shared_id_column	Character string: name of the ID column
lng_col	Character string: name of longitude column (default: "longitude")
lat_col	Character string: name of latitude column (default: "latitude")
highlight_zoom	Numeric: zoom level when highlighting (default: 12)
click_handler	Optional function: custom click handler for row selection, must have args (map_proxy, selected_data, session), overrides all default behavior

**Value**

No return value, called for side effects.

**Examples**

```
# Create a mock session for the example
session <- shiny::MockShinySession$new()

# Create a registry
registry <- create_link_registry(session)

# Sample reactive data
my_data <- shiny::reactive({
  data.frame(
    id = 1:5,
    name = c("A", "B", "C", "D", "E"),
    longitude = -111.9 + runif(5, -0.1, 0.1),
    latitude = 40 + runif(5, -0.1, 0.1)
  )
})
```

```

        latitude = 40.7 + runif(5, -0.1, 0.1)
    )
})

# Register a leaflet component
register_leaflet(session, registry, "my_map", my_data, "id")

# Verify registration
print(registry$get_components())

```

**setup\_datatable\_observers***Setup DataTable Observers***Description**

**setup\_datatable\_observers** Sets up reactive observers for a DataTable component to handle user interactions and state changes. This function establishes the necessary event handlers for selection changes and synchronizes the component with the shared application state.

**Usage**

```
setup_datatable_observers(
  component_id,
  session,
  components,
  shared_state,
  on_selection_change,
  registry = NULL
)
```

**Arguments**

<code>component_id</code>	Character string. Unique identifier for the DataTable component.
<code>session</code>	'shiny' session object. The current 'shiny' session for reactive context.
<code>components</code>	List. Collection of UI components in the application.
<code>shared_state</code>	Reactive values object. Shared state container for cross-component communication.
<code>on_selection_change</code>	Function. Callback function to execute when table selection changes.
<code>registry</code>	List or NULL. Optional registry for component management. Defaults to NULL.

**Details**

This function creates reactive observers that monitor DataTable interactions and update the shared state accordingly. It handles selection events and ensures proper synchronization between the DataTable component and other application components.

## Value

NULL. This function is called for its side effects of setting up observers.

---

setup\_leaflet\_observers  
*Setup Leaflet Map Observers*

---

## Description

`setup_leaflet_observers` creates two observers for handling Leaflet map interactions in a linked component system. The first observer handles direct marker clicks on the map, while the second observer responds to selection changes from other linked components.

## Usage

```
setup_leaflet_observers(  
  component_id,  
  session,  
  components,  
  shared_state,  
  on_selection_change,  
  registry = NULL  
)
```

## Arguments

component_id	Character string. The unique identifier for the Leaflet component.
session	'shiny' session object for the current user session.
components	List containing component configuration data including data reactivities and shared ID columns.
shared_state	Reactive values object containing selected_id and selection_source for coordinating selections across components.
on_selection_change	Function to call when selection changes (currently unused).
registry	Optional registry object with set_selection method for managing selections. If NULL, falls back to direct shared_state updates.

## Details

The marker click observer:

- Extracts clicked marker ID from the click event
- Retrieves corresponding data row from the component's data
- Clears existing popups and applies click behavior (custom or default)
- Updates selection state through registry or direct shared\_state modification

The selection response observer:

- Only responds to selections from other components (not self-selections)
- Updates the map visualization to reflect the new selection

### **Value**

List containing two observer objects:

observer1	Handles marker click events on the map
observer2	Responds to selection changes from other components

## **update\_dt\_selection      *Update DT Selection Based on Shared ID***

### **Description**

`update_dt_selection` Updates the selection state of a DataTable (DT) component when a shared ID is selected or deselected from another linked component. This function handles both custom click handlers and default selection behavior.

### **Usage**

```
update_dt_selection(component_id, selected_id, session, components)
```

### **Arguments**

component_id	Character string. The ID of the DT component to update.
selected_id	The shared ID value to select. If NULL, deselects all rows.
session	'shiny' session object for the current user session.
components	List containing component configuration information, including data reactivities, shared ID columns, and optional custom click handlers.

### **Details**

The function performs the following steps:

- Validates that the DT package is available
- Retrieves current data from the component's reactive data source
- Validates that the shared ID column exists in the data
- Creates a DT proxy for programmatic table manipulation
- Finds the matching row based on the shared ID
- Executes either custom click handler or default selection behavior

**Value**

NULL (invisible). Function is called for side effects only.

**Custom Click Handlers**

If a custom click handler is provided in the component configuration (`component_info$config$click_handler`), it will be called with the DT proxy, selected data (or NULL for deselection), and session. Otherwise, default row selection/deselection is performed.

---

`update_leaflet_selection`

*Update Leaflet Map Selection*

---

**Description**

`update_leaflet_selection` updates a Leaflet map component to reflect a new selection state. This function handles both selection and deselection events, applying either custom user-defined click handlers or default behaviors.

**Usage**

```
update_leaflet_selection(component_id, selected_id, session, components)
```

**Arguments**

<code>component_id</code>	Character string. The ID of the Leaflet map component to update.
<code>selected_id</code>	Character string or NULL. The ID of the selected item. If NULL, indicates deselection.
<code>session</code>	'shiny' session object. The current 'shiny' session.
<code>components</code>	List. A named list containing component information, where each element contains component configuration including <code>data_reactive</code> , <code>shared_id_column</code> , and <code>config</code> settings.

**Details**

The function performs the following operations:

- Validates that the leaflet package is available
- Checks that required columns (`shared_id_column`, `lng_col`, `lat_col`) exist in the data
- Clears existing popups on the map
- For selections: finds the selected data row and applies either custom click handler or default behavior
- For deselections: delegates to custom handler or performs default cleanup

Required columns in the component data:

- `shared_id_column`: Column containing unique identifiers for map features
- `lng_col`: Column containing longitude coordinates
- `lat_col`: Column containing latitude coordinates

**Value**

NULL (invisibly). The function is called for its side effects on the Leaflet map.

**Note**

If the leaflet package is not available, the function returns early without error. Missing required columns will generate a warning and cause early return.

# Index

apply\_default\_leaflet\_behavior, 2  
create\_link\_registry, 3  
create\_link\_registry(), 6, 8, 9  
DT::DTOutput, 8  
link\_plots, 5  
linkeR-imports, 5  
register\_dt, 7  
register\_dt(), 6  
register\_leaflet, 8  
register\_leaflet(), 6  
setup\_component\_observers(), 4  
setup\_datatable\_observers, 10  
setup\_leaflet\_observers, 11  
update\_dt\_selection, 12  
update\_leaflet\_selection, 13