

# Package ‘mlbplotR’

July 23, 2025

**Type** Package

**Title** Create 'ggplot2' and 'gt' Visuals with Major League Baseball Logos

**Version** 1.1.0

**Description** Tools to help visualize Major League Baseball analysis in 'ggplot2' and 'gt'. You provide team/player information and 'mlbplotR' will transform that information into team colors, logos, or player headshots for graphics.

**URL** <https://github.com/camdenk/mlbplotR>,  
<https://camdenk.github.io/mlbplotR/>

**BugReports** <https://github.com/camdenk/mlbplotR/issues>

**Imports** cli, data.table, ggplot2, gt, lifecycle, magick, magrittr,  
rlang, scales

**Suggests** base64enc, dplyr, ggtext, gridtext, knitr, rsvg, rmarkdown,  
rstudioapi, sjmisc

**Encoding** UTF-8

**License** MIT + file LICENSE

**RoxygenNote** 7.2.3

**Depends** R (>= 3.5.0)

**NeedsCompilation** no

**Author** Sebastian Carl [aut],  
Camden Kay [aut, cre, cph]

**Maintainer** Camden Kay <camden.kay23@gmail.com>

**Repository** CRAN

**Date/Publication** 2023-06-20 04:20:02 UTC

## Contents

clean_team_abbrs . . . . .	2
element . . . . .	3

geom_cap_logos . . . . .	6
geom_from_path . . . . .	10
geom_lines . . . . .	12
geom_mlb_headshots . . . . .	15
geom_mlb_logos . . . . .	18
ggpreview . . . . .	21
gt_fmt_mlb_headshot . . . . .	23
gt_merge_stack_team_color . . . . .	24
gt_mlb . . . . .	25
gt_mlb_column_labels . . . . .	26
load_headshots . . . . .	27
load_mlb_teams . . . . .	28
mlb_player_tiers . . . . .	28
mlb_team_factor . . . . .	31
mlb_team_tiers . . . . .	32
scale_axes_mlb . . . . .	35
scale_mlb . . . . .	37
theme_mlb . . . . .	40
valid_team_names . . . . .	41
<b>Index</b>	<b>43</b>

---

clean_team_abbrs	<i>Standardize MLB Team Abbreviations</i>
------------------	---

---

**Description**

This function standardizes MLB team abbreviations to Baseball Savant defaults. This helps for joins and plotting

**Usage**

```
clean_team_abbrs(abbr, keep_non_matches = TRUE)
```

**Arguments**

- abbr                    a character vector of abbreviations
- keep\_non\_matches       will non-matches be kept in the vector?

**Value**

A character vector with the length of abbr and cleaned team abbreviations if they are included in team\_data. Non matches may be replaced with NA (depending on the value of keep\_non\_matches).

## Examples

```
x <- c("PIE", "STL", "WSN", "CWS", "CHW")
# use current location and keep non matches
clean_team_abbrs(x)
```

---

element

*Theme Elements for Image Grobs*

---

## Description

In conjunction with the [ggplot2::theme](#) system, the following `element_` functions enable images in non-data components of the plot, e.g. axis text.

- `element_mlb_logo()`, `element_mlb_scoreboard_logo()`, `element_mlb_dot_logo()`: draws MLB team logos instead of their abbreviations.
- `element_mlb_dark_cap_logo()` and `element_mlb_light_cap_logo()`: draws MLB team cap logos instead of their abbreviations.
- `element_mlb_headshot()`: draws MLB player headshots instead of their MLB IDs
- `element_path()`: draws images from valid image URLs instead of the URL.

## Usage

```
element_mlb_logo(
  alpha = NULL,
  colour = NA,
  hjust = NULL,
  vjust = NULL,
  color = NULL,
  size = 0.5
)
```

```
element_mlb_scoreboard_logo(
  alpha = NULL,
  colour = NA,
  hjust = NULL,
  vjust = NULL,
  color = NULL,
  size = 0.5
)
```

```
element_mlb_dot_logo(
  alpha = NULL,
  colour = NA,
  hjust = NULL,
  vjust = NULL,
```

```
    color = NULL,  
    size = 0.5  
  )  
  
  element_mlb_dark_cap_logo(  
    alpha = NULL,  
    colour = NA,  
    hjust = NULL,  
    vjust = NULL,  
    color = NULL,  
    size = 0.5  
  )  
  
  element_mlb_light_cap_logo(  
    alpha = NULL,  
    colour = NA,  
    hjust = NULL,  
    vjust = NULL,  
    color = NULL,  
    size = 0.5  
  )  
  
  element_mlb_headshot(  
    alpha = NULL,  
    colour = NA,  
    hjust = NULL,  
    vjust = NULL,  
    color = NULL,  
    size = 0.5  
  )  
  
  element_path(  
    alpha = NULL,  
    colour = NA,  
    hjust = NULL,  
    vjust = NULL,  
    color = NULL,  
    size = 0.5  
  )  
)
```

### Arguments

alpha	The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
colour, color	The image will be colorized with this color. Use the special character "b/w" to set it to black and white. For more information on valid color names in ggplot2 see <a href="https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill">https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill</a> .

<code>hjust, vjust</code>	The horizontal and vertical adjustment respectively. Must be a numerical value between 0 and 1.
<code>size</code>	The output grob size in cm (!).

### Details

The elements translate MLB team abbreviations or MLB player IDs into logo images or headshots, respectively.

### Value

An S3 object of class `element`.

### See Also

[geom\\_mlb\\_logos\(\)](#), [geom\\_mlb\\_headshots\(\)](#), and [geom\\_from\\_path\(\)](#) for more information on valid team abbreviations, player ids, and other parameters.

### Examples

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove league logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AL", "NL", "MLB")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_mlb(type = "secondary") +
  scale_fill_mlb(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_mlb_logo())

# use logos for y-axis
ggplot(df, aes(y = teams, x = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_mlb(type = "secondary") +
  scale_fill_mlb(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.y = element_mlb_logo())

#####
# Headshot Examples
#####
library(mlbplotR)
```

```
library(ggplot2)

dfh <- data.frame(
  random_value = runif(9, 0, 1),
  player_id = c("594798",
                "592450",
                "605141",
                "665742",
                "545361",
                "665487",
                "571448",
                "0",
                "543037")
)

# use headshots for x-axis
ggplot(dfh, aes(x = player_id, y = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.x = element_mlb_headshot())

# use headshots for y-axis
ggplot(dfh, aes(y = player_id, x = random_value)) +
  geom_col(width = 0.5) +
  theme_minimal() +
  theme(axis.text.y = element_mlb_headshot())
```

---

geom\_cap\_logos

ggplot2 Layer for Visualizing MLB Team Cap Logos

---

## Description

`geom_mlb_dark_cap_logos()` and `geom_mlb_dark_cap_logos()` are used to plot MLB team cap and league logos instead of points in a ggplot. It requires x, y aesthetics as well as a valid MLB team abbreviation. The latter can be checked with `valid_team_names()` but is also cleaned before being plotted.

## Usage

```
geom_mlb_dark_cap_logos(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  nudge_x = 0,
  nudge_y = 0,
```

```

    na.rm = FALSE,
    show.legend = FALSE,
    inherit.aes = TRUE
  )

  geom_mlb_light_cap_logos(
    mapping = NULL,
    data = NULL,
    stat = "identity",
    position = "identity",
    ...,
    nudge_x = 0,
    nudge_y = 0,
    na.rm = FALSE,
    show.legend = FALSE,
    inherit.aes = TRUE
  )

```

## Arguments

mapping	Set of aesthetic mappings created by <a href="#">aes()</a> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	<p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot()</a>.</p> <p>A data frame, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify()</a> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a data frame, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p>
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code> ), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to <a href="#">ggplot2::layer()</a> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.
nudge_x, nudge_y	Horizontal and vertical adjustment to nudge labels by. Useful for offsetting text from points, particularly on discrete scales. Cannot be jointly specified with <code>position</code> .
na.rm	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.

<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

## Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

## Aesthetics

`geom_mlb_dark_cap_logos()` and `geom_mlb_dark_cap_logos()` understand the following aesthetics (required aesthetics are in bold):

- **x** - The x-coordinate.
- **y** - The y-coordinate.
- **team\_abbr** - The team abbreviation. Need to use Savant's abbreviation.
- `alpha = NULL` - The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `colour = NULL` - The image will be colourized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>
- `angle = 0` - The angle of the image as a numerical value between 0° and 360°.
- `hjust = 0.5` - The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.
- `vjust = 0.5` - The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.
- `height = 1.0` - The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples). For cap logos, the scaling works better when adjusting height and not width.
- `width = 1.0` - The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.075` (see below examples). For cap logos, the scaling works better when adjusting height and not width.

## Examples

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("NL", "AL", "MLB")]
```



```

df <- data.frame(
  a = rep(1:6, 5),
  b = sort(rep(1:5, 6), decreasing = TRUE),
  teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
# also set a custom fill colour for the non "A" teams
df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all logos
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_dark_cap_logos(aes(team_abbr = teams), height = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_dark_cap_logos(aes(team_abbr = teams, alpha = alpha), height = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_colour_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_light_cap_logos(aes(team_abbr = teams, alpha = alpha, colour = colour), height = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  scale_colour_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_light_cap_logos(aes(team_abbr = teams), height = 0.075, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# it's also possible to plot league logos
league <- data.frame(a = 1:3, b = 0, teams = c("AL", "NL", "MLB"))
ggplot(league, aes(x = a, y = b)) +
  geom_mlb_dark_cap_logos(aes(team_abbr = teams), width = 0.3) +
  geom_label(aes(label = teams), nudge_y = -0.4, alpha = 0.5) +
  coord_cartesian(xlim = c(0.5, 3.5), ylim = c(-0.75, .75)) +
  theme_void()

```

geom\_from\_path

*ggplot2 Layer for Visualizing Images from URLs or Local Paths***Description**

This geom is used to plot MLB images instead of points in a ggplot. It requires x, y aesthetics as well as a path.

**Usage**

```
geom_from_path(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  nudge_x = 0,
  nudge_y = 0,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

**Arguments**

mapping	Set of aesthetic mappings created by <a href="#">aes()</a> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	<p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot()</a>.</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify()</a> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p>
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code> ), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to <a href="#">ggplot2::layer()</a> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.

nudge_x, nudge_y	Horizontal and vertical adjustment to nudge labels by. Useful for offsetting text from points, particularly on discrete scales. Cannot be jointly specified with position.
na.rm	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

## Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

## Aesthetics

`geom_mlb_logos()` understands the following aesthetics (required aesthetics are in bold):

- **x** - The x-coordinate.
- **y** - The y-coordinate.
- **path** - a file path, url, raster object or bitmap array. See `magick::image_read()` for further information.
- `alpha = NULL` - The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `colour = NULL` - The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>
- `angle = 0` - The angle of the image as a numerical value between 0° and 360°.
- `hjust = 0.5` - The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.
- `vjust = 0.5` - The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.
- `width = 1.0` - The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.1` (see below examples).
- `height = 1.0` - The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

## Examples

```
library(mlbplotR)
library(ggplot2)

# create x-y-coordinates of a triangle and add league logo urls
df <- data.frame(
  a = c(sin(2 * pi * (0:4) / 5), 0),
  b = c(cos(2 * pi * (0:4) / 5), 0),
  url = c(
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/virginia.svg",
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/michigan-st.svg",
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/lsu.svg",
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/texas.svg",
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/oregon.svg",
    "https://i.turner.ncaa.com/sites/default/files/images/logos/schools/bgl/james-madison.svg"
  )
)

# plot images directly from url
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15) +
  coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
  theme_void()

# plot images directly from url and apply transparency
ggplot(df, aes(x = a, y = b)) +
  geom_from_path(aes(path = url), width = 0.15, alpha = 0.5) +
  coord_cartesian(xlim = c(-2, 2), ylim = c(-1.3, 1.5)) +
  theme_void()

# It is also possible and recommended to use the underlying Geom inside a
# ggplot2 annotation
ggplot() +
  annotate(
    mlbplotR::GeomFromPath,
    x = 0,
    y = 0,
    path = "https://a.espncdn.com/combiner/i?img=/i/teamlogos/leagues/500/mlb.png",
    width = 0.4
  ) +
  theme_minimal()
```

---

geom\_lines

*ggplot2 Layer for Horizontal and Vertical Reference Lines*

---

## Description

These geoms can be used to draw horizontal or vertical reference lines in a ggplot. They use the data in the aesthetics `v_var` and `h_var` to compute their median or mean and draw the as a line.

**Usage**

```
geom_median_lines(
  mapping = NULL,
  data = NULL,
  ...,
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)

geom_mean_lines(
  mapping = NULL,
  data = NULL,
  ...,
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

**Arguments**

mapping	Set of aesthetic mappings created by <a href="#">aes()</a> .
data	The data to be displayed in this layer. There are three options: If NULL, the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot()</a> . A data.frame, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify()</a> for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a data.frame, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code> ).
...	Other arguments passed on to <a href="#">layer()</a> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired geom/stat.
na.rm	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behavior from the default plot specification.

**Value**

A `ggplot2` layer ([ggplot2::layer\(\)](#)) that can be added to a plot created with [ggplot2::ggplot\(\)](#).

## Aesthetics

`geom_median_lines()` and `geom_mean_lines()` understand the following aesthetics (at least one of the bold aesthetics is required):

- **v\_var** - The variable for which to compute the median/mean that is drawn as vertical line.
- **h\_var** - The variable for which to compute the median/mean that is drawn as horizontal line.
- `alpha = NA` - The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `color = "black"` - The color of the drawn lines.
- `linetype = 2` - The linetype of the drawn lines.
- `linewidth = 0.5` - The size of the drawn lines.

## See Also

The underlying ggplot2 geoms `geom_hline()` and `geom_vline()`

## Examples

```
library(mlbplotR)
library(ggplot2)

# inherit top level aesthetics
ggplot(mtcars, aes(x = disp, y = mpg, h_var = mpg, v_var = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# draw horizontal line only
ggplot(mtcars, aes(x = disp, y = mpg, h_var = mpg)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# draw vertical line only
ggplot(mtcars, aes(x = disp, y = mpg, v_var = disp)) +
  geom_point() +
  geom_median_lines() +
  geom_mean_lines(color = "blue") +
  theme_minimal()

# choose your own value
ggplot(mtcars, aes(x = disp, y = mpg)) +
  geom_point() +
  geom_median_lines(v_var = 400, h_var = 15) +
  geom_mean_lines(v_var = 150, h_var = 30, color = "blue") +
  theme_minimal()
```

---

geom\_mlb\_headshots      *ggplot2 Layer for Visualizing MLB Player Headshots*


---

## Description

This geom is used to plot MLB player headshots instead of points in a ggplot. It requires x, y aesthetics as well as a valid MLBAM id (The same ID associated with their Baseball Savant page).

## Usage

```
geom_mlb_headshots(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  nudge_x = 0,
  nudge_y = 0,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)
```

## Arguments

mapping	Set of aesthetic mappings created by <a href="#">aes()</a> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	<p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot()</a>.</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify()</a> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p>
stat	The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code> ), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to <a href="#">ggplot2::layer()</a> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.

nudge_x, nudge_y	Horizontal and vertical adjustment to nudge labels by. Useful for offsetting text from points, particularly on discrete scales. Cannot be jointly specified with position.
na.rm	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

## Value

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

## Aesthetics

`geom_mlb_headshots()` understands the following aesthetics (required aesthetics are in bold):

- **x** - The x-coordinate.
- **y** - The y-coordinate.
- **player\_id** - The players' MLB (Baseball Savant) id.
- `na_headshot_to_logo = TRUE` - Should NA/non-matches return the MLB logo instead of a grayed out blank headshot? Defaults to TRUE
- `alpha = NULL` - The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `colour = NULL` - The image will be colorized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>
- `angle = 0` - The angle of the image as a numerical value between 0° and 360°.
- `hjust = 0.5` - The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.
- `vjust = 0.5` - The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.
- `width = 1.0` - The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).
- `height = 1.0` - The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).



**Examples**

```

library(mlbplotR)
library(ggplot2)

df <- data.frame(
  a = c(rep(1:3, 3), 1.5, 2.5),
  b = c(sort(rep(1:3, 3), decreasing = TRUE), 2.5, 2.5),
  player_id = c("660670",
                "545361",
                "605141",
                "571448",
                "594798",
                "518692",
                "0",
                "521692",
                "120074",
                "665487",
                "518934"),
  player_name = c("Ronald Acuña Jr.",
                  "Mike Trout",
                  "Mookie Betts",
                  "Nolan Arenado",
                  "Jacob deGrom",
                  "Freddie Freeman",
                  "Non Match",
                  "Salvador Perez",
                  "David Ortiz",
                  "Fernando Tatis Jr.",
                  "DJ LeMahieu")
)

# set a custom fill colour for one player
df$colour <- ifelse(df$a == 2 & df$b == 2, NA, "b/w")

# scatterplot of the headshots
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_headshots(aes(player_id = player_id), height = 0.2) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply alpha as constant and use non default na replacement
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_headshots(aes(player_id = player_id), height = 0.2, alpha = 0.5,
                    na_headshot_to_logo = FALSE) +
  geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +
  coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +
  theme_void()

# apply colour as an aesthetic
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_headshots(aes(player_id = player_id, colour = colour), height = 0.2) +

```

```
geom_label(aes(label = player_name), nudge_y = -0.35, alpha = 0.5) +  
coord_cartesian(xlim = c(0.75, 3.25), ylim = c(0.7, 3.25)) +  
scale_colour_identity() +  
theme_void()
```

---

geom\_mlb\_logos

*ggplot2 Layer for Visualizing MLB Team Logos*

---

## Description

`geom_mlb_logos()`, `geom_mlb_scoreboard_logos()`, and `geom_mlb_dot_logos()` are used to plot MLB team and league logos instead of points in a ggplot. It requires x, y aesthetics as well as a valid MLB team abbreviation. The latter can be checked with `valid_team_names()` but is also cleaned before being plotted.

## Usage

```
geom_mlb_logos(  
  mapping = NULL,  
  data = NULL,  
  stat = "identity",  
  position = "identity",  
  ...,  
  nudge_x = 0,  
  nudge_y = 0,  
  na.rm = FALSE,  
  show.legend = FALSE,  
  inherit.aes = TRUE  
)  
  
geom_mlb_scoreboard_logos(  
  mapping = NULL,  
  data = NULL,  
  stat = "identity",  
  position = "identity",  
  ...,  
  nudge_x = 0,  
  nudge_y = 0,  
  na.rm = FALSE,  
  show.legend = FALSE,  
  inherit.aes = TRUE  
)  
  
geom_mlb_dot_logos(  
  mapping = NULL,
```

```

data = NULL,
stat = "identity",
position = "identity",
...,
nudge_x = 0,
nudge_y = 0,
na.rm = FALSE,
show.legend = FALSE,
inherit.aes = TRUE
)

```

## Arguments

mapping	Set of aesthetic mappings created by <a href="#">aes()</a> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	<p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot()</a>.</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify()</a> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p>
stat	The statistical transformation to use on the data for this layer, either as a <code>ggproto</code> <code>Geom</code> subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")
position	Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code> ), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.
...	Other arguments passed on to <a href="#">ggplot2::layer()</a> . These are often aesthetics, used to set an aesthetic to a fixed value. See the below section "Aesthetics" for a full list of possible arguments.
nudge_x, nudge_y	Horizontal and vertical adjustment to nudge labels by. Useful for offsetting text from points, particularly on discrete scales. Cannot be jointly specified with <code>position</code> .
na.rm	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <a href="#">borders()</a> .

**Value**

A ggplot2 layer (`ggplot2::layer()`) that can be added to a plot created with `ggplot2::ggplot()`.

**Aesthetics**

`geom_mlb_logos()`, `geom_mlb_scoreboard_logos()`, and `geom_mlb_dot_logos()` understand the following aesthetics (required aesthetics are in bold):

- **x** - The x-coordinate.
- **y** - The y-coordinate.
- **team\_abbr** - The team abbreviation. Need to use Savant's abbreviation.
- `alpha = NULL` - The alpha channel, i.e. transparency level, as a numerical value between 0 and 1.
- `colour = NULL` - The image will be colourized with this colour. Use the special character "b/w" to set it to black and white. For more information on valid colour names in ggplot2 see <https://ggplot2.tidyverse.org/articles/ggplot2-specs.html?q=colour#colour-and-fill>
- `angle = 0` - The angle of the image as a numerical value between 0° and 360°.
- `hjust = 0.5` - The horizontal adjustment relative to the given x coordinate. Must be a numerical value between 0 and 1.
- `vjust = 0.5` - The vertical adjustment relative to the given y coordinate. Must be a numerical value between 0 and 1.
- `width = 1.0` - The desired width of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `width = 0.075` (see below examples).
- `height = 1.0` - The desired height of the image in npc (Normalised Parent Coordinates). The default value is set to 1.0 which is *big* but it is necessary because all used values are computed relative to the default. A typical size is `height = 0.1` (see below examples).

**Examples**

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("NL", "AL", "MLB")]

df <- data.frame(
  a = rep(1:6, 5),
  b = sort(rep(1:5, 6), decreasing = TRUE),
  teams = team_abbr
)

# keep alpha == 1 for all teams including an "A"
matches <- grepl("A", team_abbr)
df$alpha <- ifelse(matches, 1, 0.2)
```

```

# also set a custom fill colour for the non "A" teams
df$colour <- ifelse(matches, NA, "gray")

# scatterplot of all logos
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_logos(aes(team_abbr = teams), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# apply alpha via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() to use the alpha
# values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_scoreboard_logos(aes(team_abbr = teams, alpha = alpha), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  theme_void()

# apply alpha and colour via an aesthetic from inside the dataset `df`
# please note that you have to add scale_alpha_identity() as well as
# scale_colour_identity() to use the alpha and colour values in your dataset!
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_logos(aes(team_abbr = teams, alpha = alpha, colour = colour), width = 0.075) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  scale_alpha_identity() +
  scale_colour_identity() +
  theme_void()

# apply alpha as constant for all logos
ggplot(df, aes(x = a, y = b)) +
  geom_mlb_dot_logos(aes(team_abbr = teams), width = 0.075, alpha = 0.6) +
  geom_label(aes(label = teams), nudge_y = -0.35, alpha = 0.5) +
  theme_void()

# it's also possible to plot league logos
league <- data.frame(a = 1:3, b = 0, teams = c("AL", "NL", "MLB"))
ggplot(league, aes(x = a, y = b)) +
  geom_mlb_logos(aes(team_abbr = teams), width = 0.3) +
  geom_label(aes(label = teams), nudge_y = -0.4, alpha = 0.5) +
  coord_cartesian(xlim = c(0.5, 3.5), ylim = c(-0.75, .75)) +
  theme_void()

```

## Description

This function previews a ggplot in its actual dimensions in order to see how it will look when saved. It is also significantly faster than the default preview in RStudio for ggplots created using mlbplotR.

**Usage**

```
ggpreview(
  plot = ggplot2::last_plot(),
  width = NA,
  height = NA,
  asp = NULL,
  dpi = 300,
  device = "png",
  units = c("in", "cm", "mm", "px"),
  scale = 1,
  limitsize = TRUE,
  bg = NULL,
  ...
)
```

**Arguments**

<code>plot</code>	Plot to save, defaults to last plot displayed.
<code>width, height, units</code>	Plot size in units ("in", "cm", "mm", or "px"). If not supplied, uses the size of current graphics device.
<code>asp</code>	The aspect ratio of the plot calculated as width / height. If this is a numeric value (and not NULL) the height of the plot will be recalculated to height = width / asp.
<code>dpi</code>	Plot resolution. Also accepts a string input: "retina" (320), "print" (300), or "screen" (72). Applies only to raster output types.
<code>device</code>	Device to use. Can either be a device function (e.g. <a href="#">png</a> ), or one of "eps", "ps", "tex" (pictex), "pdf", "jpeg", "tiff", "png", "bmp", "svg" or "wmf" (windows only).
<code>scale</code>	Multiplicative scaling factor.
<code>limitsize</code>	When TRUE (the default), ggsave() will not save images larger than 50x50 inches, to prevent the common error of specifying dimensions in pixels.
<code>bg</code>	Background colour. If NULL, uses the plot.background fill value from the plot theme.
<code>...</code>	Other arguments passed on to the graphics device function, as specified by device.

**Value**

No return value, called for side effects.

**Examples**

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
```

```
# remove league logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AL", "NL", "MLB")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

# use logos for x-axis
# note that the plot is assigned to the object "p"
p <- ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_mlb(type = "secondary") +
  scale_fill_mlb(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_mlb_logo())

# preview p with defined width and aspect ratio (only available in RStudio)
if (rstudioapi::isAvailable()){
  ggpreview(p, width = 5, asp = 16/9)
}
```

---

gt\_fmt\_mlb\_headshot      *Render Player Headshots in 'gt' Tables*

---

## Description

gt\_fmt\_mlb\_headshot takes an existing gt\_tbl object and converts player ids into headshots. This is a wrapper around `gtExtras::gt_image_rows()` written by Tom Mock, which is a wrapper around `gt::text_transform()` + `gt::web_image()` / `gt::local_image()` with the necessary boilerplate already applied.

## Usage

```
gt_fmt_mlb_headshot(
  gt_object,
  columns,
  height = 30,
  na_headshot_to_logo = TRUE
)
```

## Arguments

gt_object	An existing gt table object of class gt_tbl
columns	The columns wherein changes to cell data colors should occur. Has no effect if locations is not NULL
height	The absolute height (px) of the image in the table cell

na\_headshot\_to\_logo

should NA/non matches return the MLB logo instead of a grayed out blank headshot? Defaults to TRUE

### Value

An object of class gt\_tbl.

### Examples

```
library(gt)
library(mlbplotR)
gt_headshot_example <- mlbplotR::load_headshots() %>%
  head(5) %>%
  dplyr::select(player_name, savant_id) %>%
  gt::gt() %>%
  gt_fmt_mlb_headshot(columns = "savant_id")
```

---

gt\_merge\_stack\_team\_color

*Merge and stack text from two columns in gt and color one with team colors*

---

### Description

The `gt_merge_stack_team_color()` function takes an existing gt table and merges column 1 and column 2, stacking column 1's text on top of column 2's. Top text is in all caps while the lower text is bigger, bolded, and colored by the team name in another column. This is a slightly modified version of `gtExtras::gt_merge_stack()` written by Tom Mock.

### Usage

```
gt_merge_stack_team_color(
  gt_object,
  col1,
  col2,
  team_col,
  font_sizes = c(12, 14),
  font_weights = c("lighter", "bold"),
  font_variants = c("small-caps"),
  color = "black"
)
```

### Arguments

gt_object	An existing gt table object of class gt_tbl
col1	The column to stack on top.



col2	The column to merge and place below with the text team color that corresponds to team_col.
team_col	The column of team abbreviations (cleaned with <code>clean_team_abbrs()</code> ) that match <code>valid_team_names()</code> for the color of the bottom text.
font_sizes	the font size for the top and bottom text in px. Can be vector of length 1 or 2. Defaults to <code>c(12, 14)</code>
font_weights	the font weight of the top and bottom text. Can be vector of length 1 or 2. Defaults to <code>c("lighter", "bold")</code>
font_variants	the font variant of the top and bottom text. Can be vector of length 1 or 2. Defaults to <code>"small-caps"</code>
color	The color for the top text.

### Value

An object of class `gt_tbl`.

### Examples

```
library(gt)
library(mlbplotR)

gt_merge_example <- mlbplotR::load_mlb_teams() %>%
  dplyr::slice(1:5) %>%
  dplyr::select(team_abbr, team_location, team_mascot) %>%
  gt::gt() %>%
  gt_merge_stack_team_color(col1 = "team_location",
                           col2 = "team_mascot",
                           team_col = "team_abbr")
```

---

gt\_mlb

*Add MLB team logos into rows of a gt table*

---

### Description

The `gt_fmt_mlb_logo`, `gt_fmt_mlb_scoreboard_logo`, and `gt_fmt_mlb_dot_logo` functions take an existing `gt_tbl` object and converts MLB team names from `valid_team_names()` into team logos. This is a wrapper around `gtExtras::gt_image_rows()` written by Tom Mock, which is a wrapper around `gt::text_transform()` + `gt::web_image()` / `gt::local_image()` with the necessary boilerplate already applied.

### Usage

```
gt_fmt_mlb_logo(gt_object, columns, height = 30)

gt_fmt_mlb_scoreboard_logo(gt_object, columns, height = 30)

gt_fmt_mlb_dot_logo(gt_object, columns, height = 30)
```

**Arguments**

gt_object	An existing gt table object of class gt_tbl
columns	The columns wherein changes to cell data colors should occur.
height	The absolute height (px) of the image in the table cell

**Value**

An object of class gt\_tbl.

**Examples**

```
library(gt)
library(mlbplotR)

df <- data.frame(team = valid_team_names()[1:5],
                 logo = valid_team_names()[1:5],
                 scoreboard_logo = valid_team_names()[1:5],
                 dot_logo = valid_team_names()[1:5])

gt_logo_example <- df %>%
  gt::gt() %>%
  gt_fmt_mlb_logo(columns = "logo") %>%
  gt_fmt_mlb_scoreboard_logo(columns = "scoreboard_logo") %>%
  gt_fmt_mlb_dot_logo(columns = "dot_logo")
```

---

gt_mlb_column_labels	<i>Replace Team Abbreviations/Player IDs With Images In Column Labels</i>
----------------------	---

---

**Description**

gt\_column\_example takes in a value of a team abbreviation or player id and converts the designated column to the corresponding image.

**Usage**

```
gt_mlb_column_labels(
  value,
  type = c("mlb_logo", "scoreboard_logo", "headshot"),
  height = 30,
  na_headshot_to_logo = TRUE
)
```

**Arguments**

value	What team abbreviation/player id should be replaced with an image?
type	What type of image is replacing the value?
height	The absolute height (px) of the image
na_headshot_to_logo	should NA/non player id matches return the MLB logo instead of a grayed out blank headshot? Defaults to TRUE

**Value**

HTML tag for image

**Examples**

```
library(gt)
library(mlbplotR)

df <- data.frame(BAL = 1,
                  TEX = 1,
                  "Mike_Trout" = 1,
                  "Shohei_Ohtani" = 1
                  )

gt_column_example <- df %>%
  gt::gt() %>%
  gt::cols_label(BAL = gt_mlb_column_labels("BAL", "mlb_logo"),
                 TEX = gt_mlb_column_labels("TEX", "scoreboard_logo"),
                 "Mike_Trout" = gt_mlb_column_labels(545361, "headshot"),
                 "Shohei_Ohtani" = gt_mlb_column_labels(660271, "headshot"))
```

---

load_headshots	<i>Output MLB Team Abbreviations</i>
----------------	--------------------------------------

---

**Description**

Output MLB Team Abbreviations

**Usage**

```
load_headshots()
```

**Value**

A tibble of player names and ids from various sources.

**Examples**

```
load_headshots()
```

---

load_mlb_teams	<i>Load MLB Team Colors, and Logos</i>
----------------	--

---

**Description**

Loads team colors, and logos - useful for plots!

**Usage**

```
load_mlb_teams()
```

**Value**

A tibble of team-level abbreviations, image URLs, and hex color codes.

**See Also**

Issues with this data should be filed here: <https://github.com/camdenk/mlbplotR>

**Examples**

```
load_mlb_teams()
```

---

mlb_player_tiers	<i>Create MLB Player Tiers</i>
------------------	--------------------------------

---

**Description**

This function sets up a ggplot to visualize MLB player tiers. Adapted from [nflplotR](#)

**Usage**

```
mlb_player_tiers(
  data,
  title = "MLB Player Tiers",
  subtitle = "Created with the #mlbplotR Tiermaker",
  caption = NULL,
  tier_desc = c(`1` = "MVP Candidates", `2` = "Very Good", `3` = "Medium", `4` = "Bad",
    `5` = "Negative WAR", `6` = "", `7` = ""),
  presort = FALSE,
  alpha = 1,
  width = 0.1,
  no_line_below_tier = NULL,
  devel = FALSE,
  background_color = "#1e1e1e",
  line_color = "#e0e0e0",
  title_color = "white",
  subtitle_color = "#8e8e93",
  caption_color = subtitle_color,
  tier_label_color = title_color,
  na_headshot_to_logo = TRUE
)
```

**Arguments**

data	A data frame that has to include the variables <code>tier_no</code> (the number of the tier starting from the top tier no. 1) and <code>player_id</code> (the player's MLBAM/Savant ID). If data includes the variable <code>tier_rank</code> , these ranks will be used within each tier. Otherwise, if <code>presort = FALSE</code> , the function will assume that data is already sorted and if <code>presort = TRUE</code> , teams will be sorted alphabetically within tiers.
title	The title of the plot. If <code>NULL</code> , it will be omitted.
subtitle	The subtitle of the plot. If <code>NULL</code> , it will be omitted.
caption	The caption of the plot. If <code>NULL</code> , it will be omitted.
tier_desc	A named vector consisting of the tier descriptions. The names must equal the tier numbers from <code>tier_no</code>
presort	If <code>FALSE</code> (the default) the function assumes that the teams are already sorted within the tiers. Will otherwise sort alphabetically.
alpha	The alpha channel of the logos, i.e. transparency level, as a numerical value between 0 and 1. Defaults to 1
width	The desired width of the logo in npc (Normalised Parent Coordinates). A typical size is 0.1.
no_line_below_tier	Vector of tier numbers. The function won't draw tier separation lines below these tiers. This is intended to be used for tiers that shall be combined (see examples).

**devel** Determines if headshots shall be rendered. If FALSE (the default), headshots will be rendered on each run. If TRUE the player ids will be plotted instead of the logos. This is much faster and helps with the plot development.

**background\_color** Background color for the plot. Defaults to "#1e1e1e"

**line\_color** Line color for the plot. Defaults to "#e0e0e0"

**title\_color** Text color for the title. Defaults to "white"

**subtitle\_color** Text color the the subtitle. Defaults to "#8e8e93"

**caption\_color** Text color the the caption. Defaults to be equal to the subtitle

**tier\_label\_color** Text color for the tier labels. Defaults to be equal to the title

**na\_headshot\_to\_logo** Should NA/non-matches return the MLB logo instead of a grayed out blank headshot? Defaults to TRUE

### Value

A plot object created with `ggplot2::ggplot()`.

### Examples

```
library(ggplot2)
library(dplyr, warn.conflicts = FALSE)
player_ids <- load_headshots() |>
  head(35) |>
  pull(savant_id)

# Build the player tiers data frame
# This is completely random!
df <- data.frame(
  tier_no = sample(1:5, length(player_ids), replace = TRUE),
  player_id = player_ids
) %>%
  dplyr::group_by(tier_no) %>%
  dplyr::mutate(tier_rank = sample(1:n(), n()))

# Plot player tiers
mlb_player_tiers(df)

# Create a combined tier which is useful for tiers with lots of players that
# should be split up in two or more rows. This is done by setting an empty
# string for the tier 5 description and removing the tier separation line
# below tier number 4.
# This example also shows how to turn off the subtitle and add a caption
mlb_player_tiers(df,
  subtitle = NULL,
  caption = "This is the caption",
  tier_desc = c("1" = "MVP Candidates",
               "2" = "Very Good",
               "3" = "Medium",
```

```

      "4" = "A Combined Tier",
      "5" = ""),
  no_line_below_tier = 4)

# For the development of the tiers, it can be useful to turn off image
# rendering as this can take quite a long time. By setting `devel = TRUE`, the
# headshots are replaced by player ids which is much faster
mlb_player_tiers(df,
  tier_desc = c("1" = "MVP Candidates",
    "2" = "Very Good",
    "3" = "",
    "4" = "A Combined Tier",
    "5" = ""),
  no_line_below_tier = c(2, 4),
  devel = TRUE)

```

mlb\_team\_factor

*Create Ordered MLB Team Factor***Description**

Convert a vector of MLB team abbreviations to an ordered factor by division and team name. Intended to be used for faceted plots where team logos are used in strip texts.

**Usage**

```
mlb_team_factor(teams)
```

**Arguments**

**teams** A vector of MLB team abbreviations that should be included in `valid_team_names()`. The function tries to clean team names internally by calling `clean_team_abbrs()`.

**Value**

Object of class "factor"

**Examples**

```

# unsorted vector including NFL team abbreviations
teams <- c("ATL", "WSH", "MIA", "BAL", "NYY", "BOS", "PHI", "NYM", "TB", "TOR")

# defaults to sort by division and nick name in ascending order
mlb_team_factor(teams)

##### HOW TO USE IN PRACTICE #####

library(ggplot2)

```

```

library(magrittr)
# load some sample data from the ggplot2 package
plot_data <- mpg
# add a new column by randomly sampling the above defined teams vector
plot_data$team <- sample(teams, nrow(mpg), replace = TRUE)

# Now we plot the data and facet by team abbreviation. ggplot automatically
# converts the team names to a factor and sorts it alphabetically
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~team, ncol = 5) +
  theme_minimal()

# We'll change the order of facets by making another team name column and
# converting it to an ordered factor. Again, this defaults to sort by division,
# league, and location in ascending order.
plot_data$ordered_team <- sample(teams, nrow(mpg), replace = TRUE) %>%
  mlb_team_factor()

# Let's check how the facets are ordered now.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 5) +
  theme_minimal()

# The facet order looks weird because the defaults is meant to be used with
# MLB team logos. So let's use the actual logos and look at the result.
ggplot(plot_data, aes(displ, hwy)) +
  geom_point() +
  facet_wrap(~ordered_team, ncol = 5) +
  theme_minimal() +
  theme(strip.text = element_mlb_logo(size = .85))

```

---

mlb\_team\_tiers

---

*Create MLB Team Tiers*


---

## Description

This function sets up a ggplot to visualize MLB team tiers. Adapted from [nflplotR](#)

## Usage

```

mlb_team_tiers(
  data,
  title = "MLB Team Tiers",
  subtitle = "Created with the #mlbplotR Tiermaker",
  caption = NULL,
  tier_desc = c(`1` = "World Series", `2` = "Very Good", `3` = "Medium", `4` = "Bad", `5`

```



```

    = "Tankathon", `6` = "", `7` = ""),
  presort = FALSE,
  alpha = 1,
  width = 0.075,
  no_line_below_tier = NULL,
  devel = FALSE,
  background_color = "#1e1e1e",
  line_color = "#e0e0e0",
  title_color = "white",
  subtitle_color = "#8e8e93",
  caption_color = subtitle_color,
  tier_label_color = title_color,
  logo_type = "main"
)

```

## Arguments

data	A data frame that has to include the variables tier_no (the number of the tier starting from the top tier no. 1) and team_abbr (the team abbreviation). team_abbr should be one of <a href="#">valid_team_names()</a> and the function tries to clean team names internally by calling <a href="#">clean_team_abbrs()</a> . If data includes the variable tier_rank, these ranks will be used within each tier. Otherwise, if presort = FALSE, the function will assume that data is already sorted and if presort = TRUE, teams will be sorted alphabetically within tiers.
title	The title of the plot. If NULL, it will be omitted.
subtitle	The subtitle of the plot. If NULL, it will be omitted.
caption	The caption of the plot. If NULL, it will be omitted.
tier_desc	A named vector consisting of the tier descriptions. The names must equal the tier numbers from tier_no
presort	If FALSE (the default) the function assumes that the teams are already sorted within the tiers. Will otherwise sort alphabetically.
alpha	The alpha channel of the logos, i.e. transparency level, as a numerical value between 0 and 1. Defaults to 1
width	The desired width of the logo in npc (Normalised Parent Coordinates). A typical size is 0.075.
no_line_below_tier	Vector of tier numbers. The function won't draw tier separation lines below these tiers. This is intended to be used for tiers that shall be combined (see examples).
devel	Determines if logos shall be rendered. If FALSE (the default), logos will be rendered on each run. If TRUE the team abbreviations will be plotted instead of the logos. This is much faster and helps with the plot development.
background_color	Background color for the plot. Defaults to "#1e1e1e"
line_color	Line color for the plot. Defaults to "#e0e0e0"
title_color	Text color for the title. Defaults to "white"

subtitle\_color Text color the the subtitle. Defaults to "#8e8e93"  
 caption\_color Text color the the caption. Defaults to be equal to the subtitle  
 tier\_label\_color  
                     Text color for the tier labels. Defaults to be equal to the title  
 logo\_type           What logo should be used for each team ("main", "scoreboard", or "dot")? Defaults to "main"

## Value

A plot object created with `ggplot2::ggplot()`.

## Examples

```

library(ggplot2)
library(dplyr, warn.conflicts = FALSE)
teams <- valid_team_names()
# remove conference logos from this example
teams <- teams[!teams %in% c("AL", "NL", "MLB")]

# Build the team tiers data frame
# This is completely random!
df <- data.frame(
  tier_no = sample(1:5, length(teams), replace = TRUE),
  team_abbr = teams
) %>%
  dplyr::group_by(tier_no) %>%
  dplyr::mutate(tier_rank = sample(1:n(), n()))

# Plot team tiers
mlb_team_tiers(df)

# Create a combined tier which is useful for tiers with lots of teams that
# should be split up in two or more rows. This is done by setting an empty
# string for the tier 5 description and removing the tier separation line
# below tier number 4.
# This example also shows how to turn off the subtitle and add a caption
mlb_team_tiers(df,
  subtitle = NULL,
  caption = "This is the caption",
  tier_desc = c("1" = "World Series",
               "2" = "Very Good",
               "3" = "Medium",
               "4" = "A Combined Tier",
               "5" = ""),
  no_line_below_tier = 4)

# For the development of the tiers, it can be useful to turn off logo image
# rendering as this can take quite a long time. By setting `devel = TRUE`, the
# logo images are replaced by team abbreviations which is much faster
mlb_team_tiers(df,
  tier_desc = c("1" = "World Series",

```

```

      "2" = "Very Good",
      "3" = "",
      "4" = "A Combined Tier",
      "5" = ""),
  no_line_below_tier = c(2, 4),
  devel = TRUE)

```

---

scale\_axes\_mlb

*Axis Scales for MLB Team Logos*


---

## Description

**[Superseded]** `scale_x_mlb()` and `scale_y_mlb()` have been superseded in favor of `element_*_logo()` functions. These functions map MLB team names to their team logos and make them available as axis labels.

## Usage

```

scale_x_mlb(
  ...,
  expand = ggplot2::waiver(),
  guide = ggplot2::waiver(),
  position = "bottom",
  size = 12
)

scale_y_mlb(
  ...,
  expand = ggplot2::waiver(),
  guide = ggplot2::waiver(),
  position = "left",
  size = 12
)

```

## Arguments

... Arguments passed on to [discrete\\_scale](#)

palette A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., [scales::hue\\_pal\(\)](#)).

breaks One of:

- NULL for no breaks
- `waiver()` for the default breaks (the scale limits)
- A character vector of breaks
- A function that takes the limits as input and returns breaks as output. Also accepts rlang [lambda](#) function notation.

	<p><b>limits</b> One of:</p> <ul style="list-style-type: none"> <li>• NULL to use the default scale values</li> <li>• A character vector that defines possible values of the scale and their order</li> <li>• A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang <a href="#">lambda</a> function notation.</li> </ul> <p><b>drop</b> Should unused factor levels be omitted from the scale? The default, TRUE, uses the levels that appear in the data; FALSE uses all the levels in the factor.</p> <p><b>na.translate</b> Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify <code>na.translate = FALSE</code>.</p> <p><b>na.value</b> If <code>na.translate = TRUE</code>, what aesthetic value should the missing values be displayed as? Does not apply to position scales where NA is always placed at the far right.</p> <p><b>aesthetics</b> The names of the aesthetics that this scale works with.</p> <p><b>scale_name</b> The name of the scale that should be used for error messages associated with this scale.</p> <p><b>name</b> The name of the scale. Used as the axis or legend title. If <code>waiver()</code>, the default, the name of the scale is taken from the first mapping used for that aesthetic. If NULL, the legend title will be omitted.</p> <p><b>labels</b> One of:</p> <ul style="list-style-type: none"> <li>• NULL for no labels</li> <li>• <code>waiver()</code> for the default labels computed by the transformation object</li> <li>• A character vector giving labels (must be same length as breaks)</li> <li>• An expression vector (must be the same length as breaks). See <code>?plot-math</code> for details.</li> <li>• A function that takes the breaks as input and returns labels as output. Also accepts rlang <a href="#">lambda</a> function notation.</li> </ul> <p><b>super</b> The super class to use for the constructed scale</p>
expand	For position scales, a vector of range expansion constants used to add some padding around the data to ensure that they are placed some distance away from the axes. Use the convenience function <a href="#">expansion()</a> to generate the values for the expand argument. The defaults are to expand the scale by 5% on each side for continuous variables, and by 0.6 units on each side for discrete variables.
guide	A function used to create a guide or its name. See <a href="#">guides()</a> for more information.
position	For position scales, The position of the axis. <code>left</code> or <code>right</code> for y axes, <code>top</code> or <code>bottom</code> for x axes.
size	The logo size in pixels. It is applied as height for an x-scale and as width for an y-scale.

## Details

The scale translates MLB team abbreviations into raw image html and places the html as axis labels. Because of the way ggplots are constructed, it is necessary to adjust the [theme\(\)](#) after calling this

scale. This can be done by calling `theme_x_mlb()` or `theme_y_mlb()` or alternatively by manually changing the relevant axis.text to `ggtext::element_markdown()`. However, this will only work if an underlying dependency, "gridtext", is installed with a newer version than 0.1.4

### Value

A discrete ggplot2 scale created with `ggplot2::scale_x_discrete()` or `ggplot2::scale_y_discrete()`.

### Examples

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove league logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AL", "NL", "MLB")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)

if (utils::packageVersion("gridtext") > "0.1.4"){
  # use logos for x-axis
  ggplot(df, aes(x = teams, y = random_value)) +
    geom_col(aes(color = teams, fill = teams), width = 0.5) +
    scale_color_mlb(type = "secondary") +
    scale_fill_mlb(alpha = 0.4) +
    scale_x_mlb() +
    theme_minimal() +
    # theme*_mlb requires gridtext version > 0.1.4
    theme_x_mlb()

  # use logos for y-axis
  ggplot(df, aes(y = teams, x = random_value)) +
    geom_col(aes(color = teams, fill = teams), width = 0.5) +
    scale_color_mlb(type = "secondary") +
    scale_fill_mlb(alpha = 0.4) +
    scale_y_mlb() +
    theme_minimal() +
    # theme*_mlb requires gridtext version > 0.1.4
    theme_y_mlb()
}
```

---

scale\_mlb

*Scales for MLB Team Colors*

---

### Description

These functions map MLB team names to their team colors in color and fill aesthetics

**Usage**

```

scale_color_mlb(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)

scale_colour_mlb(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "colour",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)

scale_fill_mlb(
  type = c("primary", "secondary"),
  values = NULL,
  ...,
  aesthetics = "fill",
  breaks = ggplot2::waiver(),
  na.value = "grey50",
  guide = NULL,
  alpha = NA
)

```

**Arguments**

<code>type</code>	One of "primary" or "secondary" to decide which colortype to use.
<code>values</code>	If NULL (the default) use the internal team color vectors. Otherwise a set of aesthetic values to map data values to. The values will be matched in order (usually alphabetical) with the limits of the scale, or with breaks if provided. If this is a named vector, then the values will be matched based on the names instead. Data values that don't match will be given <code>na.value</code> .
<code>...</code>	Arguments passed on to <a href="#">discrete_scale</a>
	<code>palette</code> A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., <a href="#">scales::hue_pal()</a> ).
	<code>limits</code> One of:

	<ul style="list-style-type: none"> <li>• NULL to use the default scale values</li> <li>• A character vector that defines possible values of the scale and their order</li> <li>• A function that accepts the existing (automatic) values and returns new ones. Also accepts rlang <a href="#">lambda</a> function notation.</li> </ul>
	<p>drop Should unused factor levels be omitted from the scale? The default, TRUE, uses the levels that appear in the data; FALSE uses all the levels in the factor.</p> <p>na.translate Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify <code>na.translate = FALSE</code>.</p> <p>scale_name The name of the scale that should be used for error messages associated with this scale.</p> <p>name The name of the scale. Used as the axis or legend title. If <code>waiver()</code>, the default, the name of the scale is taken from the first mapping used for that aesthetic. If NULL, the legend title will be omitted.</p> <p>labels One of:</p> <ul style="list-style-type: none"> <li>• NULL for no labels</li> <li>• <code>waiver()</code> for the default labels computed by the transformation object</li> <li>• A character vector giving labels (must be same length as breaks)</li> <li>• An expression vector (must be the same length as breaks). See <code>?plot-math</code> for details.</li> <li>• A function that takes the breaks as input and returns labels as output. Also accepts rlang <a href="#">lambda</a> function notation.</li> </ul> <p>guide A function used to create a guide or its name. See <a href="#">guides()</a> for more information.</p> <p>super The super class to use for the constructed scale</p>
aesthetics	Character string or vector of character strings listing the name(s) of the aesthetic(s) that this scale works with. This can be useful, for example, to apply colour settings to the colour and fill aesthetics at the same time, via <code>aesthetics = c("colour", "fill")</code> .
breaks	<p>One of:</p> <ul style="list-style-type: none"> <li>• NULL for no breaks</li> <li>• <code>waiver()</code> for the default breaks (the scale limits)</li> <li>• A character vector of breaks</li> <li>• A function that takes the limits as input and returns breaks as output</li> </ul>
na.value	The aesthetic value to use for missing (NA) values
guide	A function used to create a guide or its name. If NULL (the default) no guide will be plotted for this scale. See <a href="#">ggplot2::guides()</a> for more information.
alpha	Factor to modify color transparency via a call to <a href="#">scales::alpha()</a> . If NA (the default) no transparency will be applied. Can also be a vector of alphas. All alpha levels must be in range $[0, 1]$ .

## Value

A discrete ggplot2 scale created with [ggplot2::scale\\_color\\_manual\(\)](#) or [ggplot2::scale\\_fill\\_manual\(\)](#).

## Examples

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove league logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AL", "NL", "MLB")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)
ggplot(df, aes(x = teams, y = random_value)) +
  geom_col(aes(color = teams, fill = teams), width = 0.5) +
  scale_color_mlb(type = "secondary") +
  scale_fill_mlb(alpha = 0.4) +
  theme_minimal() +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

---

 theme\_mlb

*Theme for MLB Team Logos*


---

## Description

**[Superseded]** `theme_x_mlb()` and `theme_y_mlb()` have been superseded in favor of `element_*_logo()` functions. These functions are convenience wrappers around a theme call that activates markdown in x-axis and y-axis labels using `ggtext::element_markdown()`.

## Usage

```
theme_x_mlb()
```

```
theme_y_mlb()
```

## Details

These functions are a wrapper around the function calls `ggplot2::theme(axis.text.x = ggtext::element_markdown())` as well as `ggplot2::theme(axis.text.y = ggtext::element_markdown())`. They are made to be used in conjunction with `scale_x_mlb()` and `scale_y_mlb()` respectively.

## Value

A ggplot2 theme created with `ggplot2::theme()`.

## See Also

`theme_x_mlb()`, `theme_y_mlb()`



## Examples

```
library(mlbplotR)
library(ggplot2)

team_abbr <- valid_team_names()
# remove conference logos from this example
team_abbr <- team_abbr[!team_abbr %in% c("AL", "NL", "MLB")]

df <- data.frame(
  random_value = runif(length(team_abbr), 0, 1),
  teams = team_abbr
)
if (utils::packageVersion("gridtext") > "0.1.4"){
  ggplot(df, aes(x = teams, y = random_value)) +
    geom_col(aes(color = teams, fill = teams), width = 0.5) +
    scale_color_mlb(type = "secondary") +
    scale_fill_mlb(alpha = 0.4) +
    scale_x_mlb() +
    theme_minimal() +
    # theme_*_mlb requires gridtext version > 0.1.4
    theme_x_mlb()
}
```

---

valid\_team\_names

*Output Valid MLB Team Abbreviations*

---

## Description

Output Valid MLB Team Abbreviations

## Usage

```
valid_team_names(remove_league_info = FALSE)
```

## Arguments

remove\_league\_info

Should "AL", "NL", and "MLB" be removed from the returned vector? Defaults to FALSE.

## Value

A vector of type "character".

**Examples**

```
# List valid team abbreviations excluding duplicates
valid_team_names()
valid_team_names(TRUE)
```

# Index

`aes()`, 7, 10, 13, 15, 19

`borders()`, 8, 11, 16, 19

`clean_team_abbrs`, 2

`clean_team_abbrs()`, 31, 33

`discrete_scale`, 35, 38

`element`, 3

`element_mlb_dark_cap_logo` (`element`), 3

`element_mlb_dot_logo` (`element`), 3

`element_mlb_headshot` (`element`), 3

`element_mlb_light_cap_logo` (`element`), 3

`element_mlb_logo` (`element`), 3

`element_mlb_scoreboard_logo` (`element`), 3

`element_path` (`element`), 3

`expansion()`, 36

`fortify()`, 7, 10, 13, 15, 19

`geom_cap_logos`, 6

`geom_from_path`, 10

`geom_from_path()`, 5

`geom_hline()`, 14

`geom_lines`, 12

`geom_mean_lines` (`geom_lines`), 12

`geom_median_lines` (`geom_lines`), 12

`geom_mlb_dark_cap_logos` (`geom_cap_logos`), 6

`geom_mlb_dot_logos` (`geom_mlb_logos`), 18

`geom_mlb_headshots`, 15

`geom_mlb_headshots()`, 5

`geom_mlb_light_cap_logos` (`geom_cap_logos`), 6

`geom_mlb_logos`, 18

`geom_mlb_logos()`, 5

`geom_mlb_scoreboard_logos` (`geom_mlb_logos`), 18

`geom_vline()`, 14

`ggplot()`, 7, 10, 13, 15, 19

`ggplot2::ggplot()`, 8, 11, 13, 16, 20, 30, 34

`ggplot2::guides()`, 39

`ggplot2::layer()`, 7, 8, 10, 11, 13, 15, 16, 19, 20

`ggplot2::scale_color_manual()`, 39

`ggplot2::scale_fill_manual()`, 39

`ggplot2::scale_x_discrete()`, 37

`ggplot2::scale_y_discrete()`, 37

`ggplot2::theme`, 3

`ggplot2::theme()`, 40

`ggpreview`, 21

`ggtext::element_markdown()`, 37, 40

`gt_fmt_mlb_dot_logo` (`gt_mlb`), 25

`gt_fmt_mlb_headshot`, 23

`gt_fmt_mlb_logo` (`gt_mlb`), 25

`gt_fmt_mlb_scoreboard_logo` (`gt_mlb`), 25

`gt_merge_stack_team_color`, 24

`gt_mlb`, 25

`gt_mlb_column_labels`, 26

`guides()`, 36, 39

`lambda`, 35, 36, 39

`layer()`, 13

`load_headshots`, 27

`load_mlb_teams`, 28

`magick::image_read()`, 11

`mlb_player_tiers`, 28

`mlb_team_factor`, 31

`mlb_team_tiers`, 32

`png`, 22

`scale_axes_mlb`, 35

`scale_color_mlb` (`scale_mlb`), 37

`scale_colour_mlb` (`scale_mlb`), 37

`scale_fill_mlb` (`scale_mlb`), 37

`scale_mlb`, 37

`scale_x_mlb` (`scale_axes_mlb`), 35

`scale_x_mlb()`, 40

`scale_y_mlb(scale_axes_mlb)`, 35  
`scale_y_mlb()`, 40  
`scales::alpha()`, 39  
`scales::hue_pal()`, 35, 38  
  
`theme()`, 36  
`theme_mlb`, 40  
`theme_x_mlb(theme_mlb)`, 40  
`theme_x_mlb()`, 37, 40  
`theme_y_mlb(theme_mlb)`, 40  
`theme_y_mlb()`, 37, 40  
  
`valid_team_names`, 41  
`valid_team_names()`, 6, 18, 31, 33