

Package ‘ohoegdm’

July 22, 2025

Title Ordinal Higher-Order Exploratory General Diagnostic Model for
Polytomous Data

Version 0.1.0

Description Perform a Bayesian estimation of the ordinal exploratory
Higher-order General Diagnostic Model (OHOEGDM) for Polytomous Data
described by Culpepper, S. A. and Bala-
muta, J. J. (In Press) <[doi:10.1080/00273171.2021.1985949](https://doi.org/10.1080/00273171.2021.1985949)>.

URL <https://github.com/tmsalab/ohoegdm>,
<https://tmsalab.github.io/ohoegdm/>

BugReports <https://github.com/tmsalab/ohoegdm/issues>

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 7.1.2

LinkingTo Rcpp, RcppArmadillo

Imports Rcpp

Suggests edmdata, covr

NeedsCompilation yes

Author Steven Andrew Culpepper [aut, cph] (ORCID:
<<https://orcid.org/0000-0003-4226-6176>>),
James Joseph Balamuta [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-2826-8458>>)

Maintainer James Joseph Balamuta <balamut2@illinois.edu>

Repository CRAN

Date/Publication 2022-02-24 09:30:02 UTC

Contents

GenerateAtable	2
gen_bijectionvector	2
ohoegdm	3
sim_slcm	7

GenerateAtable	<i>Generate tables that store different design elements</i>
----------------	---

Description

Each table provides a "cache" of pre-computed values.

Usage

GenerateAtable(nClass, K, M, order)

Arguments

- nClass Number of Attribute Classes
- K Number of Attributes
- M Number of Responses
- order Highest interaction order to consider. Default model-specified k.

Details

This is **an internal function** briefly used to simulate data and, thus, has been exported into *R* as well as documented. **Output from this function can change in future versions.**

Value

Return a list containing the table caches for different parameters

gen_bijectionvector	<i>Generate a vector to map polytomous vector to integers</i>
---------------------	---

Description

Converts class into a bijection to integers

Usage

gen_bijectionvector(K, M)

Arguments

- K Number of Attributes
- M Number of Response Categories

Value

Return a *K*-length vector containing the bijection vector.

ohoegdm

Ordinal Higher-Order General Diagnostic Model under the Exploratory Framework (OHOEGDM)

Description

Performs the Gibbs sampling routine for an ordinal higher-order EGDM.

Usage

```
ohoegdm(
  y,
  k,
  m = 2,
  order = k,
  sd_mh = 0.4,
  burnin = 1000L,
  chain_length = 10000L,
  l0 = c(1, rep(100, sum(choose(k, seq_len(order))))),
  l1 = c(1, rep(1, sum(choose(k, seq_len(order))))),
  m0 = 0,
  bq = 1
)
```

Arguments

y	Ordinal Item Matrix
k	Dimension to estimate for Q matrix
m	Number of Item Categories. Default is 2 matching the binary case.
order	Highest interaction order to consider. Default model-specified k.
sd_mh	Metropolis-Hastings standard deviation tuning parameter.
burnin	Amount of Draws to Burn
chain_length	Number of Iterations for chain.
l0	Spike parameter. Default 1 for intercept and 100 coefficients
l1	Slab parameter. Default 1 for all values.
m0, bq	Additional tuning parameters.

Details

The estimates list contains the mean information from the sampling procedure. Meanwhile, the chain list contains full MCMC values. Moreover, the details list provides information regarding the estimation call. Lastly, the recovery list stores values that can be used when assessing the method under a simulation study.

Value

A ohoegdm object containing four named lists:

- estimates: Averaged chain iterations
 - thetas: Average theta coefficients
 - betas: Average beta coefficients
 - deltas: Average activeness of coefficients
 - classes: Average class membership
 - m21ls: Average negative two times log-likelihood
 - omegas: Average omega
 - kappas : Average category threshold parameter
 - taus: Average K -vectors of factor intercept
 - lambdas: Average K -vectors of factor loadings
 - guessing: Average guessing item parameter
 - slipping: Average slipping item parameter
 - QS: Average activeness of Q matrix entries
- chain: Chain iterations from the underlying C++ routine.
 - thetas: Theta coefficients iterations
 - betas: Beta coefficients iterations
 - deltas: Activeness of coefficients iterations
 - classes: Class membership iterations
 - m21ls: Negative two times log-likelihood iterations
 - omegas: Omega iterations
 - kappas : Category threshold parameter iterations
 - taus: K -vector of factor intercept iterations
 - lambdas: K -vector of factor loadings iterations
 - guessing: Guessing item parameter iterations
 - slipping: Slipping item parameter iterations
- details: Properties used to estimate the model
 - n: Number of Subjects
 - j: Number of Items
 - k: Number of Traits
 - m: Number of Item Categories.
 - order: Highest interaction order to consider. Default model-specified k.
 - sd_mh: Metropolis-Hastings standard deviation tuning parameter.
 - l0: Spike parameter
 - l1: Slab parameter
 - m0, bq: Additional tuning parameters
 - burnin: Number of Iterations to discard
 - chain_length: Number of Iterations to keep
 - runtime: Elapsed time algorithm run time in the C++ code.
- recovery: Assess recovery metrics under a simulation study.
 - Q_item_encoded: Per-iteration item encodings from Q matrix.
 - MHsum: Average acceptance from metropolis hastings sampler

Examples

```

# Simulation Study
if (requireNamespace("edmdata", quietly = TRUE)) {
  # Q and Beta Design ----

  # Obtain the full K3 Q matrix from edmdata
  data("qmatrix_oracle_k3_j20", package = "edmdata")
  Q_full = qmatrix_oracle_k3_j20

  # Retain only a subset of the original Q matrix
  removal_idx = -c(3, 5, 9, 12, 15, 18, 19, 20)
  Q = Q_full[removal_idx, ]

  # Construct the beta matrix by-hand
  beta = matrix(0, 20, ncol = 8)

  # Intercept
  beta[, 1] = 1

  # Main effects
  beta[1:3, 2] = 1.5
  beta[4:6, 3] = 1.5
  beta[7:9, 5] = 1.5

  # Setup two-way effects
  beta[10, c(2, 3)] = 1
  beta[11, c(3, 4)] = 1

  beta[12, c(2, 5)] = 1
  beta[13, c(2, 5)] = 1
  beta[14, c(2, 6)] = 1

  beta[15, c(3, 5)] = 1
  beta[16, c(3, 5)] = 1
  beta[17, c(3, 7)] = 1

  # Setup three-way effects
  beta[18:20, c(2, 3, 5)] = 0.75

  # Decrease the number of Beta rows
  beta = beta[removal_idx,]

  # Construct additional parameters for data simulation
  Kappa = matrix(c(0, 1, 2), nrow = 20, ncol = 3, byrow = TRUE) # mkappa
  lambda = c(0.25, 1.5, -1.25) # mlambdas
  tau = c(0, -0.5, 0.5) # mtaus

  # Simulation conditions ----
  N = 100      # Number of Observations
  J = nrow(beta) # Number of Items
  M = 4        # Number of Response Categories

```

```

Malpha = 2      # Number of Classes
K = ncol(Q)     # Number of Attributes
order = K       # Highest interaction to consider
sdmtheta = 1    # Standard deviation for theta values

# Simulate data ----

# Generate theta values
theta = rnorm(N, sd = sdmtheta)

# Generate alphas
Zs = matrix(1, N, 1) %*% tau +
      matrix(theta, N, 1) %*% lambda +
      matrix(rnorm(N * K), N, K)
Alphas = 1 * (Zs > 0)

vv = gen_bijectionvector(K, Malpha)
CLs = Alphas %*% vv
Atab = GenerateAtable(Malphi ^ K, K, Malphi, order)$Atable

# Simulate item-level data
Ysim = sim_slcm(N, J, M, Malphi ^ K, CLs, Atab, beta, Kappa)

# Establish chain properties
# Standard Deviation of MH. Set depending on sample size.
# If sample size is:
# - small, allow for larger standard deviation
# - large, allow for smaller standard deviation.
sd_mh = .4
burnin = 50      # Set for demonstration purposes, increase to at least 5,000 in practice.
chain_length = 100 # Set for demonstration purposes, increase to at least 40,000 in practice.

# Setup spike-slab parameters
l0s = c(1, rep(100, Malphi ^ K - 1))
l1s = c(1, rep(1, Malphi ^ K - 1))

my_model = ohoegdm::ohoegdm(
  y = Ysim,
  k = K,
  m = M,
  order = order,
  l0 = l0s,
  l1 = l1s,
  m0 = 0,
  bq = 1,
  sd_mh = sd_mh,
  burnin = burnin,
  chain_length = chain_length
)
}

```

sim_slcm

*Simulate Ordinal Item Data from a Sparse Latent Class Model***Description**

Simulate Ordinal Item Data from a Sparse Latent Class Model

Usage

```
sim_slcm(N, J, M, nClass, CLASS, Atable, BETA, KAPPA)
```

Arguments

N	Number of Observations
J	Number of Items
M	Number of Item Categories (2, 3, ..., M)
nClass	Number of Latent Classes
CLASS	A vector of N observations containing the class ID of the subject.
Atable	A matrix of dimensions $M^K \times M^O$ containing the attribute classes in bijection-form. Note, O refers to the model's highest interaction order.
BETA	A matrix of dimensions $J \times M^K$ containing the coefficients of the reparameterized β matrix.
KAPPA	A matrix of dimensions $J \times M$ containing the category threshold parameters

Value

An ordinal item matrix of dimensions $N \times J$ with M response levels.

See Also

[ohoegdm](#)

Index

`gen_bijectionvector`, [2](#)

`GenerateAtable`, [2](#)

`ohoegdm`, [3](#), [7](#)

`sim_slcm`, [7](#)