

Package ‘smoothHR’

July 23, 2025

Encoding UTF-8

Type Package

Version 1.0.5

Date 2024-02-25

Title Smooth Hazard Ratio Curves Taking a Reference Value

Depends R (>= 2.12.0), survival, splines

Description Provides flexible hazard ratio curves allowing non-linear relationships between continuous predictors and survival. To better understand the effects that each continuous covariate has on the outcome, results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. Confidence bands for these curves are also derived.

License GPL-3

URL <https://github.com/arturstat/smoothHR>

BugReports <https://github.com/arturstat/smoothHR/issues>

LazyLoad yes

LazyData yes

NeedsCompilation no

Author Artur Araujo [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-1419-4208>>),
Luis Meira-Machado [aut] (ORCID:
<<https://orcid.org/0000-0002-8577-7665>>)

Maintainer Artur Araujo <artur.stat@gmail.com>

Repository CRAN

Date/Publication 2024-02-25 18:40:02 UTC

Contents

| | |
|----------------------------|---|
| smoothHR-package | 2 |
| dfmacox | 3 |

| | |
|----------------------|-----------|
| plot.HR | 5 |
| predict.HR | 7 |
| print.HR | 8 |
| smoothHR | 9 |
| whas500 | 11 |
| Index | 12 |

| | |
|------------------|--|
| smoothHR-package | <i>Smooth Hazard Ratio Curves Taking a Reference Value</i> |
|------------------|--|

Description

Provides flexible hazard ratio curves allowing non-linear relationships between continuous predictors and survival. To better understand the effects that each continuous covariate has on the outcome, results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. Confidence bands for these curves are also derived.

Details

| | |
|-----------|------------|
| Package: | smoothHR |
| Type: | Package |
| Version: | 1.0.5 |
| Date: | 2024-02-25 |
| License: | GPL-3 |
| LazyLoad: | yes |
| LazyData: | yes |

Author(s)

Artur Araújo and Luís Meira-Machado <lmachado@math.uminho.pt>
Maintainer: Artur Araújo <artur.stat@gmail.com>

References

Cadarso-Suarez, C. and Meira-Machado, L. and Kneib, T. and Gude, F. (2010). Flexible hazard ratio curves for continuous predictors in multi-state models: an application to breast cancer data. *Statistical Modelling*, **10**(3), 291-314. doi:[10.1177/1471082X0801000303](https://doi.org/10.1177/1471082X0801000303)

Eilers, Paul H. and Marx, Brian D. (1996). Flexible smoothing with B-splines and penalties. *Statistical Science*, **11**(2), 89-121. doi:[10.1214/ss/1038425655](https://doi.org/10.1214/ss/1038425655)

Hosmer, D. W. and Lemeshow, S. and May, S. (2008). *Applied Survival Analysis: Regression Modeling of Time to Event Data: Second Edition*, John Wiley and Sons Inc., New York, NY.

Hurvich, C. M. and Simonoff, J. S. and Tsai, Chih-Ling (1998). Smoothing parameter selection in nonparametric regression using an improved Akaike information criterion. *JRSSB*, **60**(2), 271-293. doi:10.1111/14679868.00125

Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:10.1155/2013/745742

dfmacox

Degrees of freedom in multivariate additive Cox models

Description

Provides the degrees of freedom for flexible continuous covariates in multivariate additive Cox models.

Usage

```
dfmacox(time, time2=NULL, status, nl.predictors, other.predictors,
smoother, method, mindf=NULL, maxdf=NULL, ntimes=NULL, data)
```

Arguments

| | |
|------------------|---|
| time | For right censored data, this is the follow up time. For interval data, the first argument is the starting time for the interval. |
| time2 | Ending time of the interval for interval censored or counting process data only. Intervals are assumed to be open on the left and closed on the right, (start, end]. For counting process data, event indicates whether an event occurred at the end of the interval. |
| status | The status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE = death) or 1/2 (2=death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have an event. |
| nl.predictors | Vector with covariates to be introduced in the additive Cox model with a non-linear effect. |
| other.predictors | Vector with remaining covariates to be introduced in the additive Cox model. This will include qualitative covariates or continuous covariates with a linear effect. |
| smoother | Smoothing method to be used in the additive Cox model. Possible options are 'ns' for natural spline smoothing or 'pspline' for penalized spline smoothing. |
| method | The desired method to obtain the optimal degrees of freedom. If method ="AIC", then the AIC = (loglik -df) is used to choose the "optimal" degrees of freedom. The corrected AIC of Hurvich et. al. (method="AICc") and the BIC criterion (method = "BIC") can also be used. |

| | |
|--------|--|
| mindf | Vector with minimum degrees of freedom for each nonlinear predictor. By default this value is a vector of the same length of nl.predictors all with value 1, if smoother is 'ns'; a vector with the same length of nl.predictors all with value 1.5, if smoother is 'pspline'. |
| maxdf | Vector with maximum degrees of freedom for each nonlinear predictor. By default, when penalized spline is used (smoother='pspline'), the corrected AIC from Hurvich obtained in the corresponding univariate additive Cox model is used. When penalized spline is used (smoother='ns') a vector with the same length of nl.predictors all with values 1.5. |
| ntimes | Internal procedure which involves repetition of some convergence steps to attain the optimal degrees of freedom. By default is 5. |
| data | A data.frame in which to interpret the variables named in the arguments time, time2, and status. |

Value

An object of class `list`, basically a list including the elements:

| | |
|---------------|---|
| df | Degrees of freedom of the 'nl.predictors'. |
| AIC | Akaike's Information Criterion score of the fitted model. |
| AICc | Corrected Akaike's Information Criterion score of the fitted model. |
| BIC | Bayesian Information Criterion score of the fitted model. |
| myfit | Fitted (additive Cox) model based on the chosen degrees of freedom. |
| method | The method used for obtaining the degrees of freedom. |
| nl.predictors | Vector with the nonlinear predictors. |

Author(s)

Artur Araújo and Luís Meira-Machado

References

- Eilers, Paul H. and Marx, Brian D. (1996). Flexible smoothing with B-splines and penalties. *Statistical Science*, **11**(2), 89-121. doi:[10.1214/ss/1038425655](https://doi.org/10.1214/ss/1038425655)
- Hurvich, C. M. and Simonoff, J. S. and Tsai, Chih-Ling (1998). Smoothing parameter selection in nonparametric regression using an improved Akaike information criterion. *JRSSB*, **60**(2), 271-293. doi:[10.1111/14679868.00125](https://doi.org/10.1111/14679868.00125)
- Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:[10.1155/2013/745742](https://doi.org/10.1155/2013/745742)

Examples

```
# Example 1
library(survival)
data(whas500)
mydf_ns <- dfmacox(time="lenfol", status="fstat", nl.predictors=c("los", "bmi"),
```

```

other.predictors=c("age", "hr", "gender", "diasbp"), smoother="ns", data=whas500)
print(mydf_ns)

# Example 2
mydf_ps <- dfmacox(time="lenfol", status="fstat", nl.predictors=c("los", "bmi"),
other.predictors=c("age", "hr", "gender", "diasbp"), smoother="pspline", data=whas500)
print(mydf_ps)

```

| | |
|---------|--|
| plot.HR | <i>Flexible hazard ratio curves taking a specific covariate value as reference</i> |
|---------|--|

Description

Plots flexible hazard ratio curves allowing non-linear relationships between continuous predictors and survival. To better understand the effects that each continuous covariate has on the outcome, results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. Confidence bands for these curves are also derived.

Usage

```

## S3 method for class 'HR'
plot(x, predictor, prob=NULL, pred.value=NULL, conf.level=0.95, round.x=NULL,
ref.label=NULL, col, main, xlab, ylab, lty, xlim, ylim, xx, ylog=TRUE,
log=ifelse(ylog, "", "y"), ...)

```

Arguments

| | |
|------------|---|
| x | An object of class HR |
| predictor | Variable named in the formula or included as a predictor in the coxfit. Usually a continuous predictor of survival for which the results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. |
| prob | Value between 0 and 1. If prob=0 the reference value will be the minimum of the hazard ratio curve. If prob=1 the reference value will be the maximum of the hazard ratio curve. For values between 0 and 1 the reference value will be the corresponding quantile of the variable predictor. |
| pred.value | Value from the variable predictor to be taken as the reference value. |
| conf.level | Level of confidence. Defaults to 0.95 (corresponding to 95%). |
| round.x | Rounding of numbers in the plot. |
| ref.label | Label for the reference covariate. By default is the name of the covariate. |
| col | Vector of dimension 3 for the colors to plot. |
| main | These arguments to title have useful defaults here. |
| xlab | The range of x and y values with sensible defaults. |
| ylab | The range of x and y values with sensible defaults. |

| | |
|------|---|
| lty | Vector of dimension 2 for the line type. |
| xlim | The range of x and y values with sensible defaults. |
| ylim | The range of x and y values with sensible defaults. |
| xx | Vector of values (from the variable predictor) to be shown in the x axis. |
| ylog | If TRUE plots natural logarithm of hazard ratio. |
| log | Axis logarithmic scale. See plot.default for details. |
| ... | Other arguments. |

Value

Invisibly returns the plot data, a data.frame including the elements:

| | |
|---------|-------------------------------------|
| x | Predictor. |
| y | Hazard ratio or log hazard ratio. |
| y.lower | Lower bound of confidence interval. |
| y.upper | Upper bound of confidence interval. |

Author(s)

Artur Araújo and Luís Meira-Machado

References

Cadarso-Suarez, C. and Meira-Machado, L. and Kneib, T. and Gude, F. (2010). Flexible hazard ratio curves for continuous predictors in multi-state models: an application to breast cancer data. *Statistical Modelling*, **10**(3), 291-314. doi:[10.1177/1471082X0801000303](#)

Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:[10.1155/2013/745742](#)

See Also

[smoothHR](#).

Examples

```
# Example 1
library(survival)
data(whas500)
fit <- coxph(Surv(lenfol, fstat)~age+hr+gender+diasbp+pspline(bmi)+pspline(los),
data=whas500, x=TRUE)
hr1 <- smoothHR(data=whas500, coxfit=fit)
plot(hr1, predictor="bmi", prob=0, conf.level=0.95)

# Example 2
hr2 <- smoothHR( data=whas500, time="lenfol", status="fstat", formula=~age+hr+gender+diasbp+
pspline(bmi)+pspline(los) )
plot(hr2, predictor="los", pred.value=7, conf.level=0.95, xlim=c(0,30), round.x=1,
```

```
ref.label="Ref.", xaxt="n")
xx <- c(0, 5, 10, 15, 20, 25, 30)
axis(1, xx)
```

| | |
|------------|--|
| predict.HR | <i>predict method for an object of class 'HR'.</i> |
|------------|--|

Description

predict method for an object of class 'HR'.

Usage

```
## S3 method for class 'HR'
predict(object, predictor, prob=NULL, pred.value=NULL, conf.level=0.95,
prediction.values=NULL, round.x=NULL, ref.label=NULL, ...)
```

Arguments

| | |
|-------------------|---|
| object | An object of class HR. |
| predictor | Variable named in the formula or included as a predictor in the <code>coxfit</code> . Usually a continuous predictor of survival for which the results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. |
| prob | Value between 0 and 1. If <code>prob=0</code> the reference value will be the minimum of the hazard ratio curve. If <code>prob=1</code> the reference value will be the maximum of the hazard ratio curve. For values between 0 and 1 the reference value will be the corresponding quantile of the variable predictor. |
| pred.value | Value from the variable predictor to be taken as the reference value. |
| conf.level | Level of confidence. Defaults to 0.95 (corresponding to 95%). |
| prediction.values | Vector of values ranging between minimum and maximum of the variable predictor. |
| round.x | Rounding of numbers in the predict. |
| ref.label | Label for the reference covariate. By default is the name of the covariate. |
| ... | Other arguments. |

Value

Returns a matrix with the prediction values.

Author(s)

Artur Araújo and Luís Meira-Machado

References

Cadarso-Suarez, C. and Meira-Machado, L. and Kneib, T. and Gude, F. (2010). Flexible hazard ratio curves for continuous predictors in multi-state models: an application to breast cancer data. *Statistical Modelling*, **10**(3), 291-314. doi:10.1177/1471082X0801000303

Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:10.1155/2013/745742

See Also

[smoothHR](#).

Examples

```
# Example 1
library(survival)
data(whas500)
fit <- coxph(Surv(lenfol, fstat)~age+hr+gender+diasbp+pspline(bmi)+pspline(los),
data=whas500, x=TRUE)
hr1 <- smoothHR(data=whas500, coxfit=fit)
predict(hr1, predictor="bmi", prob=0, conf.level=0.95)

# Example 2
hr2 <- smoothHR( data=whas500, time="lenfol", status="fstat", formula=~age+hr+gender+diasbp+
pspline(bmi)+pspline(los) )
pdval <- c(1, 2, 3, 4, 5, 6, 7, 8, 10, 12, 15, 18, 22, 25)
predict(hr2, predictor="los", pred.value=7, conf.level=0.95, prediction.values=pdval,
ref.label="Ref.")
```

```
print.HR
```

```
print method for a Smooth Hazard Ratio Object
```

Description

This class of objects is returned by the HR class of functions to represent smooth hazard ratio curve. Objects of this class have methods for print, predict and plot.

Usage

```
## S3 method for class 'HR'
print(x, ...)
```

Arguments

```
x          An object of class HR.
...        Other arguments.
```


Value

No value is returned.

Author(s)

Artur Araújo and Luís Meira-Machado

References

Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:[10.1155/2013/745742](https://doi.org/10.1155/2013/745742)

See Also

[smoothHR](#).

Examples

```
# Example 1
library(survival)
data(whas500)
fit <- coxph(Surv(lenfol, fstat)~age+hr+gender+diasbp+pspline(bmi)+pspline(los),
data=whas500, x=TRUE)
hr1 <- smoothHR(data=whas500, coxfit=fit)
print(hr1)

# Example 2
hr2 <- smoothHR( data=whas500, time="lenfol", status="fstat", formula=~age+hr+gender+diasbp+
pspline(bmi)+pspline(los) )
print(hr2)
```

smoothHR

Smooth Hazard Ratio Curves Taking a Reference Value

Description

Provides flexible hazard ratio curves allowing non-linear relationships between continuous predictors and survival. To better understand the effects that each continuous covariate has on the outcome, results are expressed in terms of hazard ratio curves, taking a specific covariate value as reference. Confidence bands for these curves are also derived.

Usage

```
smoothHR(data, time=NULL, time2=NULL, status=NULL, formula=NULL, coxfit,
status.event=NULL)
```

Arguments

| | |
|---------------------------|---|
| <code>data</code> | A data.frame in which to interpret the variables named in the formula or in the arguments <code>time</code> , <code>time2</code> , <code>status</code> and <code>coxfit</code> . |
| <code>time</code> | For right censored data, this is the follow up time. For interval data, the first argument is the starting time for the interval. |
| <code>time2</code> | Ending time of the interval for interval censored or counting process data only. Intervals are assumed to be open on the left and closed on the right, (start, end]. For counting process data, event indicates whether an event occurred at the end of the interval. |
| <code>status</code> | The status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE = death) or 1/2 (2=death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have an event. |
| <code>formula</code> | A formula object, with the terms on the right after the ~ operator. |
| <code>coxfit</code> | An object of class <code>coxph</code> . This argument is optional, being an alternative to the arguments <code>time</code> , <code>time2</code> , <code>status</code> and <code>formula</code> . |
| <code>status.event</code> | The status indicator is a qualitative variable where usually the highest value is left for the event of interest (usually 0=alive, 1=dead). If that is not the case the <code>status.event</code> indicates which value denotes the event of interest. |

Value

An object of class `HR`. There are methods for `print`, `predict` and `plot`. `HR` objects are implemented as a list with elements:

| | |
|----------------------|--|
| <code>dataset</code> | Dataset used. |
| <code>coxfit</code> | The object of class <code>'coxph'</code> used. |
| <code>phtest</code> | Result from testing the proportional hazards assumption. |

Author(s)

Artur Araújo and Luís Meira-Machado

References

- Cadarso-Suarez, C. and Meira-Machado, L. and Kneib, T. and Gude, F. (2010). Flexible hazard ratio curves for continuous predictors in multi-state models: an application to breast cancer data. *Statistical Modelling*, **10**(3), 291-314. doi:[10.1177/1471082X0801000303](https://doi.org/10.1177/1471082X0801000303)
- Meira-Machado, L. and Cadarso-Suárez, C. and Gude, F. and Araújo, A. (2013). smoothHR: An R Package for Pointwise Nonparametric Estimation of Hazard Ratio Curves of Continuous Predictors. *Computational and Mathematical Methods in Medicine*, **2013**, 11 pages. doi:[10.1155/2013/745742](https://doi.org/10.1155/2013/745742)

Examples

```
# Example 1
library(survival)
data(whas500)
fit <- coxph(Surv(lenfol, fstat)~age+hr+gender+diasbp+pspline(bmi)+pspline(los), data=whas500,
x=TRUE)
hr1 <- smoothHR(data=whas500, coxfit=fit)
print(hr1)

# Example 2
hr2 <- smoothHR( data=whas500, time="lenfol", status="fstat", formula=~age+hr+gender+diasbp+
pspline(bmi)+pspline(los) )
print(hr2)
```

whas500

*Worcester Heart Attack Study WHAS500 Data***Description**

Data from the Worcester Heart Attack Study

Usage

```
data(whas500)
```

Format

A data frame with 500 observations with 22 variables.

Details

Data from the Worcester Heart Attack Study whose main goal was to describe factors associated with trends over time in the incidence and survival rates following hospital admission for acute myocardial infarction.

Source

Worcester Heart Attack Study data from Dr. Robert J. Goldberg of the Department of Cardiology at the University of Massachusetts Medical School.

References

Hosmer, D. W. and Lemeshow, S. and May, S. (2008). *Applied Survival Analysis: Regression Modeling of Time to Event Data: Second Edition*, John Wiley and Sons Inc., New York, NY.

Examples

```
data(whas500)
```

Index

- * **datasets**
 - whas500, [11](#)
- * **hplot**
 - plot.HR, [5](#)
- * **methods**
 - plot.HR, [5](#)
 - predict.HR, [7](#)
 - print.HR, [8](#)
- * **models**
 - dfmacox, [3](#)
 - smoothHR, [9](#)
- * **package**
 - smoothHR-package, [2](#)
- * **print**
 - print.HR, [8](#)
- * **regression**
 - dfmacox, [3](#)
 - smoothHR, [9](#)
- * **survival**
 - dfmacox, [3](#)
 - plot.HR, [5](#)
 - predict.HR, [7](#)
 - print.HR, [8](#)
 - smoothHR, [9](#)

dfmacox, [3](#)

plot.default, [6](#)
plot.HR, [5](#)
predict.HR, [7](#)
print.HR, [8](#)

smoothHR, [6](#), [8](#), [9](#), [9](#)
smoothHR-package, [2](#)

whas500, [11](#)