

Package ‘tab2xml’

July 22, 2025

Type Package

Title XML Generation from Tables

Version 1.1.0

Description Converting structured data from tables into XML format using predefined templates ensures consistency and flexibility, making it ideal for data exchange, reporting, and automated workflows.

License MIT + file LICENSE

URL <https://josesamos.github.io/tab2xml/>,
<https://github.com/josesamos/tab2xml>

BugReports <https://github.com/josesamos/tab2xml/issues>

Imports readODS, readxl, stringr, tools

Suggests knitr, rmarkdown, testthat (>= 3.0.0), xml2

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Jose Samos [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4457-3439>>),
Universidad de Granada [cph]

Maintainer Jose Samos <jsamos@ugr.es>

Repository CRAN

Date/Publication 2025-04-01 18:30:02 UTC

Contents

check_tab	2
sheet2xml	2
Index	4

check_tab	<i>Validate and Check Spreadsheet Data</i>
-----------	--

Description

This function validates the structure of a spreadsheet file by checking its sheets, primary keys (PKs), and foreign keys (FKs). If a template file is provided, it also checks the column definitions.

Usage

```
check_tab(file_path, template_path = NULL)
```

Arguments

file_path	Character. Path to the spreadsheet file to be validated.
template_path	Character (optional). Path to the template file for validation. If 'NULL', only the sheet structure is checked.

Value

Logical. Returns "TRUE" but warns of possible errors.

sheet2xml	<i>Convert a Spreadsheet to XML</i>
-----------	-------------------------------------

Description

It reads a spreadsheet file (Excel or ODS), processes it using a provided XML template, and generates an XML output file.

Usage

```
sheet2xml(file_path, template_path, xml_path = NULL, optimize = FALSE)
```

Arguments

file_path	Character. Path to the spreadsheet file to be converted. Supports Excel (.xlsx) and ODS formats.
template_path	Character. Path to the XML template file to guide the transformation process.
xml_path	Character (optional). Output path for the generated XML file. If NULL, it is considered an XML file with the same name and location as the spreadsheet file.
optimize	Boolean. Remove empty nodes from the xml file.

Value

Character. The file path of the generated XML document.

Examples

```
source_xml <- system.file("extdata", "schema_template.xml", package = "tab2xml")

source_xlsx <- system.file("extdata", "schema.xlsx", package = "tab2xml")
temp_file1 <- tempfile(fileext = ".xml")
sheet2xml(source_xlsx, source_xml, temp_file1)

source_ods <- system.file("extdata", "schema.ods", package = "tab2xml")
temp_file2 <- tempfile(fileext = ".xml")
sheet2xml(source_ods, source_xml, temp_file2)
```

Index

check_tab, [2](#)

sheet2xml, [2](#)